



ULTRA AVIATION SERVICES, INC.

General Operations Manual

APPENDIX: 1

SAFETY & SECURITY BULLETIN (U-SMS-09)

Revision: Original

Date: 7/1/2015

Bulletin No: 18-008

Date: 13/Apr/18

Reissued

SUBJECT: RAMP procedures reminder Post Arrival and Pre departure walk around

APPLICABLE TO: ALL RAMP PERSONNEL

Remember company SOP dictate that before an aircraft is allow to depart, and after an aircraft has arrived a complete safety walk around must be conducted. This practice prevent the aircraft from departing with damage to the fuselage, and will discover any damage that the aircraft might had sustained a previous station

MUST BE CONDUCTED WITHIN 5 minutes of ARRIVAL or 10 min. before DEPARTURE

Post arrival/ Departures walk around

- 1- On arrivals Do not allow any door to be opened until the walk around is completed.
- 2- Start with the area around L1,
- 3- Move to the right side checking , nose area, C1 cargo door frame , engine 2 (R) make sure that you check cowling an intake and exhaust areas; check R main gear
- 4- Check area in and around C2 cargo door frame
- 5- Once you have check the cargo door you can allow your crew to OPEN the door. For departures after closing door make sure there is not damage to any portion of door or its frame
- 6-Continue to the tail section and go to L side of aircraft, check Belly 5 door (on 767)
- 7- Continue of L side check L main and L engine
- 8 Finish at L1 area.

9- Report any finding immediately,. If any damage is found do not open/ close compartments adjacent to damage



C1 area



C2 area



Engine area

Be SAFE follow all ramp safety rules and company SOP

PREPARED BY:

Safety Department