

1 Syntax

Variables	x
Boolean Values	$b \in \mathbb{B}$
Types	$\tau ::= \text{Bool} \mid \tau \rightarrow \tau$
Expressions	$e ::= x \mid b \mid \lambda x : \tau. e \mid e e$
Contexts	$\Gamma ::= \emptyset \mid \Gamma, x : \tau$

Fig. 1. Syntax

$\frac{\text{TYP-VAR}}{x : \tau \in \Gamma}$	$\frac{\text{TYP-BLIT}}{\Gamma \vdash b : \text{Bool}}$	$\frac{\text{TYP-ABS}}{\Gamma, x : \tau_1 \vdash e : \tau_2}$	$\frac{\text{TYP-APP}}{\Gamma \vdash e_1 : \tau_1 \rightarrow \tau_2 \quad \Gamma \vdash e_2 : \tau_1}$
$\Gamma \vdash x : \tau$		$\Gamma \vdash \lambda x : \tau_1. e : \tau_1 \rightarrow \tau_2$	$\Gamma \vdash e_1 e_2 : \tau_2$

Fig. 2. Syntactic Typing

2 Semantics

Values	$v ::= b \mid \lambda x : \tau. e$
Substitutions	$\sigma ::= \text{id} \mid \sigma[x \mapsto v]$

Fig. 3. Values and Substitutions

$\frac{\text{STEP-BETA}}{(\lambda x : \tau. e) v \hookrightarrow e[v/x]}$	$\frac{\text{STEP-APP}_1}{e_1 \hookrightarrow e'_1}$	$\frac{\text{STEP-APP}_2}{e_2 \hookrightarrow e'_2}$
	$e_1 e_2 \hookrightarrow e'_1 e_2$	$v e_2 \hookrightarrow v e'_2$

Fig. 4. Reduction

$$\begin{aligned}\text{id}(e) &:= e \\ \sigma[x \mapsto v](e) &:= \sigma(e[v/x])\end{aligned}$$

Fig. 5. Substitution

$$\begin{aligned}\mathcal{V}[\![\text{Bool}]\!] &:= \mathbb{B} \\ \mathcal{V}[\![\tau_1 \rightarrow \tau_2]\!] &:= \{\lambda x : \tau_1. e \mid \forall v \in \mathcal{V}[\![\tau_1]\!]. e[v/x] \in \mathcal{E}[\![\tau_2]\!]\} \\ \mathcal{E}[\![\tau]\!] &:= \{e \mid \exists v \in \mathcal{V}[\![\tau]\!]. e \hookrightarrow^* v\} \\ \mathcal{G}[\![\emptyset]\!] &:= \{\text{id}\} \\ \mathcal{G}[\![\Gamma, x : \tau]\!] &:= \{\sigma[x \mapsto v] \mid \sigma \in \mathcal{G}[\![\Gamma]\!] \wedge v \in \mathcal{V}[\![\tau]\!]\}\end{aligned}$$

Fig. 6. Logical Relations

$$\Gamma \models e : \tau := \forall \sigma \in \mathcal{G}[\![\Gamma]\!]. \sigma(e) \in \mathcal{E}[\![\tau]\!]$$

Fig. 7. Semantic Typing