

TLS 1.3

Eric Rescorla

Mozilla

`ekr@rtfm.com`

Overview

- Background/Review of TLS
- Some problems with TLS 1.2
- Objectives for TLS 1.3
- What does TLS 1.3 look like?
- Open issues/schedule/etc.

What is Transport Layer Security?


- Probably the Internet's most important security protocol
- Designed over 20 years ago by Netscape for Web transactions
 - Back then, called Secure Sockets Layer
- But used for just about everything you can think of
 - HTTP
 - SSL-VPNs
 - E-mail
 - Voice/video
 - IoT
- Maintained by the Internet Engineering Task Force
 - We're now at version 1.2

A Secure Channel

- Client connects to a known server (e.g., it has the domain name)
- Server is (almost) always authenticated by TLS
- Client may or may not be authenticated by TLS
 - Often authenticated by the application, e.g., with a password
- After setup, data is encrypted and authenticated
 - Though what “authenticated” means to the server is fuzzy

IPSec and Transport Layer Security (TLS)

Security at layers 3 and 4



- ❑ Security services
 - Authentication
 - Integrity protection
 - Confidentiality
- ❑ Security services become independent, wherever possible, from upper and lower layers



TLS: introduction

- ❑ *Transport Layer Security* is a protocol suite defined to offer security to applications: it works between TCP or UDP and applications
- ❑ Security features
 - Authentication
 - Integrity protection
 - Confidentiality
- ❑ TLS' goal is to provide a secure, authenticated channel based on ephemeral keys derived from longer cryptographic credentials of several kinds:
 - X.509 certificates
 - PSK
 - PSK/Kerberos
 - OpenPGP keys
 - Secure Remote Passwords (SRP)
- ❑ Two protocol variants
 - [RFC 4346] TLSv1.1, works above TCP
 - [RFC 4347] DTLSv1.0, works above UDP
- ❑ Here we will just see TLS (v1.0)



TLS: historical notes

❑ The story so far:

- 1995: *Secure Socket Layer* (SSL) v2, Netscape Inc., protection of HTTP sessions
- 1997: SSLv3, bug fixes, the most widely used variant to date
- 1999: TLS (Transport Layer Security) v1.0, SSLv3 standardized by IETF, supports DSS along with RSA (works around the RSA patent), plus other minor differences
- 2005/2006: TLS v1.1 e DTLS v1.0, minor differences from TLS v1.0, DTLS works on top of UDP [RFC 4347], support for PSKs [RFC 4279], support for OpenPGP keys, SRPs, etc.

❑ We will focus on SSLv3/TLSv1.0


- TCP only (no UDP)
- Long term credentials: DSS or RSA keypairs, i.e., X.509 certificates (no PSK)



The TLS architecture

TLS Record Protocol


- ❑ Same services to above layers as TCP, with the added security
- ❑ Transports either user data, or other TLS protocol messages
- ❑ Once the TLS session is up and running (ephemeral keys have been installed), anything that the record protocol transports is protected (integrity, authentication, confidentiality)



The TLS architecture

TLS Handshake Protocol

- ❑ Protocol used to manage security all parameters, such as cipher suite, ephemeral keys, etc., and handle authentication
- ❑ Deriving ephemeral keys is expensive, so TLS introduces the concept of **session**, over which multiple **connections** can be setup



The TLS architecture


TLS Change CipherSpec and Alert Protocol

❑ Change CipherSpec Protocol

- A really, really simple protocol: 1-bit message, signaling the end of the cleartext part of the handshake

❑ Alert Protocol

- Used to signal error conditions, for example when there are problems with the underlying transport protocol



TLS Handshake protocol: high level overview

❑ Goals

- Authentication of B to A and, optionally, of A to B
- Setup of ephemeral **session** key K_{ms} (*Master Secret*), as a “seed” for one or more **connection** keys

❑ In TLS, A (*initiator*) is the **client**, while B (*responder*) is the **server**

❑ The Handshake protocol messages are transported by the TLS Record protocol

❑ Each record message can contain more than one handshake messages

- For example, record message (2) usually contains messages “server_hello, certificate, [certificate_request], server_hello_done”


❑ R_A, R_B : random numbers

❑ $Auth_A = SIG_{K_{privA}}(\text{hash}(\text{previous messages}))$

❑ PMS: pre-master secret, random number chosen by A


❑ $K_{ms} = f_{PMS}(R_A, R_B)$, where f is a MAC function derived from both SHA1 and MD5

❑ $hash_{A/B} = g_{K_{ms}}(\{\text{client/server}\}, \text{previous messages})$, where g is another MAC function derived from both SHA1 and MD5



TLS Handshake protocol

- ❑ At this point we have a **TLS session**
 - Authentication [optionally mutual]
 - A authenticates B by the fact that B can prove they are able to decrypt PMS (i.e., calculate the correct K_{ms}) with the private key associated to $CERT_B$
 - Optionally, B authenticates A through $Auth_A$
 - TLS session, identified by $(K_{ms}, \text{sess-id})$. K_{ms} is a 384 bit (48 byte) string
- ❑ One or more **TLS connections** can now be instantiated, by deriving the necessary ephemeral keys from K_{ms} . User traffic will be protected by these TLS connections inside the TLS record protocol
- ❑ By key expansion, **three key pairs** are derived from K_{ms}
 - Client write MAC, client write, client IV (K_{cm}, K_c, IV_c)
 - Server write MAC, server write, server IV (K_{sm}, K_s, IV_s)
 - Key expansion is similar to the one used to derive K_{ms} from PMS, i.e., it is based on a MAC function that works on K_{ms}, R_A, R_B
 - Note that there are three keys **for each of the two directions**




TLS Handshake protocol: notes

- ❑ PFS is optional: K_{ms} can optionally be derived from a PMS=DH key
- ❑ CA hierarchies
 - When A or B send a certificate, they can also include ***chains of (CA) certificates***
 - When B request that A authenticates with their certificate, usually B includes in the request a list of ***known and admissible CAs***




Session/connection: *session resumption*

- ❑ Once a TLS session is in place, A and B can derive multiple sessions without going through the initial exchange, i.e., without having to derive a new K_{ms}
- ❑ This variant is used to continue a session (actually, open another connection) for which we still have a valid pair (sess-id, K_{ms})
- ❑ Cipher suite can be re-negotiated
- ❑ R_A and R_B are re-negotiated



Encrypting data

- ❑ TLS Record protocol, once a TLS connection is active, cryptographically protects all user data and all subsequent TLS messages (e.g., TLS Alert protocol)
- ❑ Compression is optional
- ❑ MAC = HMAC in TLS, HMAC-like in SSLv3



Note: IV. The first TLS Record in a given connection will need to use the IV derived from K_{ms} . Next records will use as IV the last bytes of the previous record (v1.0). A different mechanism is used in v1.1.



TLS cipher suites


- ❑ Contrary to IKE, SSLv3 and TLS define a finite and pre-set number of cipher suites
- ❑ As usual, each cipher suite defines algorithms, modes of operation, parameters, etc.
 - For example: 3DES-CBC + HMAC-MD5 + SHA1, etc.
- ❑ Client tells Server what cipher suites it supports, in descending order of preference
- ❑ The Server selects one, usually the one that it supports that is highest on the list
- ❑ Warning: never use “EXPORTABLE” cipher suites (40 bit ephemeral keys!)




TLS Structure

- Handshake protocol
 - Establish shared keys (typically using public key cryptography)
 - Negotiate algorithms, modes, parameters
 - Authenticate one or both sides
- Record protocol
 - Carry individual messages
 - Protected under symmetric keys
- This is a common design (SSH, IPsec, etc.)


TLS 1.2: RSA Handshake Skeleton



TLS 1.2: (EC)DHE Skeleton



TLS 1.2: (EC)DHE + Client Authentication



More on Negotiation

- ClientHello contains more than just random values

```
struct {
    ProtocolVersion client_version;
    Random random;
    SessionID session_id;
    CipherSuite cipher_suites<2..216-2>;
    CompressionMethod compression_methods<1..28-1>;
    select (extensions_present) {
        case false:
            struct {};
        case true:
            Extension extensions<0..216-1>;
    };
} ClientHello;
```

Client Offers, Server Chooses

```
struct {  
    ProtocolVersion server_version;  
    Random random;  
    SessionID session_id;  
    CipherSuite cipher_suite;  
    CompressionMethod compression_method;  
    select (extensions_present) {  
        case false:  
            struct {};  
        case true:  
            Extension extensions<0.. $2^{16}-1$ >;  
    };  
} ServerHello;
```


What's in a Cipher Suite?

- Key Exchange (RSA, DHE, ECDHE, PSK, ...)
- Authentication (RSA, DSS, ECDSA, ...)
- Encryption (AES, Camellia, ...)
- MAC (MD5, SHA1, SHA256, ...)


Session Resumption

- “Public key” operations are comparatively expensive
 - They used to be *really* expensive
- Solution: amortize this operation across multiple connections

Session Establishment



Session Resumption



- No new public key operations
- Reuse MS from last handshake

TLS 1.3 Objectives

- *Clean up*: Remove unused or unsafe features
- *Security*: Improve security by using modern security analysis techniques
- *Privacy*: Encrypt more of the protocol
- *Performance*: Our target is a 1-RTT handshake for naive clients; 0-RTT handshake for repeat connections
- *Continuity*: Maintain existing important use cases

Removed Features

- Static RSA
- Custom (EC)DHE groups
- Compression
- Renegotiation*
- Non-AEAD ciphers
- Simplified resumption

*Special accommodation for inline client authentication

Removed Feature: Static RSA Key Exchange

- Most SSL servers prefer non-PFS cipher suites [SSL14] (specifically static RSA)
- Obviously suboptimal performance characteristics
- No PFS
- Gone in TLS 1.3
- Important: you can still use RSA certificates
 - But with ECDHE or DHE
 - Using ECDHE minimizes performance hit

Removed Feature: Compression

- Recently published vulnerabilities [DR12]
- Nobody really knows how to use compression safely and generically
 - Sidenote: HTTP2 uses very limited context-specific compression [PR14]
- TLS 1.3 bans compression entirely
 - TLS 1.3 clients **MUST NOT** offer any compression
 - TLS 1.3 servers **MUST** fail if compression is offered

Removed Feature: Non-AEAD Ciphers

- Symmetric ciphers have been under a lot of stress (thanks, Kenny and friends)
 - RC4 [ABP⁺13]
 - AES-CBC [AP13] in MAC-then-Encrypt mode
- TLS 1.3 bans all non-AEAD ciphers
 - Current AEAD ciphers for TLS: AES-GCM, AES-CCM, ARIA-GCM, Camellia-GCM, ChaCha/Poly (coming soon)

Removed Feature: Custom (EC)DHE groups


- Previous versions of TLS allowed the server to specify their own DHE group
 - The only way things worked for finite field DHE
 - (Almost unused) option for ECDHE
- This isn't optimal
 - Servers didn't know what size FF group client would accept
 - Hard for client to validate group [BLF⁺14]
- TLS 1.3 only uses predefined groups
 - Existing RFC 4492 [BWBG⁺06] EC groups (+ whatever CFRG comes up with)*
 - New FF groups defined in [Gil14]

*Bonus: removed point format negotiation too

Optimizing Through Optimism


- TLS 1.2 assumed that the client knew nothing
 - First round trip mostly consumed by learning server capabilities
- TLS 1.3 narrows the range of options
 - Only (EC)DHE
 - Limited number of groups
- Client can make a good guess at server's capabilities
 - Pick its favorite groups and send a DH share

TLS 1.3 1-RTT Handshake Skeleton



- Server can write on its first flight
- Client can write on second flight
- Keys derived from handshake transcript through server MAC
- Server certificate is encrypted
 - Only secure against passive attackers


TLS 1.3 1-RTT Handshake w/ Client Authentication Skeleton



- Client certificate is encrypted
- Secure against an active attacker
- Effectively SIGMA [Kra03]

What happens if the client is wrong?

- Client sends some set of groups (P-256)
- Server wants another group (P-384)




- This shouldn't happen often because there are a small number of groups
 - Client should memorize server's preferences

0-RTT Handshake

- Basic observation: client can cache server's parameters [Lan10]
 - Then send *application data* on its first flight
- Server has to *prime* the client with its configuration in a previous handshake

TLS 1.3 0-RTT Handshake Skeleton



Anti-Replay

- TLS anti-replay is based on each side providing random value
 - Mixed into the keying material
- Not compatible with 0-RTT
 - Client has anti-replay (since they speak first)
 - Server's random isn't incorporated into client's first flight

Anti-Replay (borrowed from Snap Start)

- Server needs to keep a list of client nonces
- Indexed by a server-provided context token
- Client provides a timestamp so server can maintain an anti-replay window

Traffic Analysis Defenses

- TLS 1.2 is very susceptible to traffic analysis
 - Content “type” in the clear
 - Packet length has minimal padding
 - * 0-255 bytes in block cipher modes
 - * No padding in stream and AEAD modes
- TLS 1.3 changes
 - Content type is encrypted
 - Arbitrary amounts of padding allowed
 - ... but it’s the application’s job to set padding policy

Packet Format



TLS 1.2 Packet Layout



TLS 1.3 Packet Layout


The Heartbeat extension to TLS

- ▶ designed to enable a low-cost, keep-alive mechanism
- ▶ so that client and server know that they're still connected and all is well
- ▶ described in RFC 6520 for TLS and DTLS
- ▶ supported in OpenSSL v1.0.1, enabled by default



Protocol

1. client sends a a packet of type **heartbeat_request**, along with an arbitrary payload and a field that defines the payload length.
2. server answers with a **heartbeat_response** that contains an exact copy of the payload.

Heartbeat correct execution



Heartbleed attack



Lesson learnt

The Heartbleed vulnerability looks really trivial. . .

- ▶ it's essentially a buffer overread vulnerability, where inadequate bounds-checking is carried out at runtime
- ▶ a client should not trust the payload length presented in the heartbeat_request packet
- ▶ more generally, placing trust in user-supplied input is often a bad idea
- ▶ also. . . a lot can go wrong between design and implementation