


Go-Back-N :

(1)




two state channel $0 = \text{good}$ $1 = \text{bad}$

note: when bad tx, we retry m slots later, i.e., we skip $m-1$ slots.

let $C = \begin{pmatrix} p_{00} & p_{01} \\ p_{10} & p_{11} \end{pmatrix}$ be the matrix of the two-state channel.

$$C_m = \begin{pmatrix} p_{00}(m) & p_{01}(m) \\ p_{10}(m) & p_{11}(m) \end{pmatrix}$$

Markov chain for the protocol



time metric is 1 for state G and m for B.

$$T_B = m, T_G = 1$$

success metrics: $R_B = 0, R_G = 1$

The matrix for the embedded Markov chain is:

(3)

$$P = \begin{pmatrix} p_{00} & p_{01} \\ p_{10}(m) & p_{11}(m) \end{pmatrix}$$

$$\bar{\pi}_B = \frac{p_{01}}{p_{01} + p_{10}(m)}$$

$$\bar{\pi}_G = \frac{p_{10}(m)}{p_{01} + p_{10}(m)}$$

$$\text{throughput} = \frac{\bar{\pi}_G R_G + \bar{\pi}_B R_B}{\bar{\pi}_G T_G + \bar{\pi}_B T_B} =$$

$$= \frac{p_{10}(m)}{p_{10}(m) + m p_{01}}$$

$$= \frac{1 - \epsilon}{1 - \epsilon + m \epsilon}$$

↑
if iid errors.

low suppose feedback errors - w. matrix $\begin{pmatrix} q_{00} & q_{01} \\ q_{10} & q_{11} \end{pmatrix}$ ③

bad slot: slot where either way is corrupted.

state : $\begin{matrix} & 00 & 01 & 10 & 11 \\ \uparrow & \uparrow & & & \\ \text{prev.} & \text{feedback.} & & & \end{matrix}$

trans. matrix:

	00	01	10	11
00	$p_{00}q_{00}$	$p_{00}q_{01}$	$p_{01}q_{00}$	$p_{01}q_{01}$
01	$p_{00}(w)q_{10}(w)$	$p_{00}(w)q_{11}(w)$...	-
10	$p_{10}(w)q_{00}(w)$	$p_{10}(w)q_{01}(w)$...	-
11

→ solve to get the \bar{n}_i 's

Throughput: one reward is gained when visiting state 00, else nothing -

$$\frac{R(t)}{t} \rightarrow \frac{\sum_i \bar{n}_i R_i}{\sum_i \bar{n}_i T_i} = \frac{\bar{n}_{00}}{\bar{n}_{00} + m(1 - \bar{n}_{00})}$$

Statistics of successful slots up to time n : ①

Let the error process be Markov, two-state X_n
 $0 = \text{correct tx}$; $1 = \text{erroneous tx}$.

Define

$$\phi_{ij}(k, n) = P[k \text{ good slots in } 0, 1, \dots, n-1, \text{ and } j \text{ in } n | i \text{ in } 0] \\ = P\left[\sum_{m=0}^{n-1} I\{X_m = 0\} = k, X_n = j \mid X_0 = i\right]$$

Condition on last transition:

$$\phi_{ij}(k, n) = \phi_{i0}(k-1, n-1)p_{0j} + \phi_{i1}(k, n-1)p_{1j}, \quad \begin{matrix} n > 0 \\ k \leq n \end{matrix}$$

$$\phi_{ij}(k, 0) = \begin{cases} 1 & \text{per } i=j, k=0, n=0 \\ 0 & \text{otherwise} \end{cases} = \delta_{ij} \delta(n) \delta(k)$$

$$\phi_{ij}(k, n) = 0 \quad k < 0 \quad \text{or} \quad n < 0 \quad \text{or} \quad k > n.$$

Finally:

$$\phi_{ij}(k, n) = \phi_{i0}(k-1, n-1)p_{0j} + \phi_{i1}(k, n-1)p_{1j} + \delta_{ij} \delta(n) \delta(k)$$

In matrix form: $\phi(k, n) = \begin{pmatrix} \phi_{00}(k, n) & \phi_{01}(k, n) \\ \phi_{10}(k, n) & \phi_{11}(k, n) \end{pmatrix}$

$$\phi(k, n) = \phi(k-1, n-1) \begin{pmatrix} p_{00} & p_{01} \\ 0 & 0 \end{pmatrix} + \phi(k, n-1) \begin{pmatrix} 0 & 0 \\ p_{10} & p_{11} \end{pmatrix} + \delta(n) \delta(k) I$$

$$\text{Let } P(0) = \begin{pmatrix} 0 & 0 \\ p_{10} & p_{11} \end{pmatrix} \text{ and } P(1) = \begin{pmatrix} p_{00} & p_{01} \\ 0 & 0 \end{pmatrix}$$

(2)

Therefore:

$$\phi(k, n) = \phi(k-1, n-1)P(1) + \phi(k, n-1)P(0) + f(n)f(k)I, n \geq 0$$

note: $P(1)$ contains "good" transitions (starting from 0)
 $P(0)$ "bad" (" " ")

$\rightarrow P(i)$ corresponds to i successes, $i=0,1$.

We can apply the same analysis to any finite-state Markov chain where we want to count transitions of a certain type.

note: if we condition on first transition:

$$\phi_{0j}(k, n) = p_{00}\phi_{0j}(k-1, n-1) + p_{01}\phi_{1j}(k-1, n-1) + \phi_{0j}f(n)f(k)$$

$$\phi_{1j}(k, n) = p_{10}\phi_{0j}(k, n-1) + p_{11}\phi_{1j}(k, n-1) + \phi_{1j}f(n)f(k)$$

In matrix form:

$$\phi(k, n) = P(1)\phi(k-1, \overset{n-1}{\cancel{n}}) + P(0)\phi(k, \overset{n-1}{\cancel{n}}) + f(n)f(k)I \quad n \geq 0$$

* compared to the other equation, the order of the matrix products is reversed

* these matrix equations are convolutional.

How to solve these equations:

(3)

1) compute recursively

2) use transforms.

$$\varphi(s, z) = \sum_{k=0}^{+\infty} s^k \sum_{n=0}^{+\infty} z^n \phi(k, n)$$

$$\varphi(s, z) = \varphi(s, z) P(1)sz + \varphi(s, z) P(0)z + I$$

$$\varphi(s, z) = [I - P(1)sz - P(0)z]^{-1} = [I - z(P(1)s + P(0))]^{-1}$$
$$= \sum_{n=0}^{+\infty} [P(1)s + P(0)]^n z^n$$

$$\rightarrow \varphi(s, n) = \sum_{k=0}^{+\infty} s^k \phi(k, n) = \begin{matrix} \text{transform over } k \\ \text{for a given } n \end{matrix}$$
$$= (P(1)s + P(0))^n$$

which in principle could be inverted.

Example: average number of good slots in $0, 1, 2, \dots, n-1$, given initial state i :

$\varphi_{i0}(s, n) + \varphi_{i1}(s, n)$ is the generating function of the number of times state 0 is visited in $0, 1, 2, \dots, n-1$, given that we start in i (note: we need to sum over j). The average number of visits is obtained by taking the first derivative for $s=1$.

$$\varphi'(1, n) = \left. \frac{d\varphi(s, n)}{ds} \right|_{s=1} =$$

(4)

$$= \sum_{k=0}^{n-1} \left(P(1)s + P(0) \right)^k P(1) \left(P(1)s + P(0) \right)^{n-1-k} \Big|_{s=1}$$

$$= \sum_{k=0}^{n-1} P^k P(1) P^{n-1-k}$$

What we want to compute is given by

$$\varphi'(1, n) \begin{pmatrix} 1 \\ 1 \end{pmatrix} = \left(\text{we sum the elements of each row, i.e., over the final state } j \right)$$

$$= \sum_{k=0}^{n-1} P^k P(1) P^{n-1-k} \begin{pmatrix} 1 \\ 1 \end{pmatrix} = \sum_{k=0}^{n-1} P^k P(1) \begin{pmatrix} 1 \\ 1 \end{pmatrix} =$$

$$= \sum_{k=0}^{n-1} P^k \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \begin{pmatrix} \sum_{k=0}^{n-1} P_{00}^{(k)} \\ \sum_{k=0}^{n-1} P_{10}^{(k)} \end{pmatrix} \text{ as expected.}$$

Remark : we found the equation :

(5)

$$\phi(k, n) = \phi(k-1, n-1)P(1) + \phi(k, n-1)P(0) + f(n)f(k)I$$

$n \geq 0$

where we identified two types of transitions
(good and bad, i.e., one or zero successes).

Suppose we associate an integer weight to each transition. Let $P(l)$ be the matrix that contains all elements of P that correspond to a "reward" of l . We have :

$$\phi(k, n) = \sum_{l=0}^{+\infty} \phi(k-l, n-1)P(l) + I f(n)f(k)$$

with transform

$$\varphi(s, z) = \varphi(s, z)\psi(s)z + I$$

where $\psi(s) = \sum_{l=0}^{+\infty} P(l)s^l$

As before :

$$\varphi(s, z) = [I - \psi(s)z]^{-1}$$

$$\varphi(s, n) = [\psi(s)]^n.$$

note:

(6)

1. we can find average number of rewards in $0, 1, \dots, n-1$ as before (it was a particular case when $\psi(s) = P(0) + P(1)s$)
2. each transition $i \rightarrow j$ has a "label" $\psi_{ij}(s)$
3. in $\psi(s, z)$, s labels successes and z labels ~~the~~ the number of transitions.
4. the label on each transition does not need to be a single term. That is, we can have

$$\psi_{ij}(s) = \sum_{l=0}^{+\infty} P_{ij}^*(l) s^l$$

where $P_{ij}^*(l)$ is the probability of transition $i \rightarrow j$ and that the metric has the value l .

Properties of $\psi_{ij}(s)$:

a) $\psi_{ij}(1) = P_{ij}$; $\psi(1) = P$

b) $\frac{\psi_{ij}(s)}{P_{ij}}$ is the generating function of the distribution of the metric given the transition.

c) $\psi'_{ij}(1) = \left. \frac{d\psi_{ij}}{ds} \right|_{s=1} = P_{ij} \cdot \text{average metric on } i \rightarrow j$

d) if the metric is the reward, $R_i = \sum_{j \neq i} \psi'_{ij}(1)$
(average reward for a visit to state i)

5. We can define multiple metrics,
i.e., \underline{s} could be a vector (s_1, s_2, \dots)
In this case, the average becomes:

$$P_{ij} \text{ - average of the } k\text{-th metric on } ij = \frac{\partial \psi_{ij}(s_1, s_2, \dots)}{\partial s_k} \Big|_{\underline{s} = \underline{1}}$$

6. How to compute $\psi_{ij}(\underline{s})$:

a) let $E(i, j)$ be the set of all events that correspond to a transition from state i to state j

b) let $P[A]$ the probability of event A

c) let $\underline{s}(A) = s_1^{l_1(A)} s_2^{l_2(A)} \dots$ where $l_k(A)$ is the value of the k -th metric that corresponds to the event A .

d) we have:

$$\psi_{ij}(\underline{s}) = \sum_{A \in E(i, j)} P[A] \underline{s}(A)$$

$$\text{note that } \psi_{ij}(\underline{1}) = \sum_{A \in E(i, j)} P[A] = P_{ij}$$

Example: GBN with iid feedback
emissions (prob. δ).

(8)

Table of possible events:

from	to	prob.	reward	time
G	G	$(1-\delta) p_{00}$	1	1
G	B	$(1-\delta) p_{01}$	1	1
G	G	$\delta p_{00}(m)$	ρ	m
G	B	$\delta p_{01}(m)$	0	m
B	G	$(1-\delta) p_{10}(m)$	ρ	m
B	B	$(1-\delta) p_{11}(m)$	0	m
B	G	$\delta p_{10}(m)$	ρ	m
B	B	$\delta p_{11}(m)$	0	m

$$\psi(s_1, s_2) = \begin{pmatrix} (1-\delta) p_{00} s_1 s_2 + \delta p_{00}(m) s_2^m & (1-\delta) p_{01} s_1 s_2 + \delta p_{01}(m) s_2^m \\ p_{10}(m) s_2^m & p_{11}(m) s_2^m \end{pmatrix}$$

(9)

$$P = \psi(1,1) = \begin{pmatrix} (1-s)p_{00} + s p_{00}(m) & (1-s)p_{01} + s p_{01}(m) \\ p_{10}(m) & p_{11}(m) \end{pmatrix}$$

$$\bar{n}_G = \frac{p_{10}(m)}{p_{10}(m) + (1-s)p_{01} + s p_{01}(m)} ; \bar{n}_B = 1 - \bar{n}_G$$

R_{ij} are the elements of

$$\left. \frac{\partial \psi}{\partial s_1} \right|_{s_1=s_2=1} = \begin{pmatrix} (1-s)p_{00} & (1-s)p_{01} \\ 0 & 0 \end{pmatrix}$$

T_{ij} are the elements of

$$\left. \frac{\partial \psi}{\partial s_2} \right|_{s_1=s_2=1} = \begin{pmatrix} (1-s)p_{00} + m s p_{00}(m) & (1-s)p_{01} + m s p_{01}(m) \\ m p_{10}(m) & m p_{11}(m) \end{pmatrix}$$

$$\underline{R} = \left. \frac{\partial \psi}{\partial s_1} \right|_{s_1=s_2=1} \cdot \begin{pmatrix} 1 \\ 1 \end{pmatrix} = \begin{pmatrix} 1-s \\ 0 \end{pmatrix}$$

$$\underline{T} = \left. \frac{\partial \psi}{\partial s_2} \right|_{s_1=s_2=1} \cdot \begin{pmatrix} 1 \\ 1 \end{pmatrix} = \begin{pmatrix} 1-s + m s \\ m \end{pmatrix}$$

$$\text{throughput} = \frac{\bar{n}_G R_G + \bar{n}_B R_B}{\bar{n}_G T_G + \bar{n}_B T_B} = \frac{(1-s) p_{10}(m)}{(1-s + m s) p_{10}(m) + m [(1-s)p_{01} + s p_{01}(m)]}$$