

# Lecture 5

## More on perfect secrecy

Nicola Laurenti      October 14, 2020



Except where otherwise stated, this work is licensed under the  
Creative Commons Attribution-ShareAlike 4.0 International License.

# Lecture 5— Contents

Review of basic Information Theory notions


The price of perfect secrecy

- Necessary condition


- Unconditional secrecy

Classification of attacks

# Security goals, threats, services and mechanisms



# Visualization of entropy relationships



## Chain rules for (conditional) entropy

Some basic properties of entropy:

1.  $H(x, z) \geq H(x)$
2.  $H(x|z) \leq H(x)$
3.  $H(x, z) = H(x|z) + H(z)$

They can be generalized to any collection of rvs  $x_1, \dots, x_n, y_1, \dots, y_m, z_1, \dots, z_\ell$  as the following chain rules:

1.  $H(x_1, \dots, x_n, z_1, \dots, z_\ell | y_1, \dots, y_m) \geq H(x_1, \dots, x_n | y_1, \dots, y_m)$ , entropy increases with more conditioned variables
2.  $H(x_1, \dots, x_n | y_1, \dots, y_m, z_1, \dots, z_\ell) \leq H(x_1, \dots, x_n | y_1, \dots, y_m)$ , entropy decreases with more conditioning variables
3.  $H(x_1, \dots, x_n, z_1, \dots, z_\ell | y_1, \dots, y_m) = H(x_1, \dots, x_n | y_1, \dots, y_m, z_1, \dots, z_\ell) + H(z_1, \dots, z_\ell | y_1, \dots, y_m)$

# Necessary condition for perfect secrecy

## Theorem

*A necessary condition for perfect secrecy and decodability is that*

$$H(k) \geq H(u)$$

## Proof.

Assume perfect secrecy holds, that is  $u$  is independent of  $x$ . Then,

$$\begin{aligned} H(u) &= H(u|x) && \text{by independence of } u, x \\ &\leq H(u, k|x) && \text{by chain rule 1} \\ &= H(u|x, k) + H(k|x) && \text{by chain rule 3} \\ &= H(k|x) && \text{by perfect decodability} \\ &\leq H(k) && \text{by chain rule 2} \end{aligned}$$

## Necessary condition for perfect secrecy (cont.)

### Corollary

*In a system with perfect secrecy for all message distributions  $p_u$  we have*

$$\log_2 |\mathcal{K}| \geq H(k) \geq \log_2 |\mathcal{M}|$$

### Proof.

$H(k) \leq \log_2 |\mathcal{K}|$  is the upper bound for entropy.

From the previous theorem  $H(k) \geq H(u)$  must hold for any  $p_u$ .

In particular, for uniform  $u \sim \mathcal{U}(\mathcal{M})$ , where  $H(u) = \log_2 |\mathcal{M}|$ . □

### Corollary

*In a system with  $\mathcal{M} = \mathcal{A}^{\ell_u}$ ,  $\mathcal{K} = \mathcal{A}^{\ell_k}$ , and perfect secrecy, it is  $\ell_k \geq \ell_u$*

So, in order to have perfect secrecy, the key must be “at least as long as” the message.

## Why “one-time”?

We may wonder if, in case several messages  $u_1, u_2, \dots$  need to be encrypted, the same key  $k$  can be reused **without sacrificing perfect secrecy**, that is

$$x_1 = E_k(u_1) \quad , \quad x_2 = E_k(u_2) \quad , \quad x_3 = E_k(u_3) \quad , \quad \dots$$

Alas! This is not possible. In fact, observe that the above problem can be viewed as the encryption of a large plaintext message  $u = (u_1, u_2, \dots)$  into a large ciphertext  $x = (x_1, x_2, \dots)$  with the same key  $k$ .

So, the entropy of  $u$  increases with each  $u_i$ , while that of  $k$  remains constant, eventually violating the necessary condition for perfect secrecy

### Example

In fact, it turns out that by reusing  $k$ ,  $u$  is no longer statistically independent from  $x$ . For instance if  $u_1 = u_2$ , it must also be  $x_1 = x_2$

Repeated use of the same key can only offer **computational secrecy**



## More properties of the Kullback-Leibler divergence

1. **(relation with entropy)** If  $x, y$  are discrete and  $y \sim \mathcal{U}(\mathcal{A}_x)$ ,  $D(p_x \| p_y) = H(y) - H(x)$ .

Proof:

$$D(p_x \| p_y) = \mathbb{E} \left[ \log_2 \frac{p_x(x)}{p_y(x)} \right] = \mathbb{E} [\log_2 p_x(x)] - \mathbb{E} [\log_2 p_y(x)] = -H(x) + \log_2 |\mathcal{A}_x|$$

2. **(relation with mutual information)** Let  $x, y$  have joint pmd  $p_{xy}$  and let  $x', y'$  be independent rvs with  $p_{x'} = p_x$  and  $p_{y'} = p_y$ . Then,

$$\begin{aligned} D(p_{xy} \| p_{x'y'}) &= \mathbb{E} \left[ \log_2 \frac{p_{xy}(x, y)}{p_{x'y'}(x, y)} \right] = \mathbb{E} \left[ \log_2 \frac{p_{xy}(x, y)}{p_{x'}(x)p_{y'}(y)} \right] \\ &= \mathbb{E} \left[ \log_2 \frac{p_{xy}(x, y)}{p_x(x)p_y(y)} \right] = I(x, y) \quad (\text{aka } D(p_{xy} \| p_x p_y)) \end{aligned}$$

## Measuring unconditional (not perfect) secrecy

For a non perfect secrecy system  $M$

$$\begin{aligned} d(M, M^*) &= \max_{a \in \mathcal{M}} d_V(p_{\tilde{u}x|u=a}, p_{\tilde{u}^*x^*|u^*=a}) \\ &\leq \max_{a \in \mathcal{M}} d_V(p_{\tilde{u}x|u=a}, p_{\tilde{u}^*x|u^*=a}) + d_V(p_{\tilde{u}^*x|u=a}, p_{\tilde{u}^*x^*|u^*=a}) \\ &\leq \max_{a \in \mathcal{M}} \mathbb{P}[\tilde{u} \neq u | u = a] + d_V(p_{ux}, p_u p_x) \end{aligned}$$

Then, by Pinsker inequality

$$\begin{aligned} &\leq \max_{a \in \mathcal{M}} \mathbb{P}[\tilde{u} \neq u | u = a] + \frac{1}{2} \sqrt{D(p_{ux} \| p_u p_x)} \\ &= \max_{a \in \mathcal{M}} \mathbb{P}[\tilde{u} \neq u | u = a] + \frac{1}{2} \sqrt{I(u, x)} \end{aligned}$$

If in a system  $M$ , we have  $\mathbb{P}[\tilde{u} \neq u | u = a] \leq \varepsilon'$  and  $I(u, x) \leq \varepsilon''$ , then it is  $\varepsilon$ -unconditionally secure with  $\varepsilon = \varepsilon' + \frac{1}{2} \sqrt{\varepsilon''}$

## Classification of attacks against encryption

The attacks carried out against an encryption method **reusing the same key for many instances** are classified according to:

**known ciphertext attacks (KCA)** after **observing  $N$  ciphertexts**  $x_1, \dots, x_N$  the attacker aims to find  $u_N$ , or the key  $k$

**known plaintext attacks (KPA)** after **observing  $N - 1$  ciphertexts-plaintext pairs**  $(u_1, x_1), \dots, (u_{N-1}, x_{N-1})$  and the ciphertext  $x_N$  the attacker aims to find the plaintext  $u_N$ , or the key  $k$

**chosen plaintext attacks (CPA)** the attacker is allowed to access the encoder  $E_k$ ; he can **choose  $N - 1$  plaintext values**  $a_1, \dots, a_{N-1} \in \mathcal{M}$  and **learn the corresponding ciphertext values**  $b_1, \dots, b_{N-1} \in \mathcal{X}$ , with  $b_i = E_k(a_i)$ . Then he aims to find the plaintext  $u_N$ , or the key  $k$  from the observation of  $x_N$

**chosen ciphertext attacks (CCA)** the attacker is allowed to temporarily access the decoder  $D_k$ ; he can **choose  $N - 1$  ciphertext values**  $b_1, \dots, b_{N-1} \in \mathcal{X}$  and **learn the corresponding plaintexts**  $a_1, \dots, a_{N-1} \in \mathcal{M}$ . Then he aims to find the plaintext  $u_N$ , or the key  $k$  from the observation of  $x_N$

# Classification of attacks against encryption

## Ordering of attacks

In increasing order of strength (or information available to the attacker) we have

$$\text{KCA} < \text{KPA} < \text{CPA} < \text{KCA}$$

Which of the above attack classes can break a “one-time pad” reusing the same key  $k$ ?

# Summary


In this lecture we have:

- ▶ reviewed basic notions of Information Theory:
  - ▶ entropy of a rv
  - ▶ joint and conditional entropies
  - ▶ mutual information
- ▶ stated a necessary condition for perfect secrecy
- ▶ introduced unconditional secrecy measures
- ▶ classified attacks according to the information available to the attackers

## Assignment

- ▶ class notes
- ▶ textbook, §3.4–§3.6

## End of lecture



THROUGH 20 YEARS OF EFFORT, WE'VE SUCCESSFULLY TRAINED EVERYONE TO USE PASSWORDS THAT ARE HARD FOR HUMANS TO REMEMBER, BUT EASY FOR COMPUTERS TO GUESS.

this comic reproduced from [xkcd](https://xkcd.com/936) URL: [xkcd.com/936](https://xkcd.com/936)