

Randomized quicksort

IDEA: Partition around a *random* element.

- Running time is independent of the input order.
- No assumptions need to be made about the input distribution.
- No specific input elicits the worst-case behavior.
- The worst case is determined only by the output of a random-number generator.

Randomized quicksort analysis

Let $T(n)$ = the random variable for the running time of randomized quicksort on an input of size n , assuming random numbers are independent.

For $k = 0, 1, \dots, n-1$, define the *indicator random variable*

$$X_k = \begin{cases} 1 & \text{if PARTITION generates a } k : n-k-1 \text{ split,} \\ 0 & \text{otherwise.} \end{cases}$$

$E[X_k] = \Pr\{X_k = 1\} = 1/n$, since all splits are equally likely, assuming elements are distinct.

Analysis (continued)

$$T(n) = \begin{cases} T(0) + T(n-1) + \Theta(n) & \text{if } 0 : n-1 \text{ split,} \\ T(1) + T(n-2) + \Theta(n) & \text{if } 1 : n-2 \text{ split,} \\ \vdots & \\ T(n-1) + T(0) + \Theta(n) & \text{if } n-1 : 0 \text{ split,} \end{cases}$$
$$= \sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n)).$$

Calculating expectation

$$E[T(n)] = E\left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n))\right]$$

Take expectations of both sides.

Calculating expectation

$$\begin{aligned} E[T(n)] &= E\left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n))\right] \\ &= \sum_{k=0}^{n-1} E[X_k (T(k) + T(n-k-1) + \Theta(n))] \end{aligned}$$

Linearity of expectation.

Calculating expectation

$$\begin{aligned} E[T(n)] &= E\left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n))\right] \\ &= \sum_{k=0}^{n-1} E[X_k (T(k) + T(n-k-1) + \Theta(n))] \\ &= \sum_{k=0}^{n-1} E[X_k] \cdot E[T(k) + T(n-k-1) + \Theta(n)] \end{aligned}$$

Independence of X_k from other random choices.

Calculating expectation

$$\begin{aligned} E[T(n)] &= E\left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n))\right] \\ &= \sum_{k=0}^{n-1} E[X_k (T(k) + T(n-k-1) + \Theta(n))] \\ &= \sum_{k=0}^{n-1} E[X_k] \cdot E[T(k) + T(n-k-1) + \Theta(n)] \\ &= \frac{1}{n} \sum_{k=0}^{n-1} E[T(k)] + \frac{1}{n} \sum_{k=0}^{n-1} E[T(n-k-1)] + \frac{1}{n} \sum_{k=0}^{n-1} \Theta(n) \end{aligned}$$

Linearity of expectation; $E[X_k] = 1/n$.

Calculating expectation

$$\begin{aligned} E[T(n)] &= E\left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n))\right] \\ &= \sum_{k=0}^{n-1} E[X_k (T(k) + T(n-k-1) + \Theta(n))] \\ &= \sum_{k=0}^{n-1} E[X_k] \cdot E[T(k) + T(n-k-1) + \Theta(n)] \\ &= \frac{1}{n} \sum_{k=0}^{n-1} E[T(k)] + \frac{1}{n} \sum_{k=0}^{n-1} E[T(n-k-1)] + \frac{1}{n} \sum_{k=0}^{n-1} \Theta(n) \\ &= \frac{2}{n} \sum_{k=1}^{n-1} E[T(k)] + \Theta(n) \end{aligned}$$

Summations have identical terms.

Hairy recurrence

$$E[T(n)] = \frac{2}{n} \sum_{k=2}^{n-1} E[T(k)] + \Theta(n)$$

(The $k = 0, 1$ terms can be absorbed in the $\Theta(n)$.)

Prove: $E[T(n)] \leq an \lg n$ for constant $a > 0$.

- Choose a large enough so that $an \lg n$ dominates $E[T(n)]$ for sufficiently small $n \geq 2$.

Use fact: $\sum_{k=2}^{n-1} k \lg k \leq \frac{1}{2} n^2 \lg n - \frac{1}{8} n^2$

Substitution method

$$E[T(n)] \leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n)$$

Substitute inductive hypothesis.

Substitution method

$$\begin{aligned} E[T(n)] &\leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n) \\ &\leq \frac{2a}{n} \left(\frac{1}{2} n^2 \lg n - \frac{1}{8} n^2 \right) + \Theta(n) \end{aligned}$$

Use fact.

Substitution method

$$\begin{aligned} E[T(n)] &\leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n) \\ &\leq \frac{2a}{n} \left(\frac{1}{2} n^2 \lg n - \frac{1}{8} n^2 \right) + \Theta(n) \\ &= an \lg n - \left(\frac{an}{4} - \Theta(n) \right) \end{aligned}$$

Express as *desired – residual*.

Substitution method

$$\begin{aligned} E[T(n)] &\leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n) \\ &= \frac{2a}{n} \left(\frac{1}{2} n^2 \lg n - \frac{1}{8} n^2 \right) + \Theta(n) \\ &= an \lg n - \left(\frac{an}{4} - \Theta(n) \right) \\ &\leq an \lg n, \end{aligned}$$

if a is chosen large enough so that $an/4$ dominates the $\Theta(n)$.

Quicksort in practice

- Quicksort is a great general-purpose sorting algorithm.
- Quicksort is typically over twice as fast as merge sort.
- Quicksort can benefit substantially from *code tuning*.
- Quicksort behaves well even with caching and virtual memory.