



(<https://www.udemy.com/user/joseportilla/>)

Content Copyright by Pierian Data

Functions and Methods Homework Solutions

Write a function that computes the volume of a sphere given its radius.

```
In [1]: def vol(rad):  
        return (4/3)*(3.14)*(rad**3)
```

```
In [2]: # Check  
        vol(2)
```

```
Out[2]: 33.49333333333333
```

Write a function that checks whether a number is in a given range (inclusive of high and low)

```
In [3]: def ran_check(num,low,high):  
        #Check if num is between low and high (including low and high)  
        if num in range(low,high+1):  
            print('{} is in the range between {} and {}'.format(num,low,high))  
        else:  
            print('The number is outside the range.')
```

```
In [4]: # Check  
        ran_check(5,2,7)
```

5 is in the range between 2 and 7

If you only wanted to return a boolean:

```
In [5]: def ran_bool(num,low,high):  
        return num in range(low,high+1)
```

```
In [6]: ran_bool(3,1,10)
```

```
Out[6]: True
```

Write a Python function that accepts a string and calculates the number of upper case letters and lower case letters.

Sample String : 'Hello Mr. Rogers, how are you this fine Tuesday?'

Expected Output :

No. of Upper case characters : 4

No. of Lower case Characters : 33

If you feel ambitious, explore the Collections module to solve this problem!

```
In [7]: def up_low(s):  
        d={"upper":0, "lower":0}  
        for c in s:  
            if c.isupper():  
                d["upper"]+=1  
            elif c.islower():  
                d["lower"]+=1  
            else:  
                pass  
        print("Original String : ", s)  
        print("No. of Upper case characters : ", d["upper"])  
        print("No. of Lower case Characters : ", d["lower"])
```

```
In [8]: s = 'Hello Mr. Rogers, how are you this fine Tuesday?'  
        up_low(s)
```

Original String : Hello Mr. Rogers, how are you this fine Tuesday?

No. of Upper case characters : 4

No. of Lower case Characters : 33

Write a Python function that takes a list and returns a new list with unique elements of the first list.

Sample List : [1,1,1,1,2,2,3,3,3,3,4,5]

Unique List : [1, 2, 3, 4, 5]

```
In [9]: def unique_list(lst):  
        # Also possible to use list(set())  
        x = []  
        for a in lst:  
            if a not in x:  
                x.append(a)  
        return x
```

```
In [10]: unique_list([1,1,1,1,2,2,3,3,3,3,4,5])
```

```
Out[10]: [1, 2, 3, 4, 5]
```

Write a Python function to multiply all the numbers in a list.

Sample List : [1, 2, 3, -4]

Expected Output : -24

```
In [11]: def multiply(numbers):  
        total = 1  
        for x in numbers:  
            total *= x  
        return total
```

```
In [12]: multiply([1,2,3,-4])
```

```
Out[12]: -24
```

Write a Python function that checks whether a word or phrase is palindrome or not.

Note: A palindrome is word, phrase, or sequence that reads the same backward as forward, e.g., madam,kayak,racecar, or a phrase "nurses run". Hint: You may want to check out the .replace() method in a string to help out with dealing with spaces. Also google search how to reverse a string in Python, there are some clever ways to do it with slicing notation.

```
In [13]: def palindrome(s):  
        s = s.replace(' ','') # This replaces all spaces ' ' with no space ''. (Fixes  
        return s == s[::-1] # Check through slicing
```

```
In [14]: palindrome('nurses run')
```

```
Out[14]: True
```

```
In [15]: palindrome('abcba')
```

```
Out[15]: True
```

Hard:

Write a Python function to check whether a string is pangram or not. (Assume the string passed in does not have any punctuation)

Note : Pangrams are words or sentences containing every letter of the alphabet at least once.

For example : "The quick brown fox jumps over the lazy dog"

Hint: You may want to use `.replace()` method to get rid of spaces.

Hint: Look at the [string module \(https://stackoverflow.com/questions/16060899/alphabet-range-in-python\)](https://stackoverflow.com/questions/16060899/alphabet-range-in-python)

Hint: In case you want to use [set comparisons \(https://medium.com/better-programming/a-visual-guide-to-set-comparisons-in-python-6ab7edb9ec41\)](https://medium.com/better-programming/a-visual-guide-to-set-comparisons-in-python-6ab7edb9ec41)

```
In [7]: import string

def ispangram(str1, alphabet=string.ascii_lowercase):
    # Create a set of the alphabet
    alphasets = set(alphabet)

    # Remove spaces from str1
    str1 = str1.replace(" ", '')

    # Lowercase all strings in the passed in string
    # Recall we assume no punctuation
    str1 = str1.lower()

    # Grab all unique letters in the string as a set
    str1 = set(str1)

    # Now check that the alphabet set is same as string set
    return str1 == alphasets
```

```
In [8]: ispangram("The quick brown fox jumps over the lazy dog")
```

```
Out[8]: True
```

```
In [18]: string.ascii_lowercase
```

```
Out[18]: 'abcdefghijklmnopqrstuvwxyz'
```