



(<https://www.udemy.com/user/joseportilla/>)

Content Copyright by Pierian Data

***args and **kwargs**

Work with Python long enough, and eventually you will encounter `*args` and `**kwargs`. These strange terms show up as parameters in function definitions. What do they do? Let's review a simple function:

```
In [1]: def myfunc(a,b):  
        return sum((a,b))*0.05  
  
myfunc(40,60)
```

Out[1]: 5.0

This function returns 5% of the sum of **a** and **b**. In this example, **a** and **b** are *positional* arguments; that is, 40 is assigned to **a** because it is the first argument, and 60 to **b**. Notice also that to work with multiple positional arguments in the `sum()` function we had to pass them in as a tuple.

What if we want to work with more than two numbers? One way would be to assign a *lot* of parameters, and give each one a default value.

```
In [2]: def myfunc(a=0,b=0,c=0,d=0,e=0):  
        return sum((a,b,c,d,e))*0.05  
  
myfunc(40,60,20)
```

Out[2]: 6.0

Obviously this is not a very efficient solution, and that's where `*args` comes in.

***args**

When a function parameter starts with an asterisk, it allows for an *arbitrary number* of arguments, and the function takes them in as a tuple of values. Rewriting the above function:

```
In [3]: def myfunc(*args):  
        return sum(args)*.05  
  
myfunc(40,60,20)
```

Out[3]: 6.0

Notice how passing the keyword "args" into the `sum()` function did the same thing as a tuple of arguments.

It is worth noting that the word "args" is itself arbitrary - any word will do so long as it's preceded by an asterisk. To demonstrate this:

```
In [4]: def myfunc(*spam):  
        return sum(spam)*.05  
  
myfunc(40,60,20)
```

Out[4]: 6.0

****kwargs**

Similarly, Python offers a way to handle arbitrary numbers of *keyworded* arguments. Instead of creating a tuple of values, `**kwargs` builds a dictionary of key/value pairs. For example:

```
In [5]: def myfunc(**kwargs):  
        if 'fruit' in kwargs:  
            print(f"My favorite fruit is {kwargs['fruit']}") # review String Formatting  
        else:  
            print("I don't like fruit")  
  
myfunc(fruit='pineapple')
```

My favorite fruit is pineapple

```
In [6]: myfunc()
```

I don't like fruit

***args and **kwargs combined**

You can pass `*args` and `**kwargs` into the same function, but `*args` have to appear before `**kwargs`

```
In [7]: def myfunc(*args, **kwargs):
        if 'fruit' and 'juice' in kwargs:
            print(f"I like {' and '.join(args)} and my favorite fruit is {kwargs['fruit']}")
            print(f"May I have some {kwargs['juice']} juice?")
        else:
            pass

myfunc('eggs', 'spam', fruit='cherries', juice='orange')
```

I like eggs and spam and my favorite fruit is cherries
May I have some orange juice?

Placing keyworded arguments ahead of positional arguments raises an exception:

```
In [8]: myfunc(fruit='cherries', juice='orange', 'eggs', 'spam')

File "<ipython-input-8-fc6ff65addcc>", line 1
    myfunc(fruit='cherries', juice='orange', 'eggs', 'spam')
                                                ^
SyntaxError: positional argument follows keyword argument
```

As with "args", you can use any name you'd like for keyworded arguments - "kwargs" is just a popular convention.

That's it! Now you should understand how `*args` and `**kwargs` provide the flexibility to work with arbitrary numbers of arguments!