

Shell Basics

Shells

- A shell can be used in one of two ways:
 - ~ *A command interpreter*, used interactively
 - ~ *A programming language*, to write shell scripts (your own custom commands)

Shell Script

- A shell script is just a file containing shell commands, but with a few extras:
 - The first line of a shell script should be a comment of the following form:
 - `#!/bin/sh`
- for a Bourne shell script. Bourne shell scripts are the most common, since C Shell scripts have buggy features.
- A shell script must be readable and executable.
 - `chmod u+rx scriptname`
- As with any command, a shell script has to be “in your path” to be executed.
- If “.” is not in your PATH, you must specify “./scriptname” instead of just “scriptname”

Shell Script Example

- Here is a “hello world” shell script:
 - `$ ls -l`
 - `-rwxr-xr-x 1 <user> 48 Feb 08 19:50 hello*`
 - `$ cat hello`
 - `#!/bin/sh`
 - `# comment lines start with the # character`
 - `echo "Hello world"`
 - `$ hello`
 - `Hello world`
 - `$`
- The `echo` command functions like a print command in shell scripts.

Shell Variables

- The user variable name can be any sequence of letters, digits, and the underscore character, but the first character must be a letter.
- To assign a value to a variable:
 - `number=25`
 - `name="ABC XYZ"`
- There cannot be any space before or after the "="
- Internally, all values are stored as strings.

Shell Variables

- To use a variable, precede the name with a "\$":

```
⋈ $ cat test1
⋈ #!/bin/sh
⋈ number=25
⋈ name="XYZ ABC"
⋈ echo "$number $name"
⋈ $ test1
⋈ 25 XYZ ABC
⋈ $
```

Shell Variables

- Use the `read` command to get and store input from the user.

```
$ cat test2
#!/bin/sh
echo "Enter name: "
read name
echo "Enter Course: "
read number
echo "Enter Year: "
read y
echo "$name is studying in
$number $y year"
```

```
$ test2
Enter name:
XYZ
Enter Course:
B.Tech.
Enter Year
3rd
XYZ is studying in B.Tech. 3rd year
```

Variables in Shell

- In UNIX (Shell), there are 2 types of variables:
 - **System variables** - Created and maintained by Linux itself. This type of variable defined in CAPITAL LETTERS.
 - **User defined variables (UDV)** - Created and maintained by user. This type of variable defined in `{(a-z)+(0-9)+_}`* not starting with a digit.

Variables in Shell (cntd...)

Defining Variables

- variable_name=variable_value
- Variables of this type are called scalar variables. A **scalar** variable can hold only one value at a time.
- The shell enables us to store any value you want in a variable.
 - VAR1="Zara Ali"
 - VAR2=100

Variables in Shell (cntd...)

Accessing Variable Values

- To access the value stored in a variable, prefix its name with the dollar sign (\$)
 - For example, following script would access the value of defined variable NAME and would print it on STDOUT:

```
#!/bin/sh
```

```
NAME="XYZ"
```

```
echo $NAME
```

This would produce following value:

```
XYZ
```

Variables in Shell (cntd...)

Read-only Variables

- The shell provides a way to mark variables as read-only by using the readonly command.
- After a variable is marked read-only, its value cannot be changed.

```
#!/bin/sh
```

```
NAME="DEEKAY"
```

```
readonly NAME
```

```
NAME="DIVYA"
```

This would produce following result: /bin/sh: NAME: This variable is read only.

Variables in Shell (cntd...)

Unsetting Variables

- Unsetting or deleting a variable tells the shell to remove the variable from the list of variables that it tracks.
- Once you unset a variable, you would not be able to access stored value in the variable.

```
#!/bin/sh
```

```
NAME="XYZ"
```

```
unset NAME
```

```
echo $NAME
```

Above example would not print anything.

>>You cannot use the unset command to **unset** variables that are marked **readonly**.

Variables in Shell (cntd...)

Null Variables

- You can define NULL variable as follows (NULL variable is variable which has no value at the time of definition)

For e.g.

```
$ vech=
```

```
$ vech=""
```

Try to print it's value by issuing following command:

```
$ echo $vech
```

Nothing will be shown because variable has no value i.e. NULL variable.

Variables in Shell (cntd...)

Special Variables

- That we can't use as normal variables.

Variables	Description
\$0	The filename of the current script.
\$n	These variables correspond to the arguments with which a script was invoked. Here n is a positive decimal number corresponding to the position of an argument (the first argument is \$1, the second argument is \$2, and so on).
\$#	The number of arguments supplied to a script.
\$*	All the arguments are double quoted. If a script receives two arguments, \$* is equivalent to \$1 \$2.

Variables in Shell (cntd...)

Special Variables

Variables	Description
<code>\$@</code>	All the arguments are individually double quoted. If a script receives two arguments, <code>\$@</code> is equivalent to <code>\$1 \$2</code> .
<code>\$?</code>	The exit status of the last command executed.
<code>\$\$</code>	The process number of the current shell. For shell scripts, this is the process ID under which they are executing.
<code>#!</code>	The process number of the last background command.

Variables in Shell (cntd...)

- **Special Variables**

- The command-line arguments \$1, \$2, \$3,...\$9 are positional parameters, with \$0 pointing to the actual command, program, shell script, or function and \$1, \$2, \$3, ...\$9 as the arguments to the command.

Variables in Shell (cntd...)

```
#!/bin/sh
```

```
echo "File Name: $0"
```

```
echo "First Parameter : $1"
```

```
echo "Second Parameter : $2"
```

```
echo "Quoted Values: $@"
```

```
echo "Quoted Values: $*"
```

```
echo "Total Number of Paramers : $#"
```

OUTPUT

```
./test.sh divya kumar
```

```
File Name : ./test.sh
```

```
First Parameter : divya
```

```
Second Parameter : kumar
```

```
Quoted Values: divya kumar
```

```
Quoted Values: divya kumar
```

```
Total Number of Paramers : 2
```

Variables in Shell (cntd...)

- **Special Parameters \$* & \$@**

- The "\$*" special parameter takes the entire list as one argument with spaces between.
- The "\$@" special parameter takes the entire list and separates it into separate arguments.

Variables in Shell (cntd...)

- **Special Parameters \$* & @\$**

```
#!/bin/sh
```

```
for TOKEN in $*
```

```
do
```

```
echo $TOKEN
```

```
done
```

OUTPUT

```
./test.sh divya kumar 25 Years Old
```

```
divya
```

```
kumar
```

```
25
```

```
Years
```

```
Old
```

EXIT Status

- The `$?` variable represents the exit status of the previous command.
- Exit status is a numerical value returned by every command upon its completion.
- As a rule, most commands return an exit status of 0 if they were successful, and 1 if they were unsuccessful.

Special Characters & Quoting

- List of Special Characters and what they mean

<RETURN> Execute command

Start a comment

<SPACE> Argument separator

` Command substitution

" Weak Quotes

' Strong Quotes

\ Single Character Quote

Special Characters & Quoting (cntd...)

- List of Special Characters and what they mean

&	Run program in background
?	Match one character
*	Match any number of characters
;	Command separator
::	End of Case statement

Special Characters & Quoting (cntd...)

- List of Special Characters and what they mean

~ Home Directory

~user User's Home Directory

! History of Commands (csh only)

\$# Number of arguments to script

\$* Arguments to script

\$@ Original arguments to script

Special Characters & Quoting (cntd...)

- List of Special Characters and what they mean

`$?` Status of previous command

`$$` Process identification number

`$!` PID of last background job

`&&` Short-circuit AND

`||` Short-circuit OR

`[]` Match range of characters OR Test

Special Characters & Quoting (cntd...)

- List of Special Characters and what they mean

`(cmd;cmd)` Runs `cmd;cmd` as a sub-shell

`{cmd;cmd }` Runs `cmd;cmd` without subshell

`>file` Output to

`>>file` Append output to

`<file` Input from

Special Characters & Quoting (cntd...)

- **Quoting** is used to remove the special meaning of certain characters or words to the shell.
- Quoting can be used to disable special treatment for special characters, to prevent reserved words from being recognized as such, and to prevent parameter expansion.

Special Characters & Quoting (cntd...)

- **Backslash (\)**

Any character immediately following the backslash loses its special meaning.

Special Characters & Quoting (cntd...)

- **Single quote (')**

All special characters between these quotes lose their special meaning.

```
echo <-$1500.**>; (update?) [y|n]
```

```
echo \<-\$1500.\*\*\>\; \ (update\?\) \ [y\|n\]
```

```
echo '<-$1500.**>; (update?) [y|n]'
```

Special Characters & Quoting (cntd...)

- **Single quote (')**

>> HOW TO CORRECTLY WRITE...??

echo divya's book

Special Characters & Quoting (cntd...)

- **Double quote (“)**

Enclosing characters in **double quotes** preserves the literal value of all characters within the quotes, with the exception of \$, `, and \.

Special Characters & Quoting (cntd...)

- **Double quote (“)**

\$ for parameter substitution.

Backquotes for command substitution.

\\$ to enable literal dollar signs.

\` to enable literal backquotes.

\" to enable embedded double quotes.

\\ to enable embedded backslashes.

Special Characters & Quoting (cntd...)

```
VAR=BOB
```

```
echo '$VAR owes -$15; [ on (`date +%m/%d`)]'
```

```
>>>>>$VAR owes -$15; [ on (`date +%m/%d`)]
```

```
echo "$VAR owes -$15; [ on (`date +%m/%d`)]"
```

```
>>>>> BOB owes -$15; [ on (03/05) ]
```


Operators in Shell

- There are following operators which we are going to discuss:
- Arithmetic Operators.
- Relational Operators.
- Boolean Operators.
- String Operators.
- File Test Operators.

Operators in Shell (cntd...)

- **Arithmetic Operators**

- Assume variable a holds 10 and variable b holds 20 then:

- + `expr \$a + \$b` will give 30
- - `expr \$a - \$b` will give -10
- * `expr \$a * \$b` will give 200
- / `expr \$b / \$a` will give 2
- % `expr \$b % \$a` will give 0 (modulus or reminder)
- = a=\$b will assign value of b into a (Assignment)
- == [\$a == \$b] would return false (equality)
- != [\$a != \$b] would return true (inequality)

- Mind the space for the last 2

Operators in Shell (cntd...)

- **Relational Operators**

- Assume variable a holds 10 and variable b holds 20 then:

- -eq [\$a -eq \$b] is not true.
 - -ne [\$a -ne \$b] is true.
 - -gt [\$a -gt \$b] is not true.
 - -lt [\$a -lt \$b] is true.
 - -ge [\$a -ge \$b] is not true.
 - -le [\$a -le \$b] is true.

Operators in Shell (cntd...)

- **Relational Operators**

Example:

```
#!/bin/sh
```

```
a=10 b=20
```

```
if [ $a -eq $b ]
```

```
then
```

```
    echo "$a -eq $b : a is equal to b"
```

```
else
```

```
    echo "$a -eq $b: a is not equal to b"
```

```
fi
```

Operators in Shell (cntd...)

- **Boolean Operators**

–Assume variable a holds 10 and variable b holds 20 then:

! This is logical negation.

[! false] is true.

-o This is logical OR.

[\$a -lt 20 -o \$b -gt 100] is true.

-a This is logical AND.

[\$a -lt 20 -a \$b -gt 100] is false.

Operators in Shell (cntd...)

- String Operators (=, !=)

Example:

```
#!/bin/sh
```

```
a="abc"
```

```
b="efg"
```

```
if [ $a = $b ]
```

```
# vice versa for !=
```

```
then
```

```
    echo "$a = $b : a is equal to b"
```

```
else
```

```
    echo "$a = $b: a is not equal to b"
```

```
fi
```

Operators in Shell (cntd...)

```
if [ -z $a ]  
then  
    echo "-z $a : string length is zero"  
else  
    echo "-z $a : string length is not zero"  
fi
```

```
if [ -n $a ]  
then  
    echo "-n $a : string length is not zero"  
else  
    echo "-n $a : string length is zero"  
Fi
```

Operators in Shell (cntd...)

- **File Test Operators**

- **Example**

```
#!/bin/sh
```

```
file="somedir/test.sh"
```

```
if [ -r $file ]
```

```
then
```

```
    echo "File has read access"
```

```
else
```

```
    echo "File does not have read access"
```

```
fi
```


Operators in Shell (cntd...)

```
if [ -w $file ]
```

```
#similar for execute x
```

```
then
```

```
    echo "File has write permission"
```

```
else
```

```
    echo "File does not have write permission"
```

```
fi
```

Operators in Shell (cntd...)

```
if [ -f $file ]  
then  
    echo "File is an ordinary file"  
else  
    echo "This is sepcial file"  
fi
```

Operators in Shell (cntd...)

d for directory;

s for size gt zero;

e for file exists;

b for block file;

c for character file;

Extra thoughts

- More operators in csh:

<< >>

& |

&& ||

++

--

-o file (if USER owns the file)

<op>=

History lists

Arrays

- We can use a single array to store all the above mentioned names. This is expressed as follows:

NAME[0]="ABC"

NAME[1]="DEF"

NAME[2]="ghi"

NAME[3]="Jkl"

NAME[4]="XYZ"

Arrays (cntd...)

Another Syntax for defining arrays

array_name=(value1 ... valuen)

Example:

```
array=( zero one two three four five )
```

```
# Element 0      1      2      3      4      5
```

Arrays (cntd...)

Yet another Syntax for defining arrays

```
array=( [0]="first element" [1]="second  
        element" [3]="fourth element" )
```

Arrays (cntd...)

Fetching the values

Expression	Meaning
<code>\${array[0]}</code>	Value of first element
<code>\${array:1}</code>	Parameter extension from first character
<code>\${#array[0]}</code> or <code>\${#array}</code>	Length of first element
<code>\${#array[*]}</code>	Number of elements in array
<code>\${#array[@]}</code>	

Arrays (cntd...)

Fetching the values

Expression	Meaning
<code>\${array[0]}</code>	Value of first element
<code>\${array:1}</code>	Parameter extension from first character
<code>\${#array[0]}</code> or <code>\${#array}</code>	Length of first element
<code>\${#array[*]}</code>	Number of elements in array
<code>\${#array[@]}</code>	

Arrays (cntd...)

String operations on arrays

```
#!/bin/bash
```

```
arrayZ=( one two three four five five )
```

```
# Trailing Substring Extraction
```

```
echo ${arrayZ[@]:0}
```

```
# one two three four five five # All elements.
```

```
echo ${arrayZ[@]:1}
```

```
# two three four five five # All elements following element[0].
```

```
echo ${arrayZ[@]:1:2}
```

```
# two three # Only the two elements after element[0].
```

Arrays (cntd...)

String operations on arrays

#String Removal

```
echo ${arrayZ[@]#f*r}
```

Removes shortest match from front of string(s).

```
echo ${arrayZ[@]##f*r}
```

Removes longest match from front of string(s).

```
echo ${arrayZ[@]%t*e}
```

% Removes shortest match from back of string(s).

```
echo ${arrayZ[@]%%t*e}
```

%% Removes shortest match from back of string(s).

Arrays (cntd...)

String operations on arrays

Substring Replacement

```
echo ${arrayZ[@]/five/WXYZ}
```

Replace first occurrence of substring with replacement.

```
echo ${arrayZ[@]//five/YYYY}
```

Replace all occurrences of substring.

Then >>>> **echo \${arrayZ[@]//five/}** will do??

Arrays (cntd...)

Example to load the contents of a file into array

```
$cat sample_file
```

```
1 a b c
```

```
2 d e f g
```

Arrays (cntd...)

Example to load the contents of a file into array

```
#!/bin/bash
filename=sample_file
declare -a array1
array1=( `cat "$filename"` )
echo ${array1[@]}
element_count=${#array1[*]}
echo $element_count
```

1 a b c 2 d e fg

8