
STANDARD ARRIVAL CHART -**INSTRUMENT (STAR) - ICAO**

TRANSITION ALTITUDE 5000

HARRY MWAANGA NKUMBULA INTL/Livingstone APP 124.300 (FLHN) TWR 118.100 **RNAV STAR RWY 10**

APGIS 1A, AVOMU 1A, AXOSO 1A, EXOBO 1A, FA 1A



STANDARD ARRIVAL CHART - INSTRUMENT (STAR) - ICAO

HARRY MWAANGA NKUMBULA INTL/Livingstone (FLHN) RNAV STAR RWY 10

APGIS 1A, AVOMU 1A, AXOSO 1A, EXOBO 1A, FA 1A

TABULAR DESCRIPTION

RNAV STAR RWY 10

APGIS 1A

	Serial Number	Path Descriptor	Waypoint Identifier	Fly- over	Course M°(T°)	Magnetic Variation (°)	Distance (NM) / Duration	Turn Direction	Altitude (FT)	Speed Limit (KT)	VPA (%)	Rec Navaids	Navigation Specification
$I \Gamma$	010	IF	APGIS	-	-	-	-	-	+FL140	-	-	-	RNAV 1
	020	TF	APKIM	-	144 (138.0)	1	39.0	-	+6300	-	-	1	RNAV 1

AVOMU 1A

Serial Number	Path Descriptor	Waypoint Identifier	Fly- over	Course M°(T°)	Magnetic Variation (°)	Distance (NM) / Duration	Turn Direction	Altitude (FT)	Speed Limit (KT)	VPA (%)	Rec Navaids	Navigation Specification
010	IF	AVOMU	-	-	-	-	-	+FL180	-	-	-	RNAV 1
020	TF	EGVOK	-	233 (226.2)	-	37.5	-	-	-	-	-	RNAV 1
030	TF	APKIM	-	267 (260.3)	-	19.4	-	+6300	-	-	-	RNAV 1

AXOSO 1A

	Serial Number	Path Descriptor	Waypoint Identifier	Fly- over	Course M°(T°)	Magnetic Variation (°)	Distance (NM) / Duration	Turn Direction	Altitude (FT)	Speed Limit (KT)VPA (%)	Rec Navaids	Navigation Specification
II	010	IF	AXOSO	-	-	-	-	-	+FL120	-	-	-	RNAV 1
Ш	020	TF	FA	-	260 (253.0)	-	16.6	-	+FL095	=	-	1	RNAV 1
I	030	TF	EGSUS	-	330 (322.9)	-	12.9	-	+6300	-	-	-	RNAV 1

EXOBO 1A

	Serial Number	Path Descriptor	Waypoint Identifier	Fly- over	Course M°(T°)	Magnetic Variation (°)	Distance (NM) / Duration	Turn Direction	Altitude (FT)	Speed Limit (KT)	VPA (%)	Rec Navaids	Navigation Specification
I	010	IF	EXOBO	-	-	-	-	-	+FL100	-	-		RNAV 1
I	020	TF	ATUSO	-	024 (016.6)	-	21.8	-	+6300	-	-		RNAV 1

FA 1A

	Serial Number	Path Descriptor	Waypoint Identifier	Fly- over	Course M°(T°)	Magnetic Variation (°)	Distance (NM) / Duration	Turn Direction	Altitude (FT)	Speed Limit (KT)	VPA (%)	Rec Navaids	Navigation Specification
l	010	IF	FA	-	-	-	-	-	+FL095	-	-	-	RNAV 1
L	020	TF	FGSUS	-	330 (322.9)	-	12.9	-	+6300	_	-		RNAV 1

STANDARD ARRIVAL CHART - INSTRUMENT (STAR) - ICAO

HARRY MWAANGA NKUMBULA INTL/Livingstone (FLHN) RNAV STAR RWY 10

APGIS 1A, AVOMU 1A, AXOSO 1A, EXOBO 1A, FA 1A

WAYPOINT LIST RNAV STAR RWY 10

WaypointIdentifier	Cod	ordinates
APGIS	S 17 14 13.0	E 025 11 11.6
APKIM	S 17 43 14.1	E 025 38 31.5
ATUSO	S 17 48 09.8	E 025 32 34.8
AVOMU	S 17 13 58.0	E 026 26 53.0
AXOSO	S 17 59 22.1	E 026 02 33.8
EGSUS	S 17 53 51.6	E 025 37 43.5
EGVOK	S 17 39 57.9	E 025 58 34.5
EXOBO	S 18 09 09.0	E 025 26 02.7
FA	S 18 04 13.1	E 025 45 54.0

ROUTING

NAME	ТЕХТ						
APGIS 1A	From APGIS track 144° to APKIM.						
	MEL/MEA: APGIS AT or ABOVE FL140, APKIM AT or ABOVE 6300'.						
AVOMU 1A	From AVOMU track 233° to EGVOK, track 267° to APKIM.						
	MEL/MEA: AVOMU AT or ABOVE FL180, APKIM AT or ABOVE 6300'.						
AXOSO 1A	From AXOSO track 260° to FA, track 330° to EGSUS.						
	MEL/MEA: AXOSO AT or ABOVE FL120, FA AT or ABOVE FL095, EGSUS AT or ABOVE 6300'.						
EXOBO 1A	From EXOBO track 024° to ATUSO.						
	MEL/MEA: EXOBO AT or ABOVE FL100, ATUSO AT or ABOVE 6300'.						
FA 1A	From FA track 330° to EGSUS.						
	MEL/MEA: FA AT or ABOVE FL095, EGSUS AT or ABOVE 6300'.						