



INSTRUMENT
APPROACH
CHART - ICAOAERODROME ELEV 3780 FT
HEIGHTS RELATED TO
THR RWY 28 - ELEV 3748 FTAPP 121.300
120.100
TWR 118.100KENNETH KAUNDA INTL/Lusaka
(FLKK)
VOR RWY 28

DISTANCE to THR 28	5.3	4.1	3.1	2.1	1.5	-	-
DISTANCE to VLS DME	8.3	7	6	5	4.4	-	-
ADVISORY ALT (HGT)	5500 (1752)	5100 (1352)	4780 (1032)	4460 (712)	4260 (512)	-	-

MISSED APPROACH:

Climb to 6100 FT on RDL 280 VLS
and contact Lusaka Approach
on 121.3 Mhz.

TRANSITION ALT 6000



OCA (OCH) CMV (m)		A	B	C	D
Straight-in Approach	VOR/DME	4260 (512)			
		2400			
CIRCLING VIS (m)		4460 (680)	4540 (760)	4830 (1050)	4840 (1060)
		3100	3500	4900	4900

GS (kt)	80	120	150	180	210
FAF to MAPt 5.3 NM	4:00	2:40	2:08	1:47	1:32
ROD (fpm) 5.2%	420	640	800	960	1110