hashtable.cm

```
Copyright (c) 2012-2016 Seppo Laakko
    http://sourceforge.net/projects/cmajor/
    Distributed under the GNU General Public License, version 3 (GPLv3).
    (See\ accompanying\ LICENSE.\ txt\ or\ http://www.gnu.org/licenses/gpl.html)
// Copyright (c) 1994
// Hewlett-Packard Company
// Copyright (c) 1996
// Silicon Graphics Computer Systems, Inc.
// Copyright (c) 2009 Alexander Stepanov and Paul McJones
using System;
using System. Concepts;
namespace System. Collections
    public static class HashtablePrimes
        static nothrow HashtablePrimes()
             try
             {
                 primes.Reserve(26);
                 primes .Add(53);
                 primes .Add(97);
                 primes .Add(193);
                 primes .Add(389);
                 primes .Add(769);
                 primes .Add(1543);
                 primes. Add(3079);
                 primes .Add(6151);
                 primes.Add(12289);
                 primes .Add(24593);
                 primes .Add(49157);
                 primes . Add (98317);
                 primes . Add(196613);
                 primes .Add(393241);
                 primes .Add(786433);
                 primes . Add(1572869);
                 primes.Add(3145739);
                 primes.Add(6291469);
                 primes.Add(12582917);
                 primes.Add(25165843);
```

```
primes.Add(50331653);
             primes.Add(100663319);
             primes.Add(201326611);
             primes.Add(402653189);
             primes.Add(805306457);
             primes .Add(1610612741);
         catch (const Exception& ex)
             \mathbf{try}
             {
                  Console.\,Error\,(\,)\,<<\,\,{\rm "hash} table\ primes\ initialization
                      failed" << endl();
             catch (const Exception&)
             exit(1);
         }
    }
    public static nothrow int GetNextPrime(int n)
         List < int >. ConstIterator p = LowerBound(primes. CBegin(),
            primes.CEnd(), n);
         if (p < primes.CEnd())</pre>
             return *p;
         return primes.Back();
    private static List<int> primes;
\textbf{public nothrow in line ulong} \ \operatorname{GetHashCode}(\ \textbf{long} \ \ x)
    return cast<ulong>(x);
public nothrow inline ulong GetHashCode(ulong x)
    return x;
public nothrow inline ulong GetHashCode(char x)
    return cast<ulong>(x);
public nothrow inline ulong GetHashCode(void* x)
    return cast < ulong > (x);
```

```
public nothrow inline ulong GetHashCode(const string& s)
    ulong hashCode = 14695981039346656037u;
    for (char c : s)
        hashCode = hashCode ^ cast<ulong>(c);
        hashCode = hashCode * 1099511628211u;
    return hashCode;
}
public class Hasher<T>: UnaryFun<T, ulong>
    public nothrow inline ulong operator()(const T& x)
        return GetHashCode(x);
public class Bucket<T> where T is Semiregular
    public typedef T ValueType;
    public Bucket(const ValueType& value_, Bucket<ValueType>* next_):
        value(value_), next(next_)
    public nothrow inline const ValueType& Value() const
        return value;
    public nothrow inline ValueType& Value()
        return value;
    public nothrow inline Bucket<ValueType>* Next() const
        return next;
    public nothrow void SetNext(Bucket<ValueType>* next_)
        next = next_{-};
    private ValueType value;
    private Bucket<ValueType>* next;
public abstract class HashtableBase<T> where T is Semiregular
    public typedef T ValueType;
    public default nothrow HashtableBase();
    public default nothrow HashtableBase(const HashtableBase<T>&);
```

```
public default nothrow HashtableBase(HashtableBase<T>&&);
    public default nothrow void operator=(const HashtableBase<T>&);
    public default nothrow void operator=(HashtableBase<T>&&);
    public virtual nothrow ~HashtableBase()
    public abstract nothrow int GetBucketCount() const;
    public abstract nothrow int GetBucketIndex(const ValueType& value
       ) const;
    public abstract nothrow Bucket<ValueType>* GetBucket(int index)
       const:
}
public class HashtableIterator<T, R, P>
    public typedef T ValueType;
    public typedef R ReferenceType;
    public typedef P PointerType;
    public typedef HashtableIterator<ValueType, ReferenceType,</pre>
       PointerType> Self;
    public nothrow HashtableIterator(): table(null), bucket(null)
    public nothrow HashtableIterator(HashtableBase<ValueType>* table_
       , Bucket<ValueType>* bucket_): table(table_), bucket(bucket_)
    public nothrow ReferenceType operator*()
        #assert(bucket != null);
        return bucket->Value();
    public nothrow PointerType operator->() const
        #assert (bucket != null);
        return &(bucket->Value());
    public nothrow Self& operator++()
        #assert (bucket != null && table != null);
        Bucket<ValueType>* old = bucket;
        bucket = bucket->Next();
        if (bucket == null)
            int index = table ->GetBucketIndex(old ->Value());
            \#assert (index != -1);
            ++index;
            int n = table ->GetBucketCount();
            while (bucket = null && index < n)
                bucket = table -> GetBucket(index);
                ++index;
```

```
}
         return *this;
    public nothrow inline Bucket<ValueType>* GetBucket() const
         return bucket;
    private HashtableBase<ValueType>* table;
    private Bucket<ValueType>* bucket;
public nothrow bool operator T, R, P>(const HashtableIterator T, R,
    P>& left, const HashtableIterator<T, R, P>& right)
    return left.GetBucket() == right.GetBucket();
public class Hashtable<KeyType, ValueType, KeyOfValue, HashFun =
    Hasher<KeyType>, Compare = EqualTo<KeyType>> : HashtableBase<
    ValueType>
    where KeyType is Semiregular and ValueType is Semiregular and
        Key Selection Function {<} Key Of Value \,, \;\; Key Type \,, \;\; Value Type {>} \;\; \textbf{and}
        HashFunction<HashFun, KeyType> and Compare is Relation and
        Compare. Domain is KeyType
{
    public typedef Hashtable<KeyType, ValueType, KeyOfValue, HashFun,</pre>
         Compare> Self;
    \textbf{public typedef} \hspace{0.1cm} \textbf{HashtableIterator} \negthinspace < \negthinspace \textbf{ValueType} \hspace{0.1cm}, \hspace{0.1cm} \textbf{ValueType} \hspace{0.1cm} \&, \hspace{0.1cm} \textbf{ValueType} \hspace{0.1cm}
        *> Iterator;
    public typedef HashtableIterator<ValueType, const ValueType&,</pre>
        const ValueType*> ConstIterator;
    public nothrow Hashtable(): base(), buckets(), count(0),
        loadFactor(0.0), maxLoadFactor(0.8), keyOf(), hash(), equal()
    public Hashtable(const Self& that)
         CopyFrom(that);
    public default nothrow Hashtable (Self&&);
    public void operator=(const Self& that)
         Clear();
         CopyFrom(that);
    public default nothrow void operator=(Self&&);
    public nothrow override ~Hashtable()
         Clear();
    public nothrow inline int Count() const
```

```
{
   return count;
public nothrow inline bool IsEmpty() const
    return count == 0;
public nothrow void Clear()
    int n = buckets.Count();
    for (int i = 0; i < n; ++i)
        Bucket<ValueType>* bucket = buckets[i];
        while (bucket != null)
            Bucket<ValueType>* next = bucket->Next();
            delete bucket;
            bucket = next;
        buckets[i] = null;
    count = 0;
public nothrow Iterator Begin()
    return Iterator(this, GetFirstBucket());
public nothrow ConstIterator Begin() const
    return ConstIterator(this, GetFirstBucket());
public nothrow ConstIterator CBegin() const
    return ConstIterator(this, GetFirstBucket());
public nothrow Iterator End()
    return Iterator(this, null);
public nothrow ConstIterator End() const
    return ConstIterator(this, null);
public nothrow ConstIterator CEnd() const
    return ConstIterator(this, null);
public nothrow void SetMaxLoadFactor(double maxLoadFactor_)
    maxLoadFactor = maxLoadFactor_;
public Pair<Iterator , bool> Insert(const ValueType& value)
```

```
if (buckets.Count() == 0)
        buckets. Resize (HashtablePrimes. GetNextPrime (0));
    const KeyType& key = KeyOf(value);
    int index = Hash(key);
    \#assert (index != -1);
    Bucket<ValueType>* bucket = buckets[index];
    while (bucket != null)
        if (Equal(KeyOf(bucket->Value()), key))
            return MakePair(Iterator(this, bucket), false);
        bucket = bucket->Next();
    bucket = new Bucket<ValueType>(value, buckets[index]);
    buckets [index] = bucket;
    ++count;
    SetLoadFactor();
    CheckForRehash();
    return MakePair(Iterator(this, bucket), true);
public nothrow void Remove(const KeyType& key)
    int index = Hash(key);
    if (index = -1) return;
    Bucket<ValueType>* bucket = buckets[index];
    Bucket<ValueType>* prev = null;
    while (bucket != null)
        if (Equal(KeyOf(bucket->Value()), key))
            if (prev != null)
            {
                prev->SetNext(bucket->Next());
            }
            else
            {
                buckets [index] = bucket->Next();
            delete bucket;
            --count;
            SetLoadFactor();
            return;
        prev = bucket;
        bucket = bucket->Next();
public nothrow void Remove(Iterator pos)
    Bucket<ValueType>* bucket = pos.GetBucket();
```

```
if (bucket != null)
        int index = Hash(KeyOf(bucket->Value()));
        if (index = -1) return;
        Bucket<ValueType>* b = buckets[index];
        Bucket<ValueType>* prev = null;
        while (b != bucket && b != null)
            prev = b;
            b = b - Next();
        if (b == bucket)
            if (prev != null)
                prev->SetNext(b->Next());
            else
                buckets [index] = b->Next();
            delete bucket;
            --count:
            SetLoadFactor();
        }
    }
public nothrow Iterator Find(const KeyType& key)
    int index = Hash(key);
    if (index >= 0)
        Bucket<ValueType>* bucket = buckets[index];
        while (bucket != null)
            if (Equal(KeyOf(bucket->Value()), key))
                return Iterator (this, bucket);
            bucket = bucket->Next();
    return Iterator(this, null);
public nothrow ConstIterator Find(const KeyType& key) const
    int index = Hash(key);
    if (index >= 0)
        Bucket<ValueType>* bucket = buckets[index];
        while (bucket != null)
            if (Equal(KeyOf(bucket->Value()), key))
```

```
{
                return ConstIterator(this, bucket);
            bucket = bucket->Next();
    return ConstIterator(this, null);
public nothrow ConstIterator CFind(const KeyType& key) const
    int index = Hash(key);
    if (index >= 0)
        Bucket<ValueType>* bucket = buckets[index];
        while (bucket != null)
            if (Equal(KeyOf(bucket->Value()), key))
                return ConstIterator(this, bucket);
            bucket = bucket->Next();
    return ConstIterator(this, null);
public override nothrow int GetBucketCount() const
    return buckets.Count();
public override nothrow int GetBucketIndex(const ValueType& value
   ) const
    return Hash(KeyOf(value));
public override nothrow Bucket<ValueType>* GetBucket(int index)
   const
    return buckets [index];
private nothrow inline void SetLoadFactor()
    int bc = buckets.Count();
    \mathbf{if} (bc == 0)
        loadFactor = 1.0;
    else
        double c = count;
        loadFactor = c / bc;
private void CheckForRehash()
```

```
{
    if (loadFactor > maxLoadFactor)
        Rehash();
private void Rehash()
    List <Bucket <ValueType>*> b;
    Swap(buckets, b);
    int n = b.Count();
    buckets. Resize (HashtablePrimes. GetNextPrime(n + 1));
    for (int i = 0; i < n; ++i)
        Bucket < Value Type > * bucket = b[i];
        while (bucket != null)
            const KeyType& key = KeyOf(bucket->Value());
            int index = Hash(key);
            \#assert (index != -1);
            Bucket<ValueType>* next = bucket->Next();
            bucket->SetNext(buckets[index]);
            buckets[index] = bucket;
            bucket = next;
        }
    }
private nothrow Bucket<ValueType>* GetFirstBucket() const
    Bucket<ValueType>* bucket = null;
    int n = buckets.Count();
    for (int i = 0; i < n; ++i)
        bucket = buckets[i];
        if (bucket != null)
            break;
    return bucket;
private void CopyFrom(const Self& that)
    int n = that.buckets.Count();
    buckets. Resize(n);
    for (int i = 0; i < n; ++i)
        Bucket<ValueType>* bucket = that.buckets[i];
        while (bucket != null)
            buckets [i] = new Bucket < Value Type > (bucket -> Value (),
                buckets[i]);
            bucket = bucket->Next();
```

```
}
        count = that.count;
        loadFactor = that.loadFactor;
        maxLoadFactor = that.maxLoadFactor;
    private nothrow inline const KeyType& KeyOf(const ValueType&
       value) const
    {
        return keyOf(value);
    private nothrow inline int Hash(const KeyType& key) const
        if (buckets.IsEmpty()) return -1;
        return cast<int>(hash(key) % cast<ulong>(buckets.Count()));
    private nothrow inline bool Equal(const KeyType& left, const
       KeyType& right) const
        return equal(left, right);
    private List < Bucket < Value Type > *> buckets;
    private int count;
    private double loadFactor;
    private double maxLoadFactor;
    private KeyOfValue keyOf;
    private HashFun hash;
    private Compare equal;
}
```