## utility.cm

```
Copyright (c) 2012-2016 Seppo Laakko
    http://source forge.net/projects/cmajor/
    Distributed under the GNU General Public License, version 3 (GPLv3).
    (See\ accompanying\ LICENSE.\ txt\ or\ http://www.gnu.org/licenses/gpl.html)
    */
// Copyright (c) 1994
// Hewlett-Packard Company
// Copyright (c) 1996
// Silicon Graphics Computer Systems, Inc.
// Copyright (c) 2009 Alexander Stepanov and Paul McJones
namespace System. Support
    public nothrow inline ulong Align(ulong n, ulong alignment)
        #assert (alignment > 0u);
        return (n + alignment - 1u) & -alignment;
    public nothrow int StrLen(const char* s)
        int len = 0;
        if (s != null)
             while (*s != '\setminus 0')
                ++len;
                ++s;
        return len;
    }
    public nothrow int StrLen(const wchar* s)
        int len = 0;
        if (s != null)
             while (*s != '\setminus 0')
                ++len;
                ++s;
```

```
return len;
\mathbf{public} \ \mathbf{nothrow} \ \mathbf{int} \ \mathrm{StrLen}\left(\mathbf{const} \ \mathrm{uchar} * \ \mathrm{s} \right)
     int len = 0;
     if (s != null)
          while (*s != ' \setminus 0')
               ++len;
               ++s;
     return len;
public nothrow void StrCopy(char* buf, const char* from)
    #assert(buf != null);
     if (from != null)
          while (*from != '\setminus 0')
               *buf++ = *from++;
     *buf = ' \setminus 0';
}
public nothrow void StrCopy(wchar* buf, const wchar* from)
    #assert(buf != null);
     if (from != null)
          while (*from != ' \setminus 0')
               *buf++ = *from++;
     *buf = ' \setminus 0';
}
public nothrow void StrCopy(uchar* buf, const uchar* from)
    #assert(buf != null);
     if (from != null)
          while (*from != ' \setminus 0')
               *buf++ = *from++;
```

```
}
*buf = '\0';
public nothrow int StrCopy(char* buf, const char* from, int length)
    int resultLen = 0;
    #assert(buf != null);
    if (from != null)
         while (resultLen < length)
             \mathbf{if} \ (*from = ' \setminus 0')
                  break;
             *buf++ = *from++;
             ++resultLen;
         }
    *buf = ' \setminus 0';
    return resultLen;
}
public nothrow int StrCopy(wchar* buf, const wchar* from, int length)
    int resultLen = 0;
    #assert (buf != null);
    if (from != null)
         while (resultLen < length)
             \mathbf{if} \ (*from = ' \setminus 0')
                  break;
             *buf++ = *from++;
             ++resultLen;
         }
    *buf = ' \setminus 0';
    return resultLen;
public nothrow int StrCopy(uchar* buf, const uchar* from, int length)
    int resultLen = 0;
    #assert (buf != null);
    if (from != null)
         while (resultLen < length)
             \mathbf{if} \ (*from = ' \setminus 0')
```

```
break;
            *buf++ = *from++;
            ++resultLen;
    *buf = ' \setminus 0';
    return resultLen;
}
public nothrow ulong MemGrow(ulong size)
    if (size < 8u)
        return 8u;
    else if (size < 64u)
        return 64u;
    else if (size < 512u)
        return 512u;
    else if (size < 4096u)
        return 4096u;
    else
        return 2u * Align(size, 4096u);
public nothrow int Write(int fd, const char* s)
    return write_64 (fd, s, cast<ulong>(StrLen(s)));
public const int EXIT_INSUFFICIENT_MEMORY = 253;
public nothrow void* MemAlloc(ulong size)
    void* block = malloc(size);
    if (block == null)
        Write(stderr, "insufficient memory\n");
        exit (EXIT_INSUFFICIENT_MEMORY);
    return block;
}
```

```
public nothrow void MemFree(void* block)
{
    free(block);
}

public nothrow void* DebugHeapMemAlloc(ulong size)
{
    void* block = dbgheap_malloc(size);
    if (block == null)
    {
        Write(stderr, "insufficient memory\n");
        exit(EXIT_INSUFFICIENT_MEMORY);
    }
    return block;
}

public nothrow void DebugHeapMemFree(void* block)
{
    dbgheap_free(block);
}
```