

# Getting Started Guide for Cmajor 1.0.0-beta-5

Seppo Laakko

June 18, 2015

## 1 Installation in Windows

### 1.1 Prerequisites

Note: You must uninstall any previous Cmajor version before installing this version (1.0.0-beta-5).

It is also recommended that you delete the %APPDATA%\Cmajor directory before installing this version because configuration files and system library files have been changed.

- Download and install Mingw-w64 GCC:  
<http://sourceforge.net/projects/mingw-w64/files/Toolchains%20targetting%20Win32/Personal%20Builds/mingw-builds/installer/mingw-w64-install.exe/download>

Installation settings for my system:

- Version 5.1.0
- Architecture: x86\_64
- Threads: **posix**
- Exception: sjlj
- Build revision: 0

Note: Threads setting must be “posix”.

After installation insert the bin-directory to the **PATH** environment variable. In my system this is

C:\Program Files\mingw-w64\x86\_64-5.1.0-posix-sjlj-rt\_v4-rev0\mingw64\bin directory.

### 1.2 Cmajor Installation

- Download and run **cmajor-1.0.0-beta-5-win-x86-setup.exe** (for 32-bit Windows) or **cmajor-1.0.0-beta-5-win-x64-setup.exe** (for 64-bit Windows).
- Cmajor is installed by default to C:\Program Files\Cmajor directory (under 32-bit Windows) or to C:\Program Files (x86)\Cmajor directory (32-bit and 64-bit versions under 64-bit Windows).

Note: The x64 version is also installed by default under C:\Program Files (x86) directory although the programs are genuinely 64-bit versions). This is due to restrictions of InstallShield Limited Edition. You may want to change the install location under C:\Program Files directory in this case.

- The setup adds `C:\Program Files\Cmajor\bin` directory (or wherever you installed it) to your systems **PATH** environment variable, so the Cmajor programs can be executed from any directory from the command prompt without specifying full paths.
- The setup also adds a **CM\_LIBRARY\_PATH** environment variable and sets it to contain a path to the Cmajor System Library directory that is `%APPDATA%\Cmajor\system`. If you need to modify the **CM\_LIBRARY\_PATH** environment variable, you can find it from the Advanced System Settings pane in the System Control Panel.

In my computer the `%APPDATA%` points actually to the `C:\Users\Seppo\AppData\Roaming\` directory. The **AppData** folder is hidden by default. To see it you will have to modify the settings in the *Folder Options* Control Panel.

- The setup adds an icon to **Cmajor Development Environment** to the desktop.
- After installation you have to build the Cmajor System Library.

### 1.3 Building the Cmajor System Library

- Option 1: using batch file:
  - Open command prompt and change to Cmajor system directory by issuing command `cd %APPDATA%\Cmajor\system`.
  - Run **build.bat**. This builds the Cmajor System Library for each backend (LLVM/C) and configuration (debug/release).
  - Now the Cmajor system is ready for building user projects.
- Option 2: using IDE:
  - Start **Cmajor Development Environment**.
  - Open the File|Built-in Projects|System Library project.
  - Run Build|Rebuild Solution command for the **debug** configuration.
  - Select **release** configuration from the configuration combo box and run Build|Rebuild Solution command for the **release** configuration.
  - Select **debug** configuration from the configuration combo box and **C** backend from the backend combo box and run Build|Rebuild Solution command for the **C** backend and the **debug** configuration.
  - Select **release** configuration from the configuration combo box and run Build|Rebuild Solution command for the **C** backend and for the **release** configuration.
  - Now the Cmajor system is ready for building user projects.

Note: If you are updating from previous Cmajor version, it is important to issue the **rebuild** command (not just build command), because System Library directories are not cleared when uninstalling Cmajor.

## 1.4 Troubleshooting

- **cmc I2 error library reference 'system.cml' not found.**

You have to build the System Library for the used configuration (debug/release) and backend (LLVM/C) first.

- **Cannot start llc.exe because libgcc\_s\_sjlj-1.dll is missing** (or something like that).

The bin directory of mingw-w6

(in my machine

C:\Program Files\mingw-w64\x86\_64-5.1.0-posix-sjlj-rt\_v4-rev0\mingw64\bin)  
must be in the PATH environment variable.

- The compiler is still in experimental stage, so surely many bugs exist...

Hope this helps!

## 2 Installation in Linux

### 2.1 Prerequisites

- GCC

Must be recent enough to compile C++11 code.

- Download, build and install Boost (<http://www.boost.org/>). You will need to build and install the filesystem library.
- Download, build and install LLVM tools (<http://llvm.org/>). Installation instructions can be found in <http://llvm.org/docs/GettingStarted.html> document.

### 2.2 Cmajor Installation

- Download and extract **cmajor-1.0.0-src.tar.gz** to some directory here called <cmajor>.
- Change to <cmajor> directory and run `make` and then `[sudo] make install`.
- Set an environment variable `CM_LIBRARY_PATH` to contain path to <cmajor>/system directory. You may want to insert a statement like:  
`export CM_LIBRARY_PATH=/path/to/cmajor/system`  
into your `.bashrc` script.

### 2.3 Building the System Library

- Run command `make sys` from <cmajor> directory.
- Now the Cmajor system is ready for building user projects.

## 2.4 Troubleshooting

- library reference 'system.cml' not found

You have to build the System Library for the used configuration (debug/release) and backend (LLVM/C) first.

- sh: 1: llc: not found

You have probably not installed LLVM tools.

- The compiler is still in experimental stage, so surely many bugs exist...

Hope this helps!