

JavaBeans and Software Architecture

Nikunj R. Mehta

Outline

- Java and JavaBeans
- JavaBean characteristics
- Enterprise JavaBeans
- JavaBeans & Java technologies
- Relation to software architecture
- Conclusion

Java and software development

- Developing large complex systems
 - Component-based development standards
 - Middleware platforms
 - Software architecture
- Java programming language
 - Object oriented PL with native multi-threading support
 - Reduces common programming mistakes
 - Provides greater control over software organization
- Java platform
 - Portable, secure, standards based

3

JavaBeans

- Original software component model for Java
- Flexible, loosely coupled architecture
- Enables large-scale, coarse-grained reuse
 - Large number of JavaBeans created, sold, and used
 - Used in many application domains
- Intuitive programming paradigm
 - No special class inheritance needed
 - Drag-and-drop visual editing of programs
 - API, programming conventions, and naming patterns
- Basis for many Java component technologies


4

Usage And Applications

- JavaBeans
 - A reusable software component that can be manipulated visually in a builder tool
- Separation of interfaces
 - Compile time and run time capabilities
 - Configuration and customization support
- GUI and non-graphical JavaBean components
- An important constituent of Java IDEs
 - Mostly used in developing *bigger* widgets and GUI applications
 - Visual editing as well as manual programming

5

NetBeans IDE: A Visual Builder




6

Outline

- Java and JavaBeans
- JavaBean characteristics
- Enterprise JavaBeans
- JavaBeans & Java technologies
- Relation to software architecture
- Conclusion

7

JavaBean Characteristics

- Introspection
 - Customization
 - Properties
 - Events
 - Persistence
 - Packaging
 - Methods
- 
- Design time
- Run time

8


Methods

- Used at run time
 - Exposes services provided by JavaBean
 - Synchronous communication mechanism
- Same as regular Java methods
 - Lexical and syntactic rules, always *public*
 - Invocation semantics
- Excludes certain name prefixes
 - *is*, *get*, *set*, *add*, *remove*

9

Events

- Central to JavaBeans
 - Represent the occurrence of an incident of interest
 - Loosely coupled, publish-subscribe interaction
 - Event listener – any interested Java object
 - Event producer – a JavaBean
- Subscription management
 - Add, remove listeners
- Event dispatch
 - Send event message (subclass of *java.util.EventObject*) to all listeners
 - Uses regular Java method calls



10

Properties

- Provide access to JavaBean state
 - Have name and type
 - Read only, read-write, or write-only
 - For customization at design time
 - To modify behavior at run time
- Defined as a set of methods
 - Naming patterns
 - Separate class behavior from interface
- Many types
 - single valued, multivalued, indexed, bound, constrained

11

Example JavaBean

```
public class Circle extends java.awt.Component implements java.io.Serializable {  
    ...  
    // Paint the circle on the screen  
    public void paint(Graphics g)  
    ...  
    // Get the boolean Shown property  
    public boolean isShown()  
    ...  
    // Get the Radius property  
    public int getRadius()  
    ...  
    // Set the Radius property  
    public void setRadius(int radius) throws PropertyVetoException  
    ...  
    // Get the Border Size property  
    public int getBorderSize()  
    ...  
    // Set the Border Size property  
    public void setBorderSize(int size)  
}
```

12

Persistence

- For recreating JavaBean instances
 - Communicate design customization for execution
- Three mechanisms
 - Serialization
 - Virtual machine level, special logic
 - Externalization
 - Self management of internal state by JavaBean
 - Encoding
 - Standardized encoding of properties by a utility
- Portability of persistent information
- Efficiency of storage and retrieval

13


Packaging

- Package related Java classes, persistent state, documentation, resources, etc.
- Special archive format
 - Java archive (Jar) file
 - Reduce clutter
 - Platform-independent
 - Uses ZIP compression
 - Additional manifest file to describe contents
- Deployment can produce previously customized JavaBean instances

14

Introspection

- Acquire design information about bean type
 - To compose applications, or composite bean
 - Automatic discovery of configuration/customization capabilities
- Introspection architecture
 - Fault-tolerant
 - Separate introspection info. reduces run time overhead
 - Based on standard naming patterns of JavaBeans
- High-level design information
 - Unlike reflection only gives implementation details



15

Customization

- Only used at design time
 - Visual application design using JavaBeans
- Important capability afforded by visual editors
 - Construct visual editing interfaces through introspection
 - Connect different JavaBeans and events
 - Specify custom properties through property editors
 - Visualize designs
 - Generate Java source code
- JavaBeans can provide custom property editors

16

Outline

- Java and JavaBeans
- JavaBean characteristics
- Enterprise JavaBeans
- JavaBeans & Java technologies
- Relation to software architecture
- Conclusion

17

Enterprise JavaBeans

- Distributing JavaBeans
 - Network communication using RMI
 - Transparent invocation semantics
 - Serialization of parameters, return values
 - Using JNDI for object location
- Enterprise JavaBeans
 - Aimed at reducing TCO of business applications
 - Concurrently accessed by large number of users
 - Perform data access and information processing
 - Provide greater availability, security, resource mgmt.
 - Infrastructure services provided by EJB middleware


18

EJB Middleware Facilities

- Deployment
- Memory and instance management
- Thread management
- Communication management
- Security
- Location
- Messaging
- Invocation
- Persistence
- Transaction management

19

EJB Architecture



20

Outline

- Java and JavaBeans
- JavaBean characteristics
- Enterprise JavaBeans
- JavaBeans & Java technologies
- Relation to software architecture
- Conclusion

21

JavaBeans & Java Technologies

- JavaBeans
 - A generic component model
 - Applicable in both consumer and business applications
 - Most suited to the client environment
- Java technologies influenced by JavaBeans
 - Abstract windowing toolkit
 - Java database connectivity
 - JavaMail
 - Java management extensions

22

Abstract Windowing Toolkit

- Standard API for producing GUI applications in Java
- AWT beans are JavaBeans
 - Reusable software components
 - Can be visually manipulated in a builder tool
 - Can be customized for use in an application
 - Use methods, properties, events
- Java foundation classes
 - Lightweight visual components
 - Richer set of widgets

23

Java Database Connectivity

- JavaBean persistence often inadequate
 - Serialization, externalization, encoding
 - Insufficient durability and integrity
 - Memory inefficient
- Bridge JavaBeans with database technology
 - ACID transactions
 - Establish connections, perform queries, manipulate result sets
 - Events and properties on the above
 - Enables use of components for data access
 - Simplifies application development

24

JavaMail

- Used in mail applications
 - Based on standard mail protocols
 - SMTP, POP3, IMAP, NNTP
 - Enable componentization of mail clients
- Non-graphical JavaBeans
 - Design time specification of connection properties
 - Run time management of connections and mail stores
 - Events in response to user actions and data received from mail servers

25

Java Management Extensions

- For managing applications and networks
 - Fine-grained instrumentation – components
 - Coarse-grained instrumentation – application
 - Obtain information about running components
 - Control run-time behavior
- MBeans
 - Follow special naming patterns
 - Implement management interfaces
 - Contain properties, methods, and notifications
 - Define meta data as introspection information
 - Register with MBean servers to provide remote access

26

Outline

- Java and JavaBeans
- JavaBean characteristics
- Enterprise JavaBeans
- JavaBeans & Java technologies
- Relation to software architecture
- Conclusion

27

Relation to Software Architecture

- Components
 - EJB – session, entity, message-driven beans
 - AWT – GUI widgets
 - JDBC – connections, queries, result sets
 - JavaMail – folder, store, message, transport
 - JMX – MBean
- Connectors
 - EJB container provides facilities through EJB *wrapper*
 - RMI, asynchronous messages in EJB
 - JavaBeans, AWT, JDBC, JavaMail use events, properties and methods for interaction

28

Support for Architectural Styles

- JavaBeans support publish-subscribe style
 - Interaction through events
 - Components are producers and consumers of events
- EJBs are in the distributed object style
 - Synchronous and asynchronous communication
- JavaBeans and C2 style
 - Rosenblum & Natarajan
 - C2 style-aware visual builder tool for JavaBeans
 - Components are JavaBeans
 - Interaction through events
 - Configurations adhere to C2 style

29

Outline

- Java and JavaBeans
- JavaBean characteristics
- Enterprise JavaBeans
- JavaBeans & Java technologies
- Relation to software architecture
- Conclusion

30

Conclusion

- Component-based software
 - Promising for object technologies
 - Address challenges facing large, complex software systems
- JavaBeans
 - Loosely coupled architectural style
 - Basis for Java component technologies
- Java and the Internet
 - Best of programming and delivery worlds