

```

1  """Script for computing the one-step error probability."""
2
3  import numpy as np
4  from hopfield import DeterministicHopfieldNetwork
5  from pattern_utilities import generate_n_random_patterns, print_pattern
6
7
8  def main():
9      n_neurons = 120
10     n_patterns_vector = [12, 24, 48, 70, 100, 120]
11     # Set diagonal_weights_rule to "non-zero" in second task
12     diagonal_weights_rule = "zero"
13     n_iterations = int(1e5)
14     one_step_error_probability = np.zeros(len(n_patterns_vector))
15
16     for n_patterns_i, n_patterns in enumerate(n_patterns_vector):
17         n_errors = 0
18         for _ in range(n_iterations):
19             network = DeterministicHopfieldNetwork()
20
21             patterns = generate_n_random_patterns(n_patterns, n_neurons)
22             network.set_patterns(patterns)
23             network.set_diagonal_weights_rule(diagonal_weights_rule)
24             network.generate_weights()
25
26             pattern_to_feed_index = np.random.randint(n_patterns)
27             original_pattern = patterns[pattern_to_feed_index, :]
28             neuron_to_update_index = np.random.randint(n_neurons)
29
30             updated_pattern = network.update_neuron(
31                 original_pattern,
32                 neuron_to_update_index
33             )
34             updated_neuron = updated_pattern[neuron_to_update_index]
35             original_neuron = original_pattern[neuron_to_update_index]
36             updated_neuron = updated_pattern[neuron_to_update_index]
37
38             if original_neuron != updated_neuron:
39                 n_errors += 1
40
41             one_step_error_probability[n_patterns_i] = n_errors/n_iterations
42
43     print_pattern(one_step_error_probability)
44
45
46 if __name__ == "__main__":
47     main()

```

```

1  """Script for recognizing digits."""
2
3  import numpy as np
4  from hopfield import DeterministicHopfieldNetwork
5  import pattern_utilities as utils
6
7
8  def main():
9      # Change get_pattern1 to get_pattern2 and get_pattern3 for questions
10     # 2 and 3.
11     pattern_to_feed = get_pattern1()
12     n_neurons = pattern_to_feed.size
13     stored_patterns = get_stored_patterns()
14     n_epochs = int(1e3)
15
16     network = DeterministicHopfieldNetwork()
17     network.set_diagonal_weights_rule("zero")
18     network.set_patterns(stored_patterns)
19     network.generate_weights()
20
21     updated_pattern = pattern_to_feed.copy()
22     for epoch in range(n_epochs):
23         # Update the pattern in typewriter order (since pattern is
24         # flattened, just go in normal element-order).
25         for neuron in range(n_neurons):
26             updated_pattern = network.update_neuron(updated_pattern, neuron)
27
28     matching_pattern_index = utils.get_index_of_equal_pattern(
29         updated_pattern, stored_patterns)
30     inverted_stored_patterns = -1 * stored_patterns
31     matching_inverted_pattern_index = utils.get_index_of_equal_pattern(
32         updated_pattern, inverted_stored_patterns)
33     if matching_pattern_index >= 0:
34         matching_pattern = stored_patterns[matching_pattern_index, :]
35         matching_pattern_index += 1
36     elif matching_inverted_pattern_index >= 0:
37         matching_pattern = inverted_stored_patterns[
38             matching_inverted_pattern_index, :]
39         matching_pattern_index = -1 * matching_inverted_pattern_index
40         matching_pattern_index -= 1
41     else:
42         matching_pattern_index = 6
43         matching_pattern = np.array([])
44
45     print("Converged to pattern {}".format(matching_pattern_index))
46
47     print("Actual pattern: ")

```

```

48     utils.print_ttypewriter_pattern(updated_pattern, n_columns=10)
49
50
51 def get_stored_patterns():
52     x1 = np.array(
53         [ [-1, -1, -1, -1, -1, -1, -1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1,
          ↪ -1, -1, -1], [-1, -1, 1, 1, 1, 1, 1, 1, -1, -1], [-1, 1, 1, 1, -1,
          ↪ -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1,
          ↪ 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1,
          ↪ 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1,
          ↪ -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1,
          ↪ 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1,
          ↪ -1, 1, 1, 1, -1], [-1, -1, 1, 1, 1, 1, 1, 1, -1, -1], [-1, -1, -1,
          ↪ 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, -1, -1, -1, -1, -1, -1, -1]
          ↪ ]
54     ).flatten();
55
56     x2 = np.array(
57         [ [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1,
          ↪ -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1,
          ↪ 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1,
          ↪ -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1,
          ↪ -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1,
          ↪ 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1,
          ↪ 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1,
          ↪ -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1,
          ↪ 1, 1, -1, -1, -1] ]
58     ).flatten();
59
60     x3 = np.array(
61         [ [ 1, 1, 1, 1, 1, 1, 1, 1, -1, -1], [ 1, 1, 1, 1, 1, 1, 1, 1, -1,
          ↪ -1], [-1, -1, -1, -1, -1, 1, 1, 1, -1, -1], [-1, -1, -1, -1, -1,
          ↪ 1, 1, 1, -1, -1], [-1, -1, -1, -1, -1, 1, 1, 1, -1, -1], [-1, -1,
          ↪ -1, -1, -1, 1, 1, 1, -1, -1], [-1, -1, -1, -1, -1, 1, 1, 1, -1,
          ↪ -1], [ 1, 1, 1, 1, 1, 1, 1, 1, -1, -1], [ 1, 1, 1, 1, 1, 1, 1, 1,
          ↪ -1, -1], [ 1, 1, 1, -1, -1, -1, -1, -1, -1, -1], [ 1, 1, 1, -1, -1,
          ↪ -1, -1, -1, -1, -1], [ 1, 1, 1, -1, -1, -1, -1, -1, -1, -1], [ 1, 1,
          ↪ 1, -1, -1, -1, -1, -1, -1, -1], [ 1, 1, 1, -1, -1, -1, -1, -1, -1,
          ↪ -1], [ 1, 1, 1, 1, 1, 1, 1, 1, -1, -1], [ 1, 1, 1, 1, 1, 1, 1, 1,
          ↪ -1, -1] ]
62     ).flatten();
63
64     x4 = np.array(

```

```

65     [ [-1, -1, 1, 1, 1, 1, 1, 1, -1, -1], [-1, -1, 1, 1, 1, 1, 1, 1, 1, 1,
        ↪ -1], [-1, -1, -1, -1, -1, -1, 1, 1, 1, -1], [-1, -1, -1, -1, -1,
        ↪ -1, 1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, 1, 1, 1, -1], [-1, -1,
        ↪ -1, -1, -1, -1, 1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, 1, 1, 1, 1,
        ↪ -1], [-1, -1, 1, 1, 1, 1, 1, 1, -1, -1], [-1, -1, 1, 1, 1, 1, 1, 1,
        ↪ 1, -1, -1], [-1, -1, -1, -1, -1, -1, 1, 1, 1, -1], [-1, -1, -1,
        ↪ -1, -1, -1, 1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, 1, 1, 1, -1], [-1,
        ↪ -1, -1, -1, -1, -1, 1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, 1, 1, 1, 1,
        ↪ 1, 1, -1], [-1, -1, 1, 1, 1, 1, 1, 1, 1, -1], [-1, -1, 1, 1, 1, 1, 1,
        ↪ 1, 1, -1, -1] ]
66     ).flatten();
67
68     x5 = np.array(
69         [ [-1, 1, 1, -1, -1, -1, -1, 1, 1, -1], [-1, 1, 1, -1, -1, -1, -1, 1,
            ↪ 1, -1], [-1, 1, 1, -1, -1, -1, -1, 1, 1, -1], [-1, 1, 1, -1, -1,
            ↪ -1, -1, 1, 1, -1], [-1, 1, 1, -1, -1, -1, -1, 1, 1, -1], [-1, 1,
            ↪ 1, -1, -1, -1, -1, 1, 1, -1], [-1, 1, 1, -1, -1, -1, -1, 1, 1, 1,
            ↪ -1], [-1, 1, 1, 1, 1, 1, 1, 1, 1, -1], [-1, 1, 1, 1, 1, 1, 1, 1, 1,
            ↪ 1, -1], [-1, -1, -1, -1, -1, -1, -1, 1, 1, -1], [-1, -1, -1, -1,
            ↪ -1, -1, -1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, -1, 1, 1, -1], [-1,
            ↪ -1, -1, -1, -1, -1, -1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, -1, 1, 1,
            ↪ -1, 1, 1, -1], [-1, -1, -1, -1, -1, -1, -1, 1, 1, -1], [-1, -1,
            ↪ -1, -1, -1, -1, -1, 1, 1, -1] ]
70     ).flatten();
71
72     return np.vstack((x1, x2, x3, x4, x5))
73
74
75 def get_pattern1():
76     return np.array(
77         [[1, 1, 1, -1, -1, -1, -1, 1, 1, 1], [-1, -1, -1, 1, 1, 1, 1, -1, -1,
            ↪ -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1,
            ↪ 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1,
            ↪ 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, 1, -1, -1, -1],
            ↪ [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, 1, -1,
            ↪ -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1,
            ↪ 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, 1, -1, -1, -1], [-1, -1,
            ↪ -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, 1, -1, -1, -1],
            ↪ [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, 1, -1,
            ↪ -1, -1]]
78     ).flatten()
79
80
81 def get_pattern2():
82     return np.array(

```

```

83     [[1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1], [1, 1, 1, -1, -1, -1, -1, 1, 1, 1],
      ↪ [1, 1, -1, -1, -1, -1, -1, -1, 1, 1], [1, -1, -1, -1, 1, 1, 1, -1,
      ↪ -1, -1, 1], [1, -1, -1, -1, 1, 1, -1, -1, -1, 1], [1, -1, -1, -1,
      ↪ 1, 1, -1, -1, -1, 1], [1, -1, -1, -1, 1, 1, 1, -1, -1, -1, 1], [1,
      ↪ -1, -1, -1, 1, 1, -1, -1, -1, 1], [1, -1, -1, -1, 1, -1, 1, 1, 1,
      ↪ -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1,
      ↪ 1, 1, -1], [-1, 1, 1, 1, -1, -1, 1, 1, 1, -1], [-1, 1, 1, 1, -1,
      ↪ -1, 1, 1, 1, -1], [-1, -1, 1, 1, 1, 1, 1, 1, -1, -1], [-1, -1, -1,
      ↪ 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, -1, -1, -1, -1, -1, -1, -1]]
84     ).flatten()
85
86
87 def get_pattern3():
88     return np.array(
89         [[-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1,
          ↪ -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1,
          ↪ 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1,
          ↪ -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1],
          ↪ [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1,
          ↪ -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1,
          ↪ 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1,
          ↪ -1, 1, 1, 1, 1, -1, -1, -1], [-1, -1, -1, 1, 1, 1, 1, -1, -1, -1],
          ↪ [1, 1, 1, -1, -1, -1, -1, 1, 1, 1], [1, 1, 1, -1, -1, -1, -1, 1,
          ↪ 1, 1]]
90     ).flatten()
91
92
93 if __name__ == "__main__":
94     main()

```

```

1  """Script for estimating the order parameter."""
2
3  import numpy as np
4  from hopfield import StochasticHopfieldNetwork
5  from pattern_utilities import generate_n_random_patterns
6
7
8  def main():
9      n_neurons = 200
10     # Change n_patterns to 45 for the second question
11     n_patterns = 7
12     noise_parameter = 2
13     n_time_steps = int(2e5)
14     n_iterations = 100
15
16     patterns = generate_n_random_patterns(n_patterns, n_neurons)
17
18     network = StochasticHopfieldNetwork()

```

```

19     network.set_patterns(patterns)
20     network.set_diagonal_weights_rule("zero")
21     network.set_noise_parameter(noise_parameter)
22     network.generate_weights()
23
24     pattern1 = patterns[0, :]
25     updated_pattern = pattern1.copy()
26
27     m = np.zeros(n_iterations)
28     for i in range(n_iterations):
29         for _ in range(n_time_steps):
30             updated_pattern = network.update_random_neuron(updated_pattern)
31             m[i] += np.inner(updated_pattern, pattern1)
32         m[i] /= n_neurons
33         m[i] /= n_time_steps
34
35     m_estimate = sum(m) / n_iterations
36     print("{:.3f}".format(m_estimate))
37
38
39 if __name__ == "__main__":
40     main()

```

```

1  """Implementation of a Hopfield network using Hebb's rule."""
2
3  from abc import ABC, abstractmethod
4  import numpy as np
5  from scipy import stats
6
7
8  class HopfieldNetwork(ABC):
9      """Abstract Hopfield net using Hebb's rule to compute weights."""
10
11     def set_diagonal_weights_rule(self, diagonal_weights_rule):
12         """Specify if the diagonal weights should be zero or not.
13
14         diagonal_weights_rule must equal "zero" or "non-zero".
15         """
16
17         if diagonal_weights_rule == "zero":
18             self.diagonal_weights_equal_zero = True
19         elif diagonal_weights_rule == "non-zero":
20             self.diagonal_weights_equal_zero = False
21         else:
22             raise KeyError(
23                 diagonal_weights_rule
24                 + " not a valid diagonal_weights_rule"
25             )

```

```

26 def set_patterns(self, patterns):
27     """Specify the stored patterns."""
28
29     patterns must be a 1D- or 2D-array where each row is a pattern.
30     """
31     self.patterns = patterns
32
33 def generate_weights(self):
34     """Generate the weights for the network."""
35     _, n_neurons = self.patterns.shape
36     self.weights = np.zeros((n_neurons, n_neurons))
37     for pattern in self.patterns:
38         self.weights += np.outer(pattern, pattern)
39     self.weights /= n_neurons
40
41     if self.diagonal_weights_equal_zero:
42         np.fill_diagonal(self.weights, 0)
43
44 def update_random_neuron(self, pattern):
45     n_neurons = pattern.shape
46     neuron_index = np.random.randint(n_neurons)
47     return self.update_neuron(pattern, neuron_index)
48
49 def update_neuron(self, pattern, neuron_index):
50     """Returns updated pattern after update of neuron_index."""
51     weights_i = self.weights[neuron_index, :]
52     local_field = np.inner(weights_i, pattern)
53     updated_neuron = self.get_state_of_local_field(local_field)
54     updated_pattern = pattern.copy()
55     updated_pattern[neuron_index] = updated_neuron
56     return updated_pattern
57
58 @abstractmethod
59 def get_state_of_local_field(self, local_field):
60     pass
61
62
63 class DeterministicHopfieldNetwork(HopfieldNetwork):
64     """Concrete Hopfield net with deterministic updating."""
65
66     def get_state_of_local_field(self, local_field):
67         """Update rule when updating a neuron."""
68         return 1 if local_field >= 0 else -1
69
70
71 class StochasticHopfieldNetwork(HopfieldNetwork):
72     """Concrete Hopfield net with stochastic updating."""
73
74     def get_state_of_local_field(self, local_field):

```

```

75         """Update rule when updating a neuron.
76
77         Returns 1 with probability
78          $1 / (1 + \exp(-2 * \text{noise\_parameter} * \text{local\_field}))$ ,
79         else -1.
80         """
81         p = 1 / (1 + np.exp(-2 * self.noise_parameter * local_field))
82         rand = stats.bernoulli.rvs(p)
83         return 1 if rand else -1
84
85     def set_noise_parameter(self, noise_parameter):
86         self.noise_parameter = noise_parameter

```

```

1     """Functions for working with patterns.
2
3     A pattern is defined as a 1D-array and several patterns are stored as
4     a 2D-array, where each row corresponds to one pattern. Each element can
5     take the values -1 or +1 only.
6     """
7
8     import numpy as np
9     from scipy import stats
10
11
12     def generate_n_random_patterns(n_patterns, n_neurons):
13         """Returns n_patterns random patterns, each of length n_neurons.
14
15         If several patterns are generated, each row corresponds to one
16         pattern.
17         """
18         random_0s_and_1s = stats.bernoulli.rvs(0.5, size=(n_patterns, n_neurons))
19         random_minus_1s_and_1s = 2 * random_0s_and_1s - 1
20         return random_minus_1s_and_1s
21
22
23     def get_index_of_equal_pattern(pattern_to_match, patterns):
24         """Returns the row index of patterns corresponding to the pattern
25         that is equal to pattern_to_match.
26
27         Returns 1 if no matching pattern is found.
28         """
29         for index, pattern in enumerate(patterns):
30             n_different_neurons = get_n_different_neurons(pattern_to_match, pattern)
31             if n_different_neurons == 0:
32                 return index
33         return -1
34
35

```



```

36 def get_n_different_neurons(pattern1, pattern2):
37     return sum(pattern1 != pattern2)
38
39
40 def vector_to_ttypewriter(vector, n_columns):
41     """Returns 2D-array of vector.
42
43     The first row in the returned array consists of the first n_columns
44     elements in vector and so on.
45     """
46     return np.reshape(vector, (-1, n_columns))
47
48
49 def print_ttypewriter_pattern(pattern, n_columns):
50     """Prints a pattern in a typewriter scheme."""
51     print_pattern(vector_to_ttypewriter(pattern, n_columns))
52
53
54 def print_pattern(pattern):
55     np.set_printoptions(formatter={"float_kind": lambda x: "%.4f" % x})
56     print(repr(pattern), sep=", ")

```