

**W4995 Applied Machine Learning**

# Neural Networks

04/15/19

Andreas C. Müller

# History

- Nearly everything we talk about today existed ~1990
- What changed?
  - More data


# History

- Nearly everything we talk about today existed ~1990
- What changed?
  - More data
  - Faster computers (GPUs)


# History

- Nearly everything we talk about today existed ~1990
- What changed?
  - More data
  - Faster computers (GPUs)
  - Some improvements:
    - relu
    - Drop-out
    - adam
    - batch-normalization
    - residual networks

# Logistic regression as neural net




# Basic Architecture




$$h(x) = f(W_1x + b_1)$$

$$o(x) = g(W_2h(x) + b_2)$$

# More layers



# Nonlinear activation function





# Supervised Neural Networks

- Non-linear models for classification and regression
- Work well for very large datasets
- Non-convex optimization
- Notoriously slow to train – need for GPUs
- Use dot products etc require preprocessing, → similar to SVM or linear models, unlike trees
- MANY variants (Convolutional nets, Gated Recurrent neural networks, Long-Short-Term Memory, recursive neural networks, variational autoencoders, generative adversarial networks, deep reinforcement learning, ...)

# Training Objective

$$h(x) = f(W_1x + b_1)$$

$$o(x) = g(W_2h(x) + b_2) = g(W_2f(W_1x + b_1) + b_2)$$

# Training Objective

$$h(x) = f(W_1x + b_1)$$

$$o(x) = g(W_2h(x) + b_2) = g(W_2f(W_1x + b_1) + b_2)$$

$$\min_{W_1, W_2, b_1, b_2} \sum_{i=1}^N l(y_i, o(x_i))$$

# Training Objective

$$h(x) = f(W_1x + b_1)$$

$$o(x) = g(W_2h(x) + b_2) = g(W_2f(W_1x + b_1) + b_2)$$

$$\min_{W_1, W_2, b_1, b_2} \sum_{i=1}^N l(y_i, o(x_i))$$

$$= \min_{W_1, W_2, b_1, b_2} \sum_{i=1}^N l(y_i, g(W_2f(W_1x + b_1) + b_2))$$

# Training Objective

$$h(x) = f(W_1x + b_1)$$

$$o(x) = g(W_2h(x) + b_2) = g(W_2f(W_1x + b_1) + b_2)$$

$$\min_{W_1, W_2, b_1, b_2} \sum_{i=1}^N l(y_i, o(x_i))$$

$$= \min_{W_1, W_2, b_1, b_2} \sum_{i=1}^N l(y_i, g(W_2f(W_1x + b_1) + b_2))$$

-  $l$  Squared loss for regression. Cross-entropy loss for classification


# Backpropagation

- Need  $\frac{\partial l(y,o)}{\partial W_i}$  and  $\frac{\partial l(y,o)}{\partial b_i}$

$$\text{net}(x) := W_1 x + b_1$$

$$\frac{\partial o(\mathbf{x})}{\partial W_1} = \underbrace{\frac{\partial o(\mathbf{x})}{\partial h(\mathbf{x})}}_{\text{backpropagation of gradient of layer above.}} \underbrace{\frac{\partial h(\mathbf{x})}{\partial \text{net}(\mathbf{x})}}_{\text{Gradient of Non-linearity } f} \underbrace{\frac{\partial \text{net}(\mathbf{x})}{\partial W_1}}_{\text{Input to 1st layer } x}$$

# But wait!



# Optimizing $W, b$

Batch

$$W_i \leftarrow W_i - \eta \sum_{j=1}^N \frac{\partial l(x_j, y_j)}{\partial W_i}$$



# Optimizing $W, b$

Batch

$$W_i \leftarrow W_i - \eta \sum_{j=1}^N \frac{\partial l(x_j, y_j)}{\partial W_i}$$

Online/Stochastic

$$W_i \leftarrow W_i - \eta \frac{\partial l(x_j, y_j)}{\partial W_i}$$

# Optimizing $W, b$

Batch

$$W_i \leftarrow W_i - \eta \sum_{j=1}^N \frac{\partial l(x_j, y_j)}{\partial W_i}$$

Online/Stochastic

$$W_i \leftarrow W_i - \eta \frac{\partial l(x_j, y_j)}{\partial W_i}$$

Minibatch

$$W_i \leftarrow W_i - \eta \sum_{j=k}^{k+m} \frac{\partial l(x_j, y_j)}{\partial W_i}$$

# Learning Heuristics


- Constant  $\eta$  not good
- Can decrease  $\eta$
- Better: adaptive  $\eta$  for each entry if  $W_i$
- State-of-the-art: adam (with magic numbers)
- <https://arxiv.org/pdf/1412.6980.pdf>
- <http://sebastianruder.com/optimizing-gradient-descent/>

# Picking Optimization Algorithms

- Small dataset: off the shelf like l-bfgs
- Big dataset: adam / rmsprop
- Have time & nerve: tune the schedule

# Neural Nets in Practice


# Neural Nets with sklearn



```
mlp = MLPClassifier(solver='lbfgs', random_state=0).fit(X_train, y_train)
print(mlp.score(X_train, y_train))
print(mlp.score(X_test, y_test))
```

1.0  
0.88

# Random State



# Hidden Layer Size

```
mlp = MLPClassifier(solver='lbfgs', hidden_layer_size=(5,), random_state=10)
mlp.fit(X_train, y_train)
print(mlp.score(X_train, y_train))
print(mlp.score(X_test, y_test))
```

0.93

0.82





# Hidden Layer Size

```
mlp = MLPClassifier(solver='lbfgs', hidden_layer_sizes=(10, 10, 10),  
                    random_state=0)  
mlp.fit(X_train, y_train)  
print(mlp.score(X_train, y_train))  
print(mlp.score(X_test, y_test))
```

0.97

0.84




# Activation Functions

```
mlp = MLPClassifier(solver='lbfgs', hidden_layer_sizes=(10, 10, 10),  
                    activation='tanh', random_state=0)  
mlp.fit(X_train, y_train)  
print(mlp.score(X_train, y_train))  
print(mlp.score(X_test, y_test))
```

1.0  
0.92



# Regression



```
from sklearn.neural_network import MLPRegressor  
mlp_relu = MLPRegressor(solver="lbfgs").fit(X, y)  
mlp_tanh = MLPRegressor(solver="lbfgs", activation='tanh').fit(X, y)
```

27 / 44

# Complexity Control

- Number of parameters
- Regularization
- Early Stopping
- (drop-out)

# Grid-Searching Neural Nets

```
from sklearn.datasets import load_breast_cancer
data = load_breast_cancer()
X_train, X_test, y_train, y_test = train_test_split(
    data.data, data.target, stratify=data.target, random_state=0)

from sklearn.model_selection import GridSearchCV
pipe = make_pipeline(StandardScaler(), MLPClassifier(solver="lbfgs",
    random_state=1))
param_grid = {'mlpclassifier__alpha': np.logspace(-3, 3, 7)}
grid = GridSearchCV(pipe, param_grid, cv=5)

results = pd.DataFrame(grid.cv_results_)
res = results.pivot_table(index="param_mlpclassifier__alpha",
    values=["mean_test_score", "mean_train_score"])
res
```

	mean_test_score	mean_train_score
param_mlpclassifier__alpha		
0.001	0.978873	1.000000
0.010	0.981221	1.000000
0.100	0.971831	1.000000
1.000	0.978873	0.999412
10.000	0.983568	0.990612
100.000	0.938967	0.945427
1000.000	0.626761	0.626761



# Searching hidden layer sizes

```
from sklearn.model_selection import GridSearchCV
pipe = make_pipeline(StandardScaler(), MLPClassifier(solver="lbfgs"
                                                    ,random_state=1))
param_grid = {'mlpclassifier__hidden_layer_sizes':
              [(10,), (50,), (100,), (500,), (10, 10), (50, 50), (100, 100), (500,
              500)]
              }
grid = GridSearchCV(pipe, param_grid, cv=5)
grid.fit(X_train, y_train)
```



# Getting Flexible and Scaling Up



# Write your own neural networks

```
class NeuralNetwork(object):  
    def __init__(self):  
        # initialize coefficients and biases  
        pass  
    def forward(self, x):  
        activation = x  
        for coef, bias in zip(self.coef_, self.bias_):  
            activation = self.nonlinearity(np.dot(activation, coef) + bias)  
        return activation  
    def backward(self, x):  
        # compute gradient of stuff in forward pass  
        pass
```

# Autodiff

```
# http://mxnet.io/architecture/program_model.html
class array(object) :
    """Simple Array object that support autodiff."""
    def __init__(self, value, name=None):
        self.value = value
        if name:
            self.grad = lambda g : {name : g}
    def __add__(self, other):
        assert isinstance(other, int)
        ret = array(self.value + other)
        ret.grad = lambda g : self.grad(g)
        return ret
    def __mul__(self, other):
        assert isinstance(other, array)
        ret = array(self.value * other.value)
        def grad(g):
            x = self.grad(g * other.value)
            x.update(other.grad(g * self.value))
            return x
        ret.grad = grad
        return ret
```

34 / 44

```
a = array(np.array([1, 2]), 'a')
b = array(np.array([3, 4]), 'b')
c = b * a
d = c + 1
print(d.value)
print(d.grad(1))
```

```
[4 9]
{'b': array([1, 2]), 'a': array([3, 4])}
```


# GPU Support

TensorFlow Image Classification Training Performance



Dual CPU System: Dual Intel E5-2699 v4 @ 3.6 GHz | GPU-Accelerated System: Single Intel E5-2699 v4 @ 3.6 GHz, NVIDIA® Tesla® K80/M40/P100 (PCIe) | Google's Inception v3 image classification network, 500 steps, 64 Batch Size, cuDNN v5.1


TensorFlow Inception v3 Training Scalable Performance on Multi-GPU Node



GPU-Accelerated System: Single Intel E5-2699 v4 @ 3.6 GHz, NVIDIA® Tesla® K80/M40/P100 (PCIe) | Google's Inception v3 image classification network, 500 steps, 64 Batch Size, cuDNN v5.1

- These numbers are old.
- Up-to-date graphs at <https://developer.nvidia.com/deep-learning-performance-training-inference>

# Computation Graph



# All I want from a deep learning framework

- Autodiff
- GPU support
- Optimization and inspection of computation graph
- on-the-fly generation of the graph (?)
- distribution over multiple GPUs and/or cluster (?)

# All I want from a deep learning framework

- Autodiff
- GPU support
- Optimization and inspection of computation graph
- on-the-fly generation of the graph (?)
- distribution over multiple GPUs and/or cluster (?)
- Choices (right now):
  - TensorFlow
  - PyTorch / Torch
  - Chainer

# Deep Learning Libraries

- Keras (Tensorflow, CNTK, Theano)
- PyTorch (torch)
- Chainer (chainer)
- MXNet (MXNet)
- Also see: [http://mxnet.io/architecture/program\\_model.html](http://mxnet.io/architecture/program_model.html)



# Quick look at TensorFlow

- “down to the metal” - don’t use for everyday tasks
- Three steps for learning (originally):
  - Build the computation graph (using array operations and functions etc)
  - Create an Optimizer (gradient descent, adam, ...) attached to the graph.
  - Run the actual computation.
- Eager mode (default in Tensorflow 2.0):
  - Write imperative code directly

```
import tensorflow as tf
import numpy as np

# Create 100 phony x, y data points in NumPy, y = x * 0.1 + 0.3
x_data = np.random.rand(100).astype(np.float32)
y_data = x_data * 0.1 + 0.3

# create graph: model
W = tf.Variable(tf.random_uniform([1], -1.0, 1.0))
b = tf.Variable(tf.zeros([1]))
y = W * x_data + b

# create graph: loss
loss = tf.reduce_mean(tf.square(y - y_data))

# bind optimizer
optimizer = tf.train.GradientDescentOptimizer(0.5)
train = optimizer.minimize(loss)

# run graph
init = tf.global_variables_initializer()
sess = tf.Session()
sess.run(init)

# Fit the line.
for step in range(201):
    sess.run(train)
    if step % 20 == 0:
        print(step, sess.run(W), sess.run(b))
```

No  
computation

Allocate  
variables

All the work /  
computation

[https://www.tensorflow.org/versions/r0.10/get\\_started/](https://www.tensorflow.org/versions/r0.10/get_started/)

# Great Resources!

- <https://www.tensorflow.org/tutorials/>
- <http://playground.tensorflow.org>
- Tensorboard web interface

# Questions ?