

# swyft: Truncated Marginal Neural Ratio Estimation in Python

Benjamin Kurt Miller<sup>1,2,3</sup>, Alex Cole<sup>1</sup>, Christoph Weniger<sup>1</sup>, Francesco Nattino<sup>4</sup>, Ou Ku<sup>4</sup>, and Meiert W. Grootes<sup>4</sup>

<sup>1</sup> Gravitation Astroparticle Physics Amsterdam (GRAPPA), University of Amsterdam, Science Park 904, 1098 XH Amsterdam <sup>2</sup> Amsterdam Machine Learning Lab (AMLab), University of Amsterdam, Science Park 904, 1098 XH Amsterdam <sup>3</sup> AI4Science Lab, University of Amsterdam, Science Park 904, 1098 XH Amsterdam <sup>4</sup> Netherlands eScience Center, Science Park 140, 1098 XG Amsterdam, The Netherlands

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Pierre de Buyl](#) ↗

## Reviewers:

- [@mattpitkin](#)
- [@olgadoronina](#)

Submitted: 18 January 2022

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

Parametric stochastic numerical simulators are ubiquitous in science. They model observed phenomena by mapping a parametric representation of simulation conditions to a hypothetical observation—effectively sampling from a probability distribution over observational data known as the likelihood. Simulators are advantageous because they easily encode relevant scientific knowledge. *Simulation-based inference* (SBI) is a machine learning technique which applies a simulator, a fitted statistical surrogate model, and a set of prior beliefs to estimate a probabilistic description of the parameters which plausibly generated some observational data. This description of parameters is known as the posterior and it is the end-product of Bayesian inference.

Our package *swyft* implements a specific, simulation-efficient SBI method called *Truncated Marginal Neural Ratio Estimation* (TMNRE) ([Miller et al., 2021](#)); it estimates the likelihood-to-evidence ratio to approximate the posterior, as in [Hermans et al. \(2020\)](#). *swyft* ([Miller et al., 2020](#)) provides a collection of tools to simulate and store data, locally or in a distributed computing setting, and perform (marginalized) simulation-based Bayesian inference. It produces ready-to-publish plots that demonstrate the calibration of the posterior estimate along with the posterior itself.

## Motivation

Estimating the posterior can be prohibitively expensive for complex data and slow simulators. Part of the reason is the sequential nature of likelihood-based Markov chain Monte-Carlo ([Hastings, 1970](#); [Metropolis et al., 1953](#)). In contrast, SBI parallelizes simulation in most circumstances, thereby reducing the practical waiting time for results. In pursuit of further simulation efficiency, [Miller et al. \(2021\)](#) argue that fitting the joint posterior for all parameters is unnecessary when a marginal estimate of the posterior will suffice. Some SBI methods are amortized, whereby the statistical model is fit to estimate posteriors for all possible observations simultaneously. While amortization enables necessary posterior calibration checks, like expected coverage probability ([Hermans et al., 2021](#); [Miller et al., 2021](#)), it is more efficient to fit the model on only a subset of the parameters that could have plausibly generated the observation.

*swyft* satisfies necessary requirements, like estimating the marginal posteriors of interest and enabling posterior calibration checks, while taking a lean approach to avoid all unnecessary simulation. In this pursuit, *swyft* truncates the prior to regions relevant for given observational data and reuses compatible existing simulations. *swyft* automates irksome matters like

distributed computing and data storage. `swyft` is designed to:

1. Estimate arbitrary marginal posteriors, i.e., the posterior over parameters of interest, marginalizing over nuisance parameters.
2. Perform targeted inference by truncating the prior distribution with an indicator function estimated in a sequence of inferences.
3. Estimate the expected coverage probability of fully amortized SBI posteriors and locally amortized posteriors that are limited to truncated regions.
4. Seamlessly reuse simulations from previous analyses by drawing already-simulated data first via a flexible storage solution.
5. Integrate advanced distribution and storage tools to simplify application of complex simulators.

Although there is a rich ecosystem of SBI implementations, TMNRE did not naturally fit in an existing framework since it requires parallel estimation of marginal posteriors and a truncated prior. `swyft` aims to meet the ever-increasing demand for efficient and testable Bayesian inference in fields like physics, cosmology, and astronomy by implementing TMNRE together with practical distributed computing and storage tools.

## Existing research with `swyft`

The software package has enabled inference on dark matter substructure in strongly lensed galaxies (Coogan et al., 2020), estimated cosmological parameters from cosmic microwave background simulation data (Cole et al., 2021), and was cited in a white paper laying out a vision for astroparticle physics research during the next decade (Batista et al., 2021). Ongoing work with `swyft` aims to reduce the response time to gravitational wave triggers from LIGO-Virgo by estimating the marginal posterior with unprecedented speed. There is an existing proof-of-concept by Delaunoy et al. (2020) although the `swyft` software package was not applied. Generally, speeding up gravitational wave inference using simulation-based inference is an active area of research (Chua & Vallisneri, 2020; Dax et al., 2021; Gabbard et al., 2022). In another work-in-progress, `swyft` helps to characterize the magnetohydrodynamics of binary neutron star mergers using multi-messenger gravitational and electrodynamic data where marginalization would be impossible with likelihood-based methods.

## Related theoretical work

There is a long tradition of likelihood-free inference, also known as *Approximate Bayesian Computation* (ABC), going back to as early as the 1980s (Beaumont et al., 2009; Diggle & Gratton, 1984; Rubin, 1984; Tavaré et al., 1997; Toni et al., 2009). Traditional techniques use Monte-Carlo rejection sampling and are summarized by Sisson et al. (2018) and Karabatsos & Leisen (2018). We track the development of classifiers for the estimation of likelihood ratios to a few references. Cranmer et al. (2015) compared the ratio between the likelihood of a freely varying parameter and a fixed reference value for frequentist inference. Pham et al. (2014) estimated the ratio between likelihoods for Markov chain Monte-Carlo sampling. Thomas et al. (2016) and Gutmann et al. (2018) introduced the framework which allows for likelihood-to-evidence ratio estimation. Like `swyft`, Blum & François (2010) proposed to truncate the prior for sampling but do so within an ABC scheme.

Modern SBI is a quickly evolving field that has several techniques under development (Cranmer et al., 2020). Neural network-based methods are categorized according to the term they approximate in Bayes' formula. `swyft` is a method which approximates the likelihood-to-evidence ratio  $\frac{p(x|\theta)}{p(x)}$  where  $\theta$  are the parameters and  $x$  is the observational data. Works by Hermans et al. (2020), Durkan et al. (2020), and Rozet & Louppe (2021) are closely related to `swyft` as they also approximate the likelihood-to-evidence ratio. Like `swyft`, Rozet & Louppe (2021) estimate marginal posteriors, but unlike `swyft`, they attempt to amortize over all possible marginals with a single neural network. Other methods estimate the posterior

91 directly (Durkan et al., 2020; Greenberg et al., 2019; Lueckmann et al., 2017; Papamakarios  
92 & Murray, 2016) or the likelihood itself (Lueckmann et al., 2019; Papamakarios et al., 2019).

## 93 Related software

94 swyft is unique because it implements TMNRE and a method for simulation reuse. It also  
95 offers sophisticated distributed simulation and storage tools coupled directly to the software.  
96 We briefly discuss the alternatives in the thriving ecosystem of SBI software packages.

97 sbi (Tejero-Cantero et al., 2020) features a selection of modern neural SBI algorithms. It  
98 is accompanied by a benchmark sbibm (Lueckmann et al., 2021) which tests those methods  
99 against a set of tractable toy problems. pydelfi (Alsing, 2019) estimates the likelihood of a  
100 learned summary statistic (Alsing et al., 2018, 2019)—swyft users should pay special attention  
101 to this repository since it can also project out nuisance parameters (Alsing & Wandelt, 2019).  
102 carl (Louppe et al., 2016) uses a classifier to estimate the likelihood ratio as Cranmer et al.  
103 (2015) did and hypothesis (Hermans, 2019) includes several toy simulators.

104 Non-neural implementations for SBI also exist. elfi (Lintusaari et al., 2018) implements  
105 BOLFI, an algorithm based on Gaussian processes (Gutmann et al., 2016). pyabc (Klinger et  
106 al., 2018) and ABCpy (Dutta et al., 2017) are two suites of ABC algorithms.

## 107 Description of software

108 swyft implements *Marginal Neural Ratio Estimation* (MNRE), a method which trains an  
109 amortized likelihood-to-evidence ratio estimator for any marginal posterior of interest. swyft  
110 makes it easy to estimate a set of marginals in parallel, e.g., for a corner plot. To use swyft,  
111 the operator must provide a quantification of prior beliefs, a python-callable or bash-scriptable  
112 simulator, and an observation-of-interest.

113 Performing TMNRE with swyft, by restricting simulation to a truncated prior region, is simple  
114 and demonstrated in the documentation. Constructing these truncated regions can be done  
115 manually or based on a previous inference. Routines are provided for all necessary plots and for  
116 calculating the expected coverage probability of a given likelihood-to-evidence ratio estimator.  
117 This calculation is essential as a sanity check to determine whether the approximate posterior  
118 is calibrated.

119 The machine learning aspects of swyft are implemented in PyTorch (Paszke et al., 2019)  
120 while the truncated prior is implemented within numpy (Harris et al., 2020). Storing previously  
121 simulated data for reuse in later analyses is accomplished with zarr (Miles et al., 2021) and  
122 parallelization of simulation is achieved with dask (Dask Development Team, 2016). swyft has  
123 other important dependencies, namely scipy (Virtanen et al., 2020), seaborn (Waskom, 2021),  
124 matplotlib (Hunter, 2007), pandas (McKinney, 2010; Reback et al., 2021), and jupyter  
125 (Kluyver et al., 2016).

## 126 Acknowledgements

127 The developers of swyft want to thank early adopters of the software Adam Coogan, Noemi  
128 Anau Montel, Kosio Karchev, Elias Dubbeldam, Uddipta Bhardwaj, and Ioannis Bousdoukos.  
129 We are grateful for the additional expertise offered by Patrick Forré and Samaya Nissanke.

130 Benjamin Kurt Miller is funded by the University of Amsterdam Faculty of Science (FNWI),  
131 Informatics Institute (IvI), and the Institute of Physics (IoP). This project received funding  
132 from the European Research Council (ERC) under the European Union's Horizon 2020 research  
133 and innovation programme (Grant agreement No. 864035 – UnDark). This work was also  
134 supported by the Netherlands eScience Center and SURF under grant number ETEC.2019.018.  
135 This work was carried out on the Dutch national e-infrastructure with the support of SURF

Cooperative. We also would like to thank SURF for providing computational resources via the EINF-1194 grant.

## References

- Alsing, J. (2019). pydelfi: Density estimation likelihood-free inference. In *GitHub repository*. <https://github.com/justinalsing/pydelfi>; GitHub.
- Alsing, J., Charnock, T., Feeney, S., & Wandelt, B. (2019). Fast likelihood-free cosmology with neural density estimators and active learning. *Monthly Notices of the Royal Astronomical Society*, 488(3), 4440–4458. <https://doi.org/10.1093/mnras/stz1960>
- Alsing, J., & Wandelt, B. (2019). Nuisance hardened data compression for fast likelihood-free inference. *Monthly Notices of the Royal Astronomical Society*, 488(4), 5093–5103. <https://doi.org/10.1093/mnras/stz1900>
- Alsing, J., Wandelt, B., & Feeney, S. (2018). Massive optimal data compression and density estimation for scalable, likelihood-free inference in cosmology. *Monthly Notices of the Royal Astronomical Society*, 477(3), 2874–2885. <https://doi.org/10.1093/mnras/sty819>
- Batista, R. A., Amin, M., Barenboim, G., Bartolo, N., Baumann, D., Bauswein, A., Bellini, E., Benisty, D., Bertone, G., Blasi, P., & others. (2021). EuCAPT white paper: Opportunities and challenges for theoretical astroparticle physics in the next decade. *arXiv Preprint arXiv:2110.10074*.
- Beaumont, M. A., Cornuet, J.-M., Marin, J.-M., & Robert, C. P. (2009). Adaptive approximate bayesian computation. *Biometrika*, 96(4), 983–990.
- Blum, M. G., & François, O. (2010). Non-linear regression models for approximate bayesian computation. *Statistics and Computing*, 20(1), 63–73. <https://doi.org/10.1007/s11222-009-9116-0>
- Chua, A. J., & Vallisneri, M. (2020). Learning bayesian posteriors with neural networks for gravitational-wave inference. *Physical Review Letters*, 124(4), 041102. <https://doi.org/10.1103/PhysRevLett.124.041102>
- Cole, A., Miller, B. K., Witte, S. J., Cai, M. X., Grootes, M. W., Nattino, F., & Weniger, C. (2021). Fast and credible likelihood-free cosmology with truncated marginal neural ratio estimation. *arXiv Preprint arXiv:2111.08030*.
- Coogan, A., Karchev, K., & Weniger, C. (2020). Targeted likelihood-free inference of dark matter substructure in strongly-lensed galaxies. *Machine Learning and the Physical Sciences: Workshop at the 34th Conference on Neural Information Processing Systems (NeurIPS)*.
- Cranmer, K., Brehmer, J., & Louppe, G. (2020). The frontier of simulation-based inference. *Proc. Natl. Acad. Sci. U. S. A.*
- Cranmer, K., Pavez, J., & Louppe, G. (2015). Approximating likelihood ratios with calibrated discriminative classifiers. *arXiv Preprint arXiv:1506.02169*.
- Dask Development Team. (2016). *Dask: Library for dynamic task scheduling*. <https://dask.org>
- Dax, M., Green, S. R., Gair, J., Macke, J. H., Buonanno, A., & Schölkopf, B. (2021). Real-time gravitational wave science with neural posterior estimation. *Physical Review Letters*, 127(24), 241103. <https://doi.org/10.1103/PhysRevLett.127.241103>
- Delaunoy, A., Wehenkel, A., Hinderer, T., Nissanke, S., Weniger, C., Williamson, A. R., & Louppe, G. (2020). Lightning-fast gravitational wave parameter inference through neural amortization. *Machine Learning and the Physical Sciences: Workshop at the 34th Conference on Neural Information Processing Systems (NeurIPS)*.

- 181 Diggle, P. J., & Gratton, R. J. (1984). Monte carlo methods of inference for implicit  
182 statistical models. *Journal of the Royal Statistical Society: Series B (Methodological)*,  
183 46(2), 193–212. <https://doi.org/10.1111/j.2517-6161.1984.tb01290.x>
- 184 Durkan, C., Murray, I., & Papamakarios, G. (2020). On contrastive learning for likelihood-free  
185 inference. *International Conference on Machine Learning*, 2771–2781.
- 186 Dutta, R., Schoengens, M., Onnela, J.-P., & Mira, A. (2017). ABCpy: A user-friendly,  
187 extensible, and parallel library for approximate bayesian computation. *Proceedings of*  
188 *the Platform for Advanced Scientific Computing Conference*, 8:1–8:9. [https://doi.org/10.](https://doi.org/10.1145/3093172.3093233)  
189 [1145/3093172.3093233](https://doi.org/10.1145/3093172.3093233)
- 190 Gabbard, H., Messenger, C., Heng, I. S., Tonolini, F., & Murray-Smith, R. (2022). Bayesian  
191 parameter estimation using conditional variational autoencoders for gravitational-wave  
192 astronomy. *Nature Physics*, 18(1), 112–117. <https://doi.org/10.1038/s41567-021-01425-7>
- 193 Greenberg, D., Nonnenmacher, M., & Macke, J. (2019). Automatic posterior transformation  
194 for likelihood-free inference. *International Conference on Machine Learning*, 2404–2414.
- 195 Gutmann, M. U., Corander, J., & others. (2016). Bayesian optimization for likelihood-free  
196 inference of simulator-based statistical models. *Journal of Machine Learning Research*.
- 197 Gutmann, M. U., Dutta, R., Kaski, S., & Corander, J. (2018). Likelihood-free inference  
198 via classification. *Statistics and Computing*, 28(2), 411–425. [https://doi.org/10.1007/](https://doi.org/10.1007/s11222-017-9738-6)  
199 [s11222-017-9738-6](https://doi.org/10.1007/s11222-017-9738-6)
- 200 Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,  
201 Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk,  
202 M. H. van, Brett, M., Haldane, A., R'io, J. F. del, Wiebe, M., Peterson, P., ... Oliphant,  
203 T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. <https://doi.org/10.1038/s41586-020-2649-2>
- 204
- 205 Hastings, W. K. (1970). Monte carlo sampling methods using markov chains and their  
206 applications. *Biometrika*, 57(1), 97–109. <https://doi.org/10.1093/biomet/57.1.97>
- 207 Hermans, J. (2019). Hypothesis. In *GitHub repository*. [https://github.com/montefiore-ai/](https://github.com/montefiore-ai/hypothesis)  
208 [hypothesis](https://github.com/montefiore-ai/hypothesis); GitHub.
- 209 Hermans, J., Begy, V., & Louppe, G. (2020). Likelihood-free mcmc with amortized approximate  
210 ratio estimators. *International Conference on Machine Learning*, 4239–4248.
- 211 Hermans, J., Delaunoy, A., Rozet, F., Wehenkel, A., & Louppe, G. (2021). Averting a crisis in  
212 simulation-based inference. *arXiv Preprint arXiv:2110.06581*.
- 213 Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science &*  
214 *Engineering*, 9(3), 90–95. <https://doi.org/10.1109/MCSE.2007.55>
- 215 Karabatsos, G., & Leisen, F. (2018). An approximate likelihood perspective on ABC methods.  
216 *Statistics Surveys*, 12, 66–104. <https://doi.org/10.1214/18-ss120>
- 217 Klinger, E., Rickert, D., & Hasenauer, J. (2018). pyABC: Distributed, likelihood-free inference.  
218 *Bioinformatics*, 34(20), 3591–3593. <https://doi.org/10.1093/bioinformatics/bty361>
- 219 Kluyver, T., Ragan-Kelley, B., Pérez, F., Granger, B., Bussonnier, M., Frederic, J., Kelley,  
220 K., Hamrick, J., Grout, J., Corlay, S., Ivanov, P., Avila, D., Abdalla, S., Willing, C., &  
221 team, J. development. (2016). Jupyter notebooks - a publishing format for reproducible  
222 computational workflows. In F. Loizides & B. Schmidt (Eds.), *Positioning and power*  
223 *in academic publishing: Players, agents and agendas* (pp. 87–90). IOS Press. <https://eprints.soton.ac.uk/403913/>
- 224
- 225 Lintusaari, J., Vuollekoski, H., Kangasrääsiö, A., Skytén, K., Järvenpää, M., Marttinen,  
226 P., Gutmann, M. U., Vehtari, A., Corander, J., & Kaski, S. (2018). ELFI: Engine for  
227 likelihood-free inference. *The Journal of Machine Learning Research*, 19(1), 643–649.



- 228 Louppe, G., Cranmer, K., & Pavez, J. (2016). carl: A likelihood-free inference toolbox. *Journal*  
229 *of Open Source Software*, 1(1), 11. <https://doi.org/10.21105/joss.00011>
- 230 Lueckmann, J.-M., Bassetto, G., Karaletsos, T., & Macke, J. H. (2019). Likelihood-free  
231 inference with emulator networks. *Symposium on Advances in Approximate Bayesian*  
232 *Inference*, 32–53.
- 233 Lueckmann, J.-M., Boelts, J., Greenberg, D., Goncalves, P., & Macke, J. (2021). Benchmarking  
234 simulation-based inference. In A. Banerjee & K. Fukumizu (Eds.), *Proceedings of the 24th*  
235 *international conference on artificial intelligence and statistics* (Vol. 130, pp. 343–351).  
236 PMLR. <http://proceedings.mlr.press/v130/lueckmann21a.html>
- 237 Lueckmann, J.-M., Gonçalves, P. J., Bassetto, G., Öcal, K., Nonnenmacher, M., & Macke, J.  
238 H. (2017). Flexible statistical inference for mechanistic models of neural dynamics. *Pro-*  
239 *ceedings of the 31st International Conference on Neural Information Processing Systems*,  
240 1289–1299.
- 241 McKinney, Wes. (2010). Data Structures for Statistical Computing in Python. In Stéfan van  
242 der Walt & Jarrod Millman (Eds.), *Proceedings of the 9th Python in Science Conference*  
243 (pp. 56–61). <https://doi.org/10.25080/Majora-92bf1922-00a>
- 244 Metropolis, N., Rosenbluth, A. W., Rosenbluth, M. N., Teller, A. H., & Teller, E. (1953).  
245 Equation of state calculations by fast computing machines. *J. Chem. Phys.*, 21(6),  
246 1087–1092. <https://doi.org/10.2172/4390578>
- 247 Miles, A., jakirkham, Bussonnier, M., Moore, J., Fulton, A., Bourbeau, J., Onalan, T.,  
248 Hamman, J., Patel, Z., Rocklin, M., & al., et. (2021). *Zarr-developers/zarr-python*:  
249 <https://doi.org/10.5281/zenodo.5712786>
- 250 Miller, B. K., Cole, A., Forré, P., Louppe, G., & Weniger, C. (2021). Truncated marginal  
251 neural ratio estimation. *Advances in Neural Information Processing Systems*, 34.
- 252 Miller, B. K., Cole, A., Louppe, G., & Weniger, C. (2020). Simulation-efficient marginal  
253 posterior estimation with swyft: Stop wasting your precious time. *Machine Learning and*  
254 *the Physical Sciences: Workshop at the 34th Conference on Neural Information Processing*  
255 *Systems (NeurIPS)*.
- 256 Papamakarios, G., & Murray, I. (2016). Fast  $\epsilon$ -free inference of simulation models  
257 with bayesian conditional density estimation. In D. Lee, M. Sugiyama, U. Luxburg,  
258 I. Guyon, & R. Garnett (Eds.), *Advances in neural information processing systems*  
259 (Vol. 29). Curran Associates, Inc. [https://proceedings.neurips.cc/paper/2016/file/](https://proceedings.neurips.cc/paper/2016/file/6aca97005c68f1206823815f66102863-Paper.pdf)  
260 [6aca97005c68f1206823815f66102863-Paper.pdf](https://proceedings.neurips.cc/paper/2016/file/6aca97005c68f1206823815f66102863-Paper.pdf)
- 261 Papamakarios, G., Sterratt, D., & Murray, I. (2019). Sequential neural likelihood: Fast  
262 likelihood-free inference with autoregressive flows. *The 22nd International Conference on*  
263 *Artificial Intelligence and Statistics*, 837–848.
- 264 Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,  
265 Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M.,  
266 Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch: An  
267 imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A.  
268 Beygelzimer, F. d Alché-Buc, E. Fox, & R. Garnett (Eds.), *Advances in neural information*  
269 *processing systems* 32 (pp. 8024–8035). Curran Associates, Inc. [http://papers.neurips.](http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf)  
270 [cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf](http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf)
- 271 Pham, K. C., Nott, D. J., & Chaudhuri, S. (2014). A note on approximating ABC-MCMC  
272 using flexible classifiers. *Stat*, 3(1), 218–227. <https://doi.org/10.1002/sta4.56>
- 273 Reback, J., jbrockmendel, McKinney, W., Bossche, J. V. den, Augspurger, T., Cloud, P.,  
274 Hawkins, S., Roeschke, M., gyoung, Sinhrks, & al., et. (2021). *Pandas-dev/pandas*.  
275 <https://doi.org/10.5281/zenodo.3509134>

- 276 Rozet, F., & Louppe, G. (2021). Arbitrary marginal neural ratio estimation for simulation-based  
277 inference. *Machine Learning and the Physical Sciences: Workshop at the 35th Conference*  
278 *on Neural Information Processing Systems (NeurIPS)*.
- 279 Rubin, D. B. (1984). Bayesianly Justifiable and Relevant Frequency Calculations for the Applied  
280 Statistician. *The Annals of Statistics*, 12(4), 1151–1172. [https://doi.org/10.1214/aos/](https://doi.org/10.1214/aos/1176346785)  
281 [1176346785](https://doi.org/10.1214/aos/1176346785)
- 282 Sisson, S. A., Fan, Y., & Beaumont, M. (2018). *Handbook of approximate bayesian compu-*  
283 *tation*. CRC Press.
- 284 Tavaré, S., Balding, D. J., Griffiths, R. C., & Donnelly, P. (1997). Inferring Coalescence Times  
285 From DNA Sequence Data. *Genetics*, 145(2), 505–518. [https://doi.org/10.1093/genetics/](https://doi.org/10.1093/genetics/145.2.505)  
286 [145.2.505](https://doi.org/10.1093/genetics/145.2.505)
- 287 Tejero-Cantero, A., Boelts, J., Deistler, M., Lueckmann, J.-M., Durkan, C., Gonçalves, P. J.,  
288 Greenberg, D. S., & Macke, J. H. (2020). Sbi: A toolkit for simulation-based inference.  
289 *Journal of Open Source Software*, 5(52), 2505. <https://doi.org/10.21105/joss.02505>
- 290 Thomas, O., Dutta, R., Corander, J., Kaski, S., Gutmann, M. U., & others. (2016). Likelihood-  
291 free inference by ratio estimation. *Bayesian Analysis*. <https://doi.org/10.1214/20-ba1238>
- 292 Toni, T., Welch, D., Strelkowa, N., Ipsen, A., & Stumpf, M. P. H. (2009). Approximate  
293 bayesian computation scheme for parameter inference and model selection in dynamical  
294 systems. *J. R. Soc. Interface*, 6(31), 187–202. <https://doi.org/10.1098/rsif.2008.0172>
- 295 Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D.,  
296 Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S. J., Brett, M., Wilson,  
297 J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E., ... SciPy  
298 1.0 Contributors. (2020). SciPy 1.0: Fundamental Algorithms for Scientific Computing in  
299 Python. *Nature Methods*, 17, 261–272. <https://doi.org/10.1038/s41592-019-0686-2>
- 300 Waskom, M. L. (2021). Seaborn: Statistical data visualization. *Journal of Open Source*  
301 *Software*, 6(60), 3021. <https://doi.org/10.21105/joss.03021>