

# pymdp: A Python library for active inference in discrete state spaces

Conor Heins<sup>1,2,3,4¶</sup>, Beren Millidge<sup>4,5</sup>, Daphne Demekas<sup>6</sup>, Brennan Klein<sup>4,7,8</sup>, Karl Friston<sup>9</sup>, Iain D. Couzin<sup>1,2,3</sup>, and Alexander Tschantz<sup>4,10,11¶</sup>

<sup>1</sup> Department of Collective Behaviour, Max Planck Institute of Animal Behavior, 78457 Konstanz, Germany <sup>2</sup> Centre for the Advanced Study of Collective Behaviour, 78457 Konstanz, Germany <sup>3</sup> Department of Biology, University of Konstanz, 78457 Konstanz, Germany <sup>4</sup> VERSES Research Lab, Los Angeles, California, USA <sup>5</sup> MRC Brain Networks Dynamics Unit, University of Oxford, Oxford, UK <sup>6</sup> Department of Computing, Imperial College London, London, UK <sup>7</sup> Network Science Institute, Northeastern University, Boston, MA, USA <sup>8</sup> Laboratory for the Modeling of Biological and Socio-Technical Systems, Northeastern University, Boston, USA <sup>9</sup> Wellcome Centre for Human Neuroimaging, Queen Square Institute of Neurology, University College London, London WC1N 3AR, UK <sup>10</sup> Sussex AI Group, Department of Informatics, University of Sussex, Brighton, UK <sup>11</sup> Sackler Centre for Consciousness Science, University of Sussex, Brighton, UK ¶ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Elizabeth DuPre](#) ↗

## Reviewers:

- [@seankmartin](#)
- [@patrickmineault](#)

Submitted: 14 January 2022

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Statement of Need

Active inference is an account of cognition and behavior in complex systems which brings together action, perception, and learning under the theoretical mantle of Bayesian inference (Friston et al., 2009, 2012, 2015, 2017). Active inference has seen growing applications in academic research, especially in fields that seek to model human or animal behavior (Adams et al., 2021; Holmes et al., 2021; Parr et al., 2020). The majority of applications have focused on cognitive neuroscience, with a particular focus on modelling decision-making under uncertainty (Schwartenbeck et al., 2015; Smith et al., 2020, 2021). Nonetheless, the framework has broad applicability and has recently been applied to diverse disciplines, ranging from computational models of psychopathology (Montague et al., 2012; Smith et al., 2021), control theory (Baïoumy et al., 2021; Baltieri & Buckley, 2019; Millidge et al., 2020) and reinforcement learning (Fountas et al., 2020; Millidge, 2020; Sajid et al., 2021; Tschantz, Baltieri, et al., 2020; Tschantz, Millidge, et al., 2020), through to social cognition (Adams et al., 2021; Tison & Poirier, 2021; Wirkuttis & Tani, 2021) and even real-world engineering problems (Fox, 2021; Martínez et al., 2021; Moreno, 2021). While in recent years, some of the code arising from the active inference literature has been written in open source languages like Python and Julia (Çatal et al., 2020; T. W. van de Laar & Vries, 2019; Millidge, 2020; Tschantz, Seth, et al., 2020; Ueltzhöffer, 2018), to-date, the most popular software for simulating active inference agents is the DEM toolbox of SPM (Friston et al., 2008; Smith et al., 2022), a MATLAB library originally developed for the statistical analysis and modelling of neuroimaging data (Penny et al., 2007). DEM contains a reliable, reproducible set of functions for studying active inference, but the use of the toolbox can be restrictive for researchers in settings where purchasing a MATLAB license is financially costly. And although active inference researchers have relied heavily on DEM for simulating and fitting models of behavior, most of its functionality is restricted to single MATLAB scripts or functions, particularly one called `spm_MDP_VB_X.m`, that lack modularity and often must be customized for applications on a domain-specific basis. Increasing interest in active inference, manifested both in terms of sheer number of cited research papers as well as diversifying applications across disciplines, has thus created a need for generic, widely-available, and user-friendly code for simulating active inference in open-source scientific computing languages like Python. The software we present here, `pymdp`,

46 represents a significant step in this direction: namely, we provide the first open-source package  
47 for simulating active inference with discrete state-space generative models. The name pymdp  
48 derives from the fact that the package is written in the **Python** programming language and  
49 concerns discrete, Markovian generative models of decision-making, which take the form of  
50 Markov Decision Processes or **MDPs**.

51 pymdp is a Python package that is directly inspired by the active inference routines contained  
52 in DEM. However, pymdp is has a modular, flexible structure that allows researchers to build and  
53 simulate active inference agents quickly and with a high degree of customization. We developed  
54 pymdp in the hopes that it will increase the accessibility and exposure of the active inference  
55 framework to researchers, engineers, and developers with diverse disciplinary backgrounds. In  
56 the spirit of open-source software, we also hope that it spurs new innovation, development,  
57 and collaboration in the growing active inference and wider Bayesian modelling communities.

## 58 Summary

59 pymdp offers a suite of robust, tested, and modular routines for simulating active inference  
60 agents equipped with *partially-observable Markov Decision Process* (POMDP) generative  
61 models. Mathematically, a POMDP comprises a joint distribution over observations  $o$ , hidden  
62 states  $s$ , control states  $u$  and hyperparameters  $\phi$ :  $P(o, s, u, \phi)$ . This joint distribution further  
63 factorizes into a set of categorical and Dirichlet distributions: the likelihoods and priors of  
64 the generative model. With pymdp, one can build a generative model using a set of prior and  
65 likelihood distributions, initialize an agent, and then link it to an external environment to  
66 run active inference processes - all in a few lines of code. The Agent and Env (environment)  
67 APIs of pymdp are built according to the standardized framework of OpenAIGym commonly  
68 used in reinforcement learning, where an agent and environment object recursively exchange  
69 observations and actions over time (Brockman et al., 2016).

## 70 Introduction

71 Simulations of active inference are commonly performed in discrete time and space (Da  
72 Costa et al., 2020; Friston et al., 2015). This is partially motivated by the mathematical  
73 tractability of performing inference with discrete probability distributions, but also by the  
74 intuition of modelling choice behavior as a sequence of discrete, mutually-exclusive choices,  
75 in e.g. psychophysics or decision-making experiments. The most popular generative models  
76 – used to realize active inference in this context – are partially-observable Markov Decision  
77 Processes or *POMDPs* (Kaelbling et al., 1998). POMDPs are state-space models that model  
78 the environment in terms of hidden states that stochastically change over time, as a function of  
79 both the current state of the environment as well as the behavioral output of an agent (control  
80 states or actions). Crucially, the environment is *partially-observable*, i.e. the hidden states  
81 are not directly observed by the agent, but can only be inferred through observations that  
82 relate to hidden states in a probabilistic manner, such that observations are modelled as being  
83 generated stochastically from the current hidden state. This necessitates both “perceptual”  
84 inference of hidden states as well as control.

85 As such, in most POMDP problems, an agent is tasked with inferring the hidden state of  
86 its environment and then choosing a sequence of control states or actions to change hidden  
87 states in a way that leads to desired outcomes (maximizing reward, or occupancy within some  
88 preferred set of states).

## 89 Usage

90 In order to enhance the user-friendliness of pymdp without sacrificing flexibility, we have built  
91 the library to be highly modular and customizable, such that agents in pymdp can be specified

at a variety of levels of abstraction with desired parameterisations. The methods of the Agent class can thus be called in any particular order, depending on the application, and furthermore they can be specified with various keyword arguments that entail choices of implementation details at lower levels.

By retaining a modular structure throughout the package's dependency hierarchy, pymdp also affords the ability to flexibly compose different low level functions. This allows users to customize and integrate their active inference loops with desired inference algorithms and policy selection routines. For instance, one could sub-class the Agent class and write a customized `step()` function, that combines whichever components of active inference one is interested in.

## Related software packages

The DEM toolbox within SPM in MATLAB is the current gold-standard in active inference modelling. In particular, simulating an active inference process in DEM consists of defining the generative model in terms of a fixed set of matrices and vectors, and then calling the `spm_MDP_VB_X.m` function to simulate a sequence of trials. pymdp, by contrast, provides a user-friendly and modular development experience, with core functionality split up into different libraries that separately perform the computations of active inference in a standalone fashion. Moreover, pymdp provides the user the ability to write an active inference process at different levels of abstraction depending on the user's level of expertise or skill with the package – ranging from the high level Agent functionality, which allows the user to define and simulate an active inference agent in just a few lines of code, all the way to specifying a particular variational inference algorithm (e.g. marginal-message passing (Parr et al., 2019)) for the agent to use during state estimation. In the DEM toolbox of SPM, this would require setting undocumented flags or else manually editing the routines in `spm_MDP_VB_X.m` to enable or disable bespoke functionality. There has been one recent attempt at creating a comprehensive user-guide for building active inference agents in DEM (Smith et al., 2022), though to our knowledge there has not been a package devoted to the open source development of these powerful software tools.

A recent related, but largely non-overlapping project is ForneyLab, which provides a set of Julia libraries for performing approximate Bayesian inference via message passing on Forney Factor Graphs (Cox et al., 2019). Notably, this package has also seen several applications in simulating active inference processes, using ForneyLab as the backend for the inference algorithms employed by an active inference agent (Ergul et al., 2020; T. van de Laar et al., 2021; T. W. van de Laar & Vries, 2019; Vanderbroeck et al., 2019). While ForneyLab focuses on including a rigorous set of message passing routines that can be used to simulate active inference agents, pymdp is specifically designed to help users quickly build agents (regardless of their underlying inference routines) and plug them into arbitrary environments to run active inference in a few easy steps.

## Funding Statement

CH and IDC acknowledge support from the Office of Naval Research grant (ONR, N00014-64019-1-2556), with IDC further acknowledging support from the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement (ID: 860949), the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy-EXC 2117- 422037984, and the Max Planck Society. KF is supported by funding for the Wellcome Centre for Human Neuroimaging (Ref: 205103/Z/16/Z) and the Canada-UK Artificial Intelligence Initiative (Ref: ES/T01279X/1). CH, DD, and BK acknowledge the support of a grant from the John Templeton Foundation (61780). The opinions expressed in this publication are those of the author(s) and do not necessarily reflect the views of the John Templeton Foundation.

## Acknowledgements

The authors would like to thank Dimitrije Markovic, Arun Niranjana, Sivan Altinakar, Mahault Albarracin, Alex Kiefer, Magnus Koudahl, Ryan Smith, Casper Hesp, and Maxwell Ramstead for discussions and feedback that contributed to development of pymdp. We would also like to thank Thomas Parr for pointing out a technical error in an earlier version of the arXiv preprint for this work. Finally, we are grateful to the many users of pymdp whose feedback and usage of the package have contributed to its continued improvement and development.

## References

- Adams, R. A., Vincent, P., Benrimoh, D., Friston, K. J., & Parr, T. (2021). Everything is connected: Inference and attractors in delusions. *Schizophrenia Research*. <https://doi.org/10.1016/j.schres.2021.07.032>
- Baoumy, M., Pezzato, C., Corbato, C. H., Hawes, N., & Ferrari, R. (2021). Towards stochastic fault-tolerant control using precision learning and active inference. *arXiv Preprint arXiv:2109.05870*. [https://doi.org/10.1007/978-3-030-93736-2\\_48](https://doi.org/10.1007/978-3-030-93736-2_48)
- Baltieri, M., & Buckley, C. L. (2019). PID control as a process of active inference with linear generative models. *Entropy*, 21(3), 257. <https://doi.org/10.3390/e21030257>
- Brockman, G., Cheung, V., Pettersson, L., Schneider, J., Schulman, J., Tang, J., & Zaremba, W. (2016). Openai gym. *arXiv Preprint arXiv:1606.01540*.
- Çatal, O., Verbelen, T., Nauta, J., De Boom, C., & Dhoedt, B. (2020). Learning perception and planning with deep active inference. *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 3952–3956. <https://doi.org/10.1109/ICASSP40776.2020.9054364>
- Cox, M., Laar, T. van de, & Vries, B. de. (2019). A factor graph approach to automated design of Bayesian signal processing algorithms. *International Journal of Approximate Reasoning*, 104, 185–204. <https://doi.org/10.1016/j.ijar.2018.11.002>
- Da Costa, L., Parr, T., Sajid, N., Veselic, S., Neacsu, V., & Friston, K. J. (2020). Active inference on discrete state-spaces: A synthesis. *Journal of Mathematical Psychology*, 99, 102447. <https://doi.org/10.1016/j.jmp.2020.102447>
- Ergul, B., Laar, T. van de, Koudahl, M., Roa-Villescas, M., & Vries, B. de. (2020). Learning where to park. *International Workshop on Active Inference*, 125–132.
- Fountas, Z., Sajid, N., Mediano, P. A. M., & Friston, K. J. (2020). Deep active inference agents using monte-carlo methods. *Advances in Neural Information Processing Systems*. <https://proceedings.neurips.cc/paper/2020/hash/865dfbde8a344b44095495f3591f7407-Abstract.html>
- Fox, S. (2021). Active inference: Applicability to different types of social organization explained through reference to industrial engineering and quality management. *Entropy*, 23(2), 198. <https://doi.org/10.3390/e23020198>
- Friston, K. J., Daunizeau, J., & Kiebel, S. J. (2009). Reinforcement learning or active inference? *PLoS ONE*, 4(7), e6421. <https://doi.org/10.1371/journal.pone.0006421>
- Friston, K. J., FitzGerald, T., Rigoli, F., Schwartenbeck, P., & Pezzulo, G. (2017). Active inference: A process theory. *Neural Computation*, 29(1), 1–49. [https://doi.org/10.1162/NECO\\_a\\_00912](https://doi.org/10.1162/NECO_a_00912)
- Friston, K. J., Rigoli, F., Ognibene, D., Mathys, C., Fitzgerald, T., & Pezzulo, G. (2015). Active inference and epistemic value. *Cognitive Neuroscience*, 6(4), 187–214. <https://doi.org/10.1080/17588928.2015.1020053>

- 185 Friston, K. J., Samothrakis, S., & Montague, R. (2012). Active inference and agency:  
186 Optimal control without cost functions. *Biological Cybernetics*, 106(8-9), 523–541. <https://doi.org/10.1007/s00422-012-0512-8>  
187
- 188 Friston, K. J., Trujillo-Barreto, N., & Daunizeau, J. (2008). DEM: A variational treatment of  
189 dynamic systems. *NeuroImage*, 41(3), 849–885. [https://doi.org/10.1016/j.neuroimage.](https://doi.org/10.1016/j.neuroimage.2008.02.054)  
190 [2008.02.054](https://doi.org/10.1016/j.neuroimage.2008.02.054)
- 191 Holmes, E., Parr, T., Griffiths, T. D., & Friston, K. J. (2021). Active inference, selective  
192 attention, and the cocktail party problem. *Neuroscience & Biobehavioral Reviews*, 131,  
193 1288–1304. <https://doi.org/10.1016/j.neubiorev.2021.09.038>
- 194 Kaelbling, L. P., Littman, M. L., & Cassandra, A. R. (1998). Planning and acting in  
195 partially observable stochastic domains. *Artificial Intelligence*, 101(1-2), 99–134. [https://doi.org/10.1016/S0004-3702\(98\)00023-X](https://doi.org/10.1016/S0004-3702(98)00023-X)  
196
- 197 Laar, T. van de, Senoz, I., Özçelikkale, A., & Wymeersch, H. (2021). Chance-constrained  
198 active inference. *arXiv Preprint arXiv:2102.08792*.
- 199 Laar, T. W. van de, & Vries, B. de. (2019). Simulating active inference processes by message  
200 passing. *Frontiers in Robotics and AI*, 6, 20. <https://doi.org/10.3389/frobt.2019.00020>
- 201 Martínez, E. C., Kim, J. W., Barz, T., & Bournazou, M. N. C. (2021). Probabilistic modeling  
202 for optimization of bioreactors using reinforcement learning with active inference. *Computer*  
203 *Aided Chemical Engineering*, 50, 419–424. [https://doi.org/10.1016/B978-0-323-88506-5.](https://doi.org/10.1016/B978-0-323-88506-5.50066-8)  
204 [50066-8](https://doi.org/10.1016/B978-0-323-88506-5.50066-8)
- 205 Millidge, B. (2020). Deep active inference as variational policy gradients. *Journal of Mathe-*  
206 *matical Psychology*, 96, 102348. <https://doi.org/10.1016/j.jmp.2020.102348>
- 207 Millidge, B., Tschantz, A., Seth, A. K., & Buckley, C. L. (2020). On the relationship between  
208 active inference and control as inference. *International Workshop on Active Inference*, 3–11.  
209 [https://doi.org/10.1007/978-3-030-64919-7\\_1](https://doi.org/10.1007/978-3-030-64919-7_1)
- 210 Montague, P. R., Dolan, R. J., Friston, K. J., & Dayan, P. (2012). Computational psychiatry.  
211 *Trends in Cognitive Sciences*, 16(1), 72–80. <https://doi.org/10.1016/j.tics.2011.11.018>
- 212 Moreno, A. R. (2021). *PID control as a process of active inference applied to a refrigera-*  
213 *tion system*. [https://projekter.aau.dk/projekter/files/415131289/1034\\_PID\\_Control\\_as\\_](https://projekter.aau.dk/projekter/files/415131289/1034_PID_Control_as_Active_Inference.pdf)  
214 [Active\\_Inference.pdf](https://projekter.aau.dk/projekter/files/415131289/1034_PID_Control_as_Active_Inference.pdf)
- 215 Parr, T., Markovic, D., Kiebel, S. J., & Friston, K. J. (2019). Neuronal message passing  
216 using mean-field, bethe, and marginal approximations. *Scientific Reports*, 9(1), 1–18.  
217 <https://doi.org/10.1038/s41598-018-38246-3>
- 218 Parr, T., Rikhye, R. V., Halassa, M. M., & Friston, K. J. (2020). Prefrontal computation as  
219 active inference. *Cerebral Cortex*, 30(2), 682–695.
- 220 Penny, W. D., Friston, K. J., Ashburner, J. T., Kiebel, S. J., & Nichols, T. E. (2007). *Statistical*  
221 *parametric mapping: The analysis of functional brain images*. <https://doi.org/10.1016/B978-0-12-372560-8.X5000-1>  
222
- 223 Sajid, N., Ball, P. J., Parr, T., & Friston, K. J. (2021). Active inference: Demystified and  
224 compared. *Neural Computation*, 33(3), 674–712. [https://doi.org/10.1162/neco\\_a\\_01357](https://doi.org/10.1162/neco_a_01357)
- 225 Schwartenbeck, P., FitzGerald, T., Mathys, C., Dolan, R., & Friston, K. J. (2015). The  
226 dopaminergic midbrain encodes the expected certainty about desired outcomes. *Cerebral*  
227 *Cortex*, 25(10), 3434–3445. <https://doi.org/10.1093/cercor/bhu159>
- 228 Smith, R., Friston, K. J., & Whyte, C. J. (2022). A step-by-step tutorial on active inference  
229 and its application to empirical data. *Journal of Mathematical Psychology*, 107, 102632.  
230 <https://doi.org/10.1016/j.jmp.2021.102632>



- 231 Smith, R., Kirlic, N., Stewart, J. L., Touthang, J., Kuplicki, R., Khalsa, S. S., Feinstein,  
232 J., Paulus, M. P., & Aupperle, R. L. (2021). Greater decision uncertainty characterizes  
233 a transdiagnostic patient sample during approach-avoidance conflict: A computational  
234 modelling approach. *Journal of Psychiatry & Neuroscience*, 46(1), E74. <https://doi.org/10.1503/jpn.200032>  
235
- 236 Smith, R., Schwartenbeck, P., Stewart, J. L., Kuplicki, R., Ekhtiari, H., Paulus, M. P., &  
237 Tulsa 1000 Investigators. (2020). Imprecise action selection in substance use disorder:  
238 Evidence for active learning impairments when solving the explore-exploit dilemma. *Drug*  
239 *and Alcohol Dependence*, 215, 108208. <https://doi.org/10.1016/j.drugalcdep.2020.108208>
- 240 Tison, R., & Poirier, P. (2021). Communication as socially extended active inference: An  
241 ecological approach to communicative behavior. *Ecological Psychology*, 33, 197–235.  
242 <https://doi.org/10.1080/10407413.2021.1965480>
- 243 Tschantz, A., Baltieri, M., Seth, A. K., & Buckley, C. L. (2020). Scaling active inference.  
244 *2020 International Joint Conference on Neural Networks (IJCNN)*, 1–8. <https://doi.org/10.1109/IJCNN48605.2020.9207382>  
245
- 246 Tschantz, A., Millidge, B., Seth, A. K., & Buckley, C. L. (2020). Reinforcement learning through  
247 active inference. *Bridging AI and Cognitive Science at the International Conference on*  
248 *Learning Representations*. [https://baicsworkshop.github.io/pdf/BAICS\\_37.pdf](https://baicsworkshop.github.io/pdf/BAICS_37.pdf)
- 249 Tschantz, A., Seth, A. K., & Buckley, C. L. (2020). Learning action-oriented models through  
250 active inference. *PLoS Computational Biology*, 16(4), e1007805. <https://doi.org/10.1371/journal.pcbi.1007805>  
251
- 252 Ueltzhöffer, K. (2018). Deep active inference. *Biological Cybernetics*, 112(6), 547–573.  
253 <https://doi.org/10.1007/s00422-018-0785-7>
- 254 Vanderbroeck, M., Baioumy, M., Lans, D. van der, Rooij, R. de, & Werf, T. van der. (2019).  
255 Active inference for robot control: A factor graph approach. *Student Undergraduate*  
256 *Research E-Journal*, 5, 1–5.
- 257 Wirkuttis, N., & Tani, J. (2021). Leading or following? Dyadic robot imitative interaction using  
258 the active inference framework. *IEEE Robotics and Automation Letters*, 6(3), 6024–6031.  
259 <https://doi.org/10.1109/LRA.2021.3090015>