CORE VALUES | QUALITY PRODUCTS | SUPERIOR SERVICE

CORE® LIFTING PRODUCTS

HYDRAULIC HOISTS

J·D·NEUHAUS 1745 engineered for extremes

CoreLifting.com

HYDRAULIC HOISTS

JDN HYDRAULIC SERIES

Robust – Reliable – Low maintenance
The hydraulic solution of the PROFI series

J·D·NEUHAUS
1745
permanent excellence

JDN HYDRAULIC HOISTS AND MONORAIL HOISTS

HYDRAULIC HOISTS PROFI / HYDRAULIC MONORAIL HOISTS
CAPACITIES: 3 T UP TO 100 T

JDN Hydraulic Hoists and Hydraulic Monorail Hoists are available with capacities from 3 t up to 100 t.
Depending on motor size these hoists work with an intake pressure of 130 bar up to 180 bar.
Pressure fluid: Oil.

ADVANTAGES:

- Ideally suited for working in hazardous areas (explosion risk)
- Extremely low noise emissions
- Fully enclosed highly robust gear motor
- Integrated overload protection
- Only two supply connections at hoist "P" and "T", leakage oil drained internally
- The drive is hermetically sealed off from the environment

J.D. NEUHAUS – MORE THAN PRODUCTS

As a family-run company in its seventh generation, our commitment to clear values helps us achieve the standard of "Permanent Excellence" that we have held ourselves to for over 275 years.

The three value pairs of tradition and innovation, performance and longevity as well as partnership and passion create the foundation for our daily activities. They shape our partnership with the people who work for us, as well as with our partners and customers. They are found in the quality and German engineering of our products, and in the way we work with you and find new solutions thanks to our innovative spirit.

Our thinking is guided by sustainability, which we believe our future urgently needs and, of course, deserves.

TECHNICAL DATA

TYPE		3TI-H	6 TI-H	10 TI-H	16TI-H	20 TI-H	25 TI-H	37 TI-H	50 TI-H	75 TI-H	100 TI-H
Capacity	mt	3.2	6.3	10	16	20	25	37.5	50	75	100
Intake pressure	psi bar	1885 130					2176 150			2611 180	
Intake volume	cfm l/min	1.7 48					2.8 80			3.0 85	
Number of chain strands		1	2		3	4	2	3	4	3	4
Motor output	kW	3.5					6			9	
Motortype		KM 1/16					KM 2/32				
Lifting speed at full load	ft/min m/min	13.1 4.0	6.6 2.0	3.9 1.2	2.6 0.8	2.0 0.6	3.6 1.1	2.3 0.7	1.6 0.5	1.7 0.53	1.3 0.4
Lifting speed without load	ft/min m/min	14.8 4.5	7.6 2.3	4.1 1.25	2.7 0.82	2.0 0.6	3.9 1.2	2.6 0.8	1.6 0.5	2.0 0.6	1.5 0.45
Lowering speed at full load	ft/min m/min	14.8 4.5	7.6 2.3	4.3 1.3	2.8 0.85	2.1 0.65	3.9 1.2	2.6 0.8	1.6 0.5	2.0 0.6	1.5 0.45
Lowering speed without load	ft/min m/min	14.8 4.5	7.6 2.3	4.3 1.3	2.8 0.85	2.1 0.65	3.9 1.2	2.6 0.8	1.6 0.5	2.0 0.6	1.5 0.45
Connection		G 1/2					G 3/4				
Hose dimension		DN12					DN16				
Weight at standard lift with control	lbs kg	198.4 90	251.3 114	352.7 160	538 244	637.1 289	1282 583	2123 965	2068 940	4079 1850	4519 2050
Chain dimension	mm	13x36		16x45			23,5x66			32x90	
Weight of chain	lbs/ft kg/m	2.6 3.8		3.9 5.8			8.2 12.2			14.3 21.3	
Standard lift	ft m	10 3									
Length of control at standard lift	ft m	6.5 2									

HOISTS

JDN CONTROLS

Specially
tailored to your
requirements

J·D·NEUHAUS
1745
permanent excellence

You can order JDN hoists and cranes with different control options, specially tailored to your requirements.

ROPE CONTROL

SUITABLE FOR ANY CONTROL LENGTH:
This control type provides infinitely speed control for hoist lifting and lowering motions and is suitable for any required control length. The rope control option is available for all PROFI series hoists up to 20 t capacity. For larger capacity PROFI series hoists 25 TI, 30 TI, 37 TI, 50 TI and 100 TI the rope is replaced by a pull chain for greater strength.

S-CONTROL

SENSITIVE CONTROL, FOR EASY HANDLING:
This S-Control allows very sensitive regulation of the speeds. While developing the control the ergonomics were a focal point. The strong and robust design allows the user a pleasant working and a safe moving of loads. The use of non-rusting materials allows the application in areas with aggressive substances in the atmosphere.
The compact control hose has the hose relief already integrated – with a distinctly higher force. The S-control can optionally be expanded with an additional trigger guard for the lifting and lowering buttons.



E-CONTROL

LOW MAINTENANCE AND CORROSION PROOF:
The very robust brass construction distinguishes the E-type pendant control valve. Low weight and ergonomic design ensure ease of handling. Only available in single speed control version.

F-CONTROL

AVAILABLE FOR MULTI-FUNCTION USE:
The F-control is manufactured from an unbreakable synthetic material, resistant to external conditions. The ergonomically designed housing ensures ease of handling. Up to 18 different control functions can be incorporated in a single pendant control e.g key switch, two stage travelling speed, klaxon or simultaneous control of two hoist motors. As an option the F-control can also be delivered with infinitely variable speed control of hoisting and trolley travelling motions.

CONTROLS FOR JDN-AIR HOISTS IN MOTOR TROLLEY
AND JDN MONORAIL HOISTS:
For controlling JDN air hoists in motor trolleys and JDN monorail hoists we recommend the four button version of the E or F-control.

CONTROLS FOR JDN AIR CRANES:
For controlling JDN air cranes the F-control is the most suitable because of it's multi-function capability.