EMPIRICAL THRESHOLDING: BINARY CASE

Advanced Machine Learning

Imbalanced Learning:

Cost-Sensitive Learning Part 2

- Theoretical threshold from MECP not always best, due to e.g. wrong model class, finite data, etc.
- Simply measure costs on data with different thresholds
- Then pick best threshold (Fig. 1 in Sheng et al. 2006):

Learning goals

- Empirical thresholding
- Model-agnostic MetaCost

- What if two equal local minima? We prefer the one with wider span
- Do this on validation data / over cross-val to avoid overfitting!

EMPIRICAL THRESHOLDING: BINARY CASE

- Example: German Credit task
- Theoretical threshold from MECP not always best, due to e.g. wrong model class, finite data, etc.
- Simply measure costs on data with different thresholds
- Then pick best threshold (Fig. 1 in Sheng et al. 2006):

		True class	
		$y = \text{good}$	$y = \text{bad}$
Pred. class	$\hat{y} = \text{good}$	0	3
	$\hat{y} = \text{bad}$	1	0

- Theoretical: $C(good, bad)/(C(bad, good) + C(good, bad)) = 3/4 = c^*$
- Empirical version with 3-CV: For XGBoost, empirical minimum deviates substantially from theoretical version



- What if two equal local minima? We prefer the one with wider span
- Do this on validation data / over cross-val to avoid overfitting!

EMPIRICAL THRESHOLDING: MULTICLASS

- Example: German Credit task
- In the standard setting, we predict class $h(\mathbf{x}) = \arg\max_k \pi_k(\mathbf{x})$.
- Let's use g thresholds c_k now
- Re-scale scores $\mathbf{s} = \left(\frac{\pi(\mathbf{x})_1}{c_1}, \ldots, \frac{\pi(\mathbf{x})_g}{c_g}\right)^\top$,
- Predict class $\arg\max_k \pi_k(\mathbf{x})$
- Theoretical: $\frac{\pi(good)}{\pi(bad)} = \frac{C(bad, good)}{C(good, bad)} = 3/4 = c^*$
- Empirical version with 3-CV: For XGBoost, empirical minimum deviates substantially from theoretical version
- Compute empirical costs over cross-validation
- Optimize over g (actually: $g - 1$) dimensional threshold vector $(c_1, \ldots, c_g)^T$ to produce minimal costs

	True class	
	$y = \text{good}$	$y = \text{bad}$
Pred. class $\hat{y} = \text{good}$		3
$\hat{y} = \text{bad}$		0



METACOST: OVERVIEW

- Model-agnostic wrapper technique
- General idea:
  1. Relabel train obs with their low expected cost classes
  2. Apply classifier to relabeled data
- Example German Credit task:
- Compute empirical costs over cross-validation
- Optimize over g (actually: $g - 1$) dimensional threshold vector $(c_1, \ldots, c_g)^T$ to produce minimal costs



- Relabeled instances colored red
- Relabeling from good to bad more common because of costs

METACOST: ALGORITHM

Input: $\mathcal{D} = \{(\mathbf{x}^{(i)}, y^{(i)})\}_{i=1}^{n}$, training data, B number of bagging iterations, $\pi(\mathbf{x})$ probabilistic classifier, $\mathbf{C}$ cost matrix, empty dataset $D = \emptyset$

Bagging: Classifier is trained on different bootstrap samples.

for $b = 1, \ldots, B$ **do**

  $\mathcal{D}_b \leftarrow$ Bootstrap version of $\mathcal{D}$

  $\pi_b \leftarrow$ train classifier on $\mathcal{D}_b$

end for

Relabeling: Find classifiers for which $\mathbf{x}^{(i)}$ is OOB and compute π_b by averaging over predictions. Determine new label $\tilde{y}^{(i)}$ w.r.t. to the cost minimal class.

for $i = 1, \ldots, n$ **do**

  $\tilde{M} \leftarrow \bigcup_{m: \mathbf{x}^{(i)} \notin \mathcal{D}_m} \{m\}$

end for

for $j = 1, \ldots, g$ **do**

  $\pi_j(\mathbf{x}^{(i)}) \leftarrow \frac{1}{|\tilde{M}|} \sum_{m \in \tilde{M}} \pi_j(\mathbf{x}^{(i)} \mid f_m)$ for each j

end for

for $i = 1, \ldots, n$ **do**

  $\tilde{y}^{(i)} \leftarrow \arg\min_k \sum_{j=1}^{g} \pi_j(\mathbf{x}^{(i)}) \mathbf{C}(k, j)$

  $\tilde{D} \leftarrow \tilde{D} \cup \{(\mathbf{x}^{(i)}, \tilde{y}^{(i)})\}$

end for

Cost Sensitivity: Train on relabeled data.

$f_{meta} \leftarrow$ train f on $\tilde{D}$

- Model-agnostic wrapper technique
- General idea:
  1. Relabel train obs with their low expected cost classes
  2. Apply classifier to relabeled data
- Example German Credit task:



- Relabeled instances colored red
- Relabeling from good to bad more common because of costs

METACOST: ALGORITHM

Input: $\mathcal{D} = \{(\mathbf{x}^{(i)}, y^{(i)})\}_{i=1}^{n}$ training data, B number of bagging iterations, $\pi(\mathbf{x})$ probabilistic classifier, $\mathbf{C}$ cost matrix, empty dataset $\tilde{D} = \emptyset$

Bagging: Classifier is trained on different bootstrap samples.

for $b = 1, \ldots, B$ **do**

  $\mathcal{D}_b \leftarrow$ Bootstrap version of $\mathcal{D}$

  $\pi_b \leftarrow$ train classifier on $\mathcal{D}_b$

end for

Relabeling: Find classifiers for which $\mathbf{x}^{(i)}$ is OOB and compute π_b by averaging over predictions. Determine new label $\tilde{y}^{(i)}$ w.r.t. to the cost minimal class.

for $i = 1, \ldots, n$ **do**

  $\tilde{M} \leftarrow \bigcup_{m: \mathbf{x}^{(i)} \notin \mathcal{D}_m} \{m\}$

end for

for $j = 1, \ldots, g$ **do**

  $\pi_j(\mathbf{x}^{(i)}) \leftarrow \frac{1}{|\tilde{M}|} \sum_{m \in \tilde{M}} \pi_j(\mathbf{x}^{(i)} \mid f_m)$ for each i

end for

for $i = 1, \ldots, n$ **do**

  $\tilde{y}^{(i)} \leftarrow \arg\min_k \sum_{j=1}^{g} \pi_j(\mathbf{x}^{(i)}) C(k, j)$

  $\tilde{D} \leftarrow \tilde{D} \cup \{(\mathbf{x}^{(i)}, \tilde{y}^{(i)})\}$

end for