CCS WITH TRUE COSTS

Introduction to Machine Learning

Imbalanced Learning:

Cost Curves Part 2

Learning goals

- CCs with cost matrices
- Comparing classifiers
- Wrap-Up comparison to ROC



Assume unequal misclassif costs, i.e., $cost_{FN} \neq cost_{FP}$ and generalize error rate to **expected costs** (as function of π_+):

$$Costs(\pi_+) = (1 - \pi_+) \cdot FPR \cdot cost_{FP} + \pi_+ \cdot FNR \cdot cost_{FN}$$

Maximum of expected costs happens when

$$FPR = FNR = 1 \;\Rightarrow\; Costs_{max} = (1 - \pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}$$

Consider **normalized costs** (as function of π_+):



$$Costs_{norm}(\pi_+) = \frac{(1-\pi_+) \cdot FPR \cdot cost_{FP} + \pi_+ \cdot FNR \cdot cost_{FN}}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}}$$

$$= \frac{(1-\pi_+) \cdot cost_{FP} \cdot FPR}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}} + \frac{\pi_+ \cdot cost_{FN} \cdot FNR}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}}$$

Let "probability times cost" $PC(+)$ be normalized version of $\pi_+ \cdot cost_{FN}$:

$$PC(+) = \frac{\pi_+ \cdot cost_{FN}}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}} \text{ and } 1 - PC(+) = \frac{(1-\pi_+) \cdot cost_{FP}}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}}$$

COMPARE WITH TRIVIAL CLASSIFIERS

Assume unequal misclassification costs $cost_{FP}$ and $cost_{FN}$ and generalize error rate to expected costs (or simply costs):

$$Costs(\pi_+) = (1-\pi_+) \cdot FPR \cdot cost_{FP} + \pi_+ \cdot FNR \cdot cost_{FN}$$

Maximum of expected costs happens when

$$FPR = TPR = 1 \quad \Rightarrow \quad Costs_{max}(\pi_+) = (1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}$$

Consider **normalized costs** (as function of π_+):

$$Costs_{norm}(\pi_+) = \frac{(1-\pi_+) \cdot FPR \cdot cost_{FP} + \pi_+ \cdot FNR \cdot cost_{FN}}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}}$$

$$= FPR + \frac{\pi_+ \cdot cost_{FN} \cdot FNR}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}}$$

Let "probability times cost" $PC(+)$ be normalized version of $\pi_+ \cdot cost_{FN}$:

$$PC(+) = \frac{\pi_+ \cdot cost_{FN}}{(1-\pi_+) \cdot cost_{FP} + \pi_+ \cdot cost_{FN}} \text{ and}$$

- Operating range of a classifier is a set of $PC(+)$ values (operating points) where classifier performs better than both trivial classifiers
- Intersection of cost curves and trivial classifiers' diagonals determine operating range
- At any $PC(+)$ value, the vertical distance of trivial diagonal to a classifer's cost curve within operating range shows advantage in performance (normalized costs) of classifier

Example: Dotted lines are operating range of a classifier (here: [0.14, 0.85])



COMPARING CLASSIFIERS

- If classifier C1's expected cost is lower than classifier C2's at a $PC(+)$ value, C1 outperforms C2 at that operating point
  - The two cost curves of C1 and C2 may cross, which indicates C1 outperforms C2 for a certain operating range and vice versa
  - The vertical distance between the two cost curves of C1 and C2 at any $PC(+)$ value directly indicates the performance difference between them at that operating point

Example: Dotted cost curve has lower expected cost as dashed cost curve for $PC(+) < 0.5$ and hence outperforms dashed one in this operating range and vice versa

- Axes' labels and their interpretation have changed
- Normalized cost vs. "probability times cost"



Chris Drummond and Robert C. Holte (2006): Cost curves: An improved method for visualizing classifier performance, Machine Learning, 65, 95-130 (URL)

COMPARE WITH TRIVIAL CLASSIFIERS

- Operating range of a classifier is a set of $PC(+)$ values (operating points) where classifier performs better than both trivial classifiers
- Intersection of cost curves and trivial classifiers' diagonals determine operating range
- At any $PC(+)$ value, the vertical distance of trivial diagonal to a classifer's cost curve within operating range shows advantage in performance (normalized costs) of classifier

Example: Dotted lines are operating range of a classifier (here: $[0.14, 0.85]$)



COMPARING CLASSIFIERS

- If classifier C1's expected cost is lower than classifier C2's at a $PC(+)$ value, C1 outperforms C2 at that operating point
- The two cost curves of C1 and C2 may cross, which indicates C1 outperforms C2 for a certain operating range and vice versa
- The vertical distance between the two cost curves of C1 and C2 at any $PC(+)$ value directly indicates the performance difference between them at that operating point

Example: Dotted cost curve has lower expected cost as dashed cost curve for $PC(+) < 0.5$ and hence outperforms dashed one in this operating range and vice versa

Chris Drummond and Robert C. Holte (2006): Cost curves: An improved method for visualizing classifier performance. Machine Learning, 65, 95-130 (URL)