

# ML Basics

## Python Setup



### Learning goals

- Understand the different package management systems
- Be comfortable in setting up a python environment
- Know how to make your work reproducible with Python

# 0. INSTALLATION OF PYTHON


Python can be installed in many ways, e.g. by

- directly downloading it from `python.org`:  
`https://www.python.org/downloads/`
- downloading Miniconda:  
`https://docs.conda.io/en/latest/miniconda.html`
- installing Python via the Anaconda distribution:  
`https://docs.anaconda.com/anaconda/install/`

# 0. PACKAGE MANAGEMENT IN PYTHON

Unlike in R/RStudio (which you might be used to), package management in Python is a little more of a mess: There are *two* package management systems:

- pip (+ PyPi)
- conda (+ Anaconda repository)



# 0. PACKAGE MANAGEMENT IN PYTHON

pip

- Installs packages from the Python Package Index (PyPi)
- Pip packages are source distributions (compiler needed) or wheels<sup>1</sup>
- Installs dependencies in a recursive, serial loop
- Limited to Python software
- No built-in support for **virtual environments** (but possible)
- > 150k packages available on PyPi

<sup>1</sup>tl;dr: wheels are smaller + install faster than a source distribution and do not require a compiler

# 0. PACKAGE MANAGEMENT IN PYTHON

conda

- Installs packages from the Anaconda repository
- Conda packages are binaries, no need for compilers
- SAT solver to verify requirements of all packages
- Not limited to Python software
- Easier to create/manage **virtual environments**
- ~ 1.5k packages available in the Anaconda repository

# 1. PYTHON VIA THE CONSOLE

## Start Python in Terminal / Console / Command Line

```
1 python
```

### Approximate result:

```
Python 3.7.11 (default, Jul 27 2021, 07:03:16)
[Clang 10.0.0 ] :: Anaconda, Inc. on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> █
```

### Similar to R console:

```
1 1+1
```

### Exit with Ctrl-D or

```
1 exit()
```

## 2. ANACONDA

Anaconda is a widely used open-source distribution of Python:

<https://www.anaconda.com>



### 3. MINICONDA

We recommend downloading and installing *Miniconda*, since it

- directly brings `conda` (as well as `pip`)
- is a minimal installer (only the core parts, unlike Anaconda)



Source: <https://www.mrdbourke.com/get-your-computer-ready-for-machine-learning-using-anaconda-miniconda-and-conda/>



## 4. SPYDER

Spyder is a complete IDE for Python (very similar to RStudio)



- directly comes with the Anaconda distribution
- can also be installed from <https://www.spyder-ide.org/>

## 5. JUPYTER NOTEBOOKS/LAB


- web application that lets you develop Python code in your browser
- combine code, text, images, and other media
- execute your code in smaller parts (cells)
- Useful for explorative analyses and for beginning stages of a project, where you need frequent feedback



```
1 conda install jupyterlab
```

# 5. JUPYTER NOTEBOOKS/LAB

## Code cells vs. Markdown cells



The screenshot shows a Jupyter Notebook interface with a single cell. The cell contains a code block followed by a markdown block. The code block has two lines: `a = 7` and `a * 2`. The markdown block contains a header `# This is a Markdown cell containing a Header`, followed by two paragraphs of text. The first paragraph explains that everything after a '#' is treated as a header, and symbols like backslashes must be escaped. The second paragraph explains that this allows for interleaving code, results, and figures with comments and explanations in a visually appealing way.

```
[1]: # This is a cell containing code

a = 7
a * 2


[1]: 14

# This is a Markdown cell containing a Header

When it gets executed (Strg + Enter), everything behind the '#' will be displays as a header
and everything else as plain text (note, that certain symbols like '\' have to be escaped

This allows to mix code (with results + figures) to be interleaved with comments and explanations
in a visually appealing way (Note: This Markdown cell was executed, hence it looks different)
```

## Useful for creating and changing figures quickly




## 5. JUPYTER NOTEBOOKS/LAB

- When you click into a cell and you see your cursor, then you are in **Edit Mode**
- Write your Code/Explanations and execute with `Ctrl+Enter`
- Hit `Esc` → Cursor disappears, cell is still selected (you are in **Command mode** now)
- Now there are, among others, certain shortcuts available:
  - A will insert a new cell *above* the current one
  - B will insert one *below*
  - C copies the selected cell
  - X cuts the selected cell
  - V pastes copied/cut cell below
  - M switches the cell mode to *Markdown*
  - Y switches it to *Code*
  - Up selects cell above
  - Down selects cell below

## 6. VISUAL STUDIO CODE

- Widely used editor for many programming languages
- Main advantage: supports Jupyter Notebooks, takes care of setting up server
- install from `https://code.visualstudio.com/`



## 7. R-STUDIO

RStudio can also be used as an IDE for Python:



- Install the `reticulate` packages in R
- Select the desired Python interpreter at  
Tools > Global Options > Python
- New File > Python Script

## 8. VIRTUAL ENVIRONMENTS

Assume the following scenario:

- We have two ongoing projects, Project A and Project B
- Both projects need some package `pkg_xy`
- Project A needs `v1.2.0` while Project B requires `v2.1.3`
- What can we do about this?

Solution: **Work with virtual environments**

## 8. VIRTUAL ENVIRONMENTS

Virtual Environments allow you to

- have different entire version of Python running on your machine (Python 2, Python 3.x, Python 3.y, ..)
- maintain different versions of packages for your projects

They can be created/activated/deactivated via

```
1 conda create --name some_name python=3.9
2 conda activate some_name
3 conda deactivate some_name
```

Useful commands: [Conda Cheat Sheet](#)



# 8. VIRTUAL ENVIRONMENTS

## Different versions of Python

```
C:\Users\ri85vex>conda activate helloworld

(helloworld) C:\Users\ri85vex>python
Python 3.8.3 (default, May 19 2020, 06:50:17) [MSC v.1916 64 bit (AMD64)] :: Anaconda, Inc. on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> exit()

(helloworld) C:\Users\ri85vex>conda activate inhouse

(inhouse) C:\Users\ri85vex>python
Python 3.6.5 |Anaconda, Inc.| (default, Mar 29 2018, 13:32:41) [MSC v.1900 64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

## Different (versions of) packages

```
(inhouse) C:\Users\ri85vex>python
Python 3.6.5 |Anaconda, Inc.| (default, Mar 29 2018, 13:32:41) [MSC v.1900 64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> import matplotlib
>>> exit()

(inhouse) C:\Users\ri85vex>conda activate helloworld

(helloworld) C:\Users\ri85vex>python
Python 3.8.3 (default, May 19 2020, 06:50:17) [MSC v.1916 64 bit (AMD64)] :: Anaconda, Inc. on win32
Type "help", "copyright", "credits" or "license" for more information.
>>> import matplotlib
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ModuleNotFoundError: No module named 'matplotlib'
>>>
```

## 9. MANAGING PACKAGES

With conda:

```
1 conda install pandas
2 conda install pandas==1.3.5
3 conda update pandas
4 conda remove pandas
5 conda list
```

With pip:

```
1 pip install pandas
2 pip install pandas==1.3.5
3 pip install pandas --upgrade
4 pip uninstall pandas
5 pip freeze
```

## 9. MANAGING PACKAGES

Instruct conda which version you want to have installed:

- Exact (1.3.5)

```
1 conda install pandas==1.3.5
```

- Fuzzy (1.3.0, 1.3.1, etc.)

```
1 conda install pandas==1.3
```

- Greater or equal (1.3.5 or higher)

```
1 conda install "pandas>=1.3.5"
```

- OR (1.3.4 or 1.3.5)

```
1 conda install "pandas==1.3.4|1.3.5"
```

- AND (1.3.3, 1.3.4, but not 1.4)

```
1 conda install "pandas>=1.3.3,<1.4"
```

Standardized way of sharing code requirements with others publicly across platforms:

- `environment.yml` (conda)
- `requirements.txt` (pip)

# 10. REPRODUCIBILITY

- Create an environment:<sup>2</sup>  
(with specific Python version and some packages)

```
1 conda create -n my_env python=3.7 pandas numpy scikit-learn
```

- Activate the conda environment:

```
1 conda activate my_env
```

- Export the specifications of your conda environment:

```
1 conda env export > environment.yml
```

<sup>3</sup>-n is the short version of the --name flag

# 10. REPRODUCIBILITY

Result (abbreviated to fit on the slide):

```
1 name: my_env
2 channels:
3   - defaults
4 dependencies:
5   - blas=1.0=mkl
6   - bottleneck=1.3.2=py37h2a96729_1
7   - ...
8   - numpy=1.21.2=py37hfca59bb_0
9   - numpy-base=1.21.2=py37h0829f74_0
10  - openssl=1.1.1l=h2bbff1b_0
11  - packaging=21.3=pyhd3eb1b0_0
12  - pandas=1.3.4=py37h6214cd6_0
13  - pip=21.2.4=py37haa95532_0
14  - pyparsing=3.0.4=pyhd3eb1b0_0
15  - python=3.7.11=h6244533_0
16  - python-dateutil=2.8.2=pyhd3eb1b0_0
17  - pytz=2021.3=pyhd3eb1b0_0
18  - scikit-learn=1.0.1=py37hf11a4ad_0
19  - scipy=1.7.1=py37hbe87c03_2
20  - ...
21 prefix: C:\Users\ri85vex\Miniconda3\envs\my_env
```

## 10. REPRODUCIBILITY

- *Note 1:* As you can see, this also includes all sorts of packages that are automatically installed when creating an environment
- *Note 2:* We observe some cryptic stuff after the version of each package
- *Note 3:* Those packages installed via pip are \*\*also handled by this file\*\* (see next slide)
- *Note 4:* The `prefix` is ignored when using the `.yaml`-file for creation. So you can simply delete it after the export.

# 10. REPRODUCIBILITY

- Install some package via pip:

```
1 pip install matplotlib
2
```

- Result (abbreviated to fit on the slide):

```
1 name: my_env
2 channels:
3   - defaults
4 dependencies:
5   - blas=1.0=mkl
6   - bottleneck=1.3.2=py37h2a96729_1
7   - ca-certificates=2021.10.26=haa95532_2
8   - certifi=2021.10.8=py37haa95532_0
9   - icc_rt=2019.0.0=h0cc432a_1
10  - intel-openmp=2021.4.0=haa95532_3556
11  - ...
12  - pip:
13    - cycler==0.11.0
14    - fonttools==4.28.5
15    - kiwisolver==1.3.2
16    - matplotlib==3.5.1
17    - pillow==9.0.0
18 prefix: C:\Users\ri85vex\Miniconda3\envs\my_env
19
```



# 10. REPRODUCIBILITY

- Using the “--from-history” flag

```
1 conda env export --from-history > environment.yml
2
```

- allows you to create a reduced version of the .yaml-file containing only the packages (+ version) you explicitly installed (**via conda**):

```
1 name: my_env
2 channels:
3   - defaults
4 dependencies:
5   - scikit-learn
6   - numpy
7   - python=3.7
8   - pandas
9 prefix: C:\Users\ri85vex\Miniconda3\envs\my_env
10
```

# 10. REPRODUCIBILITY

- Export specifications of the pip packages:

```
1 pip freeze > requirements.txt
2
```

- Can be installed in a conda environment via:

```
1 pip install -r requirements.txt
2
```

- **But:** Requiring others to execute these two steps will create a lot of work!

# 10. REPRODUCIBILITY

- Best practice: Create `.yaml`-file manually

```
1 name: my_env
2 channels:
3   - defaults
4 dependencies:
5   - python=3.7.11
6   - numpy=1.21.2
7   - pandas=1.3.4
8   - scikit-learn=1.0.1
9   - pip=21.2.4
10  - pip:
11    # works for regular pip packages
12    - matplotlib==2.0.0
13    # also works for whole requirements-files:
14    - -r requirements.txt
15
```

- Finally: Create environment from `.yaml`-file:

```
1 conda env create -f environment.yaml
2
```