

Using the Transformer

BERT (Devlin et al., 2018)



Learning goals

- Understand BERT inside out

PREDECESSORS OF BERT

2013 - word2vec

Tomas Mikolov et al. publish four papers on vector representations of words constituting the *word2vec* framework

This received very much attention as it revolutionized the way words were encoded for deep learning models in the field of NLP.



2013

PREDECESSORS OF BERT

2013 - word2vec

Tomas Mikolov et al. publish four papers on vector representations of words constituting the *word2vec* framework.

This received very much attention as it revolutionized the way words were encoded for deep learning models in the field of NLP.

2013

01/2018

January 2018 - ULMFiT

The first transfer learning architecture (**Universal Language Model Fine-Tuning**) was proposed by **Howard and Ruder (2018)**.

An embedding layer at the bottom of the network was complemented by three AWD-LSTM layers (Merity et al., 2017) and a softmax layer for pre-training.

A **Unidirectional contextual** model since no biLSTMs are used.

PREDECESSORS OF BERT

2013 - word2vec

Tomas Mikolov et al. publish four papers on vector representations of words constituting the *word2vec* framework

This received very much attention as it revolutionized the way words were encoded for deep learning models in the field of NLP.

February 2018 - ELMo

Guys from **AllenNLP** developed a bidirectionally contextual framework by proposing ELMo (Embeddings from Language Models; **Peters et al., 2018**).

Embeddings from this architecture are the (weighted) combination of the intermediate-layer representations produced by the biLSTM layers.

2013

01/2018

02/2018

January 2018 - ULMFiT

The first transfer learning architecture (**Universal Language Model Fine-Tuning**) was proposed by **Howard and Ruder (2018)**.

An embedding layer at the bottom of the network was complemented by three AWD-LSTM layers (Merity et al., 2017) and a softmax layer for pre-training.

A **Unidirectional contextual** model since no biLSTMs are used.

PREDECESSORS OF BERT

2013 - word2vec

Tomas Mikolov et al. publish four papers on vector representations of words constituting the *word2vec* framework

This received very much attention as it revolutionized the way words were encoded for deep learning models in the field of NLP.

February 2018 - ELMo

Guys from **AllenNLP** developed a bidirectionally contextual framework by proposing ELMo (Embeddings from Language Models; **Peters et al., 2018**).

Embeddings from this architecture are the (weighted) combination of the intermediate-layer representations produced by the biLSTM layers.

2013

01/2018

02/2018

06/2018

January 2018 - ULMFiT

The first transfer learning architecture (Universal Language Model Fine-Tuning) was proposed by **Howard and Ruder (2018)**.

An embedding layer at the bottom of the network was complemented by three AWD-LSTM layers (Merity et al., 2017) and a softmax layer for pre-training.

A **Unidirectional contextual** model since no biLSTMs are used.

June 2018 - OpenAI GPT

Radford et al., 2018 abandon the use of LSTMs. They combine multiple Transformer decoder block with a standard language modelling objective for pre-training.

Compared to ELMo it is just **unidirectionally contextual**, since it uses only the decoder side of the Transformer. On the other hand it is **end-to-end trainable** (cf. ULMFiT) and embeddings do not have to be extracted like in the case of ELMo.

PREDECESSORS OF BERT

2013 - word2vec

Tomas Mikolov et al. publish four papers on vector representations of words constituting the *word2vec* framework

This received very much attention as it revolutionized the way words were encoded for deep learning models in the field of NLP.

February 2018 - ELMo

Guys from **AllenNLP** developed a bidirectionally contextual framework by proposing ELMo (Embeddings from Language Models; **Peters et al., 2018**).

Embeddings from this architecture are the (weighted) combination of the intermediate-layer representations produced by the biLSTM layers.

October 2018 - BERT

BERT (**Devlin et al., 2018**) is a bidirectional contextual embedding model purely relying on Self-Attention by using multiple **Transformer encoder** blocks.

BERT (and its successors) rely on the **Masked Language Modelling objective** during pre-training on huge unlabelled corpora of text.



January 2018 - ULMFiT

The first transfer learning architecture (**Universal Language Model Fine-Tuning**) was proposed by **Howard and Ruder (2018)**.

An embedding layer at the bottom of the network was complemented by three AWD-LSTM layers (Merity et al., 2017) and a softmax layer for pre-training.

A **Unidirectional contextual** model since no biLSTMs are used.

June 2018 - OpenAI GPT

Radford et al., 2018 abandon the use of LSTMs. They combine multiple Transformer decoder block with a standard language modelling objective for pre-training.

Compared to ELMo it is just **unidirectionally contextual**, since it uses only the decoder side of the Transformer. On the other hand it is **end-to-end trainable** (cf. ULMFiT) and embeddings do not have to be extracted like in the case of ELMo.