

Transformer

Efficient Transformers



Learning goals

- Understand the efficiency problems and shortcomings of transformer-based models
- Learn about some strategies to alleviate them

THE $\mathcal{O}(N^2)$ PROBLEM

Quadratic time & memory complexity of Self-Attention

- *Inductive bias of Transformer models:*
Connect all tokens in a sequence to each other
- **Pro:** Can (theoretically) learn contexts of arbitrary length
- **Con:** Bad scalability limiting (feasible) context size

Resulting Problems:

- Several tasks require models to consume longer sequences
- *Efficiency:* Are there more efficient modifications which achieve similar or even better performance?

EFFICIENT TRANSFORMERS


Broad overview on so-called "X-formers" ► Tay et al., 2020

- Efficient & fast Transformer-based models
→ Reduce complexity from $\mathcal{O}(n^2)$ to (up to) $\mathcal{O}(n)$
- Claim on-par (or even) superior performance
- Different techniques used:
 - Fixed/Factorized/Random Patterns
 - Learnable Patterns (extension of the above)
 - Low-Rank approximations or Kernels
 - Recurrence (see e.g. ► Dai et al., 2019)
 - Memory modules

Side note:

- Most Benchmark data sets not explicitly designed for evaluating long-range abilities of the models.
- Recently proposed: *Longe Range Arena: A benchmark for efficient transformers* ► Tay et al., 2020

EFFICIENT TRANSFORMERS



► Tay et al., 2020

ATTENTION PATTERNS

Reasoning:

- Making every token attend to every other token might be unnecessary
- Introduce sparsity in the commonly dense attention matrix

Example:




Figure 1: Building blocks of the attention mechanism used in BIGBIRD. White color indicates absence of attention. (a) random attention with $r = 2$, (b) sliding window attention with $w = 3$ (c) global attention with $g = 2$. (d) the combined BIGBIRD model.

► Source: Zaheer et al. (2020)

TBD

TBD

TBD