


# Deep Learning


## GAN variants



### Learning goals

- non-saturating loss
- conditional GANs

# NON-SATURATING LOSS




Credit: Daniel Seita

**Figure:** Various generator loss functions ( $J^{(G)}$ ).

- It was discovered that a relatively strong discriminator could completely dominate the generator.
- When optimizing the minimax loss, as the discriminator gets good at identifying fake images, i.e. as  $D(G(z))$  approaches 0, the gradient with respect to the generator parameters vanishes.

# NON-SATURATING LOSS



Credit: Daniel Seita

**Figure:** Various generator loss functions ( $J^{(G)}$ ).

- Solution: Use a non-saturating generator loss instead:  
$$J^{(G)} = -\frac{1}{2} \mathbb{E}_{\bar{z} \sim p(\bar{z})} [\log D(G(\mathbf{x}))]$$
- In contrast to the minimax loss, when the discriminator gets good at identifying fake images, the magnitude of the gradient of  $J^{(G)}$  increases and the generator is able to learn to produce better images in successive iterations.

# OTHER LOSS FUNCTIONS


Various losses for GAN training with different properties have been proposed:

GAN	DISCRIMINATOR LOSS	GENERATOR LOSS
MM GAN	$\mathcal{L}_D^{\text{GAN}} = -\mathbb{E}_{x \sim p_d} [\log(D(x))] - \mathbb{E}_{\hat{x} \sim p_g} [\log(1 - D(\hat{x}))]$	$\mathcal{L}_G^{\text{GAN}} = \mathbb{E}_{\hat{x} \sim p_g} [\log(1 - D(\hat{x}))]$
NS GAN	$\mathcal{L}_D^{\text{NSGAN}} = -\mathbb{E}_{x \sim p_d} [\log(D(x))] - \mathbb{E}_{\hat{x} \sim p_g} [\log(1 - D(\hat{x}))]$	$\mathcal{L}_G^{\text{NSGAN}} = -\mathbb{E}_{\hat{x} \sim p_g} [\log(D(\hat{x}))]$
WGAN	$\mathcal{L}_D^{\text{WGAN}} = -\mathbb{E}_{x \sim p_d} [D(x)] + \mathbb{E}_{\hat{x} \sim p_g} [D(\hat{x})]$	$\mathcal{L}_G^{\text{WGAN}} = -\mathbb{E}_{\hat{x} \sim p_g} [D(\hat{x})]$
WGAN GP	$\mathcal{L}_D^{\text{WGANP}} = \mathcal{L}_D^{\text{WGAN}} + \lambda \mathbb{E}_{\hat{x} \sim p_g} [(  \nabla D(\alpha x + (1 - \alpha \hat{x}))  _2 - 1)^2]$	$\mathcal{L}_G^{\text{WGANP}} = -\mathbb{E}_{\hat{x} \sim p_g} [D(\hat{x})]$
LS GAN	$\mathcal{L}_D^{\text{LSGAN}} = -\mathbb{E}_{x \sim p_d} [(D(x) - 1)^2] + \mathbb{E}_{\hat{x} \sim p_g} [D(\hat{x})^2]$	$\mathcal{L}_G^{\text{LSGAN}} = -\mathbb{E}_{\hat{x} \sim p_g} [(D(\hat{x}) - 1)^2]$
DRAGAN	$\mathcal{L}_D^{\text{DRAGAN}} = \mathcal{L}_D^{\text{GAN}} + \lambda \mathbb{E}_{\hat{x} \sim p_d + \mathcal{N}(0, c)} [(  \nabla D(\hat{x})  _2 - 1)^2]$	$\mathcal{L}_G^{\text{DRAGAN}} = \mathbb{E}_{\hat{x} \sim p_g} [\log(1 - D(\hat{x}))]$
BEGAN	$\mathcal{L}_D^{\text{BEGAN}} = \mathbb{E}_{x \sim p_d} [  x - \text{AE}(x)  _1] - k_t \mathbb{E}_{\hat{x} \sim p_g} [  \hat{x} - \text{AE}(\hat{x})  _1]$	$\mathcal{L}_G^{\text{BEGAN}} = \mathbb{E}_{\hat{x} \sim p_g} [  \hat{x} - \text{AE}(\hat{x})  _1]$

Source: Lucic et al. 2016

# ARCHITECTURE-VARIANT GANS

Motivated by different challenges in GAN training procedure described, there have been several types of architecture variants proposed. Understanding and improving GAN training is a very active area of research.




Credit: hindupuravinash

# CONDITIONAL GANS: MOTIVATION

- In an ordinary GAN, the only thing that is fed to the generator are the latent variables  $\mathbf{z}$ .
- A conditional GAN allows you to condition the generative model on additional variables.
- E.g. a generator conditioned on text input (in addition to  $\mathbf{z}$ ) can be trained to generate the image described by the text.

# CONDITIONAL GANS: ARCHITECTURE



Credit: Guim Perarnau

- In a conditional GAN, additional information in the form of vector  $y$  is fed to both the generator and the discriminator.
- $z$  can then encode all variations in  $z$  that are not encoded by  $y$ .
- E.g.  $y$  could encode the class of a hand-written number (from 0 to 9). Then,  $z$  could encode the style of the number (size, weight, rotation, etc).

# CONDITIONAL GANS: EXAMPLE

MNIST digits generated conditioned on their class label.




Source: Mirza et al. 2014

**Figure:** When the model is conditioned on a one-hot coded class label, it generates random images that belong (mostly) to that particular class. The randomness here comes from the randomly sampled  $\mathbf{z}$ . (Note :  $\mathbf{z}$  is implicit. It is not shown above.)



# CONDITIONAL GANS: MORE EXAMPLES



Source: Isola et al. 2016

**Figure:** Conditional GANs can translate images of one type to another. In each of the 4 examples above, the image on the left is fed to the network and the image on the right is generated by the network.

# MORE GENERATIVE MODELS

- Today, we learned about one kind of (directed) generative models:
- There are other interesting generative models, e.g.:
  - autoregressive models
  - restricted Boltzmann machines.
- Note:
  - It is important to bear in mind that generative models are not a solved problem.
  - There are many interesting hybrid models that combine two or more of these approaches.

# REFERENCES



Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, Yoshua Bengio (2014)

Generative Adversarial Networks

*<https://arxiv.org/abs/1406.2661>*



Santiago Pascual, Antonio Bonafonte, Joan Serra (2017)

SEGAN: Speech Enhancement Generative Adversarial Network

*<https://arxiv.org/abs/1703.09452>*



Ian Goodfellow (2016)

NIPS 2016 Tutorial: Generative Adversarial Networks

*<https://arxiv.org/abs/1701.00160>*



Lilian Weng (2017)

From GAN to WGAN

*<https://lilianweng.github.io/lil-log/2017/08/20/from-GAN-to-WGAN.html>*

# REFERENCES



Mark Chang (2016)

Generative Adversarial Networks

*<https://www.slideshare.net/ckmarkohchang/generative-adversarial-networks>*



Lucas Theis, Aaron van den Oord, Matthias Bethge (2016)

A note on the evaluation of generative models

*<https://arxiv.org/abs/1511.01844>*



Aiden Nibali (2016)

The GAN objective, from practice to theory and back again

*<https://aiden.nibali.org/blog/2016-12-21-gan-objective/>*



Mehdi Mirza, Simon Osindero (2014)

Conditional Generative Adversarial Nets

*<https://arxiv.org/abs/1411.1784>*



Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, Alexei A. Efros (2016)

Image-to-Image Translation with Conditional Adversarial Networks

*<https://arxiv.org/abs/1611.07004>*

# REFERENCES



Guim Perarnau (2017)

Fantastic GANs and where to find them

*[https://guimperarnau.com/blog/2017/03/  
Fantastic-GANs-and-where-to-find-them](https://guimperarnau.com/blog/2017/03/Fantastic-GANs-and-where-to-find-them)*