
## **Deep Learning**

# **Unsupervised Learning**



## Learning goals

- Unsupervised learning tasks
- Unsupervised deep learning

#### UNSUPERVISED LEARNING

- So far, we have described the application of neural networks to **supervised learning** in which we have labeled training data  $(x^{(1)}, y^{(1)}), \ldots, (x^{(n)}, y^{(n)}).$
- In supervised learning scenarios we exploit label information (i.e. class memberships or numeric values) to train our algorithm.
- The model learns a function to map **x** to **y**.
- Examples are: classification, regression, object detection, semantic segmentation, image captioning, etc.




Figure: Examples of unsupervised learning (Li, 2023).

## **UNSUPERVISED LEARNING**

- In **unsupervised learning** scenarios training data consists of unlabeled input points  $\mathbf{x}^{(1)}, \dots, \mathbf{x}^{(n)}$ .
- Our goal is to learn some underlying hidden structure of the data.
- Examples are: clustering, dimensionality reduction, feature learning, density estimation, etc.

#### 1. Clustering.



**Figure:** Cluster analysis results for different algorithms. Different clusters are indicated by different colors (Bullibabu et al., 2016).

- 2. Dimensionality reduction/manifold learning.
  - E.g. for visualisation in a low dimensional space.





Figure: Principal Component Analysis (PCA) (Finnstats, 2021).

- 2. Dimensionality reduction/manifold learning.
  - E.g. for image compression.



**Figure:** Example of image compression (Cycon, 2009).


3. Feature extraction/representation learning.



**Figure:** Use of kernel machines to obtain a linearly separable function (Matzer, 2019).

 E.g. for semi-supervised learning: features learned from an unlabeled dataset are employed to improve performance in a supervised setting.

4. Density fitting/learning a generative model.



**Figure:** A generative model can reconstruct the missing portions of the images (Bornschein et al., 2016).

#### UNSUPERVISED DEEP LEARNING

Given i.i.d. (unlabeled) data  $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n \sim p_{\text{data}}$ , in unsupervised deep learning, one usually trains :

 an autoencoder (a special kind of neural network) for representation learning (feature extraction, dimensionality reduction, manifold learning, ...), or,

#### UNSUPERVISED DEEP LEARNING

Given i.i.d. (unlabeled) data  $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n \sim p_{\text{data}}$ , in unsupervised deep learning, one usually trains :

- an autoencoder (a special kind of neural network) for representation learning (feature extraction, dimensionality reduction, manifold learning, ...), or,
- a generative model, i.e. a probabilistic model of the data generating distribution p<sub>data</sub> (data generation, outlier detection, missing feature extraction, reconstruction, denoising or planning in reinforcement learning, ...).

#### REFERENCES



Bornschein, J., Shabanian, S., Fischer, A., & Bengio, Y. (2016). *Bidirectional Helmholtz Machines*.



Cycon. (2009, May 4). *Bildkompression*. PPT. https://de.slideshare.net/hcycon/bildkompression



Matzer, M. (2019, April 29). Optimale clusteranalyse und segmentierung mit dem k-means-algorithmus. BigData. https://www.bigdata-insider.de/optimale-clusteranalyse-und-segmentierung-mit-dem-k-means-algorithmus.



Finnstats. (2021, May 7). Principal Component Analysis (PCA) in R: R-bloggers. R-bloggers. https://www.r-bloggers.com/2021/05/principal-component-analysis-pca-in-r/



Bullibabu, Rasamsetty & Snehal, G. & Kiran, P. (2016). *Detection of Crimes using Unsupervised Learning Techniques*. Indian Journal of Science and Technology.



Li, F.-F. (2023). Lecture 11: Detection and segmentation - Stanford University. CS231n. http:

//cs231n.stanford.edu/slides/2017/cs231n\_2017\_lecture11.pdf