

# **Introduction to Deep Learning**

**Chapter 4: CNN: Pooling** 

**Bernd Bischl** 

Department of Statistics – LMU Munich WS 2021/2022



### **MAX POOLING**

1	3	6	2
3	8	1	1
2	9	2	1
5	1	3	1

Max pooling with 2x2	
filter and stride = 2	

- We've seen how convolutions work, but there is one other operation we need to understand.
- We want to downsample the feature map but optimally lose no information.

## **MAX POOLING**

1	3	6	2			
3	8	1	1	Max pooling with 2x2 filter and stride = 2	8	
2	9	2	1	7		
5	1	3	1			

- Applying the max pooling operation, we simply look for the maximum value at each spatial location.
- That is 8 for the first location.
- Due to the filter of size 2 we have the dimensions of the original feature map and obtain downsampling.

### **MAX POOLING**

	2	6	3	1
M f	1	1	8	3
	1	2	9	2
	1	3	1	5

Max pooling with 2x2 filter and stride = 2	
•	

8	6
9	3

- The final pooled feature map has entries 8, 6, 9 and 3.
- Max pooling brings us 2 properties: 1) dimention reduction and 2) spatial invariance.
- Popular pooling functions: max and (weighted) average.

1	3	6	2			
3	8	1	1	Avg pooling with 2x2 filter and stride = 2	3.75	
2	9	2	1			
5	1	3	1			

- We've seen how max pooling worked, there are exists other pooling operation such as Avg Pooling, Fractional Pooling, LP Pooling, Wavelet Pooling, Softmax Pooling, Stochastic Pooling, Blur Pooling, Orderable Pooling, Global Average Pooling, and etc.
- Similar to max pooling, we downsample the feature map but optimally lose no information.

1	3	6	2			
3	8	1	1	Avg pooling with 2x2 filter and stride = 2	3.75	2.5
2	9	2	1	_		
5	1	3	1			

• Applying the average pooling operation, we simply look for the mean/average value at each spatial location.

1	3	6	2			
3	8	1	1	Avg pooling with 2x2 filter and stride = 2	3.75	2.5
2	9	2	1	-	4.25	
5	1	3	1			

- We use all information by Sum and backpropagated to all responses.
- It is not robust to noise.

1	3	6	2			
3	8	1	1	Average pooling with 2x2 filter and stride = 2	3.75	2.5
2	9	2	1		4.25	1.75
5	1	3	1			

• The final pooled feature map has entries 3.75, 2.5, 4.25 and 1.75.

### COMPARISION OF MAX AND AVERAGE POOLING

- Avg pooling use all information by sum but Max pooling use only highest value.
- In Max-pooling operation details are removed therefore it is suitable for sparse information (Image Classification) and Avg pooling is suitable for dense information (NLP)



**Figure:** Shortcomings of Max and Average Pooling using Toy Image (source: Williams and Li, ICLR 2018)