



Introduction to Machine Learning

Neural Networks

Single Neuron / Perceptron




Learning goals

- Graphical representation of a single neuron
- Affine transformations and non-linear activation functions
- Hypothesis spaces of a single neuron
- Typical loss functions


A SINGLE NEURON

- The perceptron is a single artificial neuron and the basic computational unit of neural networks.
- It is a weighted sum of input values, transformed by τ :

$$f(x) = \tau(w_1x_1 + \dots + w_px_p + b) = \tau(\mathbf{w}^T \mathbf{x} + b)$$



Perceptron with **input features** x_1, x_2, \dots, x_p , **weights** w_1, w_2, \dots, w_p , **bias term** b , and **activation function** τ .



A SINGLE NEURON



- **Activation function** τ : a single neuron represents different functions depending on the choice of activation function.

- The identity function gives us the simple **linear regression**:

$$f(x) = \tau(\mathbf{w}^T \mathbf{x}) = \mathbf{w}^T \mathbf{x}$$

- The logistic function gives us the **logistic regression**:

$$f(x) = \tau(\mathbf{w}^T \mathbf{x}) = \frac{1}{1 + \exp(-\mathbf{w}^T \mathbf{x})}$$




A SINGLE NEURON

- We consider a perceptron with 3-dimensional input, i.e.
 $f(\mathbf{x}) = \tau(w_1x_1 + w_2x_2 + w_3x_3 + b)$.
- Input features \mathbf{x} are represented by nodes in the “input layer”.

Input




- In general, a p -dimensional input vector \mathbf{x} will be represented by p nodes in the input layer.




A SINGLE NEURON

- Weights \mathbf{w} are connected to edges from the input layer.





- The bias term b is implicit here. It is often not visualized as a separate node.



A SINGLE NEURON



- For an explicit graphical representation, we do a simple trick:
- Add a constant feature to the inputs $\tilde{\mathbf{x}} = (1, x_1, \dots, x_p)^T$
- and absorb the bias into the weight vector $\tilde{\mathbf{w}} = (b, w_1, \dots, w_p)$.

The graphical representation is then:




A SINGLE NEURON

- You can picture the input vector being "fed" to neurons on the left followed by a sequence of computations performed from left to right. This is called a **forward pass**.




A SINGLE NEURON


- A neuron performs a 2-step computation:
- **Affine Transformation:** weighted sum of inputs plus bias.



- **Non-linear Activation:** a non-linear transformation applied to the weighted sum.



- **Notation:**
- σ : activation functions in hidden/middle layers
- τ : output activation/transformation (final layer)





A SINGLE NEURON: HYPOTHESIS SPACE

- The hypothesis space that is formed by single neuron is

$$\mathcal{H} = \left\{ f : \mathbb{R}^p \rightarrow \mathbb{R} \mid f(\mathbf{x}) = \tau \left(\sum_{j=1}^p w_j x_j + b \right), \mathbf{w} \in \mathbb{R}^p, b \in \mathbb{R} \right\}.$$

- If τ is the logistic sigmoid or identity function, \mathcal{H} corresponds to the hypothesis space of logistic or linear regression, respectively.



Left: A regression line learned by a single neuron. Right: A decision-boundary learned by a single neuron in a binary classification task.

A SINGLE NEURON: OPTIMIZATION

- To optimize this model, we minimize the empirical risk

$$\mathcal{R}_{\text{emp}} = \frac{1}{n} \sum_{i=1}^n L \left(y^{(i)}, f \left(\mathbf{x}^{(i)} \right) \right),$$


where $L(y, f(\mathbf{x}))$ is a loss function. It compares the network's predictions $f(\mathbf{x})$ to the ground truth y .

- For regression, we typically use the L2 loss (rarely L1):

$$L(y, f(\mathbf{x})) = \frac{1}{2}(y - f(\mathbf{x}))^2$$

- For binary classification, we typically apply the cross entropy loss (also known as Bernoulli loss):

$$L(y, f(\mathbf{x})) = -(y \log f(\mathbf{x}) + (1 - y) \log(1 - f(\mathbf{x})))$$



A SINGLE NEURON: OPTIMIZATION

- For a single neuron and both choices of τ the loss function is convex.
- The global optimum can be found with an iterative algorithm like gradient descent.
- A single neuron with logistic sigmoid function trained with the Bernoulli loss yields the same result as logistic regression when trained until convergence.
- Note: In the case of regression and the L2-loss, the solution can also be found analytically using the “normal equations”. However, in other cases a closed-form solution is usually not available.

