


Introduction to Machine Learning

Supervised Classification In a Nutshell



Learning goals




- Understand basic concept of classifiers
- Know concepts of probabilistic and scoring classifier
- Know distinction between discriminant and generative approach
- Understand ideas of logistic regression and Naive Bayes

CLASSIFICATION TASKS


- Learn function that assigns categorical class labels to observations
- Each observation belongs to exactly one class
- The task can contain two (binary) or multiple (multi-class) classes



Training



Prediction




BASIC DEFINITIONS

- For every observation a model outputs the probability (probabilistic classifier) or score (scoring classifier) of each class
- In the multi-class case, the class label is usually assigned by choosing the class with the maximum score or probability
- In the binary case, a class label is assigned by choosing the class whose probability or score exceeds a threshold value c




Input: Unlabeled data

Sex	Age	Health	Degree of Graduation	Level of Happiness
Male	41	Fair	Bachelor	?




LOGISTIC REGRESSION


- Logistic regression is a **discriminant approach** for binary classification.
It turns scores into probabilities with the logistic function.
- We just need to compute the probability for **one** class (usually class 1).
- If the probability exceeds a threshold value $c \Rightarrow$ class 1 is predicted.



Input: Unlabeled data



The logistic function puts all scores in order along an s-shaped line.



NAIVE BAYES

- Naive Bayes is a **generative multi-class approach**. It computes the class probability for each class based on the training data.
- It considers the data distribution on three different levels:
 - Marginal distributions $\mathbb{P}(X)$ of each feature (in the entire data set)
 - Marginal distribution $\mathbb{P}(Y)$ of classes (in the entire data set)
 - Conditional distributions $\mathbb{P}(X|Y)$ of each feature in each class

