


Introduction to Machine Learning

Random Forest Feature Importance



Learning goals

- Understand that the goal of feature importance is to enhance interpretability of RF
- Understand FI based on feature permutation
- Understand FI based on improvement in splits

PERMUTATION FEATURE IMPORTANCE

RFs improve accuracy by aggregating multiple decision trees but **lose interpretability** compared to a single tree. **Feature importance** mitigates this problem.



- How much does performance *decrease*, if feature is removed / rendered useless?
- We permute values of considered feature
- Removes association between feature and target, keeps marginal distribution
- Can obtain \widehat{GE} of RF (without and with permuted features) by predicting OOB data, to **efficiently compute FI during training**
- Avoids not only new models (if feature would be removed) but can already use “OOB test data” during training



ID	Color	Form	Origin	Length	Banana
1	yellow	round	domestic	10	no
2	brown	oblong	imported	11	yes
3	green	oblong	imported	19	yes
4	yellow	oblong	domestic	14	yes

IMPURITY IMPORTANCE




Alternative: Add up all *improvements* in splits where feature x_j is used.



-
- 1: **for** features $x_j, j = 1 \rightarrow p$ **do**
 - 2: **for** all models $\hat{b}^{[m]}, m = 1 \rightarrow M$ **do**
 - 3: Find all splits in $\hat{b}^{[m]}$ on x_j
 - 4: Extract improvement / risk reduction for these splits
 - 5: Sum them up
 - 6: **end for**
 - 7: Add up improvements over all trees for FI of x_j
 - 8: **end for**
-

IN PRACTICE / OUTLOOK

Let's compare both FI variants on `mtcars`:



- Both methods are **biased toward features with more levels** (i.e., continuous or categoricals with many categories) [▶ Strobl et al. 2007](#)
- More advanced versions exist
- PFI and FI have been generalized, see our lecture on IML!