DATA IN SL

- Supervised tasks are labeled data situations where the goal is to learn the functional relationship between inputs (features) and output (target)
- Measurements on different aspects of n objects:
  - **Target**: output variable / goal of prediction
  - **Features**: properties that describe the object
- We distinguish between **regression** and **classification** tasks, depending on whether the target is **numerical** or **categorical**



Features x				Target y
Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Species
4.3	3.0	1.1	0.1	setosa
5.0	3.4	1.6	0.6	setosa
7.7	3.8	6.7	2.2	virginica
5.5	2.5	4.0	1.3	versicolor

Regression: Target is **numerical**, e.g., predict days a patient has to stay in hospital

Classification: Target is **categorical**, e.g., predict one of two risk categories for a life insurance customer

$$\mathcal{D} = \left(\left(\mathbf{x}^{(1)}, y^{(1)}\right), \ldots, \left(\mathbf{x}^{(n)}, y^{(n)}\right)\right) \in (\mathcal{X} \times \mathcal{Y})^n$$





TASKS, MODELS AND PARAMETERS

- Supervised tasks are labeled data situations where the goal is to learn the functional relationship between inputs (features) and output (target)
- We distinguish between **regression** and **classification** tasks, depending on whether the target is **numerical** or **categorical**

Regression: Target is **numerical**, e.g., predict days a patient has to stay in hospital

Classification: Target is **categorical**, e.g., predict one of two risk categories for a life insurance customer

- A model is a function that maps features to predicted targets
- A hypothesis is a model that describes the relationship between features and target, but can also restrict the set of all possible functions
- This restricted set of functions is called **hypothesis space**. E.g., one could consider only simple linear functions as hypothesis space
- Functions are fully determined by parameters. E.g., in the case of linear functions, $y = \theta_0 + \theta_1 x$, the parameters θ_0 (intercept) and θ_1 (slope), determine the relationship between y and x
- Finding the optimal model means finding the optimal set of parameters





MODELS AND PARAMETERS

- Maps features to predicted targets
- Learns automatically the relation between features and target – given a set of training data
- Learner picks the best element of the **hypothesis space**, i.e., the function that fits the training data best

$$f_\theta : \mathcal{X} \to \mathbb{R}^g$$

Regression:

Classification:





- We consider a restricted set of parametrized functions of a certain form, the **hypothesis space**, e.g., simple linear functions
- Models are fully determined by parameters. E.g., in the case of linear functions, $y = \theta_0 + \theta_1 x$, the parameters θ_0 (intercept) and θ_1 (slope) determine the relationship between y and x
- Finding the optimal model means finding the optimal set of parameters

LEARNER

- Learner uses labeled training data to learn a model f. This model is applied to new data for predicting the target variable
- Learns automatically the relation between features and target – given a set of training data
- Learner picks the best element of the **hypothesis space**, i.e., the function that fits the training data best:

$$\mathcal{I} : \mathbb{D} \times \Lambda \to \mathcal{H}$$

EMPIRICAL RISK MINIMIZATION

- The risk surface visualizes the empirical risk for all possible parameter values of the parameter vector $\boldsymbol{\theta}$
- Minimizing the empirical risk is often done by numerical optimization

$$\hat{\boldsymbol{\theta}} = \arg\min_{\boldsymbol{\theta} \in \Theta} \mathcal{R}_{\text{emp}}(\boldsymbol{\theta}).$$