# TRAINING ERROR

Simply plugin predictions for data that model has been trained on:

$$\rho(\mathbf{y}_{\text{train}}, \boldsymbol{F}_{\text{train}}) \text{ where } \boldsymbol{F}_{\text{train}} = \begin{bmatrix} \hat{f}_{\mathcal{D}_{\text{train}}}(\mathbf{x}^{(1)}_{\text{train}}) \\ \dots \\ \hat{f}_{\mathcal{D}_{\text{train}}}(\mathbf{x}^{(m)}_{\text{train}}) \end{bmatrix}$$




A.k.a. apparent error or resubstitution error.

# EXAMPLE 1: KNN

For large data, and some models, train error **can maybe** yield a good approximation of the GE:

- Use $k$-NN ($k = 15$).
- Up to 30K points from `spirals` to train.
- Use very large extra set for testing (to measure "true GE").

We increase train size, and see how gap between train error and GE closes.



# EXAMPLE 2: POLYNOMIAL REGRESSION

Sample data from $0.5 + 0.4 \cdot \sin(2\pi x) + \epsilon$

- Fix train size to 500 and vary k.
- Low train error for small $k$ is deceptive. Model is very local and overfits.




k = 2; trainerr = 0.08, testerr = 0.14

We fit a $d^{th}$-degree polynomial:

$$f(\mathbf{x} \mid \theta) = \theta_0 + \theta_1 \mathbf{x} + \cdots + \theta_d \mathbf{x}^d = \sum_{j=0}^{d} \theta_j \mathbf{x}^j.$$

Black region are misclassifications from large test test.

# TRAIN ERROR CAN EASILY BECOME 0

- For 1-NN it is always 0 as each $\mathbf{x}^{(i)}$ is its own NN at test time.
  - Extend any ML training in the following way: After normal fitting, we also store the training data. During prediction, we first check whether $x$ is already stored in this set. If so, we replicate its label. The train error of such an (unreasonable) procedure will be 0.
  - There are so called interpolators - interpolating splines, interpolating Gaussian processes - whose predictions can always perfectly match the regression targets, they are not necessarily good as they will interpolate noise, too.

We fit a $d^{th}$-degree polynomial:

$$f(\mathbf{x} \mid \theta) = \theta_0 + \theta_1 \mathbf{x} + \cdots + \theta_d \mathbf{x}^d = \sum_{j=0}^{d} \theta_j \mathbf{x}^j.$$

# CLASSICAL STATISTICAL GOF MEASURES

- **Goodness-of-fit** measures like $R^2$, likelihood, AIC, BIC, deviance are all based on the training error.
- For models of restricted capacity, and enough data, and non-violated distributional assumptions: they might work.
- Hard to gauge when that breaks, for high-dim, more complex data.
- How do you compare to non-param ML-like models?




- $d = 1$: MSE = 0.036: clearly underfitting
- $d = 3$: MSE = 0.003: pretty OK
- $d = 9$: MSE = 0.001: clearly overfitting

**Out-of-sample testing is probably always a good idea!**

Using the train error chooses overfitting model of maximal complexity.

# TRAIN ERROR CAN EASILY BECOME 0

- For 1-NN it is always 0 as each $\mathbf{x}^{(i)}$ is its own NN at test time.
- Extend any ML training in the following way: After normal fitting, we also store the training data. During prediction, we first check whether $x$ is already stored in this set. If so, we replicate its label. The train error of such an (unreasonable) procedure will be 0.
- There are so called interpolators - interpolating splines, interpolating Gaussian processes - whose predictions can always perfectly match the regression targets, they are not necessarily good as they will interpolate noise, too.

# CLASSICAL STATISTICAL GOF MEASURES

- **Goodness-of-fit** measures like $R^2$, likelihood, AIC, BIC, deviance are all based on the training error.
- For models of restricted capacity, and enough data, and non-violated distributional assumptions: they might work.
- Hard to gauge when that breaks, for high-dim, more complex data.
- How do you compare to non-param ML-like models?

**Out-of-sample testing is probably always a good idea!**