IRIS DATA SET

Introduced by statistician Fisher, frequently used toy example.

- Classify iris subspecies based on flower measurements
- 150 iris flowers: 50 versicolor, 50 virginica, 50 setosa
- Sepal length / width and petal length / width in [cm]



Source: https://rpubs.com/vidhividhi/irisdataeda

Word of warning: “iris” is a small, clean, low-dim data set, very easy to classify; this is not necessarily true in the wild.

DATA IN SUPERVISED LEARNING

- Measurements on different aspects of n objects
  - **Target**: output variable / goal of prediction
  - **Features**: properties that describe the object
- We assume some relationship between features and target, and want to discover that predictive rule.
- We assume some kind of relationship between the features and the target, in a sense that the value of the target variable can be explained by a combination of the features.



Features x				Target y
Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Species
4.3	3.0	1.1	0.1	setosa
5.0	3.3	1.4	0.2	setosa
7.7	3.8	6.7	2.2	virginica
5.5	2.5	4.0	1.3	versicolor

DATA TYPES

- Features and target may be of different data types
  - **Numerical** variables: $\in \mathbb{R}$ have values in $\mathbb{R}$
  - **Integer** variables: $\in \mathbb{Z}$ have values in $\mathbb{Z}$
  - **Categorical** variables: $\in \{C_1, ..., C_g\}$ have values in $\{C_1, ..., C_g\}$
  - **Binary** variables: $\in \{0, 1\}$ have values in $\{0, 1\}$
- For the **target** variable, this results in different tasks of supervised learning: *regression* and *classification*.
- Most learning algorithms can only deal with numerical features, although there are some exceptions (e.g., trees can use categoricals without problems). For other types, we usually have to pick or create an appropriate **encoding**, i.e., cast them to numerical values.
- If not stated otherwise, we assume numerical features.

ENCODING FOR CATEGORICAL FEATURES

- We expand the representation of a variable x with k mutually exclusive categories from a scalar to a length-$\tilde{k}$ vector with at most one element being 1, and 0 otherwise: $\boldsymbol{o}(x)_j = [\![(x = j)]\!] \in \{0, 1\}$, $j = 1, \dots, \tilde{k}$.
- Each entry of $\boldsymbol{o}(x) \in \{0, 1\}^{\tilde{k}}$ is treated as a separate feature.
- Two popular ways to do this are
  - **One-hot encoding**: $\tilde{k} = k$ dummies, so *exactly one* element is 1 ("hot"). E.g., $x \in \{a, b, c\} \mapsto \boldsymbol{o}(x) = (x_a, x_b, x_c)$, with $x_a = x_b = 0, x_c = 1$ and $\boldsymbol{o}(x) = (0, 0, 1)$ for $x = c$.
  - **Dummy encoding**: $\tilde{k} = k - 1$ dummies, so *at most one* element is 1, removing the redundancy of one-hot encoding (necessary for learners that require non-singular input matrices, such as in linear regression). E.g., $x \in \{a, b, c\} \mapsto \boldsymbol{o}(x) = (x_a, x_b)$ for reference category c, with $x_a = x_b = 0$ and $\boldsymbol{o}(x) = (0, 0)$ for $x = c$.
- We also often use this encoding for categorical targets.
- For features with a natural **order** in their categories we resort to encodings that reflect this ordinality, e.g., a sequence of integer values.

OBSERVATION LABELS

- We call the entries of the target column **labels**.
- We distinguish two types of data:
  - **Labeled data**: target is observed
  - **Unlabeled data**: target is unknown

	Features x				Target y
	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Species
labeled data	4.3	3.0	1.1	0.1	setosa
	5.0	3.3	1.4	0.2	setosa
	7.7	3.8	6.7	2.2	virginica
	5.5	2.5	4.0	1.3	versicolor
unlabeled data	5.9	3.0	5.1	1.8	?
	4.4	3.2	1.3	0.2	?

NOTATION FOR DATA

In formal notation, the data sets we are given are of the following form:

$$\mathcal{D} = \left(\left(\mathbf{x}^{(1)}, y^{(1)}\right), \ldots, \left(\mathbf{x}^{(n)}, y^{(n)}\right)\right) \in (\mathcal{X} \times \mathcal{Y})^n$$

$$\mathcal{D} = \left(\left(\mathbf{x}^{(1)}, y^{(1)}\right), \ldots, \left(\mathbf{x}^{(n)}, y^{(n)}\right)\right) \in (\mathcal{X} \times \mathcal{Y})^n.$$

- $\mathcal{X}$: input space, usually $\mathcal{X} \subset \mathbb{R}^p$
- $\mathcal{Y}$: output / target space
- $\left(\mathbf{x}^{(i)}, y^{(i)}\right) \in \mathcal{X} \times \mathcal{Y}$: i-th observation
- $\mathbf{x}_j = \left(x_j^{(1)}, \ldots, x_j^{(n)}\right)^\top$: j-th feature vector

We call

- $\mathcal{X}$ the input space with $p = \dim(\mathcal{X})$ (for now: $\mathcal{X} \subset \mathbb{R}^p$),
- $\mathcal{Y}$ the output / target space,
- the tuple $\left(\mathbf{x}^{(i)}, y^{(i)}\right) \in \mathcal{X} \times \mathcal{Y}$ the i-th observation,
- $\mathbf{x}_j = \left(x_j^{(1)}, \ldots, x_j^{(n)}\right)^\top$ the j-th feature vector.

We also use

- $(\mathcal{X} \times \mathcal{Y})^n$, i.e., the set of all data sets of size n, as $\mathbb{D}_n$,
- $\bigcup_{n \in \mathbb{N}} (\mathcal{X} \times \mathcal{Y})^n$, i.e., the set of all finite data sets, as $\mathbb{D}$.

We denote

- $(\mathcal{X} \times \mathcal{Y})^n$, i.e., the set of all data sets of size n, as $\mathbb{D}_n$,
- $\bigcup_{n \in \mathbb{N}} (\mathcal{X} \times \mathcal{Y})^n$, i.e., the set of all finite data sets, as $\mathbb{D}$.

$\Rightarrow$ We observe n objects, described by p features.

So we have observed n objects, described by p features.

DATA-GENERATING PROCESS

- We assume the observed data $\mathcal{D}$ to be generated by a process that can be characterized by some probability distribution

$$\mathbb{P}_{xy},$$

defined on $\mathcal{X} \times \mathcal{Y}$.

- We denote the random variables following this distribution by lowercase $\mathbf{x}$ and y.
- We usually assume the true distribution to be **unknown**. Learning (part of) its structure to predict y is what ML is all about.

DATA-GENERATING PROCESS

- We assume data to be drawn *i.i.d.* from the joint probability density function (pdf) / probability mass function (pmf) $p(\mathbf{x}, y)$.
  - i.i.d. stands for **i**ndependent and **i**dentically **d**istributed.
  - This means: We assume that all samples are drawn from the same distribution and are mutually independent – the i-th realization does not depend on the other $n-1$ ones.
  - This is a strong yet crucial assumption that is precondition to most theory in (basic) ML.



DATA-GENERATING PROCESS

Remarks:

- With a slight abuse of notation we write random variables, e.g., $\mathbf{x}$ and y, in lowercase, as normal variables or function arguments. The context will make clear what is meant.
- Often, distributions are characterized by a parameter vector $\theta \in \Theta$. We then write $p(\mathbf{x}, y \mid \theta)$.
- This lecture mostly takes a frequentist perspective. Distribution parameters θ appear behind the $\mid$ for improved legibility, not to imply that we condition on them in a probabilistic Bayesian sense. So, strictly speaking, $p(\mathbf{x}|\theta)$ should usually be understood to mean $p_\theta(\mathbf{x})$ or $p(\mathbf{x}, \theta)$ or $p(\mathbf{x}; \theta)$. On the other hand, this notation makes it very easy to switch to a Bayesian view.