# Introduction to Machine Learning

## Neural Networks
## Single Hidden Layer Networks for Multi-Class Classification




**Learning goals**

- Neural network architectures for multi-class classification
- Softmax activation function
- Softmax loss

# MULTI-CLASS CLASSIFICATION



- We have only considered regression and binary classification problems so far.

- How can we get a neural network to perform multiclass classification?

# MULTI-CLASS CLASSIFICATION



- The first step is to add additional neurons to the output layer.
- Each neuron in the layer will represent a specific class (number of neurons in the output layer = number of classes).




e of a single hidden layer, feed-forward neural network for g-class classification problems (bias term omitted).

# MULTI-CLASS CLASSIFICATION



- **Notation:**
  - For $g$-class classification, $g$ output units:

$$\mathbf{f} = (f_1, \ldots, f_g)$$

  - $m$ hidden neurons $z_1, \ldots, z_m$, with

$$z_j = \sigma(\mathbf{W}_j^T \mathbf{x}), \quad j = 1, \ldots, m.$$

  - Compute linear combinations of derived features $z$:

$$f_{in,k} = \boldsymbol{U}_k^T \mathbf{z}, \quad \mathbf{z} = (z_1, \ldots, z_m)^T, \quad k = 1, \ldots, g$$

# MULTI-CLASS CLASSIFICATION



- The second step is to apply a **softmax** activation function to the output layer.

- This gives us a probability distribution over $g$ different possible classes:

$$f_{out,k} = \tau_k(f_{in,k}) = \frac{\exp(f_{in,k})}{\sum_{k'=1}^{g} \exp(f_{in,k'})}$$

- This is the same transformation used in softmax regression!

- Derivative $\frac{\partial \tau(\mathbf{f}_{in})}{\partial \mathbf{f}_{in}} = \text{diag}(\tau(\mathbf{f}_{in})) - \tau(\mathbf{f}_{in})\tau(\mathbf{f}_{in})^T$

- It is a "smooth" approximation of the argmax operation, so $\tau((1, 1000, 2)^T) \approx (0, 1, 0)^T$ (picks out 2nd element!).

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).




$$\begin{pmatrix} 3 & -9 & 2 \\ 11 & -2 & 7 \\ -6 & 3 & -4 \\ 6 & -1 & 5 \end{pmatrix} \begin{pmatrix} 5 \\ 2 \\ -1 \\ 1 \end{pmatrix}$$

$W^T$ $\mathbf{b}$

$$\begin{pmatrix} 3 & -12 & 8 & 1 \\ 2 & -3 & 9 & 1 \\ -5 & 1 & -1 & 7 \end{pmatrix} \begin{pmatrix} 6 \\ 0 \\ -8 \end{pmatrix}$$

$U^T$ $\mathbf{c}$

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).






$$\begin{bmatrix} -3 \\ 1 \\ 5 \end{bmatrix}$$

$\mathbf{x}$

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).






$$\mathbf{x} = \begin{bmatrix} -3 \\ 1 \\ 5 \end{bmatrix} \qquad \mathbf{z}_{in} = \mathbf{w}^T\mathbf{x} + \mathbf{b} = \begin{pmatrix} (-3)*3 + 1*(-9) + 5*2 + 5 \\ (-3)*11 + 1*(-2) + 5*7 + 2 \\ (-3)*(-6) + 1*3 + 5*(-4) + (-1) \\ (-3)*6 + 1*(-1) + 5*5 + 1 \end{pmatrix}$$

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).






$$\mathbf{x} = \begin{bmatrix} -3 \\ 1 \\ 5 \end{bmatrix} \qquad \mathbf{z}_{in} = \begin{bmatrix} -3 \\ 2 \\ 0 \\ 7 \end{bmatrix} \qquad \mathbf{z} = \mathbf{z}_{out} = \sigma(\mathbf{z}_{in}) = \begin{pmatrix} 1/(1+\exp(-(-3))) \\ 1/(1+\exp(-2)) \\ 1/(1+\exp(-0)) \\ 1/(1+\exp(-7)) \end{pmatrix}$$

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).






$$\mathbf{x} = \begin{bmatrix} -3 \\ 1 \\ 5 \end{bmatrix} \qquad \mathbf{z}_{in} = \begin{bmatrix} -3 \\ 2 \\ 0 \\ 7 \end{bmatrix} \qquad \mathbf{z} = \begin{bmatrix} 0.05 \\ 0.88 \\ 0.5 \\ 0.99 \end{bmatrix} \qquad \begin{pmatrix} (0.05)*3 + (0.88)*(-12) + (0.5)*8 + (0.99)*1 + 6 \\ (0.05)*2 + (0.88)*(-3) + (0.5)*9 + (0.99)*1 + 0 \\ (0.05)*(-5) + (0.88)*1 + (0.5)*(-1) + (0.99)*7 + -8 \end{pmatrix}$$

$$\mathbf{f}_{in} = U^T\mathbf{z} + \mathbf{c}$$

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).






# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).




$$\begin{bmatrix} 0.57 \\ 2.95 \\ -0.92 \end{bmatrix}$$

$$\mathbf{f}_{in}$$

$$\begin{pmatrix} \frac{\exp(0.57)}{\exp(0.57)+\exp(2.95)+\exp(-0.92)} \\ \frac{\exp(2.95)}{\exp(0.57)+\exp(2.95)+\exp(-0.92)} \\ \frac{\exp(-0.92)}{\exp(0.57)+\exp(2.95)+\exp(-0.92)} \end{pmatrix}$$

$$\mathbf{f} = \mathbf{f}_{out} = \tau(\mathbf{f}_{in})$$

# MULTI-CLASS CLASSIFICATION: EXAMPLE

Forward pass (Hidden: Sigmoid, Output: Softmax).



# OPTIMIZATION: SOFTMAX LOSS



- The loss function for a softmax classifier is

$$L(y, f(\mathbf{x})) = -\sum_{k=1}^{g} [y = k] \log \left( \frac{\exp(f_{in,k})}{\sum_{k'=1}^{g} \exp(f_{in,k'})} \right)$$

where $[y = k] = \begin{cases} 1 & \text{if } y = k \\ 0 & \text{otherwise} \end{cases}$.

- This is equivalent to the cross-entropy loss when the label vector $\boldsymbol{y}$ is one-hot coded (e.g. $\mathbf{y} = (0, 0, 1, 0)^T$).
- Optimization: Again, there is no analytic solution.