# Interpretable Machine Learning

## Shapley Values




### Learning goals

- Learn what game theory is
- Understand the concept behind cooperative games
- Understand the Shapley value in game theory

# COOPERATIVE GAMES IN GAME THEORY

Shapley (1951)

- Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value





Interpretable Machine Learning – 1 / 10

# COOPERATIVE GAMES IN GAME THEORY

Shapley (1951)

- Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value
- Cooperative games: For all possible players $P = \{1, \ldots, p\}$, each subset of players $S \subseteq P$ forms a coalition – each coalition $S$ achieves a certain payout





Interpretable Machine Learning – 1 / 10

# COOPERATIVE GAMES IN GAME THEORY

Shapley (1951)

- Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value
- Cooperative games: For all possible players $P = \{1, \ldots, p\}$, each subset of players $S \subseteq P$ forms a coalition – each coalition $S$ achieves a certain payout
- A value function $v : 2^P \mapsto \mathbb{R}$ maps all $2^{|P|}$ possible coalitions to their payout (or gain)



Interpretable Machine Learning – 1 / 10

# COOPERATIVE GAMES IN GAME THEORY

Shapley (1951)

- Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value
- Cooperative games: For all possible players $P = \{1, \ldots, p\}$, each subset of players $S \subseteq P$ forms a coalition – each coalition $S$ achieves a certain payout
- A value function $v : 2^P \mapsto \mathbb{R}$ maps all $2^{|P|}$ possible coalitions to their payout (or gain)
- $v(S)$ is the payout of coalition $S \subseteq P$ (payout of empty coalition must be zero: $v(\emptyset) = 0$)



Interpretable Machine Learning – 1 / 10

# COOPERATIVE GAMES IN GAME THEORY

Shapley (1951)



- Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value
- Cooperative games: For all possible players $P = \{1, \ldots, p\}$, each subset of players $S \subseteq P$ forms a coalition – each coalition $S$ achieves a certain payout
- A value function $v : 2^P \mapsto \mathbb{R}$ maps all $2^{|P|}$ possible coalitions to their payout (or gain)
- $v(S)$ is the payout of coalition $S \subseteq P$ (payout of empty coalition must be zero: $v(\emptyset) = 0$)
- As some players contribute more than others, we want to fairly divide the total achievable payout $v(P)$ among the players according to a player's individual contribution

Interpretable Machine Learning – 1 / 10

# COOPERATIVE GAMES IN GAME THEORY

Shapley (1951)



- Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value
- Cooperative games: For all possible players $P = \{1, \ldots, p\}$, each subset of players $S \subseteq P$ forms a coalition – each coalition $S$ achieves a certain payout
- A value function $v : 2^P \mapsto \mathbb{R}$ maps all $2^{|P|}$ possible coalitions to their payout (or gain)
- $v(S)$ is the payout of coalition $S \subseteq P$ (payout of empty coalition must be zero: $v(\emptyset) = 0$)
- As some players contribute more than others, we want to fairly divide the total achievable payout $v(P)$ among the players according to a player's individual contribution
- We call the individual payout per player $\phi_j$, $j \in P$ (later: Shapley value)

Game theory is the study of strategic games between players, "game" refers to any series of interactions between actors/agents with gains and losses of quantifiable utility value
Cooperative games: For all possible players $P = \{1, \ldots, p\}$, each subset of players $S \subseteq P$ forms a coalition – each coalition $S$ achieves a certain payout
A value function $v : 2^P \mapsto \mathbb{R}$ maps all $2^{|P|}$ possible coalitions to their payout (or gain)
$v(S)$ is the payout of coalition $S \subseteq P$ (payout of empty coalition must be zero: $v(\emptyset) = 0$)
As some players contribute more than others, we want to fairly divide the total achievable payout $v(P)$ among the players according to a player's individual contribution
We call the individual payout per player $\phi_j$, $j \in P$ (later: Shapley value)



Interpretable Machine Learning – 1 / 10

# COOPERATIVE GAMES WITHOUT INTERACTIONS








Interpretable Machine Learning – 2 / 10

# COOPERATIVE GAMES WITHOUT INTERACTIONS




⇒ Fair Payouts are Trivial Without Interactions

⇒ Fair Payouts are Trivial Without Interactions



Interpretable Machine Learning – 2 / 10

# COOPERATIVE GAMES WITH INTERACTIONS









⇒ Unclear how to fairly distribute payouts when players interact

⇒ Unclear how to fairly distribute payouts when players interact



Interpretable Machine Learning – 3 / 10

# COOPERATIVE GAMES WITH INTERACTIONS

**Question:** What is a fair payout for player "yellow"?

**Idea:** Compute marginal contribution of the player of interest across different coalitions

- Compute the total payout of each coalition
- Compute difference in payouts for each coalition with and without player "yellow" (= marginal contribution)
- Average marginal contributions using appropriate weights

Interpretable Machine Learning – 4 / 10

# COOPERATIVE GAMES WITH INTERACTIONS

**Question:** What is a fair payout for player "yellow"?

**Idea:** Compute marginal contribution of the player of interest across different coalitions

**Note:** Each marginal contribution is weighted w.r.t. number of possible orders of its coalition

$\rightsquigarrow$ More players in $S \Rightarrow$ more orderings of $S$




- Compute the total payout of each coalition
- Compute difference in payouts for each coalition with and without player "yellow" (= marginal contribution)
- Average marginal contributions using appropriate weights



Interpretable Machine Learning – 4 / 10

# SHAPLEY VALUE - SET DEFINITION

This idea refers to the **Shapley value** which assigns a payout value to each player according to its marginal contribution in all possible coalitions.

- Let $v(S \cup \{j\}) - v(S)$ be the marginal contribution of player $j$ to coalition $S$
  $\rightsquigarrow$ measures how much a player $j$ increases the value of a coalition $S$



Interpretable Machine Learning – 5 / 10

# SHAPLEY VALUE - SET DEFINITION

This idea refers to the **Shapley value** which assigns a payout value to each player according to its marginal contribution in all possible coalitions.

- Let $v(S \cup \{j\}) - v(S)$ be the marginal contribution of player $j$ to coalition $S$
  $\rightsquigarrow$ measures how much a player $j$ increases the value of a coalition $S$
- Average marginal contributions for all possible coalitions $S \subseteq P \setminus \{j\}$
  $\rightsquigarrow$ order of how players join the coalition matters $\Leftrightarrow$ different weights depending on size of $S$



Interpretable Machine Learning – 5 / 10

# SHAPLEY VALUE - SET DEFINITION

This idea refers to the **Shapley value** which assigns a payout value to each player according to its marginal contribution in all possible coalitions.

- Let $v(S \cup \{j\}) - v(S)$ be the marginal contribution of player $j$ to coalition $S$
  $\rightsquigarrow$ measures how much a player $j$ increases the value of a coalition $S$
- Average marginal contributions for all possible coalitions $S \subseteq P \setminus \{j\}$
  $\rightsquigarrow$ order of how players join the coalition matters $\Leftrightarrow$ different weights depending on size of $S$
- Shapley value via **set definition** (weighting via multinomial coefficient):

$$\phi_j = \sum_{S \subseteq P \setminus \{j\}} \frac{|S|!(|P| - |S| - 1)!}{|P|!} (v(S \cup \{j\}) - v(S))$$



Interpretable Machine Learning – 5 / 10

# SHAPLEY VALUE - ORDER DEFINITION



The Shapley value was introduced as summation over sets $S \subseteq P \setminus \{j\}$, but it can be equivalently defined as a summation of all orders of players:

$$\phi_j = \frac{1}{|P|!} \sum_{\tau \in \Pi} (v(S_j^\tau \cup \{j\}) - v(S_j^\tau))$$

- $\Pi$: All possible orders of players (we have $|P|!$ in total)



Interpretable Machine Learning – 6 / 10

# SHAPLEY VALUE - ORDER DEFINITION

The Shapley value was introduced as summation over sets $S \subseteq P \setminus \{j\}$, but it can be equivalently defined as a summation of all orders of players:

$$\phi_j = \frac{1}{|P|!} \sum_{\tau \in \Pi} (v(S_j^\tau \cup \{j\}) - v(S_j^\tau))$$

- $\Pi$: All possible orders of players (we have $|P|!$ in total)
- $S_j^\tau$: Set of players before player $j$ in order $\tau = (\tau^{(1)}, \ldots, \tau^{(p)})$ where $\tau^{(i)}$ is $i$-th element

  Example: Players $1, 2, 3 \Rightarrow \Pi = \{(1,2,3), (1,3,2), (2,1,3), (2,3,1), (3,1,2), (3,2,1)\}$

  $\Rightarrow$ Example: Players $1, 2, 3 \Rightarrow$

  $\Pi = \{(1,2,3), (1,3,2), (2,1,3), (2,3,1), (3,1,2), (3,2,1)\}$

  $\rightsquigarrow$ For order $\tau = (2,1,3)$ and player of interest $j = 3 \Rightarrow S_j^\tau = \{2,1\}$

  $\rightsquigarrow$ For order $\tau = (3,1,2)$ and player of interest $j = 1 \Rightarrow S_j^\tau = \{3\}$

  $\rightsquigarrow$ For order $\tau = (3,1,2)$ and player of interest $j = 3 \Rightarrow S_j^\tau = \emptyset$


Interpretable Machine Learning – 6 / 10

# SHAPLEY VALUE - ORDER DEFINITION



The Shapley value was introduced as summation over sets $S \subseteq P \setminus \{j\}$, but it can be equivalently defined as a summation of all orders of players:

$$\phi_j = \frac{1}{|P|!} \sum_{\tau \in \Pi} \left( v(S_j^\tau \cup \{j\}) - v(S_j^\tau) \right)$$

- $\Pi$: All possible orders of players (we have $|P|!$ in total)
- $S_j^\tau$: Set of players before player $j$ in order $\tau = (\tau^{(1)}, \ldots, \tau^{(p)})$ where $\tau^{(i)}$ is $i$-th element
  - Example: Players $1, 2, 3 \Rightarrow \Pi = \{(\quad, 3), (1, 3, 2), (\quad, 3), (2, 3, 1), (3, 1, 2), (3, 2, 1)\}$
  - $\Rightarrow$ Example: Players $1, 2, 3 \Rightarrow$ For order $\tau = (2, 1, 3)$ and player of interest $j = 3 \Rightarrow S_j^\tau = \{2, 1\}$
  - $\Pi = \{(1, 2, 3), (1, 3, 2), (2, 1, 3), (2, 3, 1), (3, 1, 2), (3, 2, 1)\}$ For order $\tau = (1, 3, 2)$ and player of interest $j = 3 \Rightarrow S_j^\tau = \{3\}$
    - $\rightsquigarrow$ For order $\tau = (2, 1, 3)$ and player of interest $j = 3 \Rightarrow S_j^\tau = \{2, 1\}$
    - $\rightsquigarrow$ For order $\tau = (3, 1, 2)$ and player of interest $j = 1 \Rightarrow S_j^\tau = \{3\}$
    - $\rightsquigarrow$ For order $\tau = (3, 1, 2)$ and player of interest $j = 3 \Rightarrow S_j^\tau = \emptyset$
    - $\rightsquigarrow$ In set definition, it has the weight $\frac{(|S|-1)!(|P|-|S|)!}{|P|!} = \frac{2!0!}{3!} = \frac{2}{6}$
- Order definition: Marginal contribution of orders that yield set $S = \{1, 2\}$ is summed twice
  - $\rightsquigarrow$ In set definition, it has the weight $\frac{2!(3-2-1)!}{3!} = \frac{2 \cdot 0!}{6} = \frac{2}{6}$

# SHAPLEY VALUE - COMMENTS ON ORDER DEFINITION

- Order and set definition are equivalent
- Reason: The number of orders which yield the same coalition $S$ is $|S|!(|P| - |S| - 1)!$
  - $\Rightarrow$ There are $|S|!$ possible orders of players within coalition $S$
  - $\Rightarrow$ There are $(|P| - |S| - 1)!$ possible orders of players without $S$ and $j$



# SHAPLEY VALUE - COMMENTS ON ORDER DEFINITION

- Order and set definition are equivalent
- Reason: The number of orders which yield the same coalition $S$ is $|S|!(|P| - |S| - 1)!$
  - ⇒ There are $|S|!$ possible orders of players within coalition $S$
  - ⇒ There are $(|P| - |S| - 1)!$ possible orders of players without $S$ and $j$




- Relevance of the order definition: Approximate Shapley values by sampling permutations
  ⇝ randomly sample a fixed number of $M$ permutations and average them:

$$\phi_j = \frac{1}{M} \sum_{\tau \in \Pi_M} \left( v(S_j^\tau \cup \{j\}) - v(S_j^\tau) \right)$$

where $\Pi_M \subset \Pi$ is a random subset of $\Pi$ containing only $M$ orders of players

# WEIGHTS FOR MARGINAL CONTRIBUTION - ILLUSTRATION

Interpretable Machine Learning – 8 / 10

# WEIGHTS FOR MARGINAL CONTRIBUTION -- ILLUSTRATION






Interpretable Machine Learning – 8 / 10

# WEIGHTS FOR MARGINAL CONTRIBUTION - ILLUSTRATION






Interpretable Machine Learning – 8 / 10

# SHAPLEY VALUES - ILLUSTRATION

- Shapley value of player $j$ is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions


- Shapley value of player $j$ is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions







Interpretable Machine Learning – 9 / 10

# SHAPLEY VALUES - ILLUSTRATION

- Shapley value of player *j* is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions
- Measure and average the difference in payout after player 1 enters the coalition






Interpretable Machine Learning – 9 / 10

# SHAPLEY VALUES - ILLUSTRATION

- Shapley value of player $j$ is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions
- Measure and average the difference in payout after player 2 enters the coalition






Interpretable Machine Learning – 9 / 10

# SHAPLEY VALUES - ILLUSTRATION

- Shapley value of player $j$ is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions
- Measure and average the difference in payout after player 3 enters the coalition






Interpretable Machine Learning – 9 / 10

# SHAPLEY VALUES - ILLUSTRATION

- Shapley value of player i is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions


- Shapley value of player i is the marginal contribution to the value when it enters any coalition
- Produce all possible joining orders of player coalitions







Interpretable Machine Learning – 9 / 10

# AXIOMS OF FAIR PAYOUTS

Why is this a fair payout solution?

One possibility to define fair payouts are the following axioms for a given value function $v$:

- **Efficiency**: Player contributions add up to the total payout of the game: $\sum_{j=1}^{p} \phi_j = v(P)$


- **Efficiency**: Player contributions add up to the total payout of the game: $\sum_{j=1}^{p} \phi_j = v(P)$




Interpretable Machine Learning – 10 / 10

# AXIOMS OF FAIR PAYOUTS

Why is this a fair payout solution?

One possibility to define fair payouts are the following axioms for a given value function $v$:

- **Efficiency**: Player contributions add up to the total payout of the game: $\sum_{j=1}^{p} \phi_j = v(P)$
- **Symmetry**: Players $j, k \in P$ who contribute the same to any coalition get the same payout:
  If $v(S \cup \{j\}) = v(S \cup \{k\})$ for all $S \subseteq P \setminus \{j, k\}$, then $\phi_j = \phi_k$


- **Efficiency**: Player contributions add up to the total payout of the game:
  $\sum_{j=1}^{p} \phi_j = v(P)$
- **Symmetry**: Players $j, k \in P$ who contribute the same to any coalition get the same payout:
  If $v(S \cup \{j\}) = v(S \cup \{k\})$ for all $S \subseteq P \setminus \{j, k\}$, then $\phi_j = \phi_k$




Interpretable Machine Learning – 10 / 10

# AXIOMS OF FAIR PAYOUTS

Why is this a fair payout solution?

One possibility to define fair payouts are the following axioms for a given value function $v$:

- **Efficiency**: Player contributions add up to the total payout of the game: $\sum_{j=1}^{p} \phi_j = v(P)$
- **Symmetry**: Players $j, k \in P$ who contribute the same to any coalition get the same payout:
  If $v(S \cup \{j\}) = v(S \cup \{k\})$ for all $S \subseteq P \setminus \{j, k\}$, then $\phi_j = \phi_k$
- **Dummy/Null Player**: Payout is 0 for players who don't contribute to the value of any coalition:
  If $v(S \cup \{j\}) = v(S) \quad \forall \quad S \subseteq P \setminus \{j\}$, then $\phi_j = 0$





Interpretable Machine Learning – 10 / 10

# AXIOMS OF FAIR PAYOUTS

Why is this a fair payout solution?

One possibility to define fair payouts are the following axioms for a given value function $v$:

- **Efficiency**: Player contributions add up to the total payout of the game: $\sum_{j=1}^{p} \phi_j = v(P)$
- **Symmetry**: Players $j, k \in P$ who contribute the same to any coalition get the same payout:
  If $v(S \cup \{j\}) = v(S \cup \{k\})$ for all $S \subseteq P \setminus \{j, k\}$, then $\phi_j = \phi_k$
- **Dummy/Null Player**: Payout is 0 for players who don't contribute to the value of any coalition:
  If $v(S \cup \{j\}) = v(S) \quad \forall \quad S \subseteq P \setminus \{j\}$, then $\phi_j = 0$
- **Additivity**: For a game $v$ with combined payouts $v(S) = v_1(S) + v_2(S)$, the payout is the sum of payouts: $\phi_{j,v} = \phi_{j,v_1} + \phi_{j,v_2}$



Interpretable Machine Learning – 10 / 10