

# Interpretable Machine Learning




# Functional Decompositions
# Introduction




**Learning goals**

- Basic idea of additive functional decompositions
- Motivation and usefulness of functional decompositions
- Difficulty of obtaining or even defining a functional decomposition
- Several examples

# PRELIMINARIES




## Recap: Interactions

- Interactions between features: Effect of one feature on the prediction output depends on (one or more) other features
- Definition: Features $x_j$ and $x_k$ are considered to interact, if

$$\mathbb{E}\left[\left(\frac{\partial^2 f(\mathbf{x})}{\partial x_j \partial x_k}\right)^2\right] > 0$$

# PRELIMINARIES



### Recap: Interactions

- Interactions between features: Effect of one feature on the prediction output depends on (one or more) other features
- Definition: Features $x_j$ and $x_k$ are considered to interact, if


$$\mathbb{E}\left[\left(\frac{\partial^2 f(\mathbf{x})}{\partial x_j \partial x_k}\right)^2\right] > 0$$

### Recap: GAMs

- Decomposition into only main effects
- Do not contain any interactions

$$\hat{f}(\mathbf{x}) = \theta_0 + g_1(x_1) + g_2(x_2) + \ldots + g_p(x_p)$$

# FIRST EXAMPLE: ADDITIVE DECOMPOSITION




**Example**

Consider

$$\hat{f}(x_1, x_2) = 4 - 2x_1 + 0.3e^{x_2} + |x_1|x_2$$

- Idea: Additive decomposition depending on which features used:

# FIRST EXAMPLE: ADDITIVE DECOMPOSITION



**Example**

Consider


$$\hat{f}(x_1, x_2) = 4 - 2x_1 + 0.3e^{x_2} + |x_1|x_2$$

- Idea: Additive decomposition depending on which features used:

$$\begin{aligned} g_\emptyset(x_1, x_2) &= 4 && \text{Part depending on no features at all (intercept)} \\ \left.\begin{aligned} g_1(x_1, x_2) &= 2x_1 \\ g_2(x_1, x_2) &= 0.3e^{x_2} \end{aligned}\right\} & && \text{Parts depending on a single feature (main effects)} \\ g_{1,2}(x_1, x_2) &= |x_1|x_2 && \text{Part depending on both features (interaction)} \end{aligned} \tag{1}$$

$\rightsquigarrow$ Single terms with immediate interpretation, full model understanding

# FIRST EXAMPLE: ADDITIVE DECOMPOSITION



**Example**

Consider

$$\hat{f}(x_1, x_2) = 4 - 2x_1 + 0.3e^{x_2} + |x_1|x_2$$

- Idea: Additive decomposition depending on which features used:

$$\begin{aligned}
&g_\emptyset(x_1, x_2) = 4 && \text{Part depending on no features at all (intercept)} \\
&\left.\begin{aligned} g_1(x_1, x_2) &= 2x_1 \\ g_2(x_1, x_2) &= 0.3e^{x_2} \end{aligned}\right\} && \text{Parts depending on a single feature (main effects)} \\
&g_{1,2}(x_1, x_2) = |x_1|x_2 && \text{Part depending on both features (interaction)}
\end{aligned} \tag{1}$$


$\rightsquigarrow$ Single terms with immediate interpretation, full model understanding

$\leftrightarrow$ Not possible with effects of single features (e.g. PDPs) or GAM surrogate model (miss interaction part)


# ANOTHER EXAMPLE: ADDITIVE DECOMPOSITION

**Goal** in general: Given a black-box model $\hat{f} : \mathbb{R}^2 \to \mathbb{R}$, find a decomposition

$$\hat{f}(x_1, x_2) = g_\emptyset + g_1(x_1) + g_2(x_2) + g_{1,2}(x_1, x_2) \tag{2}$$




# ANOTHER EXAMPLE: ADDITIVE DECOMPOSITION



**Goal** in general: Given a black-box model $\hat{f} : \mathbb{R}^2 \to \mathbb{R}$, find a decomposition


$$\hat{f}(x_1, x_2) = g_\emptyset + g_1(x_1) + g_2(x_2) + g_{1,2}(x_1, x_2) \tag{2}$$

## Example




⇝ More details on this example later

# ANOTHER EXAMPLE: ADDITIVE DECOMPOSITION




**Example**

$$\hat{f}(x_1, x_2, x_3) = -2x_1 - 2\sin(x_3) + |x_1|x_2 + 0.5x_1x_2x_3 - \sin(x_2x_3) + 1$$

Again, read additive decomposition from formula:

# ANOTHER EXAMPLE: ADDITIVE DECOMPOSITION



**Example**

$$\hat{f}(x_1, x_2, x_3) = -2x_1 - 2\sin(x_3) + |x_1|x_2 + 0.5x_1x_2x_3 - \sin(x_2x_3) + 1$$


Again, read additive decomposition from formula:

$$
\begin{aligned}
&g_{\emptyset}(x_1, x_2, x_3) = 1 && \text{constant part, no effects} \\
&\left.\begin{aligned} g_1(x_1, x_2, x_3) &= -2x_1 \\ g_2(x_1, x_2, x_3) &= 0 \\ g_3(x_1, x_2, x_3) &= -2\sin(x_3) \end{aligned}\right\} && \text{main effects, no interactions} \\
&\left.\begin{aligned} g_{1,2}(x_1, x_2, x_3) &= |x_1|x_2 \\ g_{1,3}(x_1, x_2, x_3) &= 0 \\ g_{2,3}(x_1, x_2, x_3) &= -\sin(x_2x_3) \end{aligned}\right\} && \text{2-way interactions (depending on 2 features)} \\
&g_{1,2,3}(x_1, x_2, x_3) = 0.5x_1x_2x_3 && \text{3-way interactions}
\end{aligned}
\tag{3}
$$

$\Rightarrow$ 8 components in total, but some empty $\rightsquigarrow$ Certain interactions not present

# GENERAL FORM OF FUNCTIONAL DECOMPOSITION

▸ "Li and Rabitz" 2011 ▸ "Chastaing et al." 2012



**Definition**

*Functional decomposition*: Additive decomposition of a function $\hat{f} : \mathbb{R}^p \mapsto \mathbb{R}$ into a sum of components of different dimensions w.r.t. inputs $x_1, \ldots, x_p$:

$$\begin{aligned}\hat{f}(\mathbf{x}) &= \sum_{S \subseteq \{1,\ldots,p\}} g_S(\mathbf{x}_S) \\ &= g_\emptyset + g_1(x_1) + g_2(x_2) + \cdots + g_p(x_p) + \\ &\quad g_{1,2}(x_1, x_2) + \cdots + g_{p-1,p}(x_{p-1}, x_p) + \cdots + \\ &\quad g_{1,2,3}(x_1, x_2, x_3) + \cdots + g_{1,2,3,4}(x_1, x_2, x_3, x_4) + \cdots + g_{1,\ldots,p}(x_1, \ldots, x_p)\end{aligned}$$


$\rightsquigarrow$ one component for every possible combination $S$ of indices, allowed to formally only depend on these features / be a function of these features

**Problems:**

- How to find / compute such a decomposition for any black-box models $\hat{f}$?
- . . . such that the decomposition is useful / has nice properties (w.r.t. the model / w.r.t. the data)?

# GENERAL FORM OF FUNCTIONAL DECOMPOSITION

▸ "Li and Rabitz" 2011 ▸ "Chastaing et al." 2012



**Definition**

*Functional decomposition*: Additive decomposition of a function $\hat{f} : \mathbb{R}^p \mapsto \mathbb{R}$ into a sum of components of different dimensions w.r.t. inputs $x_1, \ldots, x_p$:

$$\begin{aligned}\hat{f}(\mathbf{x}) &= \sum_{S \subseteq \{1,\ldots,p\}} g_S(\mathbf{x}_S) \\ &= g_\emptyset + g_1(x_1) + g_2(x_2) + \cdots + g_p(x_p) + \\ &\quad g_{1,2}(x_1, x_2) + \cdots + g_{p-1,p}(x_{p-1}, x_p) + \cdots + \\ &\quad g_{1,2,3}(x_1, x_2, x_3) + \cdots + g_{1,2,3,4}(x_1, x_2, x_3, x_4) + \cdots + g_{1,\ldots,p}(x_1, \ldots, x_p)\end{aligned}$$


$\rightsquigarrow$ one component for every possible combination $S$ of indices

Sort terms according to degree of interaction:


- $g_\emptyset \hat{=}$ Constant mean (intercept)
- $g_j \hat{=}$ first-order or main effect of $j$-th feature alone on $\hat{f}(\mathbf{x})$
- $g_{j,k} \hat{=}$ second-order interaction effect of features $j$ and $k$ w.r.t. $\hat{f}(\mathbf{x})$
- $g_S(\mathbf{x}_S) \hat{=}$ $|S|$-order effect, depends **only** on features in $S$

# PROPERTIES OF THE DEFINITION

- **Interpretability**: Extremely powerful decomposition, reveals complete interaction structure



# PROPERTIES OF THE DEFINITION




- **Interpretability**: Extremely powerful decomposition, reveals complete interaction structure
- Compare to GAM: Same decomposition, but without interactions
  $\implies$ Any GAM already comes with its decomposition

$$\hat{f}(\mathbf{x}) = g_{\emptyset} + g_1(x_1) + g_2(x_2) + \ldots + g_p(x_p)$$

- Same for LMs: Decomposition explicitly modeled

# PROPERTIES OF THE DEFINITION




- **Interpretability**: Extremely powerful decomposition, reveals complete interaction structure
- Compare to GAM: Same decomposition, but without interactions
  $\implies$ Any GAM already comes with its decomposition

$$\hat{f}(\mathbf{x}) = g_{\emptyset} + g_1(x_1) + g_2(x_2) + \ldots + g_p(x_p)$$

- Same for LMs: Decomposition explicitly modeled
- Easy decomp. also for decision trees and tree ensembles (see below)

# PROPERTIES OF THE DEFINITION




- **Interpretability**: Extremely powerful decomposition, reveals complete interaction structure
- Compare to GAM: Same decomposition, but without interactions
  $\implies$ Any GAM already comes with its decomposition

$$\hat{f}(\mathbf{x}) = g_\emptyset + g_1(x_1) + g_2(x_2) + \ldots + g_p(x_p)$$

- Same for LMs: Decomposition explicitly modeled
- Easy decomp. also for decision trees and tree ensembles (see below)
- **Problem 1:** Calculating decomposition extremely difficult, often infeasible
  - For $p$ features: Decomposition with $2^p$ terms $\rightarrow$ too many different terms, difficult to interpret

# PROPERTIES OF THE DEFINITION




- **Interpretability**: Extremely powerful decomposition, reveals complete interaction structure
- Compare to GAM: Same decomposition, but without interactions
  $\implies$ Any GAM already comes with its decomposition

$$\hat{f}(\mathbf{x}) = g_\emptyset + g_1(x_1) + g_2(x_2) + \ldots + g_p(x_p)$$

- Same for LMs: Decomposition explicitly modeled
- Easy decomp. also for decision trees and tree ensembles (see below)
- **Problem 1:** Calculating decomposition extremely difficult, often infeasible
  - For $p$ features: Decomposition with $2^p$ terms $\rightarrow$ too many different terms, difficult to interpret
- **Problem 2:** Definition not complete: Decomposition not unique, many trivial decompositions not useful

  $\rightarrow$ More requirements or constraints needed to ensure decomposition is meaningful
  - Even worse once features are dependent or correlated (see later)

# PROBLEM 2: DEFINITION NOT ENOUGH




**Example**

Again consider

$$\hat{f}(x_1, x_2, x_3) = -2x_1 - 2\sin(x_3) + |x_1|x_2 + 0.5x_1x_2x_3 - \sin(x_2x_3) + 1$$

# PROBLEM 2: DEFINITION NOT ENOUGH



**Example**

Again consider

$$\hat{f}(x_1, x_2, x_3) = -2x_1 - 2\sin(x_3) + |x_1|x_2 + 0.5x_1x_2x_3 - \sin(x_2x_3) + 1$$


Two possible decompositions (valid according to definition):

$$g_{1,\ldots,p}(x_1, \ldots, x_p) := \hat{f}(\mathbf{x}) \text{ and for all other terms } g_S(\mathbf{x}_S) := 0,$$

or:

$$g_\emptyset = 1\,; \quad g_1(x_1) = x_1\,;\ g_2(x_2) = 2x_2\,;\ g_3(x_3) = 3x_3\,;$$
$$g_{1,2}(x_1, x_2) = \frac{1}{2}x_1x_2\,;\ g_{1,3}(x_1, x_3) = \frac{1}{3}x_1x_3\,;\ g_{2,3}(x_2, x_3) = \frac{2}{3}x_2x_3\,;$$
$$\text{and} \quad g_{1,2,3}(x_1, x_2, x_3) = \hat{f}(x_1, x_2, x_3) - \sum_{S \subsetneq \{1,2,3\}} g_S(\mathbf{x}_S)$$

# PROBLEM 2: DEFINITION NOT ENOUGH



**Example**

Again consider

$$\hat{f}(x_1, x_2, x_3) = -2x_1 - 2\sin(x_3) + |x_1|x_2 + 0.5x_1x_2x_3 - \sin(x_2x_3) + 1$$

Two possible decompositions (valid according to definition):


$$g_{1,\ldots,p}(x_1, \ldots, x_p) := \hat{f}(\mathbf{x}) \text{ and for all other terms } g_S(\mathbf{x}_S) := 0,$$

or:

$$g_\emptyset = 1\,; \quad g_1(x_1) = x_1\,;\ g_2(x_2) = 2x_2\,;\ g_3(x_3) = 3x_3\,;$$
$$g_{1,2}(x_1, x_2) = \frac{1}{2}x_1x_2\,;\ g_{1,3}(x_1, x_3) = \frac{1}{3}x_1x_3\,;\ g_{2,3}(x_2, x_3) = \frac{2}{3}x_2x_3\,;$$
$$\text{and} \quad g_{1,2,3}(x_1, x_2, x_3) = \hat{f}(x_1, x_2, x_3) - \sum_{S \subsetneq \{1,2,3\}} g_S(\mathbf{x}_S)$$


$\Longrightarrow$ Definition of decomposition not unique

# EXAMPLE: DECISION TREES




Define *interaction type t* of a node: subset of features used to build this node.


**Example:**



# EXAMPLE: DECISION TREES




Define *interaction type t* of a node: subset of features used to build this node.
**Example:**




$\Rightarrow$ Degree of interaction in each node is $|t|$.

# DECOMPOSITION FOR DECISION TREES



Here: Decomposition via indicator functions


$$\hat{f}(\mathbf{x}) = g_{\emptyset} + g_{2,4}(x_2, x_4) + g_{2,3}(x_2, x_3) + g_{1,2,4}(x_1, x_2, x_4)$$

$\Longrightarrow$ Decomposition has no main effect, but model certainly contains an effect of e.g. $x_2$

$\Longrightarrow$ Lower-order effects "hidden" inside higher-order terms

$\rightsquigarrow$ reading from decision tree not enough, "bad decomposition"

# DECOMPOSITION FOR DECISION TREES



Here: Decomposition via indicator functions

$$\hat{f}(\mathbf{x}) = g_{\emptyset} + g_{2,4}(x_2, x_4) + g_{2,3}(x_2, x_3) + g_{1,2,4}(x_1, x_2, x_4)$$


$\Longrightarrow$ Decomposition has no main effect, but model certainly contains an effect of e.g. $x_2$

$\Longrightarrow$ Lower-order effects "hidden" inside higher-order terms


$\rightsquigarrow$ reading from decision tree not enough, "bad decomposition"

**Note:** ▸ "Yang" 2024 propose a (quite complicated) solution for this case


# EXAMPLE: EBM




- See before: **GAMs** have functional decomposition by definition
- **EBMs:** Sum of the final one- and two-dimensional components



# EXAMPLE: EBM



- See before: **GAMs** have functional decomposition by definition
- **EBMs:** Sum of the final one- and two-dimensional components




- In general: Model with functional decomposition up to max. order 2 is always “inherently interpretable”
- **Reason:** Visualization of all components