

Interpretable Machine Learning




Interpretable Models 2
Explainable Boosting Machines (EBM)



Learning goals

- Understand link between GAM and EBM
- Learn univariate EBMs
  $\hat{=}$ GAM + boosting + shallow bagged trees
- Extend to GA2M: GAMs with selected pairwise interactions
- Detect interactions efficiently using FAST algorithm

RECAP: SPLIT SELECTION DECISION TREE



- **Impurity (Regression):** Variance of target Y in a node:

$$\text{Var}(Y) = \frac{1}{n}\sum_{i=1}^{n}(y^{(i)} - \bar{y})^2 = \frac{1}{n}\sum_{i=1}^{n}(y^{(i)})^2 - \bar{y}^2$$


- **Sum of squared errors (SSE) = residual sum of squares (RSS)**:

$$\text{RSS} = n \cdot \text{Var}(Y) = \sum_{i=1}^{n}(y^{(i)} - \bar{y})^2 = \cdots = \sum_{i=1}^{n}(y^{(i)})^2 - \frac{1}{n}\left(\sum_{i=1}^{n} y^{(i)}\right)^2$$

$$\text{Hence: } \boxed{\text{RSS} = SS_n - \frac{S_n^2}{n} \quad \text{with} \quad S_n = \sum_{i=1}^{n} y^{(i)}, \; SS_n = \sum_{i=1}^{n}(y^{(i)})^2}$$

- **Split criterion:**
  - **Minimize post-split RSS:** $\text{RSS}_{\text{split}} = \text{RSS}_L + \text{RSS}_R$
  - **Maximize reduction in RSS:** $\Delta\text{RSS} = \text{RSS}_{\text{parent}} - (\text{RSS}_L + \text{RSS}_R)$

NAIVE SPLIT SELECTION: EXPLICIT COMPUT.




- For a given feature X_j, sort the pairs $(x_j^{(i)}, y^{(i)})$ by increasing $x_j^{(i)}$.
- For each of the $n-1$ potential split points at $s_k = \frac{1}{2}(x_j^{(k)} + x_j^{(k+1)})$:
  - Define partitions: $\mathcal{I}_L = \{i : x^{(i)} \leq s_k\}, \quad \mathcal{I}_R = \{i : x^{(i)} > s_k\}$
  - Compute group means and counts after splitting at s_k:

$$\bar{y}_L = \frac{1}{N_L} \sum_{i \in \mathcal{I}_L} y^{(i)}, \quad \bar{y}_R = \frac{1}{N_R} \sum_{i \in \mathcal{I}_R} y^{(i)}, \text{ with } N_L = |\mathcal{I}_L|, \quad N_R = |\mathcal{I}_R|$$

  - Compute RSS after splitting at s_k:


$$\text{RSS}_{\text{split}}(s_k) = \text{RSS}_L(s_k) + \text{RSS}_R(s_k) = \sum_{i \in \mathcal{I}_L} (y^{(i)} - \bar{y}_L)^2 + \sum_{i \in \mathcal{I}_R} (y^{(i)} - \bar{y}_R)^2$$

- Select split point s_k that minimizes $\text{RSS}_{\text{split}}(s_k)$.
- **Compute cost:** $O(n^2)$ per feat. (recompute mean & RSS at each split)



$\mathcal{O}(n^2)$ operations (recompute for each split s_j per feature)

EFFICIENT SPLIT SELECTION




- **Setup:** For feature X_j, sort the data $(x_j^{(i)}, y^{(i)})_{i=1}^n$ by increasing $x_j^{(i)}$
- **Define group statistics (cumulative sums) after split at s_k:**

$$S_L = \sum_{i \in \mathcal{I}_L} y^{(i)}, \qquad SS_L = \sum_{i \in \mathcal{I}_L} (y^{(i)})^2, \qquad N_L = |\mathcal{I}_L|$$
$$S_R = S_n - S_L, \qquad SS_R = SS_n - SS_L, \qquad N_R = n - N_L$$

- **RSS for child nodes and parent node:**

$$\text{RSS}_L(s_k) = SS_L - \frac{S_L^2}{N_L}, \text{RSS}_R(s_k) = SS_R - \frac{S_R^2}{N_R}, \text{RSS}_{\text{parent}} = SS_L + SS_R - \frac{S_n^2}{n}$$

EFFICIENT SPLIT SELECTION



- **Setup:** For feature X_j, sort the data $(x_j^{(i)}, y^{(i)})_{i=1}^n$ by increasing $x_j^{(i)}$
- **Define group statistics (cumulative sums) after split at s_k:**

$$S_L = \sum_{i \in \mathcal{I}_L} y^{(i)}, \qquad SS_L = \sum_{i \in \mathcal{I}_L} (y^{(i)})^2, \qquad N_L = |\mathcal{I}_L|$$
$$S_R = S_n - S_L, \qquad SS_R = SS_n - SS_L, \qquad N_R = n - N_L$$

- **RSS for child nodes and parent node:**

$$\text{RSS}_L(s_k) = SS_L - \frac{S_L^2}{N_L}, \text{RSS}_R(s_k) = SS_R - \frac{S_R^2}{N_R}, \text{RSS}_{\text{parent}} = SS_L + SS_R - \frac{S_n^2}{n}$$


- **Reduction in RSS:**

$$\Delta\text{RSS}(s_k) = \text{RSS}_{\text{parent}} - (\text{RSS}_L + \text{RSS}_R) = \frac{S_L^2}{N_L} + \frac{S_R^2}{N_R} - \frac{S_n^2}{n}$$


All squared-target terms SS_L, SS_R cancel. Only first-order sums needed.

- **Search:** Choose best split $s_k^\star = \arg\max_{s_k} \Delta\text{RSS}(s_k)$
- **Complexity per feature:**
  $O(n \log n)$ (sorting) + $O(n)$ (cumulative sums and scan)

EFFICIENT SPLIT SELECTION - EXAMPLE




$$y^{(1)}=1.2,\ y^{(2)}=2.0,\ y^{(3)}=1.5,\ y^{(4)}=3.2,\ y^{(5)}=2.8,\ y^{(6)}=4.1 \qquad (x_j^{(1)} \le \cdots \le x_j^{(6)})$$



- $G(k)$ omits $-S_n^2/n$ (identical for all splits $\Rightarrow$ does not affect arg max).
- Only cumulative sums S_k are required, no SS_k is stored or updated.
- $\mathcal{O}(1)$ per split $\Rightarrow \mathcal{O}(n)$ per feature.

EXPLAINABLE BOOSTING MACHINES (EBM)



Recall GAM:


$$g(\mathbb{E}[y \mid \mathbf{x}]) = \theta_0 + f_1(x_1) + f_2(x_2) + \ldots + f_p(x_p),$$

- One shape function f_j per feature x_j
  $\rightsquigarrow$ **Feature-level interpretability**
- Captures non-linear univariate effects
  $\rightsquigarrow$ **Better performance / more flexible than GLMs**

EBM idea: GAMs train with **gradient boosting** over **shallow bagged trees**


- **GAMs** - feature-wise interpretability via separate shape functions $f_j(x_j)$
  $\rightsquigarrow$ Potentially include pairwise interactions manually
- **Gradient Boosting** - incrementally fits residuals to improve predictive performance while retaining additivity
- **Shallow Bagged Trees** - low-depth trees (2-4 leaves) reduce variance and create interpretable shape functions

EBM - TWO-STAGE MODEL CONSTRUCTION



1. **Stage 1: Fit Main Effects (Univariate Terms)** ▸ "Lou et al." 2012
   - Train EBM using only feature-wise shape functions $f_j(x_j)$
   - Freeze the univariate model after convergence
2. **Stage 2: Add Selected Pairwise Interactions** ▸ "Lou et al." 2013
   - Apply **FAST** to rank all $O(p^2)$ feat pairs by potential reduction in RSS
   - Select top K pairwise interactions and store them in $\mathcal{K}$
   - Use boosting to fit pairwise interaction terms $f_{ij}(x_i, x_j)$ on residuals
   - Final model: $\hat{f}(\mathbf{x}) = \sum_{j=1}^{p} f_j(x_j) + \sum_{(i,j)\in\mathcal{K}} f_{ij}(x_i, x_j)$

UNIVARIATE EBM - INITIALIZATION



- Set all shape functions to zero:

$$f_j^{[0]}(x_j) = 0 \quad \text{for all } j = 1, \ldots, p$$

- Compute initial model prediction:


$$\hat{y}^{[0]} = \sum_{j=1}^{p} f_j^{[0]}(x_j) = 0$$

- Compute initial pseudo-residuals (e.g., for squared loss):

$$\tilde{r}^{[0]} = -\frac{\partial L}{\partial \hat{y}} = y - \hat{y}^{[0]} = y$$

UNIVARIATE EBM - FIRST FEATURE UPDATE

Iteration	feat_1	feat_2	feat_3	...	feat_p
1					



- Fit shallow bagged tree $T_1^{[1]}$ (2-4 leaves) to training data $\left\{ \left(x_1, \tilde{r}^{[0]} \right)^{(i)} \right\}_{i=1}^{n}$
  $\rightsquigarrow$ Use only feature x_1 as input and $\tilde{r}^{[0]}$ as target
- Update first shape function with learning rate η:

$$f_1^{[1]}(x_1) = f_1^{[0]}(x_1) + \eta \cdot T_1^{[1]}(x_1)$$


- Update prediction:


$$\hat{y}^{[1]} = \sum_{j=1}^{p} f_j^{[1]}(x_j)$$

- Recompute pseudo-residuals:

$$\tilde{r}^{[1]} = -\frac{\partial L}{\partial \hat{y}} = y - \hat{y}^{[1]}$$


UNIVARIATE EBM - CYCLE THROUGH FEATURES






- 1st boosting iteration:
  Cycle through each feature $j = 2, \ldots, p$:
  - Fit shallow bagged tree $T_j^{[1]}$ using feature x_j and previous residual $\tilde{r}^{[j-1]}$
  - Update f_j: $f_j^{[1]}(x_j) = f_j^{[0]}(x_j) + \eta \cdot T_j^{[1]}(x_j)$
  - Recompute $\hat{y}$ and residuals: $\tilde{r}^{[j]} = y - \hat{y}^{[j]}$
- After one full pass over features, we complete one boosting iteration


UNIVARIATE EBM - ITERATE BOOSTING PROCESS





- Repeat feature-wise updates for M boosting iterations (e.g., $M = 10000$)
- In each boosting iteration:
  - Cycle over all features $j = 1, \ldots, p$ individually
  - Update only one f_j at a time using residuals from previous state
- Use small learning rate η to ensure smooth updates and order-invariance

UNIVARIATE EBM - PREDICTION & INTERPRETABILITY




- Final model consists of M shallow trees per feature:

$$\text{EBM Model} = \sum_{j=1}^{p} \sum_{m=1}^{M} \eta \cdot T_j^{[m]}(x_j)$$

- For each feature x_j, combine its M trees into a shape function:


$$\hat{f}_j(x_j) = \sum_{m=1}^{M} \eta \cdot T_j^{[m]}(x_j)$$

- Plot $\hat{f}_j(x_j)$ vs. $x_j \rightsquigarrow$ Shows univariate marginal effect of feature j
- One plot per feature $\rightsquigarrow$ Model is fully explainable via p additive plots



EBM WITH PAIRWISE INTERACTIONS


Generalized Additive Models plus Interactions (GA2M):




$$g\big(\mathbb{E}[y \mid \mathbf{x}]\big) = \theta_0 + \sum_{j=1}^{p} f_j(x_j) + \sum_{i<j} f_{ij}(x_i, x_j)$$


- **Motivation**: Univariate EBM does not model interactions
- **Challenge**: $O(p^2)$ potential pairwise interactions $\rightsquigarrow$ often infeasible
- **Solution - FAST algorithm** ▸ "Lou et al." 2013:
  - Efficiently estimates importance of all feature pairs
  - Ranks pairs by reduction in residual sum of squares (RSS)
  - Avoids fitting EBM with each pairwise interaction
- **Result**:
  Add only top-ranked interactions f_{ij} via a second-stage boosting step
  $\rightsquigarrow$ Performed after the univariate EBM has been trained
- **Interpretability preserved**: Each $f_{ij}(x_i, x_j)$ visualized as a 2D heatmap

FAST: PAIR-WISE INTERACTION STRENGTH



We evaluate a 4-leaf, axis-aligned tree T_{ij} over the 2D feature projection (x_i, x_j).







tree T_{ij} with 4 leaves

1. **Discretize**: Map each axis to $b \leq 256$ ordered bins (quantile or equal-width).

FAST: PAIR-WISE INTERACTION STRENGTH



We evaluate a 4-leaf, axis-aligned tree T_{ij} over the 2D feature projection (x_i, x_j).




1. **Discretize**: Map each axis to $b \leq 256$ ordered bins (quantile or equal-width).
2. **Iterate** over b^2 candidate cuts (c_i, c_j).
3. **Fit**: For each cut, assign a constant $\hat{y}_r = \text{mean}(y \in r)$ to $r \in \{A, B, C, D\}$.
4. **Compute RSS summed over all regions:**

$$\text{RSS}(c_i, c_j) = \sum_r \sum_{(x,y)\in r} (y - \hat{y}_r)^2$$

$$= \sum_r \left(\sum_{(x,y)\in r} y^2 - \frac{1}{n_r} \left(\sum_{(x,y)\in r} y \right)^2 \right)$$

5. **Select**: Keep the split with minimal RSS.
   $\rightsquigarrow$ largest RSS drop = strongest interaction.

FAST: USE RSS DROP



To evaluate a cut pair (c_i, c_j), we use precomputed per-region statistics:

- For each region $r \in \{A, B, C, D\}$, compute:

$$S_r = \sum_{(x,y)\in r} y, \quad n_r = |\{(x,y) \in r\}|, \quad \hat{y}_r = S_r/n_r$$


- Plug into RSS summed over all regions:

$$\text{RSS}(c_i, c_j) = \sum_r \left(\sum_{(x,y)\in r} y^2 - \frac{1}{n_r} \left(\sum_{(x,y)\in r} y \right)^2 \right) = \sum_r \sum_{(x,y)\in r} y^2 + \sum_r \frac{S_r^2}{n_r}$$

- For a candidate cut, compute **RSS drop**:

$$\begin{aligned} \Delta\text{RSS}(c_i, c_j) &= \text{RSS}_{\text{parent}} - \text{RSS}(c_i, c_j) \\ &= \left(\sum_{i=1}^{n} \left(y^{(i)}\right)^2 - \frac{S_n^2}{n} \right) - \sum_r \sum_{(x,y)\in r} y^2 + \sum_r \frac{S_r^2}{n_r} \end{aligned}$$

FAST: USE RSS DROP



Because $\sum_{i=1}^{n} \left(y^{(i)}\right)^2 = \sum_r \sum_{(x,y)\in r} y^2$, *all squared target terms cancel*:

$$\boxed{\Delta\text{RSS}(c_i, c_j) = \sum_r \frac{S_r^2}{n_r} - \frac{S_n^2}{n}}$$


The parent term S_n^2/n is constant across all cuts. Hence


$$\textbf{maximize } \Delta\text{RSS}(c_i, c_j) = \sum_r \frac{S_r^2}{n_r} \iff \textbf{minimize } \text{RSS}(c_i, c_j).$$


Why is this efficient?

- Precompute cumulative sums of y and counts across the binned grid
- Enables fast lookup of region statistics S_r, n_r for any cut
- No additional data scan or recomputation needed across the b^2 candidate cuts
- For the best cut: Compare and select the largest $\Delta\text{RSS}(c_i, c_j)$.

EBM - BOOSTING PAIRWISE INTERACTIONS









- **Goal:** Fit each selected interaction $f_{ij}(x_i, x_j)$ on residuals from main effects
- Use tree-like predictor, inspired by FAST
  - Use two axis-aligned cuts (c_i, c_j)
  - Plus one refinement cut to increase flexibility while keeping interpretability
- Reuse region-wise sums from FAST lookup tables
- Greedy search for cut config minimizing RSS


EBM - PREDICTION WITH PAIRWISE INTERACTIONS



- Each selected pair (x_i, x_j) is modeled by M boosted predictors trained on their residual interaction
- These are aggregated into a single bivariate function $f_{ij}(x_i, x_j)$
- The function is visualized as a 2D heatmap:
  - Axes: feature values of x_i and x_j
  - Color: contribution to the final prediction
  - Preserves human interpretability
- One heatmap is generated per selected pairwise interaction




EBM - FINAL MODEL STRUCTURE



- **Main effects:** One shape function $f_j(x_j)$ per feature (visualized as 1D plots)
- **Pairwise interactions:** Selected functions $f_{ij}(x_i, x_j)$ added for top K pairs (visualized as 2D heatmaps)
- **Prediction:** Additive sum of all univariate and selected bivariate contributions


$$\text{Prediction} = \underbrace{\text{Main}_1(\text{feat}_1)}_{\text{LAIR_ABS_body}} + \underbrace{\text{Main}_2(\text{feat}_2)}_{\text{query_url_click_count}} + \underbrace{\text{Main}_3(\text{feat}_3)}_{\text{stream_length_body}} + \ldots + \underbrace{\text{Main}_p(\text{feat}_p)}_{\text{covered_query_term_number_title}} + \underbrace{\text{Pair}_1(f_{ij})}_{\text{url_click_count vs. query_url_click_count}} + \underbrace{\text{Pair}_2(f_{ab})}_{\text{qualityscore2 vs. siterank}} + \underbrace{\text{Pair}_3(f_{cd})}_{\text{number_of_slash_in_url vs. stream_length_url}} + \ldots + \underbrace{\text{Pair}_K(f_{pq})}_{\text{pagerank vs. min_of_stream_length_normalized_term_frequency_whole_document}}$$

EBM *VS.* MODEL-BASED BOOSTING




- **Base learner**
  - **EBM**: bagged 2–4-leaf trees, *one feature* per tree
    $\Rightarrow$ step-function shape f_j "Lou et al." 2012
  - **MB-boost**: user chooses component-wise learner
    (linear term, P-spline, tree, random effect, . . .) "Bühlmann & Hothorn" 2007

EBM *VS.* MODEL-BASED BOOSTING




- **Base learner**
  - **EBM**: bagged 2–4-leaf trees, *one feature* per tree
    $\Rightarrow$ step-function shape f_j ▸ "Lou et al." 2012
  - **MB-boost**: user chooses component-wise learner
    (linear term, P-spline, tree, random effect, . . .) ▸ "Bühlmann & Hothorn" 2007
- **Iteration policy**
  - **EBM**: round-robin ($\forall j$) each boosting pass;
    tiny learning rate $\eta \approx 0.01$.
  - **MB-boost**: greedy; update the *single* component that yields the largest loss reduction.

EBM *VS.* MODEL-BASED BOOSTING




- **Base learner**
  - **EBM**: bagged 2–4-leaf trees, *one feature* per tree
    $\Rightarrow$ step-function shape f_j "Lou et al." 2012
  - **MB-boost**: user chooses component-wise learner
    (linear term, P-spline, tree, random effect, ...) "Bühlmann & Hothorn" 2007
- **Iteration policy**
  - **EBM**: round-robin ($\forall j$) each boosting pass;
    tiny learning rate $\eta \approx 0.01$.
  - **MB-boost**: greedy; update the *single* component that yields the largest loss reduction.
- **Regularisation**
  - **EBM**: many iterations M (5–10k); early stopping via *internal* CV on out-of-bag samples; bagging further lowers variance.
  - **MB-boost**: shrinkage $\nu \in (0, 1]$; early stop by CV/AIC; component selection acts like an L_0/L_1 penalty $\rightarrow$ sparsity.

EBM *VS.* MODEL-BASED BOOSTING




- **Interactions**
  - **EBM**: FAST ranks and selects top-K interaction pairs, fitted as bivariate trees $\Rightarrow$ GA2M "Lou et al." 2013
  - **MB-boost**: interactions are modelled only when the user supplies dedicated interaction base learners; no automatic pairwise search

EBM *VS.* MODEL-BASED BOOSTING



- **Interactions**
  - **EBM**: FAST ranks and selects top-K interaction pairs, fitted as bivariate trees $\Rightarrow$ GA2M "Lou et al." 2013
  - **MB-boost**: interactions are modelled only when the user supplies dedicated interaction base learners; no automatic pairwise search
- **Interpretability**
  - **EBM**:
    - one 1-D step plot for each f_j
    - small number of 2-D heat-maps for selected f_{ij}
  - **MB-boost**: depends on selected learner: linear coefficients, smooth splines, random-effect curves, etc.

EBM *VS.* MODEL-BASED BOOSTING



- **Interactions**
  - **EBM**: FAST ranks and selects top-K interaction pairs, fitted as bivariate trees $\Rightarrow$ GA2M "Lou et al." 2013
  - **MB-boost**: interactions are modelled only when the user supplies dedicated interaction base learners; no automatic pairwise search
- **Interpretability**
  - **EBM**:
    - one 1-D step plot for each f_j
    - small number of 2-D heat-maps for selected f_{ij}
  - **MB-boost**: depends on selected learner: linear coefficients, smooth splines, random-effect curves, etc.
- **Take-away**
  - *EBM* provides fast, interpretable, and interaction-sparse models
  - *MB-boost* offers flexible stat modeling with built-in variable selection