



Interpretable Machine Learning

LIME Pitfalls



Learning goals

- Learn why LIME should be used with caution
- Possible pitfalls of LIME




LIME PITFALLS

- LIME is one of the most widely used methods for local interpretability
~> But several papers highlight important (practical) limitations
- Pitfalls arise at multiple levels, which will be discussed in detail:
 - **Sampling** – ignores feature dependencies, risks extrapolation
 - **Locality definition** – kernel width and distance metrics affect sensitivity
 - **Local vs. global features** – global signals may overshadow local ones
 - **Faithfulness** – trade-off between sparsity and local accuracy
 - **Hiding biases** – explanations can be manipulated to appear fair
 - **Robustness** – explanations vary for similar points
 - **Superpixels (images)** – instability due to segmentation method




PITFALL: SAMPLING

- **Pitfall:** Common sampling strategies for $\mathbf{z} \in \mathcal{Z}$ ignore feature dependencies
- **Implication:** Surrogate model may be trained on unrealistic points
 \rightsquigarrow Undermines the fidelity and validity of the explanation




PITFALL: SAMPLING

- **Pitfall:** Common sampling strategies for $\mathbf{z} \in \mathcal{Z}$ ignore feature dependencies
- **Implication:** Surrogate model may be trained on unrealistic points
~> Undermines the fidelity and validity of the explanation
- **Solution I:** Sample locally from the true data manifold \mathcal{X}
~> Challenging in high-dimensional or mixed-type data settings
- **Solution II:** Restrict sampling to training data near \mathbf{x}
~> Requires enough training data points near \mathbf{x}



LIME PITFALL: LOCALITY


- **Pitfall:** Difficult to define locality (= how samples are weighted locally)
- **Implication:** Local model and explanation quality depend heavily on this weighting, but no principled way exists to choose it
- **Default:** Use exponential kernel as proximity measure between \mathbf{x} and \mathbf{z} :
$$\phi_{\mathbf{x}}(\mathbf{z}) = \exp(-d(\mathbf{x}, \mathbf{z})^2 / \sigma^2)$$
 with distance measure d and kernel width σ



LIME PITFALL: LOCALITY


- **Pitfall:** Difficult to define locality (= how samples are weighted locally)
- **Implication:** Local model and explanation quality depend heavily on this weighting, but no principled way exists to choose it
- **Default:** Use exponential kernel as proximity measure between \mathbf{x} and \mathbf{z} :
$$\phi_{\mathbf{x}}(\mathbf{z}) = \exp(-d(\mathbf{x}, \mathbf{z})^2 / \sigma^2)$$
 with distance measure d and kernel width σ

Example: For 2 obs. (green points), fit local surrogate models (lines) using only x_1



Line colors: different kernel widths used for proximity weighting


Right: larger kernel widths affect lines more



LIME PITFALL: LOCALITY

► Kopper et al. 2019


- **Pitfall:** Choice of kernel width (σ) critically influences locality



LIME PITFALL: LOCALITY

► Kopper et al. 2019

- **Pitfall:** Choice of kernel width (σ) critically influences locality
- **Implication of edge cases:**
 - *Large* $\sigma \rightarrow$ overemphasize distant points, hurting locality
 - *Small* $\sigma \rightarrow$ risk of too few points, leading to unstable or noisy explanations




LIME PITFALL: LOCALITY

► Kopper et al. 2019

- **Pitfall:** Choice of kernel width (σ) critically influences locality
- **Implication of edge cases:**
 - *Large* $\sigma \rightarrow$ overemphasize distant points, hurting locality
 - *Small* $\sigma \rightarrow$ risk of too few points, leading to unstable or noisy explanations
- **Solution I:** Use Gower similarity directly as weights: $\pi(\mathbf{z}) = 1 - d_{\text{Gower}}(\mathbf{x}, \mathbf{z})$
 - ↪ No kernel width required, but distant points still receive (too high) weight
 - ↪ Explanation may reflect more global than local structure
 - ↪ Used in practical LIME implementations

► lime package




LIME PITFALL: LOCALITY

► Kopper et al. 2019

- **Pitfall:** Choice of kernel width (σ) critically influences locality
- **Implication of edge cases:**
 - *Large* $\sigma \rightarrow$ overemphasize distant points, hurting locality
 - *Small* $\sigma \rightarrow$ risk of too few points, leading to unstable or noisy explanations
- **Solution I:** Use Gower similarity directly as weights: $\pi(\mathbf{z}) = 1 - d_{\text{Gower}}(\mathbf{x}, \mathbf{z})$
 - ↪ No kernel width required, but distant points still receive (too high) weight
 - ↪ Explanation may reflect more global than local structure
 - ↪ Used in practical LIME implementations
- **Solution II:** s-LIME adaptively selects σ to balance fidelity and stability


► Gaudel et al. 2022



PITFALL: LOCAL VS. GLOBAL FEATURES

► Laugel et al. 2018


- **Pitfall:** Sampling from entire input space may hide influence of locally relevant features in favor of globally relevant ones, even for narrow kernels.
- **Feature types:**
 - *Global features* influence predictions broadly across whole input space \mathcal{X}
 - *Local features* affect predictions only in small subregions of \mathcal{X}



PITFALL: LOCAL VS. GLOBAL FEATURES

► Laugel et al. 2018


- **Pitfall:** Sampling from entire input space may hide influence of locally relevant features in favor of globally relevant ones, even for narrow kernels.
- **Feature types:**
 - *Global features* influence predictions broadly across whole input space \mathcal{X}
 - *Local features* affect predictions only in small subregions of \mathcal{X}
- **Implication:** LIME's surrogate may over-weight global features, producing explanations that miss critical local signals.



PITFALL: LOCAL VS. GLOBAL FEATURES

► Laugel et al. 2018

- **Pitfall:** Sampling from entire input space may hide influence of locally relevant features in favor of globally relevant ones, even for narrow kernels.
- **Feature types:**
 - *Global features* influence predictions broadly across whole input space \mathcal{X}
 - *Local features* affect predictions only in small subregions of \mathcal{X}
- **Implication:** LIME's surrogate may over-weight global features, producing explanations that miss critical local signals.
- **Example:** Decision trees
 - Features near the root impact many instances \rightarrow global
 - Features in lower nodes act locally




PITFALL: LOCAL VS. GLOBAL FEATURES


► Laugel et al. 2018




- **Problem:** Sampling around obs. to be explained \mathbf{x} may miss decision boundary
- **Solution (LS: Local Surrogate Method):**
 - Step 1: Find closest point to \mathbf{x} (red dot) from opposite class (black cross)
 - Step 2: Sample around that point to better capture boundary
 - Step 3: Train local surrogate using those samples
 \rightsquigarrow better approximates the local direction of the decision boundary



Step 1: Closest border detection



Step 2: Local sampling





Step 3: Model training

Example: \mathbf{x} (red point), closest point from other class (black cross)


- LIME: What does the model do around this point?
- LS: How does the model change when crossing the boundary near this point?

PITFALL: LOCAL VS. GLOBAL FEATURES – EXAMPLE


- Random forest (RF) classification on half-moons dataset
 - **Background color:** Classification of RF (prediction surface)
 - **Black/grey crosses:** training data
 - **Green dot:** Obs. to be explained; **Red dot:** nearest point from opposite class
 - **Grey curve:** RF's decision boundary; **Dotted lines:** LIME decision boundaries
 - **Red line:** Local surrogate (LS) method
- Laugel et al. 2018



PITFALL: LOCAL VS. GLOBAL FEATURES – EXAMPLE



- Random forest (RF) classification on half-moons dataset
- **Background color:** Classification of RF (prediction surface)
- **Black/grey crosses:** training data
- **Green dot:** Obs. to be explained; **Red dot:** nearest point from opposite class
- **Grey curve:** RF's decision boundary; **Dotted lines:** LIME decision boundaries
- **Red line:** Local surrogate (LS) method ► Laugel et al. 2018



Feature 0 is global; class always flips when moving left (red) to right (blue)

Feature 1 is local; class flips only near boundary when moving up/down

Observation: LIME decision boundaries (blue/green) fail to match the steep local boundary captured by LS (red)

PITFALL: FAITHFULNESS

- **Problem:** Trade-off between local fidelity vs. sparsity
- **Observation:**
 - Too simple model \rightsquigarrow low fidelity \rightsquigarrow unreliable explanations
 - Complex model \rightsquigarrow high fidelity \rightsquigarrow difficult to interpret surrogate



PITFALL: FAITHFULNESS

- **Problem:** Trade-off between local fidelity vs. sparsity
- **Observation:**
 - Too simple model \rightsquigarrow low fidelity \rightsquigarrow unreliable explanations
 - Complex model \rightsquigarrow high fidelity \rightsquigarrow difficult to interpret surrogate


- **Example: Credit data**

- Random forest prediction for \mathbf{x} : $\hat{f}(\mathbf{x}) = \hat{\mathbb{P}}(y = \text{bad} \mid \mathbf{x}) = 0.143$
- Sparse LM with 3 features (age, checking.account, duration):

$$\hat{g}_{lm}(\mathbf{x}) = \hat{\theta}_0 + \hat{\theta}_1 x_{age} + \hat{\theta}_2 x_{checking.account} + \hat{\theta}_3 x_{duration} = 0.283$$

- Generalized additive model (with all 9 features) is more complex:


$$\hat{g}_{gam}(\mathbf{x}) = \hat{\theta}_0 + f_1(x_{age}) + f_2(x_{checking.account}) + f_3(x_{duration}) + \dots = 0.148$$



PITFALL: HIDING BIASES

► Slack et al. 2020

- **Problem:** LIME samples out-of-distribution (OOD) points, making it exploitable
- **Risk:** Developers can adversarially hide bias in the original model



PITFALL: HIDING BIASES

► Slack et al. 2020

- **Problem:** LIME samples out-of-distribution (OOD) points, making it exploitable
- **Risk:** Developers can adversarially hide bias in the original model
- **Attack** with adversarial model:
 - ❶ Train a detector to distinguish in-distribution vs. OOD points
 - ❷ Use **biased model** for in-distribution inputs (i.e., true predictions)
 - ❸ Use **unbiased model** for OOD samples to produce LIME explanations

~> LIME explanations rely on unbiased model \Rightarrow hides bias in original model





Image Source: ► Vres, Sikojja (2021)


PITFALL: HIDING BIASES

► Slack et al. 2020

Key insight: LIME can be fooled if explanations rely on model behavior outside the true data manifold.

Example: Credit approval



- Biased model uses features correlated with gender (parental leave duration)
 ~> used to make biased/unfair predictions
- Unbiased model uses only features unrelated to gender for fairness
 ~> used to produce explanations based on unbiased predictions to hide bias
- LIME's extrapolated samples trigger the unbiased model
 ⇒ explanation appears fair, but original predictions are biased




PITFALL: ROBUSTNESS

► Alvarez-Melis, D., & Jaakkola, T. 2018

- **Problem:** Instability of LIME explanations
- **Observation:** Explanations of two very close points could vary greatly
 \rightsquigarrow Variability driven by the stochastic sampling of \mathbf{z} for each explanation
- **Example:**



Linear task (logistic regression).
LIME returns similar coefficients for similar points.




Nonlinear task (random forest).
LIME returns different coefficients for similar points.

PITFALL: DEFINITION OF SUPERPIXELS

► Achanta et al. 2012

- **Problem:** LIME relies on superpixels (but their definition differ) for image data
- **Observation:** Definition of superpixel differ, influencing their size, shape, and alignment



PITFALL: DEFINITION OF SUPERPIXELS

► Achanta et al. 2012

- **Problem:** LIME relies on superpixels (but their definition differ) for image data
- **Observation:** Definition of superpixel differ, influencing their size, shape, and alignment
- **Implication:** Specification of superpixel has a large influence on LIME explanations
- **Attack:** Change superpixels as part of an adversarial attack \rightsquigarrow changed explanation

