



Interpretable Machine Learning

Permutation IMPortance (PIMP)





Learning goals

- Understand PIMP and its motivation
- Address multiple testing in feature importance

Interpretable Machine Learning

Feature Importances 1

Permutation IMPortance (PIMP)




Learning goals

- Understand PIMP and its motivation
- Address multiple testing in feature importance

TESTING IMPORTANCE (PIMP)

► Altmann et al. (2010)


- PIMP was originally introduced for random forest's built-in PFI scores



TESTING IMPORTANCE (PIMP)


► ALTMANN_2010

- PIMP was originally introduced for random forest's built-in PFI scores




TESTING IMPORTANCE (PIMP) ► Altmann et al. (2010)

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
~> Accounts for spurious importance due to randomness




TESTING IMPORTANCE (PIMP) ► ALTMANN_2010

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
~> Accounts for spurious importance due to randomness




TESTING IMPORTANCE (PIMP) ► Altmann et al. (2010)

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
 \rightsquigarrow Accounts for spurious importance due to randomness
- Null hypothesis H_0 : Feature X_j is conditionally independent of y (unimportant)




TESTING IMPORTANCE (PIMP) ► ALTMANN_2010

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
 \rightsquigarrow Accounts for spurious importance due to randomness
- Null hypothesis H_0 : Feature X_j is conditionally indep. of y (unimportant)




TESTING IMPORTANCE (PIMP) ▶ Altmann et al. (2010)

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
~> Accounts for spurious importance due to randomness
- Null hypothesis H_0 : Feature X_j is conditionally independent of y (unimportant)
- Approximate null distribution of PFI scores under H_0 by repeated permutations:
Permute $y \rightarrow$ retrain model \rightarrow recompute $\widehat{\text{PFI}}_j$ scores for all $j \rightarrow$ repeat B times
 \Rightarrow Permuting y breaks relationship to all features (PFI scores reflect noise only)




TESTING IMPORTANCE (PIMP) ▶ ALTMANN_2010

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
~> Accounts for spurious importance due to randomness
- Null hypothesis H_0 : Feature X_j is conditionally indep. of y (unimportant)
- Approximate null distrib. of PFI scores under H_0 by repeated permuts:
Permute $y \rightarrow$ retrain \rightarrow recompute $\widehat{\text{PFI}}_j$ scores for all $j \rightarrow$ repeat B times
 \Rightarrow Permuting y breaks relationship to all features (PFI scores reflect noise only)




TESTING IMPORTANCE (PIMP) ► Altmann et al. (2010)

- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
~> Accounts for spurious importance due to randomness
- Null hypothesis H_0 : Feature X_j is conditionally independent of y (unimportant)
- Approximate null distribution of PFI scores under H_0 by repeated permutations:
Permute $y \rightarrow$ retrain model \rightarrow recompute $\widehat{\text{PFI}}_j$ scores for all $j \rightarrow$ repeat B times
 \Rightarrow Permuting y breaks relationship to all features (PFI scores reflect noise only)
- Assess the significance of PFI scores via tail probability under H_0
 \Rightarrow Use this as a new feature importance score, adjusting for random chance



TESTING IMPORTANCE (PIMP) ► ALTMANN_2010


- PIMP was originally introduced for random forest's built-in PFI scores
- PIMP idea: Test if an observed $\widehat{\text{PFI}}_j^{\text{obs}}$ score is *significantly* greater than expected under the null hypothesis of X_j being not important
~> Accounts for spurious importance due to randomness
- Null hypothesis H_0 : Feature X_j is conditionally indep. of y (unimportant)
- Approximate null distrib. of PFI scores under H_0 by repeated permuts:
Permute $y \rightarrow$ retrain \rightarrow recompute $\widehat{\text{PFI}}_j$ scores for all $j \rightarrow$ repeat B times
 \Rightarrow Permuting y breaks relationship to all features (PFI scores reflect noise only)
- Assess the significance of PFI scores via tail probability under H_0
 \Rightarrow Use this as a new feat. importance score, adjusting for random chance



PIMP ALGORITHM

❶ For $b \in \{1, \dots, B\}$:


- Permute response vector \mathbf{y} , denote permuted target as $\mathbf{y}^{(b)}$
- Retrain model on data $(\mathbf{X}, \mathbf{y}^{(b)})$ with permuted target
- Compute feature importance $\widehat{\text{PFI}}_j^{(b)}$ for each feature j (under H_0)



PIMP ALGORITHM


❶ For $b \in \{1, \dots, B\}$:

- Permute response vector \mathbf{y} , denote permuted target as $\mathbf{y}^{(b)}$
- Retrain model on data $(\mathbf{X}, \mathbf{y}^{(b)})$ with permuted target
- Compute feature importance $\widehat{\text{PFI}}_j^{(b)}$ for each feature j (under H_0)




PIMP ALGORITHM

- ❶ For $b \in \{1, \dots, B\}$:
 - Permute response vector \mathbf{y} , denote permuted target as $\mathbf{y}^{(b)}$
 - Retrain model on data $(\mathbf{X}, \mathbf{y}^{(b)})$ with permuted target
 - Compute feature importance $\widehat{\text{PFI}}_j^{(b)}$ for each feature j (under H_0)
- ❷ Train model on original data (\mathbf{X}, \mathbf{y}) with unpermuted target



PIMP ALGORITHM

- ❶ For $b \in \{1, \dots, B\}$:
 - Permute response vector \mathbf{y} , denote permuted target as $\mathbf{y}^{(b)}$
 - Retrain model on data $(\mathbf{X}, \mathbf{y}^{(b)})$ with permuted target
 - Compute feature importance $\widehat{\text{PFI}}_j^{(b)}$ for each feature j (under H_0)
- ❷ Train model on original data (\mathbf{X}, \mathbf{y}) with unpermuted target




PIMP ALGORITHM

- 1 For $b \in \{1, \dots, B\}$:
 - Permute response vector \mathbf{y} , denote permuted target as $\mathbf{y}^{(b)}$
 - Retrain model on data $(\mathbf{X}, \mathbf{y}^{(b)})$ with permuted target
 - Compute feature importance $\widehat{\text{PFI}}_j^{(b)}$ for each feature j (under H_0)
- 2 Train model on original data (\mathbf{X}, \mathbf{y}) with unpermuted target
- 3 For each feature $j \in \{1, \dots, p\}$:
 - Compute $\widehat{\text{PFI}}_j^{\text{obs}}$ for the model without permutation of y (under H_1)
 - Fit probability distribution to all PFI scores $\{\widehat{\text{PFI}}_j^{(b)}\}_{b=1}^B$ (under H_0)
e.g., by assuming Gaussian/lognormal/gamma distribution (parametric)
 - Compute p-value: Probability that null importance exceeds observed:
 - parametric by taking tail probability of assumed distribution

$$\mathbb{P}(\widehat{\text{PFI}}_j^{(m)} \geq \widehat{\text{PFI}}_j^{\text{obs}})$$

- non-parametric by computing empirical tail probability:

$$p_j := \frac{1}{B} \sum_{b=1}^B \mathbb{I}[\widehat{\text{PFI}}_j^{(b)} \geq \widehat{\text{PFI}}_j^{\text{obs}}]$$




PIMP ALGORITHM

- 1 For $b \in \{1, \dots, B\}$:
 - Permute response vector \mathbf{y} , denote permuted target as $\mathbf{y}^{(b)}$
 - Retrain model on data $(\mathbf{X}, \mathbf{y}^{(b)})$ with permuted target
 - Compute feature importance $\widehat{\text{PFI}}_j^{(b)}$ for each feature j (under H_0)
- 2 Train model on original data (\mathbf{X}, \mathbf{y}) with unpermuted target
- 3 For each feature $j \in \{1, \dots, p\}$:
 - Compute $\widehat{\text{PFI}}_j^{\text{obs}}$ for the model without permutation of y (under H_1)
 - Fit probability distribution to all PFI scores $\{\widehat{\text{PFI}}_j^{(b)}\}_{b=1}^B$ (under H_0)
e.g., by assuming Gaussian/lognormal/gamma distrib (parametric)
 - Compute p-value: Prob. that null importance exceeds observed:
 - parametric by taking tail probability of assumed distribution

$$\mathbb{P}(\widehat{\text{PFI}}_j^{(m)} \geq \widehat{\text{PFI}}_j^{\text{obs}})$$

- non-parametric by computing empirical tail probability:


$$p_j := \frac{1}{B} \sum_{b=1}^B \mathbb{I}[\widehat{\text{PFI}}_j^{(b)} \geq \widehat{\text{PFI}}_j^{\text{obs}}]$$




PIMP FOR EXTRAPOLATION EXAMPLE

Recall: Let $y = x_3 + \epsilon_y$, with $\epsilon_y \sim \mathcal{N}(0, 0.1)$.

- $x_1 := \epsilon_1$, $x_2 := x_1 + \epsilon_2$ are highly correlated ($\epsilon_1 \sim \mathcal{N}(0, 1)$, $\epsilon_2 \sim \mathcal{N}(0, 0.01)$)
- $x_3 := \epsilon_3$, $x_4 := \epsilon_4$, with $\epsilon_3, \epsilon_4 \sim \mathcal{N}(0, 1)$ and all noise terms ϵ_j are independent
- Fitting a linear model yields $\hat{f}(\mathbf{x}) \approx 0.3x_1 - 0.3x_2 + x_3$




- Histograms: H_0 distribution of PFI scores after permuting y (1000 repetitions)
- Red: Observed PFI score (under H_1) \rightsquigarrow compare against H_0 distribution
- Recall: PFI for x_1, x_2, x_3 is nonzero suggesting they are important (red lines)
- PIMP considers x_1, x_2 not significantly relevant (p-value > 0.05)




PIMP FOR EXTRAPOLATION EXAMPLE

Recall: Let $y = x_3 + \epsilon_y$, with $\epsilon_y \sim \mathcal{N}(0, 0.1)$.

- $x_1 := \epsilon_1$, $x_2 := x_1 + \epsilon_2$; highly correlated ($\epsilon_1 \sim \mathcal{N}(0, 1)$, $\epsilon_2 \sim \mathcal{N}(0, 0.01)$)
- $x_3 := \epsilon_3$, $x_4 := \epsilon_4$, with $\epsilon_3, \epsilon_4 \sim \mathcal{N}(0, 1)$; all noise terms ϵ_j are indep.
- Fitting a linear model yields $\hat{f}(\mathbf{x}) \approx 0.3x_1 - 0.3x_2 + x_3$




- Histograms: H_0 distrib. of PFI scores after permuting y (1000 repetitions)
- Red: Observed PFI score (under H_1) \rightsquigarrow compare against H_0 distribution
- Recall: PFI for x_1, x_2, x_3 is non-0 suggesting they are important (red lines)
- PIMP considers x_1, x_2 not significantly relevant (p-value > 0.05)



DIGRESSION: MULTIPLE TESTING

► Romano et al. (2010)

- When should we reject H_0 for a given feature?
- PIMP conducts one hypothesis test per feature \Rightarrow **multiple testing problem**
- With many tests, rejections of true H_0 just by chance (type-I errors) accumulate
- To account for this, control a suitable error rate, e.g., the **family-wise error rate**
FWE: probability of making at least one type-I error across all tests
- A classical method is the **Bonferroni correction**:
reject H_0 if p-value $< \alpha/m$ where m is the number of tests



DIGRESSION: MULTIPLE TESTING

► ROMANO_2010

- When should we reject H_0 for a given feature?
- PIMP conducts one hypothesis test per feature
 \Rightarrow **multiple testing problem**
- With many tests, rejections of true H_0 just by chance (type-I errors) accumulate
- To account for this, control a suitable error rate, e.g., the **family-wise error rate**
FWE: probability of making at least one type-I error across all tests
- A classical method is the **Bonferroni correction**:
reject H_0 if p-value $< \alpha/m$ where m is the number of tests

