



Interpretable Machine Learning

Shapley Values for Local Explanations




Learning goals

- See model predictions as a cooperative game
- Transfer the Shapley value concept from game theory to machine learning




Interpretable Machine Learning

Shapley Shapley Values for Local Explanations





Learning goals

- See model predictions as a cooperative game
- Transfer the Shapley value concept from game theory to machine learning





FROM GAME THEORY TO MACHINE LEARNING

- Model prediction depends on feature interactions for a specific observation
- Goal:** Decompose prediction into **individual feature contributions**
- Idea:** Treat features as players jointly producing a prediction
- How to fairly assign credit to features?
⇒ Shapley values



FROM GAME THEORY TO MACHINE LEARNING

- Model prediction depends on feature interactions for a specific observation
- Goal:** Decompose prediction into **individual feature contributions**
- Idea:** Treat features as players jointly producing a prediction
- How to fairly assign credit to features?
⇒ Shapley values




FROM GAME THEORY TO MACHINE LEARNING

- **Game:** Predict $\hat{f}(x_1, x_2, \dots, x_p)$ for a single observation \mathbf{x}
- **Players:** Features $x_j, j \in \{1, \dots, p\}$, cooperate to produce a prediction
- **Value function:** Defines payout of coalition $S \subseteq P$ for observation \mathbf{x} by

$$v(S) = \hat{f}_S(\mathbf{x}_S) - \hat{f}_\emptyset, \text{ where}$$

- $\hat{f}_S : \mathcal{X}_S \mapsto \mathcal{Y}$ is the PD function $\hat{f}_S(\mathbf{x}_S) := \int \hat{f}(\mathbf{x}_S, X_{-S}) d\mathbb{P}_{X_{-S}}$
 \rightsquigarrow "Removes" features in $-S$ by marginalizing, keeping \hat{f} fixed
- Mean prediction $\hat{f}_\emptyset := \mathbb{E}_{\mathbf{x}}(\hat{f}(\mathbf{x}))$ is subtracted to ensure $v(\emptyset) = 0$
- **Goal:** Distribute total payout $v(P) = \hat{f}(\mathbf{x}) - \hat{f}_\emptyset$ fairly among features




FROM GAME THEORY TO MACHINE LEARNING

- **Game:** Predict $\hat{f}(x_1, x_2, \dots, x_p)$ for a single observation \mathbf{x}
- **Players:** Features $x_j, j \in \{1, \dots, p\}$, cooperate to produce a prediction
- **Value function:** Defines payout of coalition $S \subseteq P$ for observation \mathbf{x} by

$$v(S) = \hat{f}_S(\mathbf{x}_S) - \hat{f}_\emptyset, \text{ where}$$

- $\hat{f}_S : \mathcal{X}_S \mapsto \mathcal{Y}$ is the PD function $\hat{f}_S(\mathbf{x}_S) := \int \hat{f}(\mathbf{x}_S, X_{-S}) d\mathbb{P}_{X_{-S}}$
 \rightsquigarrow "Removes" features in $-S$ by marginalizing, keeping \hat{f} fixed
- Mean prediction $\hat{f}_\emptyset := \mathbb{E}_{\mathbf{x}}(\hat{f}(\mathbf{x}))$ is subtracted to ensure $v(\emptyset) = 0$
- **Goal:** Distribute total payout $v(P) = \hat{f}(\mathbf{x}) - \hat{f}_\emptyset$ fairly among features





FROM GAME THEORY TO MACHINE LEARNING

- **Game:** Predict $\hat{f}(x_1, x_2, \dots, x_p)$ for a single observation \mathbf{x}
- **Players:** Features $x_j, j \in \{1, \dots, p\}$, cooperate to produce a prediction
- **Value function:** Defines payout of coalition $S \subseteq P$ for observation \mathbf{x} by

$$v(S) = \hat{f}_S(\mathbf{x}_S) - \hat{f}_\emptyset, \text{ where}$$

- $\hat{f}_S : \mathcal{X}_S \mapsto \mathcal{Y}$ is the PD function $\hat{f}_S(\mathbf{x}_S) := \int \hat{f}(\mathbf{x}_S, X_{-S}) d\mathbb{P}_{X_{-S}}$
 \rightsquigarrow "Removes" features in $-S$ by marginalizing, keeping \hat{f} fixed
- Mean prediction $\hat{f}_\emptyset := \mathbb{E}_{\mathbf{x}}(\hat{f}(\mathbf{x}))$ is subtracted to ensure $v(\emptyset) = 0$
- **Goal:** Distribute total payout $v(P) = \hat{f}(\mathbf{x}) - \hat{f}_\emptyset$ fairly among features
- **Marginal contribution of feature j joining coalition S** (\hat{f}_\emptyset cancels):

$$\Delta(j, S) = v(S \cup \{j\}) - v(S) = \hat{f}_{S \cup \{j\}}(\mathbf{x}_{S \cup \{j\}}) - \hat{f}_S(\mathbf{x}_S)$$
- **Example (3 features):** Feature contributions for joining order $x_1 \rightarrow x_2 \rightarrow x_3$
toward total payout $v(P) = \hat{f}(\mathbf{x}) - \hat{f}_\emptyset$, each step reflects a marginal contribution



FROM GAME THEORY TO MACHINE LEARNING



- **Game:** Predict $\hat{f}(x_1, x_2, \dots, x_p)$ for a single observation \mathbf{x}
- **Players:** Features $x_j, j \in \{1, \dots, p\}$, cooperate to produce a prediction
- **Value function:** Defines payout of coalition $S \subseteq P$ for observation \mathbf{x} by

$$v(S) = \hat{f}_S(\mathbf{x}_S) - \hat{f}_\emptyset, \text{ where}$$

- $\hat{f}_S : \mathcal{X}_S \mapsto \mathcal{Y}$ is the PD function $\hat{f}_S(\mathbf{x}_S) := \int \hat{f}(\mathbf{x}_S, X_{-S}) d\mathbb{P}_{X_{-S}}$
 \rightsquigarrow "Removes" features in $-S$ by marginalizing, keeping \hat{f} fixed
- Mean prediction $\hat{f}_\emptyset := \mathbb{E}_{\mathbf{x}}(\hat{f}(\mathbf{x}))$ is subtracted to ensure $v(\emptyset) = 0$
- **Goal:** Distribute total payout $v(P) = \hat{f}(\mathbf{x}) - \hat{f}_\emptyset$ fairly among features
- **Marginal contribution of feature j joining coalition S** (\hat{f}_\emptyset cancels):

$$\Delta(j, S) = v(S \cup \{j\}) - v(S) = \hat{f}_{S \cup \{j\}}(\mathbf{x}_{S \cup \{j\}}) - \hat{f}_S(\mathbf{x}_S)$$


- **Example (3 features):** Feature contributions for joining order $x_1 \rightarrow x_2 \rightarrow x_3$
toward total payout $v(P) = \hat{f}(\mathbf{x}) - \hat{f}_\emptyset$, each step reflects a marginal contribution



SHAPLEY VALUE - DEFINITION

► Shapley (1953)

► Strumbelj et al. (2014)



Order definition: Shapley value $\phi_j(\mathbf{x})$ quantifies contribution of x_j via

$$\phi_j(\mathbf{x}) = \frac{1}{|P|!} \sum_{\tau \in \Pi} \underbrace{\hat{f}_{S_j^\tau \cup \{j\}}(\mathbf{x}_{S_j^\tau \cup \{j\}}) - \hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})}_{\Delta(j, S_j^\tau) \text{ marginal contribution of feature } j}$$

- **Interpretation:** $\phi_j(\mathbf{x})$ quantifies how much feature x_j contributes to the difference between $\hat{f}(\mathbf{x})$ and the mean prediction \hat{f}_\emptyset
 \rightsquigarrow Marginal contributions and Shapley values can be negative
- **Exact computation of ϕ_j :** Using PD function $\hat{f}_S(\mathbf{x}_S) = \frac{1}{n} \sum_{i=1}^n \hat{f}(\mathbf{x}_S, \mathbf{x}_{-S}^{(i)})$ yields


$$\phi_j(\mathbf{x}) = \frac{1}{|P|!} \sum_{\tau \in \Pi} \frac{1}{n} \sum_{i=1}^n \hat{f}(\mathbf{x}_{S_j^\tau \cup \{j\}}, \mathbf{x}_{- \{S_j^\tau \cup \{j\}\}}^{(i)}) - \hat{f}(\mathbf{x}_{S_j^\tau}, \mathbf{x}_{-S_j^\tau}^{(i)})$$

- $\rightsquigarrow \hat{f}_S$ marginalizes over all features not in S using all observations $i = 1, \dots, n$
- \rightsquigarrow Exact computation requires $|P|! \cdot n$ marginal contribution terms

SHAPLEY VALUE - DEFINITION

► SHAPLEY_1953

► STRUMBELJ_2014



Order definition: Shapley value $\phi_j(\mathbf{x})$ quantifies contribution of x_j via

$$\phi_j(\mathbf{x}) = \frac{1}{|P|!} \sum_{\tau \in \Pi} \underbrace{\hat{f}_{S_j^\tau \cup \{j\}}(\mathbf{x}_{S_j^\tau \cup \{j\}}) - \hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})}_{\Delta(j, S_j^\tau) \text{ marginal contribution of feature } j}$$

- **Interpretation:** $\phi_j(\mathbf{x})$ quantifies how much feature x_j contributes to the difference between $\hat{f}(\mathbf{x})$ and the mean prediction \hat{f}_\emptyset
 \rightsquigarrow Marginal contributions and Shapley values can be negative
- **Exact computation of ϕ_j :** Using PD function $\hat{f}_S(\mathbf{x}_S) = \frac{1}{n} \sum_{i=1}^n \hat{f}(\mathbf{x}_S, \mathbf{x}_{-S}^{(i)})$ yields

$$\phi_j(\mathbf{x}) = \frac{1}{|P|!} \sum_{\tau \in \Pi} \frac{1}{n} \sum_{i=1}^n \hat{f}(\mathbf{x}_{S_j^\tau \cup \{j\}}, \mathbf{x}_{- \{S_j^\tau \cup \{j\}\}}^{(i)}) - \hat{f}(\mathbf{x}_{S_j^\tau}, \mathbf{x}_{-S_j^\tau}^{(i)})$$


- $\rightsquigarrow \hat{f}_S$ marginalizes over all features not in S using all obs. $i = 1, \dots, n$
- \rightsquigarrow Exact computation requires $|P|! \cdot n$ marginal contribution terms

ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**

For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

\rightsquigarrow Complexity grows factorially with feature count




ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**

For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

\rightsquigarrow Complexity grows factorially with feature count



ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**


For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

↪ Complexity grows factorially with feature count

- **Additional challenge: Estimating marginal predictions (PD functions)**

Each permutation τ defines a coalition S_j^τ needing its own estimate of $\hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})$

↪ With $|P|!$ permutations and n data points, the number of such estimates grows rapidly, making marginalization costly



ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**


For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

↪ Complexity grows factorially with feature count

- **Additional challenge: Estimating marginal predictions (PD funcs)**

Each permut. τ defines a coal. S_j^τ needing its own estimate of $\hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})$

↪ With $|P|!$ permutations and n data points, the number of such estimates grows rapidly, making marginalization costly



ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**

For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

↪ Complexity grows factorially with feature count


- **Additional challenge: Estimating marginal predictions (PD functions)**

Each permutation τ defines a coalition S_j^τ needing its own estimate of $\hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})$

↪ With $|P|!$ permutations and n data points, the number of such estimates grows rapidly, making marginalization costly

- **Solution: Sampling-based approximation**

Instead of computing $|P|! \cdot n$ terms, we approximate using M random samples of permutations τ and data points



ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**

For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

↪ Complexity grows factorially with feature count


- **Additional challenge: Estimating marginal predictions (PD funcs)**

Each permut. τ defines a coal. S_j^τ needing its own estimate of $\hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})$

↪ With $|P|!$ permutations and n data points, the number of such estimates grows rapidly, making marginalization costly

- **Solution: Sampling-based approximation**

Instead of computing $|P|! \cdot n$ terms, we approximate using M random samples of permutations τ and data points



ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**

For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

↪ Complexity grows factorially with feature count

- **Additional challenge: Estimating marginal predictions (PD functions)**

Each permutation τ defines a coalition S_j^τ needing its own estimate of $\hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})$

↪ With $|P|!$ permutations and n data points, the number of such estimates grows rapidly, making marginalization costly


- **Solution: Sampling-based approximation**

Instead of computing $|P|! \cdot n$ terms, we approximate using M random samples of permutations τ and data points

- **Tradeoff: Accuracy vs. Efficiency**

Larger M improves Shapley approximation

↪ Higher cost, but better fidelity to the exact value



ESTIMATION: A PRACTICAL PROBLEM

- **Exact computation is infeasible for many features:**

For $|P| = 10$, the number of permutations is $10! \approx 3.6$ million

↪ Complexity grows factorially with feature count

- **Additional challenge: Estimating marginal predictions (PD funcs)**

Each permut. τ defines a coal. S_j^τ needing its own estimate of $\hat{f}_{S_j^\tau}(\mathbf{x}_{S_j^\tau})$

↪ With $|P|!$ permutations and n data points, the number of such estimates grows rapidly, making marginalization costly


- **Solution: Sampling-based approximation**

Instead of computing $|P|! \cdot n$ terms, we approximate using M random samples of permutations τ and data points

- **Tradeoff: Accuracy vs. Efficiency**

Larger M improves Shapley approximation


↪ Higher cost, but better fidelity to the exact value



APPROXIMATION ALGORITHM ► Strumbelj et al. (2014)

Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations



APPROXIMATION ALGORITHM ► STRUMBELJ_2014

Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations




APPROXIMATION ALGORITHM

► Strumbelj et al. (2014)

Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:




APPROXIMATION ALGORITHM

► STRUMBELJ_2014

Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:



APPROXIMATION ALGORITHM


► Strumbelj et al. (2014)

Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:

- ❶ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices



APPROXIMATION ALGORITHM


► STRUMBELJ_2014

Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations


❶ For $m = 1, \dots, M$ do:

- ❶ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices



APPROXIMATION ALGORITHM

► Strumbelj et al. (2014)



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:

- ❶ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ❷ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ

APPROXIMATION ALGORITHM

► STRUMBELJ_2014



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:

- ❶ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ❷ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ

APPROXIMATION ALGORITHM

► Strumbelj et al. (2014)



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:

- ❶ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ❷ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ❸ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)

APPROXIMATION ALGORITHM

► STRUMBELJ_2014



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

❶ For $m = 1, \dots, M$ do:

- ❶ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ❷ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ❸ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)

APPROXIMATION ALGORITHM

► Strumbelj et al. (2014)



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

➊ For $m = 1, \dots, M$ do:

- ➋ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid observations by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:

APPROXIMATION ALGORITHM

► STRUMBELJ_2014




Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

➊ For $m = 1, \dots, M$ do:

- ➋ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid obs. by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:


APPROXIMATION ALGORITHM ► Strumbelj et al. (2014)



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :


- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations
- ❶ For $m = 1, \dots, M$ do:
 - ❶ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
 - ❷ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
 - ❸ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
 - ❹ Construct two hybrid observations by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:
 - $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 - \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

APPROXIMATION ALGORITHM ► STRUMBELJ_2014



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations
- ❶ For $m = 1, \dots, M$ do:
 - ❶ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
 - ❷ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
 - ❸ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
 - ❹ Construct two hybrid obs. by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:
 - $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 - \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$




Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

➊ For $m = 1, \dots, M$ do:

- ➋ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid observations by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:
 - $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$
 - $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$




Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

➊ For $m = 1, \dots, M$ do:

- ➋ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid obs. by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:
 - $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$
 - $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations


➊ For $m = 1, \dots, M$ do:

- ➋ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid observations by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:

- $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- ➏ Compute marginal contribution $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations


➊ For $m = 1, \dots, M$ do:

- ➋ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid obs. by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:

- $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- ➏ Compute marginal contribution $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

➊ For $m = 1, \dots, M$ do:


- ➋ Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid observations by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:

- $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

➏ Compute marginal contribution $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$

➐ Compute Shapley value $\phi_j = \frac{1}{M} \sum_{m=1}^M \Delta(j, S_m)$



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

➊ For $m = 1, \dots, M$ do:


- ➋ Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- ➌ Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- ➍ Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- ➎ Construct two hybrid obs. by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:

- $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

➏ Compute marginal contribution $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$

➐ Compute Shapley value $\phi_j = \frac{1}{M} \sum_{m=1}^M \Delta(j, S_m)$



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

1 For $m = 1, \dots, M$ do:

- 1 Sample random permutation $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- 2 Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- 3 Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- 4 Construct two hybrid observations by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:


- $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- 5 Compute marginal contribution $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$

- 2 Compute Shapley value $\phi_j = \frac{1}{M} \sum_{m=1}^M \Delta(j, S_m)$

\rightsquigarrow Over M iterations, the PD functions $\hat{f}_{S_m}(\mathbf{x}_{S_m})$ and $\hat{f}_{S_m \cup \{j\}}(\mathbf{x}_{S_m \cup \{j\}})$ are approximated by $\hat{f}(\mathbf{x}_{-j}^{(m)})$ and $\hat{f}(\mathbf{x}_{+j}^{(m)})$, where features not in the coalition (to be marginalized) are imputed with values from the random data points $\mathbf{z}^{(m)}$



Estimate Shapley value ϕ_j of observation \mathbf{x} for feature j :

- **Input:** \mathbf{x} obs. of interest, j feat. of interest, \hat{f} model, \mathcal{D} data, M iterations

1 For $m = 1, \dots, M$ do:

- 1 Sample random permut. $\tau = (\tau^{(1)}, \dots, \tau^{(p)}) \in \Pi$ of feature indices
- 2 Let coalition $S_m := S_j^\tau$ be the set of features preceding j in τ
- 3 Sample random data point $\mathbf{z}^{(m)} \in \mathcal{D}$ (so-called background data)
- 4 Construct two hybrid obs. by combining values from \mathbf{x} and $\mathbf{z}^{(m)}$:

- $\mathbf{x}_{+j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, x_j, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes $\mathbf{x}_{S_m \cup \{j\}}$ (features in $S_m \cup \{j\}$ from \mathbf{x}), rest from $\mathbf{z}^{(m)}$

- $\mathbf{x}_{-j}^{(m)} = (x_{\tau^{(1)}}, \dots, x_{\tau^{(|S_m|)}}, z_j^{(m)}, z_{\tau^{(|S_m|+2)}}, \dots, z_{\tau^{(p)}})$
 \rightsquigarrow includes \mathbf{x}_{S_m} (features in S_m excl. x_j from \mathbf{x}), rest from $\mathbf{z}^{(m)}$



- 5 Compute marginal contribution $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$

- 2 Compute Shapley value $\phi_j = \frac{1}{M} \sum_{m=1}^M \Delta(j, S_m)$

\rightsquigarrow Over M iterations, the PD functions $\hat{f}_{S_m}(\mathbf{x}_{S_m})$ and $\hat{f}_{S_m \cup \{j\}}(\mathbf{x}_{S_m \cup \{j\}})$ are approximated by $\hat{f}(\mathbf{x}_{-j}^{(m)})$ and $\hat{f}(\mathbf{x}_{+j}^{(m)})$, where features not in the coalition (to be marginalized) are imputed with vals from random data points $\mathbf{z}^{(m)}$

SHAPLEY VALUE APPROXIMATION - ILLUSTRATION

Definition





	Temperature	Humidity	Windspeed	Year
\mathbf{x}	10.66	56	11	2012
\mathbf{x}_{+j}	10.66	56	random : $z_{windspeed}^{(m)}$	2012
\mathbf{x}_{-j}	10.66	56	random : $z_{windspeed}^{(m)}$	random : $z_{year}^{(m)}$

j

SHAPLEY VALUE APPROX. - ILLUSTRATION

Definition



	Temperature	Humidity	Windspeed	Year
\mathbf{x}	10.66	56	11	2012
\mathbf{x}_{+j}	10.66	56	random : $z_{windspeed}^{(m)}$	2012
\mathbf{x}_{-j}	10.66	56	random : $z_{windspeed}^{(m)}$	random : $z_{year}^{(m)}$

j


SHAPLEY VALUE APPROXIMATION - ILLUSTRATION

Definition

Contribution of feature j
to coalition S_m

$$\phi_j(\mathbf{x}) = \frac{1}{M} \sum_{m=1}^M \underbrace{\left[\hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)}) \right]}_{:= \Delta(j, S_m)}$$

- $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$ is marginal contribution of feature j to coalition S_m
- Here: Feature *year* contributes +700 bike rentals if it joins coalition $S_m = \{\text{temp}, \text{hum}\}$



	Temperature	Humidity	Windspeed	Year	Count
\mathbf{x}	10.66	56	11	2012	
\mathbf{x}_{+j}	10.66	56	random : $z_{\text{windspeed}}^{(m)}$	2012	5600
\mathbf{x}_{-j}	10.66	56	random : $z_{\text{windspeed}}^{(m)}$	random : $z_{\text{year}}^{(m)}$	4900
	j			\hat{f}	$\Delta(j, S_m)$ marginal contribution


SHAPLEY VALUE APPROX. - ILLUSTRATION

Definition

Contribution of feature j
to coalition S_m

$$\phi_j(\mathbf{x}) = \frac{1}{M} \sum_{m=1}^M \underbrace{\left[\hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)}) \right]}_{:= \Delta(j, S_m)}$$

- $\Delta(j, S_m) = \hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)})$ is marginal contribution of feature j to coalition S_m
- Here: Feature *year* contributes +700 bike rentals if it joins coalition $S_m = \{\text{temp}, \text{hum}\}$




	Temperature	Humidity	Windspeed	Year	Count
\mathbf{x}	10.66	56	11	2012	
\mathbf{x}_{+j}	10.66	56	random : $z_{\text{windspeed}}^{(m)}$	2012	5600
\mathbf{x}_{-j}	10.66	56	random : $z_{\text{windspeed}}^{(m)}$	random : $z_{\text{year}}^{(m)}$	4900
	j			\hat{f}	$\Delta(j, S_m)$ marginal contribution

SHAPLEY VALUE APPROXIMATION - ILLUSTRATION


Definition

$$\phi_j(\mathbf{x}) = \frac{1}{M} \sum_{m=1}^M \left[\hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)}) \right]$$

average the contributions of feature j



- Compute marginal contribution of feature j towards the prediction across all randomly drawn feature coalitions S_1, \dots, S_m
- Average all M marginal contributions of feature j
- Shapley value ϕ_j is the payout of feature j , i.e., how much feature *year* contributed to the overall prediction in bicycle counts of a specific observation \mathbf{x}




SHAPLEY VALUE APPROX. - ILLUSTRATION


Definition

$$\phi_j(\mathbf{x}) = \frac{1}{M} \sum_{m=1}^M \left[\hat{f}(\mathbf{x}_{+j}^{(m)}) - \hat{f}(\mathbf{x}_{-j}^{(m)}) \right]$$


average the contributions of feature j



- Compute marginal contribution of feature j towards the prediction across all randomly drawn feature coalitions S_1, \dots, S_m
- Average all M marginal contributions of feature j
- Shapley value ϕ_j is the payout of feature j , i.e., how much feature *year* contributed to the overall prediction in bicycle counts of a specific obs. \mathbf{x}



REVISITED: AXIOMS FOR FAIR ATTRIBUTIONS



We adapt the classic Shapley axioms to the setting of model predictions:

- **Efficiency:** Sum of Shapley values adds up to the centered prediction:

$$\sum_{j=1}^p \phi_j(\mathbf{x}) = \hat{f}(\mathbf{x}) - \mathbb{E}_{\mathbf{x}}[\hat{f}(\mathbf{x})]$$

↪ All predictive contribution is fully distributed among features

- **Symmetry:** Identical contributors receive equal value:

$$\hat{f}_{S \cup \{j\}}(\mathbf{x}_{S \cup \{j\}}) = \hat{f}_{S \cup \{k\}}(\mathbf{x}_{S \cup \{k\}}) \quad \forall S \subseteq P \setminus \{j, k\} \Rightarrow \phi_j = \phi_k$$

↪ Interaction effects are shared equitably

- **Dummy (Null Player):** Irrelevant features receive zero attribution:

$$\hat{f}_{S \cup \{j\}}(\mathbf{x}_{S \cup \{j\}}) = \hat{f}_S(\mathbf{x}_S) \quad \forall S \subseteq P \Rightarrow \phi_j = 0$$


↪ Shapley value is zero for unused features (e.g., trees or LASSO)

- **Additivity:** Attributions are additive across models:

$$\phi_j(v_1 + v_2) = \phi_j(v_1) + \phi_j(v_2)$$

↪ Enables combining Shapley values for model ensembles

REVISITED: AXIOMS FOR FAIR ATTRIBUTIONS



We adapt the classic Shapley axioms to the setting of model predictions:

- **Efficiency:** Sum of Shapley values adds up to the centered prediction:

$$\sum_{j=1}^p \phi_j(\mathbf{x}) = \hat{f}(\mathbf{x}) - \mathbb{E}_{\mathbf{x}}[\hat{f}(\mathbf{x})]$$

↪ All predictive contribution is fully distributed among features

- **Symmetry:** Identical contributors receive equal value:

$$\hat{f}(\mathbf{x}) = \hat{f}(\mathbf{x}) \quad \forall S \subseteq P \setminus \{j, k\} \Rightarrow \phi_j = \phi_k$$

↪ Interaction effects are shared equitably

- **Dummy (Null Player):** Irrelevant features receive zero attribution:

$$\hat{f}(\mathbf{x}) = \hat{f}_S(\mathbf{x}_S) \quad \forall S \subseteq P \Rightarrow \phi_j = 0$$


↪ Shapley value is zero for unused features (e.g., trees or LASSO)

- **Additivity:** Attributions are additive across models:


$$\phi_j(v_1 + v_2) = \phi_j(v_1) + \phi_j(v_2)$$

↪ Enables combining Shapley values for model ensembles


BIKE SHARING DATASET




- Shapley decomposition for a single prediction in bike sharing dataset
- Model prediction: $\hat{f}(\mathbf{x}^{(200)}) = 4434.86$ vs. dataset average: $\mathbb{E}_{\mathbf{x}}[\hat{f}(\mathbf{x})] = 4507.67$
- Total feature attribution: $\sum_j \phi_j = -72.81$
 \rightsquigarrow Explain downward shift from mean prediction
- Temperature (with value 28.5°C) is the strongest positive contributor: +400
- Features `yr = 2011` and `days_since_2011 = 199` strongly reduce prediction
 \rightsquigarrow Model captures lower bike demand in 2011 compared to 2012



BIKE SHARING DATASET




- Shapley decomposition for a single prediction in bike sharing dataset
- Model pred.: $\hat{f}(\mathbf{x}^{(200)}) = 4434.86$ vs. dataset avg.: $\mathbb{E}_{\mathbf{x}}[\hat{f}(\mathbf{x})] = 4507.67$
- Total feature attribution: $\sum_j \phi_j = -72.81$
 \rightsquigarrow Explain downward shift from mean prediction
- Temperature (with value 28.5°C) – strongest positive contributor: +400
- `yr = 2011` and `days_since_2011 = 199` strongly reduce prediction
 \rightsquigarrow Model captures lower bike demand in 2011 compared to 2012



ADVANTAGES AND DISADVANTAGES

Advantages:

- **Strong theoretical foundation** from cooperative game theory
- **Fair attribution:** Prediction is additively distributed across features
~> Easy to interpret for users
- **Contrastive explanations:** Quantify each feature's role in deviating from the average prediction




Disadvantages:

- **Computational cost:** Exact computation scales factorially with feature count
~> Without sampling, all 2^p coalitions (or $p!$ permutations) must be evaluated
- **Issue with correlated features:** Shapley values may evaluate the model on feature combinations that do not occur in the real data

ADVANTAGES AND DISADVANTAGES

Advantages:

- **Strong theoretical foundation** from cooperative game theory
- **Fair attribution:** Prediction is additively distributed across features
~> Easy to interpret for users
- **Contrastive explanations:** Quantify each feature's role in deviating from the average prediction



Disadvantages:

- **Comput. cost:** Exact computation scales factorially with feature count
~> Without sampling, all 2^p coalitions (or $p!$ perms) must be evaluated
- **Issue with correlated features:** Shapley values may evaluate the model on feature combinations that do not occur in the real data