



Optimization in Machine Learning

Bayesian Optimization


Multicriteria Bayesian Optimization



Learning goals

- Multicriteria Optimization
- Taxonomy
- ParEGO, SMS-EGO, EHI

MULTICRITERIA BAYESIAN OPTIMIZATION



$$f : \mathcal{S} \rightarrow \mathbb{R}^m$$

$$\min_{\mathbf{x} \in \mathcal{S}} \quad f(\mathbf{x}) = (f_1(\mathbf{x}), \dots, f_m(\mathbf{x}))$$

- A configuration \mathbf{x} **dominates** (\prec) $\tilde{\mathbf{x}}$ if


$$\forall i \in \{1, \dots, m\} : \quad f_i(\mathbf{x}) \leq f_i(\tilde{\mathbf{x}})$$

$$\text{and } \exists j \in \{1, \dots, m\} : \quad f_j(\mathbf{x}) < f_j(\tilde{\mathbf{x}})$$

- Set of non-dominated solutions:

$$\mathcal{P} := \{\mathbf{x} \in \mathcal{S} \mid \nexists \tilde{\mathbf{x}} \in \mathcal{S} : \tilde{\mathbf{x}} \prec \mathbf{x}\}$$



- Pareto set \mathcal{P} , Pareto front $\mathcal{F} = f(\mathcal{P})$
- Goal: Find $\hat{\mathcal{P}}$ of non-dominated points that estimates the true Pareto set \mathcal{P}





A 3x3 grid with a blue path starting at the top-left cell (0,0) and ending at the bottom-right cell (2,2). The path consists of the following cells: (0,0), (0,1), (1,1), (1,2), and (2,2). The cells (0,2), (1,0), and (2,0) are empty. The cells (1,0) and (2,0) contain a black 'X'. The cells (0,1) and (1,1) contain a grey circle. The cell (2,1) contains a grey circle.



PAREGO



SMS-EGO





SMS-EGO

Individual models for each objective f_i

Single-objective optimization of aggregating acquisition function:
Calculate contribution of the confidence bound of candidate to the current front approximation

- Calculate LCB for each objective
- Measure contribution with regard to the hypervolume improvement
- For ε -dominated (\prec_ε) solutions, a penalty is added





SMS-EGO

Individual models for each objective f_i

Single-objective optimization of aggregating acquisition function:
Calculate contribution of the confidence bound of candidate to the current front approximation

- Calculate LCB for each objective
- Measure contribution with regard to the hypervolume improvement
- For ε -dominated (\prec_ε) solutions, a penalty is added





SMS-EGO

Individual models for each objective f_i

Single-objective optimization of aggregating acquisition function:
Calculate contribution of the confidence bound of candidate to the
current front approximation

- Calculate LCB for each objective
- Measure contribution with regard to the hypervolume improvement
- For ε -dominated (\prec_ε) solutions, a penalty is added



OUTLOOK

Many more options exist:

- Expected Hypervolume Improvement
- Multi-EGO
- Entropy based: PESMO, MESMO
- ...

