Optimization in Machine Learning

Bayesian Optimization
Noisy Bayesian Optimization



Learning goals

- Noisy surrogate modeling
- Noisy acquisition functions
- Final best point

NOISY EVALUATIONS

In many real-life applications, we cannot access the true function values $f(\boldsymbol{x})$ but only a **noisy** version thereof

$$f(\boldsymbol{x}) + \epsilon(\boldsymbol{x})$$

For the sake of simplicity, we assume $\epsilon(\boldsymbol{x}) \sim \mathcal{N}\left(0, \sigma_\epsilon^2\right)$ for now



NOISY EVALUATIONS



In many real-life applications, we cannot access the true function values $f(\boldsymbol{x})$ but only a **noisy** version thereof

$$f(\boldsymbol{x}) + \epsilon(\boldsymbol{x})$$

For the sake of simplicity, we assume $\epsilon(\boldsymbol{x}) \sim \mathcal{N}\left(0, \sigma_\epsilon^2\right)$ for now

Examples:

- HPO (due to non-deterministic learning algorithm and/or resampling technique)
- Oil drilling optimization (an oil sample is only an estimate)
- Robot gait optimization (velocity of a run of a robot is an estimate of true velocity)

NOISY EVALUATIONS



This raises the following problems:

- **Surrogate modeling:** So far we used an interpolating GP that is based on noise-free observations; as a consequence, the variance is modeled as 0
$$s^2(\boldsymbol{x}^{[i]}) = 0$$
for design points $(\boldsymbol{x}^{[i]}, y^{[i]}) \in \mathcal{D}^{[t]}$. This is problematic.
- **Acquisition functions:** Most acquisition functions are based on the best observed value $f_{\min}$ so far. If evaluations are noisy, we do not know this value (it is a random variable).
- **Final best point:** The design point evaluated best is not necessarily the true best point in design (overestimation).

SURROGATE MODEL

In case of noisy evaluations, a nugget-effect GP (GP regression) should be used instead of an interpolating GP.

The posterior predictive distribution for a new test point $\boldsymbol{x} \in \mathcal{S}$ under a GP assuming homoscedastic noise (σ_ϵ^2) is:



$$Y(\boldsymbol{x}) \mid \boldsymbol{x}, \mathcal{D}^{[t]} \sim \mathcal{N}\left(\hat{f}(\boldsymbol{x}), \hat{s}^2(\boldsymbol{x})\right)$$

with

$$\begin{aligned} \hat{f}(\boldsymbol{x}) &= k(\boldsymbol{x})^\top (\boldsymbol{K} + \sigma_\epsilon^2 \mathbf{I}_t)^{-1} \boldsymbol{y} \\ \hat{s}^2(\boldsymbol{x}) &= k(\boldsymbol{x}, \boldsymbol{x}) - k(\boldsymbol{x})^\top (\boldsymbol{K} + \sigma_\epsilon^2 \mathbf{I}_t)^{-1} k(\boldsymbol{x}) \end{aligned}$$

NOISY ACQUISITION FUNCTIONS: AEI



Augmented Expected Improvement (Huang et al. 2006)

$$a_{\mathrm{AEI}}(\boldsymbol{x}) = a_{\mathrm{EI}_{f_{\min *}}}(\boldsymbol{x})\left(1 - \frac{\sigma_\epsilon}{\sqrt{\hat{s}^2(\boldsymbol{x}) + \sigma_\epsilon^2}}\right).$$

Here, $a_{\mathrm{EI}_{f_{\min *}}}$ denotes the **Expected Improvement with Plugin**.
It uses the **effective best solution** as a plugin for the (unknown) best observed value $f_{\min}$

$$f_{\min *} = \min_{\boldsymbol{x} \in \{\boldsymbol{x}^{[1]}, \ldots, \boldsymbol{x}^{[t]}\}} \hat{f}(\boldsymbol{x}) + c\hat{s}(\boldsymbol{x}),$$

where $c > 0$ is a constant that controls the risk aversion.

σ_ϵ^2 is the nugget-effect as estimated by the GP regression.

REINTERPOLATION

Clean noise from the model and then apply a general acquisition function (EI, PI, LCB, ...)

The RP suggests to build **two models**: a nugget-effect GP (regression model; left) and then, on the predictions from the first model (grey), an interpolating GP (right)





REINTERPOLATION

Algorithm Reinterpolation Procedure

1: Build a nugget-effect GP model based on noisy evaluations
2: Compute predictions for all points in the design $\hat{f}(\boldsymbol{x}^{[1]}), \ldots, \hat{f}(\boldsymbol{x}^{[t]})$
3: Train an interpolating GP on $\left\{ \left(\boldsymbol{x}^{[1]}, \hat{f}(\boldsymbol{x}^{[1]}) \right), \ldots, \left(\boldsymbol{x}^{[t]}, \hat{f}(\boldsymbol{x}^{[t]}) \right) \right\}$
4: Based on the interpolating model, obtain a new candidate using a noise-free acquisition function





IDENTIFICATION OF FINAL BEST POINT

Another problem is the identification of a final best point:

- Assume that all evaluations are noisy
- The probability is high that **by chance**
  - bad points get overrated
  - good points get overlooked