# Optimization in Machine Learning

## First order methods
## Adam and friends




**Learning goals**

- Adaptive step sizes
- AdaGrad
- RMSProp
- Adam

# ADAPTIVE STEP SIZES

- Step size is probably the most important control parameter
- Has strong influence on performance
- Natural to use different step size for each input individually and automatically adapt them



# ADAGRAD

- AdaGrad adapts step sizes by scaling them inversely proportional to square root of the sum of the past squared derivatives
  - Inputs with large derivatives get smaller step sizes
  - Inputs with small derivatives get larger step sizes
- Accumulation of squared gradients can result in premature small step sizes (Goodfellow et al., 2016)



**Algorithm** AdaGrad

**require** Global step size $\alpha$
**require** Initial parameter $\boldsymbol{\theta}$
**require** Small constant $\beta$, perhaps $10^{-7}$, for numerical stability
**Initialize** gradient accumulation variable $\mathbf{r} = \mathbf{0}$
**while** stopping criterion not met **do**
    Sample minibatch of $m$ examples from the training set $\{\tilde{\boldsymbol{x}}^{(1)}, \ldots, \tilde{\boldsymbol{x}}^{(m)}\}$
    Compute gradient estimate: $\hat{\mathbf{g}} \leftarrow \frac{1}{m} \nabla_{\boldsymbol{\theta}} \sum_i L\left(y^{(i)}, f\left(\tilde{\boldsymbol{x}}^{(i)} \mid \boldsymbol{\theta}\right)\right)$
    Accumulate squared gradient $\mathbf{r} \leftarrow \mathbf{r} + \hat{\mathbf{g}} \odot \hat{\mathbf{g}}$ where $\odot$: element-wise product
    Compute update: $\nabla\boldsymbol{\theta} = -\frac{\alpha}{\beta + \sqrt{\mathbf{r}}} \odot \hat{\mathbf{g}}$
    Apply update: $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \nabla\boldsymbol{\theta}$
**end while**

# RMSPROP

- Modification of AdaGrad
- Resolves AdaGrad's radically diminishing step sizes
- Gradient accumulation is replaced by exponentially weighted moving average
- Theoretically, leads to performance gains in non-convex scenarios
- Empirically, RMSProp is a very effective optimization algorithm. Particularly, it is employed routinely by DL practitioners

**Algorithm** RMSProp

**require** Global step size $\alpha$ and decay rate $\rho \in [0, 1)$
**require** Initial parameter $\boldsymbol{\theta}$
**require** Small constant $\beta$, perhaps $10^{-6}$, for numerical stability
Initialize gradient accumulation variable $\mathbf{r} = \mathbf{0}$
**while** stopping criterion not met **do**
    Sample minibatch of $m$ examples from the training set $\{\tilde{\boldsymbol{x}}^{(1)}, \ldots, \tilde{\boldsymbol{x}}^{(m)}\}$
    Compute gradient estimate: $\hat{\mathbf{g}} \leftarrow \frac{1}{m} \nabla_\theta \sum_i L\left(y^{(i)}, f\left(\tilde{\boldsymbol{x}}^{(i)} \mid \boldsymbol{\theta}\right)\right)$
    Accumulate squared gradient $\mathbf{r} \leftarrow \rho \mathbf{r} + (1 - \rho) \hat{\mathbf{g}} \odot \hat{\mathbf{g}}$
    Compute update: $\nabla \boldsymbol{\theta} = -\frac{\alpha}{\beta + \sqrt{\mathbf{r}}} \odot \hat{\mathbf{g}}$
    Apply update: $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \nabla \boldsymbol{\theta}$
**end while**

# ADAM



- Adaptive Moment Estimation also has adaptive step sizes
- Uses the 1st and 2nd moments of gradients
  - Keeps an exponentially decaying average of past gradients (1st moment)
  - Like RMSProp, stores an exp-decaying avg of past squared gradients (2nd moment)
  - Can be seen as combo of RMSProp + momentum

# ADAM

**Algorithm** Adam

**require** Global step size $\alpha$ (suggested default: 0.001)
**require** Exponential decay rates for moment estimates, $\rho_1$ and $\rho_2$ in $[0, 1)$ (suggested defaults: 0.9 and 0.999 respectively)
**require** Small constant $\beta$ (suggested default $10^{-8}$)
**require** Initial parameters $\boldsymbol{\theta}$
Initialize time step $t = 0$
Initialize 1st and 2nd moment variables $\mathbf{s}^{[0]} = 0, \mathbf{r}^{[0]} = 0$
**while** stopping criterion not met **do**
  $t \leftarrow t + 1$
  Sample a minibatch of $m$ examples from the training set $\{\tilde{x}^{(1)}, \ldots, \tilde{x}^{(m)}\}$
  Compute gradient estimate: $\hat{\mathbf{g}}^{[t]} \leftarrow \frac{1}{m} \nabla_{\boldsymbol{\theta}} \sum_i L\left(y^{(i)}, f\left(\tilde{\boldsymbol{x}}^{(i)} \mid \boldsymbol{\theta}\right)\right)$
  Update biased first moment estimate: $\mathbf{s}^{[t]} \leftarrow \rho_1 \mathbf{s}^{[t-1]} + (1 - \rho_1)\hat{\mathbf{g}}^{[t]}$
  Update biased second moment estimate: $\mathbf{r}^{[t]} \leftarrow \rho_2 \mathbf{r}^{[t-1]} + (1 - \rho_2)\hat{\mathbf{g}}^{[t]} \odot \hat{\mathbf{g}}^{[t]}$
  Correct bias in first moment: $\hat{\mathbf{s}} \leftarrow \frac{\mathbf{s}^{[t]}}{1-\rho_1^t}$
  Correct bias in second moment: $\hat{\mathbf{r}} \leftarrow \frac{\mathbf{r}^{[t]}}{1-\rho_2^t}$
  Compute update: $\nabla\boldsymbol{\theta} = -\alpha \frac{\hat{\mathbf{s}}}{\sqrt{\hat{\mathbf{r}}}+\beta}$
  Apply update: $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \nabla\boldsymbol{\theta}$
**end while**

# ADAM: BIAS IN MOMENT ESTIMATES

- Initializes moment variables $\mathbf{s}$ and $\mathbf{r}$ with zero $\Rightarrow$ Bias towards zero

$$\mathbb{E}[\mathbf{s}^{[t]}] \neq \mathbb{E}[\hat{\mathbf{g}}^{[t]}] \quad \text{and} \quad \mathbb{E}[\mathbf{r}^{[t]}] \neq \mathbb{E}[\hat{\mathbf{g}}^{[t]} \odot \hat{\mathbf{g}}^{[t]}]$$

  ($\mathbb{E}$ calculated over minibatches)

- Indeed: Unrolling $\mathbf{s}^{[t]}$ yields

$$\begin{aligned}
\mathbf{s}^{[0]} &= 0 \\
\mathbf{s}^{[1]} &= \rho_1 \mathbf{s}^{[0]} + (1-\rho_1)\hat{\mathbf{g}}^{[1]} = (1-\rho_1)\hat{\mathbf{g}}^{[1]} \\
\mathbf{s}^{[2]} &= \rho_1 \mathbf{s}^{[1]} + (1-\rho_1)\hat{\mathbf{g}}^{[2]} = \rho_1(1-\rho_1)\hat{\mathbf{g}}^{[1]} + (1-\rho_1)\hat{\mathbf{g}}^{[2]} \\
\mathbf{s}^{[3]} &= \rho_1 \mathbf{s}^{[2]} + (1-\rho_1)\hat{\mathbf{g}}^{[3]} = \rho_1^2(1-\rho_1)\hat{\mathbf{g}}^{[1]} + \rho_1(1-\rho_1)\hat{\mathbf{g}}^{[2]} + (1-\rho_1)\hat{\mathbf{g}}^{[3]}
\end{aligned}$$

- Therefore: $\mathbf{s}^{[t]} = (1-\rho_1)\sum_{i=1}^{t} \rho_1^{t-i}\hat{\mathbf{g}}^{[i]}$
- **Note:** Contributions of past $\hat{\mathbf{g}}^{[i]}$ decreases rapidly

# ADAM: BIAS CORRECTION

- We continue with

$$\begin{aligned}\mathbb{E}[\mathbf{s}^{[t]}] &= \mathbb{E}[(1-\rho_1)\sum_{i=1}^{t}\rho_1^{t-i}\hat{\mathbf{g}}^{[i]}] \\ &= \mathbb{E}[\hat{\mathbf{g}}^{[t]}](1-\rho_1)\sum_{i=1}^{t}\rho_1^{t-i} + \zeta \\ &= \mathbb{E}[\hat{\mathbf{g}}^{[t]}](1-\rho_1^t) + \zeta,\end{aligned}$$

  where we approximated $\hat{\mathbf{g}}^{[i]}$ by $\hat{\mathbf{g}}^{[t]}$. The resulting error is put in $\zeta$ and be kept small due to the exponential weights of past gradients

- Therefore: $\mathbf{s}^{[t]}$ is a biased estimator of $\hat{\mathbf{g}}^{[t]}$
- But bias vanishes for $t \to \infty$ ($\rho_1^t \to 0$)
- Ignoring $\zeta$, we correct for the bias by $\hat{\mathbf{s}}^{[t]} = \frac{\mathbf{s}^{[t]}}{(1-\rho_1^t)}$
- Analogously: $\hat{\mathbf{r}}^{[t]} = \frac{\mathbf{r}^{[t]}}{(1-\rho_2^t)}$

# COMPARISON OF OPTIMIZERS: ANIMATION




Click for source




Click for source

**Comparison** of SGD optimizers near saddle point
**Left:** After start. **Right:** Later
All methods accelerate compared to vanilla SGD
Best is RMSProp, then AdaGrad (Adam is missing here)

Credits: Dettmers (2015) and Radford

# COMPARISON ON QUADRATIC FORM




SGD vs SGD with Momentum vs Adam on a quadratic form