Optimization in Machine Learning

Evolutionary Algorithms
ES / Numerical Encodings



Learning goals

- Recombination
- Mutation
- A few simple examples

RECOMBINATION FOR NUMERIC



Options for recombination of two individuals $\boldsymbol{x}, \tilde{\boldsymbol{x}} \in \mathbb{R}^d$:

- **Uniform crossover**: Choose gene j of parent 1 with probability p and of parent 2 with probability $1 - p$
- **Intermediate recombination**: Offspring is created from mean of two parents: $\frac{1}{2}(\boldsymbol{x} + \tilde{\boldsymbol{x}})$
- **Simulated Binary Crossover (SBX)**: generate **two offspring**

$$\bar{\boldsymbol{x}} \pm \frac{1}{2}\beta(\tilde{\boldsymbol{x}} - \boldsymbol{x}),\ \bar{\boldsymbol{x}} = \frac{1}{2}(\boldsymbol{x} + \tilde{\boldsymbol{x}}),\ \beta \in [0, 1] \text{ uniformly at random}$$





MUTATION FOR NUMERIC

Mutation: Individuals get modified

Example for $\boldsymbol{x} \in \mathbb{R}^d$:

- **Uniform mutation:** Select random gene x_j and replace it by uniformly distributed value (within feasible range).
- **Gauss mutation:** $\boldsymbol{x} \pm \mathcal{N}(0, \sigma \mathbf{I})$
- **Polynomial mutation:** Use a different distribution instead of normal distribution



Source: K. Deb, D. Deb. Analysing mutation schemes for real-parameter genetic algorithms, 2014

EXAMPLE OF AN EVOLUTIONARY ALGORITHM

(Simple) EA on 1-dim Ackley function on $[-30, 30]$. Usually, for optimizing a function $f : \mathbb{R}^d \to \mathbb{R}$, individuals are encoded as real vectors $\boldsymbol{x} \in \mathbb{R}^d$.



EXAMPLE OF AN EVOLUTIONARY ALGORITHM

Random initial population with size $\mu = 10$



EXAMPLE 1: ACKLEY FUNCTION

We choose $\lambda = 5$ offsprings by neutral selection (red individuals).



EXAMPLE 1: ACKLEY FUNCTION

Use Gaussian mutation with $\sigma = 2$, but without recombination.



EXAMPLE 1: ACKLEY FUNCTION

Use $(\mu + \lambda)$ selection. Selected individuals are marked in green.



EXAMPLE 1: ACKLEY FUNCTION

After 50 iterations:





EXAMPLE 2: GRID OF BALLS

Consider a grid in which n balls with random radius are placed.



Aim: Find the circle with the largest possible radius in the grid that does **not** intersect with the other existing circles.

- What is the fitness function?
- How is the population defined?

Implementation: `https://juliambr.shinyapps.io/balls/`