SOURCE CODING / 2

- Formally, given a discrete alphabet/dictionary X of message symbols, a **binary code** is a mapping from symbols in X to a set of codewords of binary strings.
- For example, if our dictionary only consists of the words "dog", "cat", "fish" and "bird", each word can be encoded as a binary string of length 2 : "dog" $\rightarrow$ **00**, "cat" $\rightarrow$ **01**, "fish" $\rightarrow$ **10** and "bird" $\rightarrow$ **11**.
- For this code, a binary string can be decoded by replacing each successive pair of digits with the associated word.

0 0 0 1 0 0 1 1	encoded string
00 01 00 11	codewords
dog cat dog bird	source symbols

Credit: Chris Olah

Chris Olah (2015): Visual Information Theory. http://colah.github.io/posts/2015-09-Visual-Information/

SOURCE CODING / 3

- Encoded messages are emitted by a source which can be modeled as a probability distribution over the message symbols in the dictionary.
- Let X be a random variable that represents a symbol from our data source and let $p(x) = \mathbb{P}(X = x)$, for symbol x in our dictionary.



Credit: Chris Olah

- Length $L(x)$ is simply number of bits in corresponding codeword. Here all codewords have length 2.
- Area of rectangles on the right reflect contributions to $\mathbb{E}[L(X)]$

SOURCE CODING / 4

- Maybe we can create better average-length coding schemes with **variable-length** codes by assigning shorter codes to more likely messages and longer one to less likely messages.
- However, this can be problematic because we want the receiver to be able to unambiguously decode the encoded string.
- Let us say the words in our dictionary are encoded in this way: "dog" $\rightarrow$ **0**, "cat" $\rightarrow$ **1**, "fish" $\rightarrow$ **01** and "bird" $\rightarrow$ **11**.
- In this case, the string 00110101 can be decoded in multiple ways.



- One way to make variable-length messages unambiguous is by ensuring that no codeword is a prefix (initial segment) of any other codeword. Such a code is known as a **prefix code**.

SOURCE CODING / 5

- In general, the number of possible codewords grows exponentially in length L.
- For binary codes, there are two possible words of length one, four possible words of length two and 2^L possible words of length L.



- In total, there are $(2^{L+1} - 2)$ codewords of length $\leq$ L.

SOURCE CODING / 6

- Here, if the codeword **01** is assigned to a symbol, then **010** and **011** cannot be assigned to any other symbol because that would break the prefix property.
- If a codeword of length L is assigned to a symbol, then $\frac{1}{2^L}$ of the possible codewords of length $> L$ must be discarded.
- If some symbols are assigned short codewords, due to the prefix property, many marginally longer codewords cannot be assigned to other symbols.

SOURCE CODING / 7

- An example of prefix code:
  "dog" → **0**, "cat" → **10**, "fish" → **110** and "bird" → **111**.



- Here, the expected code length is :

$$
\begin{aligned}
\mathbb{E}[L(X)] &= \frac{1}{2}\cdot 1 + \frac{1}{4}\cdot 2 + \frac{1}{8}\cdot 3 + \frac{1}{8}\cdot 3 \\
&= -\frac{1}{2}\cdot \log_2\left(\frac{1}{2}\right) - \frac{1}{4}\cdot \log_2\left(\frac{1}{4}\right) - \frac{1}{8}\cdot \log_2\left(\frac{1}{8}\right) - \frac{1}{8}\cdot \log_2\left(\frac{1}{8}\right) \\
&= H(X) = 1.75 \text{ bits. } (< 2 \text{ bits})
\end{aligned}
$$

SOURCE CODING / 8

- Actually, this coding scheme is the most efficient way to store and transmit these messages. It is simply not possible to do better!
- In fact, Shannon's **source coding theorem** (or **noiseless coding theorem**) tells us that the optimal trade-off is made when the code length of a symbol with probability p is $\log(1/p)$.
- In other words, the entropy of the source distribution is the theoretical lower bound on the average code length.
- If it is any lower, some information will be distorted or lost.
- In practice, algorithms such as Huffman Coding can be used to find variable-length codes that are close (in terms of expected length) to the theoretical limit.