Introduction to Machine Learning

Classification
Linear Classifiers



Learning goals

- Linear classifier
- Linear decision boundaries
- Linear separability

LINEAR CLASSIFIERS



Important subclass of classification models.

Definition: If discriminant(s) $f_k(\mathbf{x})$ can be written as affine linear function(s) (possibly through a rank-preserving, monotone transformation g):

$$g(f_k(\mathbf{x})) = \boldsymbol{w}_k^\top \mathbf{x} + b_k,$$

we will call the classifier **linear**.

- $\boldsymbol{w}_k$ and b_k do not necessarily refer to parameters $\boldsymbol{\theta}_k$, although they often coincide; discriminant simply must be writable in an affine-linear way
- reasons for the transformation is that we only care about the position of the decision boundary

LINEAR DECISION BOUNDARIES



We can also easily show that the decision boundary between classes i and j is a hyperplane. For every $\mathbf{x}$ where there is a tie in scores:

$$
\begin{aligned}
f_i(\mathbf{x}) &= f_j(\mathbf{x}) \\
g(f_i(\mathbf{x})) &= g(f_j(\mathbf{x})) \\
\boldsymbol{w}_i^\top \mathbf{x} + b_i &= \boldsymbol{w}_j^\top \mathbf{x} + b_j \\
(\boldsymbol{w}_i - \boldsymbol{w}_j)^\top \mathbf{x} + (b_i - b_j) &= 0
\end{aligned}
$$

This represents a **hyperplane** separating two classes:



EXAMPLE: 2 CLASSES WITH CENTROIDS

- Model binary problem with centroid $\boldsymbol{\mu_k}$ per class as "parameters"
- Don't really care how the centroids are estimated;
  could use class means, but the following doesn't depend on it
- Classify point **x** by assigning it to class k of nearest centroid



EXAMPLE: 2 CLASSES WITH CENTROIDS



Let's calculate the decision boundary:

$$d_1 = ||\mathbf{x}-\boldsymbol{\mu_1}||^2 = \mathbf{x}^\top\mathbf{x}-2\mathbf{x}^\top\boldsymbol{\mu_1}+\boldsymbol{\mu_1}^\top\boldsymbol{\mu_1} = \mathbf{x}^\top\mathbf{x}-2\mathbf{x}^\top\boldsymbol{\mu_2}+\boldsymbol{\mu_2}^\top\boldsymbol{\mu_2} = ||\mathbf{x}-\boldsymbol{\mu_2}||^2 = d_2$$

Where d is measured using Euclidean distance. This implies:

$$-2\mathbf{x}^\top\boldsymbol{\mu_1} + \boldsymbol{\mu_1}^\top\boldsymbol{\mu_1} = -2\mathbf{x}^\top\boldsymbol{\mu_2} + \boldsymbol{\mu_2}^\top\boldsymbol{\mu_2}$$

Which simplifies to:

$$2\mathbf{x}^\top(\boldsymbol{\mu_2} - \boldsymbol{\mu_1}) = \boldsymbol{\mu_2}^\top\boldsymbol{\mu_2} - \boldsymbol{\mu_1}^\top\boldsymbol{\mu_1}$$

Thus, it's a linear classifier!

LINEAR SEPARABILITY

If there exists a linear classifier that perfectly separates the classes of some dataset, the data are called **linearly separable**.





linearly separable



not linearly separable



FEATURE TRANSFORMATIONS

Note that linear classifiers can represent **non-linear** decision boundaries in the original input space if we use derived features like higher order interactions, polynomial features, etc.





Here we used absolute values to find suitable derived features.