# Introduction to Machine Learning

## Information Theory
## Entropy I




**Learning goals**

- Entropy measures expected information for discrete RVs
- Know entropy and its properties

# INFORMATION THEORY

- **Information Theory** is a field of study based on probability theory.
- Foundation was laid by Claude Shannon in 1948; since then been applied in: communication theory, computer science, optimization, cryptography, machine learning and statistical inference.
- Quantify the "amount" of information gained or uncertainty reduced when a random variable is observed.
- Also about storing and transmitting information.



# INFORMATION THEORY / 2

- We introduce the basic concepts from a probabilistic perspective, without referring too much to communication, channels or coding.
- We will show some proofs, but not for everything. We recommend *Elements of Information Theory* by Cover and Thomas as a reference for more.
- The application of information theory to the concepts of statistics and ML can sometimes be confusing, we will try to make the connection as clear as possible.
- In this unit we develop entropy as a measure of uncertainty in terms of expected information.

# ENTROPY AS SURPRISAL AND UNCERTAINTY

For a discrete random variable $X$ with domain $\mathcal{X} \ni x$ and pmf $p(x)$:

$$H(X) := H(p) = -\mathbb{E}[\log_2(p(X))] \qquad = -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$$

$$= \mathbb{E}\left[\log_2\left(\frac{1}{p(X)}\right)\right] \qquad = \sum_{x \in \mathcal{X}} p(x) \log_2 \frac{1}{p(x)}$$

Some technicalities first:

- $H$ is actually Greek capital letter **E**ta ($\eta$) for **e**ntropy
- Base of the log simply specifies the unit we measure information in, usually bits (base 2) or 'nats' (base $e$)
- If $p(x) = 0$ for an $x$, then $p(x) \log_2 p(x)$ is taken to be zero, because $\lim_{p \to 0} p \log_2 p = 0$.

# ENTROPY AS SURPRISAL AND UNCERTAINTY

$$H(X) = -\mathbb{E}[\log_2(p(X))] = -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$$

Now: What's the point?

- The negative log probabilities $-\log_2 p(x)$ are called "surprisal"
- More surprising means less likely
- PMFs surprising, so with higher H, when events more equally likely
- Entropy is simply expected surprisal




- The final entropy is $H(X) = 2.12$ (bits).

# ENTROPY BASIC PROPERTIES

$$H(X) := H(p) = -\mathbb{E}[\log_2(p(X))] = -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$$

1. Entropy is non-negative, so $H(X) \geq 0$
2. If one event has probability $p(x) = 1$, then $H(X) = 0$
3. Adding or removing an event with $p(x) = 0$ doesn't change it
4. $H(X)$ is continuous in probabilities $p(x)$

All these properties follow directly from the definition.

# ENTROPY RE-ORDERING

❺ Symmetry. If the values $p(x)$ in the pmf are re-ordered, entropy does not change (proof is trivial).



# ENTROPY OF UNIFORM DISTRIBUTIONS

Let $X$ be a uniform, discrete RV with $g$ outcomes ($g$-sided fair die).

$$H(X) = -\sum_{i=1}^{g} \frac{1}{g} \log_2 \left(\frac{1}{g}\right) = \log_2 g$$




The more sides a die has, the harder it is to predict the outcome. Unpredictability grows *monotonically* with the number of potential outcomes, but at a decreasing rate.

# ENTROPY IS MAXIMAL FOR UNIFORM




- Naive observation:
  Entropy min for 1-point and max for uniform distribution

# ENTROPY IS MAXIMAL FOR UNIFORM



6. Entropy is maximal for a uniform distribution, for domain of size $g$: $H(X) \leq -g\frac{1}{g}\log_2(\frac{1}{g}) = log_2(g)$.

**Proof**: So we want to maximize w.r.t. all $p_i$:

$$\underset{p_1,p_2,\ldots,p_g}{\text{argmax}} -\sum_{i=1}^{g} p_i \log_2 p_i$$

subject to

$$\sum_{i=1}^{g} p_i = 1$$

# ENTROPY IS MAXIMAL FOR UNIFORM / 2



The Lagrangian $L(p_1, \ldots, p_g, \lambda)$ is :

$$L(p_1, \ldots, p_g, \lambda) = -\sum_{i=1}^{g} p_i \log_2(p_i) - \lambda \left( \sum_{i=1}^{g} p_i - 1 \right)$$

Solving when requiring $\nabla L = 0$,

$$\frac{\partial L(p_1, \ldots, p_g, \lambda)}{\partial p_i} = 0 = -\log_2(p_i) - \frac{1}{\log(2)} - \lambda$$

$$\implies p_i = \frac{2^{-\lambda}}{e} \implies p_i = \frac{1}{g},$$

last step follows from that all $p_i$ are equal and constraint

**NB**: We also could have solved the constraint for $p_1$ and substitute $p_1 = 1 - \sum_{i=2}^{g} p_i$ in the objective to avoid constrained optimization.