

Introduction to Machine Learning




Information Theory
Entropy I




Learning goals

- Entropy measures expected information for discrete RVs
- Know entropy and its properties


INFORMATION THEORY



- **Information Theory** is a field of study based on probability theory.
- Foundation was laid by Claude Shannon in 1948; since then been applied in: communication theory, computer science, optimization, cryptography, machine learning and statistical inference.
- Quantify the "amount" of information gained or uncertainty reduced when a random variable is observed.
- Also about storing and transmitting information.



ENTROPY AS SURPRISAL AND UNCERTAINTY



For a discrete random variable X with domain $\mathcal{X} \ni x$ and pmf $p(x)$:


$$H(X) := H(p) = -\mathbb{E}[\log_2(p(X))] = -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$$

$$= \mathbb{E}\left[\log_2\left(\frac{1}{p(X)}\right)\right] = \sum_{x \in \mathcal{X}} p(x) \log_2 \frac{1}{p(x)}$$

Some technicalities first:

- H is actually Greek capital letter **E**ta (η) for **e**ntropy
- Base of the log simply specifies the unit we measure information in, usually bits (base 2) or 'nats' (base e)
- If $p(x) = 0$ for an x, then $p(x) \log_2 p(x)$ is taken to be zero, because $\lim_{p \to 0} p \log_2 p = 0$.


ENTROPY AS SURPRISAL AND UNCERTAINTY



$$H(X) = -\mathbb{E}[\log_2(p(X))] = -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$$

Now: What's the point?


- The negative log probabilities $-\log_2 p(x)$ are called "surprisal"
- More surprising means less likely
- PMFs surprising, so with higher H, when events more equally likely
- Entropy is simply expected surprisal



- The final entropy is $H(X) = 2.12$ (bits).

ENTROPY BASIC PROPERTIES


$$H(X) := H(p) = -\mathbb{E}[\log_2(p(X))] = -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$$




1. Entropy is non-negative, so $H(X) \geq 0$
2. If one event has probability $p(x) = 1$, then $H(X) = 0$
3. Adding or removing an event with $p(x) = 0$ doesn't change it
4. $H(X)$ is continuous in probabilities $p(x)$

All these properties follow directly from the definition.

ENTROPY RE-ORDERING




5. Symmetry. If the values $p(x)$ in the pmf are re-ordered, entropy does not change (proof is trivial).



ENTROPY OF UNIFORM DISTRIBUTIONS


Let X be a uniform, discrete RV with g outcomes (g-sided fair die).


$$H(X) = -\sum_{i=1}^{g} \frac{1}{g} \log_2 \left(\frac{1}{g} \right) = \log_2 g$$



The more sides a die has, the harder it is to predict the outcome. Unpredictability grows *monotonically* with the number of potential outcomes, but at a decreasing rate.

ENTROPY IS MAXIMAL FOR UNIFORM






- Naive observation:
  Entropy min for 1-point and max for uniform distribution

ENTROPY IS MAXIMAL FOR UNIFORM

6. Entropy is maximal for a uniform distribution, for domain of size g: $H(X) \leq -g\frac{1}{g}\log_2(\frac{1}{g}) = log_2(g)$.



Proof: So we want to maximize w.r.t. all p_i:

$$\underset{p_1,p_2,\ldots,p_g}{\text{argmax}} \; -\sum_{i=1}^{g} p_i \log_2 p_i$$

subject to

$$\sum_{i=1}^{g} p_i = 1$$