

Introduction to Machine Learning




Regularization
Bias-Variance Decomposition for Ridge Regression (Deep-Dive)



Learning goals

- Bias-Variance trade-off for ridge regression

BIAS-VARIANCE DECOMPOSITION FOR RIDGE




For a linear model $\mathbf{y} = \mathbf{X}\boldsymbol{\theta} + \boldsymbol{\varepsilon}$ with fixed design $\mathbf{X} \in \mathbb{R}^{n \times p}$ and $\boldsymbol{\varepsilon} \sim (\mathbf{0}, \sigma^2 \boldsymbol{I}_n)$, bias of ridge estimator $\hat{\theta}_{\text{ridge}}$ is given by

$$
\begin{aligned}
\text{Bias}(\hat{\theta}_{\text{ridge}}) := \mathbb{E}[\hat{\theta}_{\text{ridge}} - \boldsymbol{\theta}] &= \mathbb{E}[(\boldsymbol{X}^\top \boldsymbol{X} + \lambda \boldsymbol{I}_p)^{-1} \boldsymbol{X}^\top \boldsymbol{y}] - \boldsymbol{\theta} \\
&= \mathbb{E}[(\boldsymbol{X}^\top \boldsymbol{X} + \lambda \boldsymbol{I}_p)^{-1} \boldsymbol{X}^\top (\boldsymbol{X}\boldsymbol{\theta} + \boldsymbol{\varepsilon})] - \boldsymbol{\theta} \\
&= (\boldsymbol{X}^\top \boldsymbol{X} + \lambda \boldsymbol{I}_p)^{-1} \boldsymbol{X}^\top \boldsymbol{X}\boldsymbol{\theta} + (\boldsymbol{X}^\top \boldsymbol{X} + \lambda \boldsymbol{I}_p)^{-1} \boldsymbol{X}^\top \underbrace{\mathbb{E}[\boldsymbol{\varepsilon}]}_{=0} - \boldsymbol{\theta} \\
&= (\boldsymbol{X}^\top \boldsymbol{X} + \lambda \boldsymbol{I}_p)^{-1} \boldsymbol{X}^\top \boldsymbol{X}\boldsymbol{\theta} - \boldsymbol{\theta} \\
&= \left[(\boldsymbol{X}^\top \boldsymbol{X} + \lambda \boldsymbol{I}_p)^{-1} - (\boldsymbol{X}^\top \boldsymbol{X})^{-1} \right] \boldsymbol{X}^\top \boldsymbol{X}\boldsymbol{\theta}
\end{aligned}
$$

- Last expression shows bias of ridge estimator only vanishes for $\lambda = 0$, which is simply (unbiased) OLS solution
- It follows $\|\text{Bias}(\hat{\theta}_{\text{ridge}})\|_2^2 > 0$ for all $\lambda > 0$

BIAS-VARIANCE IN PREDICTIONS FOR RIDGE



In supervised learning, our goal is typically not to learn an unknown parameter $\boldsymbol{\theta}$, but to learn a function $f(\mathbf{x})$ that can predict y given $\mathbf{x}$.

The bias and variance of predictions $\hat{f} := \hat{f}(\mathbf{x}) = \hat{\theta}_{\text{ridge}}^{\top}\mathbf{x}$ is obtained as:

$$\begin{aligned}\text{Bias}(\hat{f}) &= \mathbb{E}[\hat{f} - f] = \mathbb{E}[\hat{\theta}_{\text{ridge}}^{\top}\mathbf{x} - \boldsymbol{\theta}^{\top}\mathbf{x}] = \mathbb{E}[\hat{\theta}_{\text{ridge}} - \boldsymbol{\theta}]^{\top}\mathbf{x} \\ &= \text{Bias}(\hat{\theta}_{\text{ridge}})^{\top}\mathbf{x} \\ \text{Var}(\hat{f}) &= \text{Var}(\hat{\theta}_{\text{ridge}}^{\top}\mathbf{x}) = \mathbf{x}^{\top}\text{Var}(\hat{\theta}_{\text{ridge}})\mathbf{x}\end{aligned}$$

The MSE of $\hat{f}$ given a fresh sample $(y, \mathbf{x})$ can now be decomposed as

$$\text{MSE}(\hat{f}) = \mathbb{E}[(y - \hat{f}(\mathbf{x}))^2] = \text{Bias}^2(\hat{f}) + \text{Var}(\hat{f}) + \sigma^2$$

This decomposition is similar to the statistical inference setting before, however, the irreducible error σ^2 only appears for predictions as an artifact of the noise in the test sample.